

TIOXHUA® R-2196+ Technical Data Sheet

High gloss, high dispersibility and high opacity

R-2196+ is well suited for solvent-based paint, gloss and matt exterior and interior architectural latex paint, industrial paint and printing ink.

Key Features

High gloss

Easy wetting and dispersing

Excellent hiding power

Excellent whiteness

Typical Properties

Crystal form	Rutile
Inorganic Surface treatment	ZrO ₂ , Al ₂ O ₃ ,
Organic Surface treatment	Yes
Classification (ISO 591-1)	R2
ASTM D476 classification	?
Color (ISO 787-25)	ΔE ≤ 0.5 relative to reference standard
Relative scattering power (ISO 787-24)	95% - 105%
Density (ISO 787-10)	4.0g/cm ³
Dispersion in polyester system (GB/T 21868.3-2008)	≤25μm

Typical Data

Items	Value
TiO ₂ content, %	93%
CIE L*, dry powder (GB/T 5950-2008)	98.5
PH of aqueous suspension	7.2
Oil absorption	19g/100g
Residue on 45μm (ISO 787-18)	0.01%
Resistivity	150Ω*m
Volatiles at 105° at packaging	0.4%

* Not to be taken for specifications. Actual data subject to measurement in COA.

Health and Safety Precautions

Relevant local health and safety guidelines should be followed. Gloves, safety goggles and respirator with submicron particle filtration should be worn. MSDS is available upon request.

Packaging

Chemate Technology Co.,Ltd

Add: NO.80 PUHUI ROAD,ZHENGZHOU CITY, HENAN PROVINCE, CHINA

URL: <https://www.chemategroup.com/tioxhua-titanium-dioxide-tio2/>

Email: sales@chemategroup.com

Phone: 0086-371-60921621

Whatsapp: +8618624832876

R-2196+ is available in 25kg paper bags, 500kg and 1000kg jumbo bags.

Product Storage

Product should be stored indoors in clean and dry conditions. The shelf life of CHTi'e TiO₂ is 2 years if stored properly. First-in, first-out regime is highly recommended to ensure the performance of the product.

Chemate Technology Co.,Ltd

Add: NO.80 PUHUI ROAD,ZHENGZHOU CITY, HENAN PROVINCE, CHINA

URL: <https://www.chemategroup.com/tioxhua-titanium-dioxide-tio2/>

Email: sales@chemategroup.com

Phone: 0086-371-60921621

Whatsapp: +8618624832876