

PANGANG TITANIUM

R-298 rutile titanium dioxide

R298 is a multi-purpose rutile TiO_2 pigment is known for its low oil absorption, high gloss, high tinting strength, durability, and dispersability. Produced by the Sulfate process, with a very fine particle size, it has excellent hiding power, blue tint undertone.

R298 has a zirconium and Al_2O_3 inorganic surface treatment, in combination with a special organic coating. It is well suited for both waterborn and solventborn coating, ink applications.

Applications

Architectural exterior coatings
Exterior industrial finishes
Powder coatings
Container coatings
Coil coatings
Ink



Properties

High dispersability in solvent and waterborne systems
Excellent gloss retention
High tinting strength
Bluish undertone

Product Characteristics

TiO_2 content %----- ≥ 93.5
Brightness %----- ≥ 95.0
Volatile at 105°C ----- ≤ 0.5
pH----- $6.0-9.0$
Oil absorption----- ≤ 19
Residue on sieve (45 μm)----- ≤ 0.02
Tinting strength Reynolds number----- ≥ 1920
Rutile content----- ≥ 98
Dispersibility----- ≥ 6.50
ISO 591-1:2000(E)-----R2
ASTM D476-00-----V

All information is based on data obtained from the manufacturer or recognized technical sources. The information is believed to be accurate. We make no representation or warranty, express, or implied, concerning the accuracy or sufficiency of the information. We are not liable for any damages resulting from the use of the information.

PANGANG TITANIUM INDUSTRY CO., LTD.