

DuPont™ Ti-Pure® R-902

Titanium Dioxide

Product Description

Ti-Pure® R-902 is a multipurpose rutile titanium dioxide pigment manufactured by the chloride process for both interior and exterior coatings applications. It is a fine dry powder with the following general properties.

Table 1
Analysis and Physical Properties of
Ti-Pure® R-902

Property	R-902
TiO ₂ , wt%, min.	91
Alumina, wt%	4.3
Amorphous Silica, wt%	1.4
Specific Gravity	4.0
Bulking Value, L/kg (gal/lb)	0.25 (0.03)
Organic Treatment	No
Color CIE L*	99.8
Median Particle Size, µm	0.42
Oil Absorption	16.1
pH	8.1
Resistance at 30°C (86°F) (1,000 ohm)	10
Carbon Black Undertone	11.7

Note: All values are typical unless otherwise specified.

Suggestions for Use

Ti-Pure® R-902 has an excellent balance of chalk resistance, hiding, and gloss for a broad range of both exterior and interior applications. Ti-Pure® R-902 is recommended for use in:

- architectural interior semigloss and exterior finishes
- exterior industrial finishes, except those that require the highest level of exterior durability
- powder coatings

Safety Precautions

- Titanium dioxide is classified as a nuisance dust. Follow all local regulations and DuPont recommendations for exposure limits as described in the Material Safety Data Sheet (MSDS). If the recommended exposure limits of TiO₂ are to be exceeded, NIOSH-approved air-purifying respirators with particulate filters should be used.
- As a matter of good industrial hygiene, gloves and safety glasses with side shields or better eye protection should be worn when handling TiO₂. For more details, refer to the MSDS.

First Aid

- If large amounts of TiO₂ are inhaled, remove victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.
- In case of eye contact, immediately flush with water for at least 15 minutes. Call a physician. In case of skin contact, the compound is not likely to be hazardous, but cleaning the skin after use is advised.

Shipping Containers

Ti-Pure® R-902 is available in 50-lb (25-kg) paper bags and semibulk containers (½ and 1 metric ton). Truckload shipments of the dry product are available directly from DuPont. Less-than-truckload volumes are available through one of the authorized DuPont distributors. Call your local sales office (see back page) for the distributor nearest you.

Water slurries are available in some regions in truckload shipments (15 metric ton) and railcar (67 metric ton).

Product Storage

The shelf life of DuPont™ Ti-Pure® TiO₂ is indefinite as long as the material is kept from direct contact with moisture.

DuPont Titanium Technologies

Chestnut Run Plaza 728/1229

P.O. Box 80728

Wilmington, DE 19880-0728

(302) 999-5184 (800) 441-9485

Fax: (302) 999-5166

www.titanium.dupont.com

The information set forth herein is furnished free of charge and based on technical data that DuPont believes to be reliable. It is intended for use by persons having technical skill, at their own risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. Nothing herein is to be taken as license to operate under or a recommendation to infringe any patents.

The DuPont oval logo, DuPont™, The miracles of science®, and Ti-Pure® are trademarks or registered trademarks of DuPont.

Copyright © 2002 E.I. du Pont de Nemours and Company. All rights reserved.

