IEEE Access
Multidisciplinary | Rapid Review | Open Access Journal

Date of publication xxxx 00, 0000, date of current version xxxx 00, 0000.

Digital Object Identifier 10.1109/ACCESS.2026.0000000

Recoverability-Aware Healing: Pilot-Guided Allocation of Data Mixture and Adaptation Scope for Depth-Pruned Small Language Models

PIYUSH DHOKA[1], and SECOND AUTHOR[2]
[1]Department, Organization, City, India (e-mail: author@domain)
[2]Department, Organization, City, India (e-mail: author@domain)

Corresponding author: Piyush Dhoka (e-mail: author@domain).

This work received no external funding.

ABSTRACT Depth pruning, the removal of whole Transformer blocks, is a simple way to shrink small instruction-tuned language models for edge deployment, but it damages capabilities unevenly, and the short fine-tuning run that follows, called healing, has a fixed token budget. Current practice spreads that budget uniformly over a generic mixture or in proportion to how damaged each capability is. We argue that the budget should instead follow how recoverable each capability is. Recoverability-aware healing fits, from a few cheap pilot runs, a recovery curve for every capability together with a transfer matrix that captures how data for one capability helps another, then solves a small concave program that jointly chooses the data mixture and the adaptation scope inside a trust region that forbids extrapolation beyond the pilots. We evaluate six capabilities (structured output, function calling, instruction following, mathematical reasoning, safety refusal, and knowledge) on four model families with one to two billion parameters pruned by Block Influence, using three seeds and paired bootstrap tests. The order in which capabilities break is highly consistent across families, but damage does not predict recovery speed. At an equal budget, the proposed allocation is never worse than uniform healing on mean retention, raises the worst-retained capability by up to seventeen points on two families, reduces over-refusal on three, and beats damage-proportional allocation on two families while matching it on the other two. Pilot-free proxies and worst-case objectives did not work; we report them as negative results. Code and all results are released.

INDEX TERMS Depth pruning, function calling, instruction-tuned language models, layer pruning, low-rank adaptation, model compression, parameter-efficient fine-tuning, small language models, structured pruning.

I. INTRODUCTION

SMALL instruction-tuned language models are what actually ships on phones, laptops and low-cost cloud instances [1]–[4]. TODO.

II. RELATED WORK

TODO.

III. PROBLEM SETTING

TODO.

IV. RECOVERABILITY-AWARE HEALING

TODO.

V. EXPERIMENTAL SETUP

TODO.

VI. RESULTS

TODO.

VII. DISCUSSION

TODO.

VIII. CONCLUSION

TODO.

ACKNOWLEDGMENT

TODO: IEEE-required disclosure of AI-assisted text, per the IEEE submission and peer review policies.

REFERENCES

[1] X. Men, M. Xu, Q. Zhang, B. Wang, H. Lin, Y. Lu, X. Han, and W. Chen, "ShortGPT: Layers in large language models are more redundant than you expect," in *arXiv preprint arXiv:2403.03853*, 2024.
[2] A. Gromov, K. Tirumala, H. Shapourian, P. Glorioso, and D. A. Roberts, "The unreasonable ineffectiveness of the deeper layers," in *arXiv preprint arXiv:2403.17887*, 2024.
[3] B. He, L. Yu, Z. Zhang *et al.*, "PASER: Post-training data selection for efficient pruned large language model recovery," in *Proc. Int. Conf. Learning Representations (ICLR)*, 2026, arXiv:2502.12594. TODO verify author list.
[4] E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang, and W. Chen, "LoRA: Low-rank adaptation of large language models," in *Proc. Int. Conf. Learning Representations (ICLR)*, 2022.

PIYUSH DHOKA TODO (100–150 words).