



Week 2 Lecture 6

▼ Class	BSCCS2003
🕒 Created	@September 15, 2021 2:23 PM
🔗 Materials	
# Module #	15
▼ Type	Lecture
☰ Week #	2

Types of CSS styling & Responsive Websites

Inline CSS

- Directly add style to the tag
- Example:

```
<h1 style="color: blue; text-align: center;">A heading</h1>
```

Internal CSS

- Embed inside the `<head>` tag
- Now, all the `<h1>` tags in the document will look the same - centrally modified

```
<style>
body {
  background-color: linen;
}

h1 {
  color: maroon;
  margin-left: 40px;
}
</style>
```

External CSS

- Extract common content for re-use

- Multiple CSS files can be included
- Latest definition of style takes the precedence

Responsive Design

- Mobile and Tablet devices have smaller screen
 - Different form factors
- Adapt to the screen - ***Respond***
- CSS controls the styling - HTML controls the client

Bootstrap

- Most commonly used framework for CSS
 - Originate from Twitter
 - Widely used now
- Standard styles for various components
 - Buttons
 - Forms
 - Icons
 - ...
- Mobile first: highly responsive layout

JavaScript

- It is an interpreted language brought into the browser
- Not really related to Java in any way - formally known as ECMAScript
- Why was JavaScript brought into the browser?
 - HTML is not a programming language
 - CSS is not a programming language too (There are ways to make it Turing complete, google it)
- We wanted to have "programmability" inside the browser
- It is not a part of the core presentation requirements
 - But still, it is very useful and will be considered later

Summary

- Presentation - Human interaction
- Separate content from style
 - Markup - HTML
 - Styling - CSS