

Paws and Pixels: Enhancing Canine Dermatology Through Image Analysis

Yashu

Chitkara University Institute of
Engineering and Technology,
Chitkara University,
Punjab, India
yashu@chitkara.edu.in

Vinay Kukreja

Chitkara University Institute of
Engineering and Technology,
Chitkara University,
Punjab, India
vinay.kukreja@chitkara.edu.in

Prateek Srivastava

Computer Science and Engineering
Graphic Era Hill University,
Dehradun, Uttarakhand, India
psrivastava@gehu.ac.in

Ashish Garg

Computer Science and Engineering
Graphic Era Deemed to be University,
Dehradun, Uttarakhand, India
ashish.garg@geu.ac.in

Shanmugasundaram Hariharan

Computer Science and Engineering
Vardhaman College of Engineering,
Hyderabad, India
hariharan.s@vardhaman.org

Abstract— This study focuses on the urgent need for sophisticated diagnostic tools in the field of canine dermatology. We have created a sophisticated system that uses Convolutional Neural Networks (CNN) and Random Forest to accurately identify and categorise seven common skin disorders in dogs. The model attained an overall accuracy of 79.02% by using a diversified dataset consisting of 4,053 photos. The precision and recall measures provide detailed and subtle observations about the model's performance in relation to various illnesses, highlighting significant advantages in some scenarios. The research emphasises the capacity of machine learning to assist veterinarians in precise and effective diagnoses, especially in the realm of skin illnesses that often present difficulties for traditional approaches. Although the current level of accuracy is encouraging, further improvement and enlargement of the dataset are necessary to further strengthen the model's reliability and suitability in various clinical situations. This study enhances canine healthcare by providing a crucial tool for promptly and accurately identifying skin illnesses. As a result, it leads to better treatment results and general well-being for our canine friends.

Keywords—Animal, CNN-Random forest, Deep Learning, Diseases, Detection, Health

I. INTRODUCTION

Dermatological problems in canines are a notable source of worry for both individuals who own pets and professionals in the field of veterinary medicine. These illnesses may have a negative impact on the health and well-being of our dogs, causing discomfort, suffering, and in extreme instances, impairing their entire quality of life. Prompt identification and precise categorization of various skin ailments are vital for prompt and efficient intervention, underscoring the need for sophisticated tools in the field of veterinary dermatology. Canine dermatological conditions are varied and may result from several factors, including as allergies, infections, parasites, autoimmune illnesses, and hereditary predispositions. Canine Atopic Dermatitis is a common skin illness in dogs that is characterised by allergic responses to environmental factors such as pollen, dust mites, and moulds. The presence of symptoms such as pruritus, erythema, and inflammation renders it very suitable for examination using sophisticated imaging and machine learning methodologies. Precisely identifying and categorising CAD at an early stage is crucial in promptly alleviating distress in dogs and averting the worsening of

symptoms. Canine Pyoderma is characterised by bacterial infections that result in the formation of pustules, papules, and crusty lesions[1],[2]. The difficulty is in accurately distinguishing this ailment from other skin disorders in order to apply appropriate therapy. Utilising Convolutional Neural Networks (CNNs) and Random Forest algorithms for analysing skin scans might greatly aid in the precise categorization of Pyoderma, hence enabling focused treatment approaches. Demodicosis, sometimes referred to as mange, is a dermatological disorder caused by an excessive proliferation of Demodex mites on the skin. This disorder may result in alopecia, inflammation, and subsequent bacterial infections. Early detection and classification of Demodicosis is important to avoid its transmission and successfully treat its accompanying symptoms. The use of sophisticated technology presents a potential opportunity for the timely detection and intervention in instances of Demodicosis. Canine Ringworm, a highly infectious fungal illness, presents a considerable difficulty since it causes circular, red sores on the skin. Precise categorization is essential for administering suitable therapy and averting its transmission to other animals and humans. Applying Convolutional Neural Networks (CNNs) and Random Forest algorithms may help differentiate Ringworm from other skin disorders, guaranteeing precise therapy approaches. Dogs often have flea infestations, which may result in an allergic response to the saliva of fleas, known as Flea Allergy Dermatitis. It is crucial to accurately identify this allergic reaction and differentiate it from other skin problems associated with infections or allergies. Utilising convolutional neural networks (CNNs) to include sophisticated visual analysis may aid in identifying distinctive patterns linked to FAD, facilitating timely and efficient intervention. Dogs with autoimmune skin illnesses, such as Pemphigus and Discoid Lupus Erythematosus, experience the immune system erroneously targeting the skin. The various clinical manifestations of these illnesses provide diagnostic problems. Utilising the capabilities of Convolutional Neural Networks (CNNs) and Random Forest algorithms may aid in identifying distinctive patterns linked to autoimmune skin conditions, hence facilitating precise and prompt categorization. Canine Seborrhea is a dermatological condition characterised by an abnormal secretion of sebum, resulting in either excessively dry or oily skin, typically accompanied by the presence of scales[3],[4]. Utilising machine learning algorithms to identify the specific patterns

associated with Seborrhea may aid in its precise diagnosis and categorization, facilitating the implementation of suitable treatment interventions. This study article aims to thoroughly investigate the possibility of integrating Convolutional Neural Networks with Random Forest algorithms to identify and categorise seven prevalent skin disorders in dogs. Through the use of machine learning, our objective is to optimise the precision and effectiveness of veterinary dermatological diagnostics, eventually leading to enhanced canine health and well-being. This study has the potential to completely transform the sector, providing new and innovative perspectives and approaches that will greatly help our cherished canine friends.

II. RELATED WORK

Scientists have investigated the difficulties in diagnosing skin disorders in dogs, studying the effectiveness of several imaging and laboratory methods to improve diagnostic precision. This research[5] aims to examine the notable concern of skin disorders in companion animals, with a specific emphasis on canines. The authors specifically highlight the exacerbating factors of congested clinics and restricted veterinary services in remote regions. The authors put out a novel solution called "HAPPY PET," which is a smartphone application that incorporates machine learning-based image processing, deep learning, and natural language processing techniques using artificial intelligence. The system was designed primarily to apply image recognition and deep learning analysis, identify authenticate and validate skin diseases in pets. Another function of this Artificial Intelligence dialogue robot consists in validating its diagnoses with pet owners, thus prompting them to provide detailed symptoms and behavior observations or even casual photos. Our aim, is for pet owners to be able to dispense firsthand and chattease cures at home, observe and manage their dog's health well. This research[6] is aimed at helping veterinary clinics to diagnose and cure the widespread skin lesions in canines effectively. In this vein, for the variety of animals they come across every day is so large that it puts them off diagnosing certain ailments, even if only temporarily. The goal of this research project is to use supervised learning techniques and convolution neural networks for accurate classification of photographs of dog skin diseases, of a level equivalent to that expected from dermatologists. The system in question will enable both the efficiency and accuracy of diagnosis to be improved. It allows visual and non-visual means to be inspected at an early stage in a wide range of patients. The implementation process includes the development of user-friendly software applications compatible with mobile devices and PCs. These applications act as an excellent resource for anyone wanting to study for coming examinations ahead of time. The method of Error-Correcting Output Codes via Image Enhancement based upon Convolutional Neural Networks has real potential for greatly increasing the effectiveness of standard veterinary clinic procedures. Even if you're entirely certain of your dog's birth date and your dog's blood group, It is quite impossible to remember your dog's immunization record. Although dog owners understand the importance of dog dermatology, the majority of them do not know a bark from a bite. The three folders of record, immunization certificate and dog licence attached to the contract help to ensure prompt processing at the hospital. There may be a possibility that expenditure on veterinary care could prove a

considerable obstacle. To fill the current gap, the authors[7] suggest an integrated, comprehensive mobile application platform that provides illness diagnosis, analysis of severity degree and information storage. They use a Convolutional Neural Network (CNN) and natural language processing (NLP) method in their system. The results are outstanding. The kind of illness is divided into types ranging from 77.78% correct rate to complete. Severity level identification from Various CNN-based models attains an estimated accuracy rate up to 99.62%.

This paper[8] aims to solve the challenging technical barriers that accompany automatic classification of melanoma by use of dermoscopic pictures. Because melanoma pictures lack contrast, exhibit substantial variations within the category itself, and look similar in many ways to non-melanoma tissue, these walls go up. To tackle these difficulties the authors proposed a new method: System XNet framework. The method proposed here combines the Difference of Gaussian (DoG) feature augmentation method with a ResNet architecture, for both efficient feature extraction and accurate melanoma classification. The performance of our framework in detecting melanoma exceeds that of earlier studies, as shown by a validation experiment (using the ISIC (2019) dataset). Empirical tests show that the proposed classification performance is robust and consistent, with sensitivity at 0.93, AUC at 0.815 and accuracy at 81%. The results of these findings suggest that it could prove to be an advantageous adjunct for clinical staff-members as it can act like a real second opinion with some credibility. In an attempt to address a major veterinary clinical issue, this reearch[9] examines poor staffing levels and hectic scenes with a large number of patients. This impedes timely recording for dog skin diseases in any veterinary hospital. Not only that, but the time lost in recording drones a fastidiously disorder.streamlining and organizing--placing an efficient pre-examination system that can automatically record visually detectable diseases like dog skin diseases. The introduction of this technology, even before the clinic is open for business or treated patients have arrived to see doctors, would bring a clinical advantage. The development encompasses the use of image processing methods and Convolutional Neural Network (CNN), with a significant improvement via the incorporation of Graphics Processing Unit (GPU) to accelerate the training of the model. The authors of this study acknowledge the value of the system under consideration, while also emphasising the continuous pursuit of enhanced methodologies that do not compromise efficiency and accuracy. This research[10] focuses on pemphigus, which refers to a group of autoimmune skin illnesses in humans. These diseases are characterised by the separation of skin cells inside the epidermis, caused by a process called acantholysis-induced cell detachment. The categorization of entities is determined by the severity of blistering in the epidermis, taking into account both superficial variations such as pemphigus foliaceus and IgA pemphigus, as well as deep variations including pemphigus vulgaris, pemphigus vegetans, and paraneoplastic pemphigus. Since the mid-1970s, subsets of pemphigus have been recognised in domestic animals, with comparisons to human categorization. This review provides a thorough examination of the occurrence, symptoms, tissue changes, immune system responses, and treatment results of superficial pemphigus in different domestic animals. The

specific types discussed include pemphigus foliaceus in dogs, cats, horses, and goats, as well as pemphigus erythematosus in dogs and cats, and panepidermal pustular pemphigus in dogs. This research[11] focuses on the incidence of dermatological conditions in dogs, which are regularly addressed by veterinarians as a common sickness. The significance of promptly diagnosing and intervening in untreated skin disorders in dogs, which may result in infections and, in extreme instances, fatality, highlights the cosmetic and health consequences. The scarcity of veterinarians in Indonesia compared to the high prevalence of canine dermatological conditions, along with a lack of knowledge among dog owners, underscores the need for a diagnosis method. This study utilises the Bayes theorem approach in an expert system to develop an application that assists veterinarians in accurately identifying and treating skin problems in dogs. This research[12] focuses on autoimmune blistering skin illnesses, which have been well-established in both people and dogs for many years. Regrettably, in canines, these ailments were formerly classified together under the inclusive label "bullous pemphigoid" without definitive verification of autoantibodies exclusively attacking bullous pemphigoid antigens. Recent progress in diagnostic techniques has revealed novel autoimmune blistering skin disorders in both people and companion animals. The current diagnostic approach involves using clinical indicators and histological findings, together with immunologic techniques to verify the existence of autoantibodies that specifically target different epidermal or basement membrane antigens, both in the skin and in the bloodstream. This article outlines the main characteristics of common subepidermal blistering skin diseases in dogs and cats, including mucous membrane pemphigoid, bullous pemphigoid, epidermolysis bullosa acquisita, and emerging variations of cutaneous lupus such as type I bullous systemic lupus erythematosus and vesicular cutaneous lupus erythematosus. The authors[13] of this research performed further validation of a pruritus severity rating for dogs. Owners were shown to be considerably impacted by the presence of numerical markings as compared to a marking scale. This compromised the scale's capacity to offer continuous data. Therefore, it was essential to include a conventional visual analogue scale. The scale was evaluated on 713 dog owners who were seeking veterinary care. It successfully measured pruritus levels ranging from 0 to 10 in 408 dogs with skin illness. A reference range of 0–1.9 was determined in a sample of 305 dogs without any skin conditions. The scale successfully differentiated between conditions that cause itching and those that do not, and its effectiveness in identifying changes in itching ratings after therapy was established with a median decrease of 4.4 points. Furthermore, the investigation revealed the owner's expectations about the extent of reaction after therapy, questioning the prevalent notion that a 50% decrease is sufficient. The method of judging clinical status and an instrument of much promise for monitoring treatment effect during clinical trials. This prompts us to try to formulate our evaluation of such a study by finding another method.

III. MATERIALS AND METHODS

The methods section offers a systematic description of the methods used in this canine dermatological research, starting with compilation of dataset and ending at model training assessment. It tells us in detail, and makes plain for

readers who worry about such things as rigor or credibility, how particular experiments were done and why we should believe their results.

A. Dataset Collection

For data collection purposes in this study, A significant dataset consisting of 4053 photographs was obtained. For model training and testing the split used was meticulous, with 70% of cases split for training while the remaining 30% became available test cases. It's absolutely key to make sure the training and testing datasets are of equal size, because then not only will a machine learning model be able to remember what it learned for new, unappreciated data points (e.g., similar snapshots in its memory), but also how much "trust" should go into any decisions based on that prior knowledge. This set contains a variety of pictures showing different situations around cer-tain skin diseases. This extensive compilation not only makes it more convenient to train Convolutional Neural Networks (CNNs), but also enables comprehensive evaluation of whether the model can correctly identify and differentiate between various kinds of canine skin disorder resemblances in pictures.

B. Data Preprocessing

At critical junctures, the data prep phase elevated the quality of photos from this effort to new heights. Before bringing machine learning models to life, the dataset went through rigorous preprocessing steps. This included resizing and standardising the photos to make them consistent, also enhancing their quality in order for them that performance might be maximized. Different normalisation methods were used to rescale pixel values, which helped speed up model convergence in the process. Data augmentation techniques such as rotation and flipping were implemented in order to increase the dataset's size and improve the model's ability to recognize a variety of patterns. This preparation process played a collective role in making an optimised dataset after which strong, accurate skin disease classification algorithms were successfully written. The dataset samples are illustrated in figure 1.




Fig. 1. Dataset sample

C. Architectural details of the proposed model

The architectural blueprint of such an applied Convolutional Neural Network (CNN) is carefully crafted to efficiently extract features It recognizes that urban patterns are hierarchical in the photos. The first Convolutional Neural Network (CNN) has three initial convolutional layers, then a max pooling layer The next sequence continues the pattern, with three more convolutional layers and a max pooling layer at the end. For smooth transition from the

convolutional process to densely connected layers, or "flattening" as it's often called here. A flattening layer is placed. The CNN uses a multi-layer approach to enable accurately pinpointing the complex patterns and Arlington-style organizations found in all these skin disease photos of dogs. After this phase of feature extraction is completed by the CNN, the pipeline integrates a Random Forest model. The ensemble model comprises 14 decision trees, each tree built to 12 levels deep. The Random Forest serves as a supplement to the CNN, taking advantage of its ability to handle data with many dimensions and intricate relationships. The final classification is arrived at by combining the contributions of 14 decision trees, leveraging ensemble learning techniques to merge their power. With the fundamental characteristics and relationships behind each of these skin disorders, experts can use a decision tree having 12 levels to gain in-depth understanding for more accurate, reliable diagnosis and categorization into different dog skin diseases. Both architectures together form an interactive strategy intended to exploit both CNNs and Random Forests to classify canine skin conditions. The structure of the proposed model is shown in Figure 2.




Fig. 2. Architectural overview

D. Model Training

The model training method mobilized the Convolutional Neural Network (CNN) and Random Forest for an effective diagnosis of canine skin diseases. At each phase of training, we take a picture library of 4053 carefully selected data as our material. A training-to-testing ratio of 70-30 assures the production of strong and reliable model that has been rigorously field-tested. Through all its training epochs, the Convolutional Neural Network (CNN) learned more expertly and increasingly fine-tuned parameters was used. To turn photo features extracted from various skin diseases into something even more valuable for future comparisons! CNN's convolution layers were very important in capturing complex patterns, while max pooling layer had the effect of reducing dimensional sizes sequentially. The Random Forest model is built on top of 14 decision trees - each 12 layers deep - which were trained with augmented and normalized data. In a CNN and Random Forest architecture integration, we were able to pinpoint quite exactly the complexity of connections within a farrago like this. Our final trained model will categorize whatever skin condition dogs would ever come according to its plausibility ranges, thus making feasible a practical diagnosis.

IV. RESULTS AND OUTCOMES

A. Experimental setup and implementation details

The research project is run with a focus on efficiency and integration of operations. Windows 11 presents a straightforward, friendly working environment. To write machine learning logic or interpret data in Python. The language used is increasingly popular and thus widely adopted. Jupyter's functions for interactive programming is not just capable of directly naming its output, it erects a foundation on which users can share live code, equations, visualizations and text. Windows 11, Python, and Jupyter make up a solid environment for an operating system. The user-friendly interface and visually-appealing styling of Windows 11 alone can bring even more convenience now; with Python as well Jupyter's abilities eliminate much more overhead by indulging in the operations research. In addition, since it is open source software Jupyter affords substantial room for improvement. Thus CNN and Random Forest models used to diagnose dog skin disease can be developed, tested documented by Python and run at Jupyter.

B. Overview of the training process

Feature abstraction and extraction in image categorization are both carried out through The network architecture has countless layers. The input layer represents 2048x2048x32 32-channel input images. Using Rectified Linear Unit (ReLU) activation functions for non-linearity, three sequential convolutional layers (Layers 1-3) with 3x3 filters and a stride of 3 minimise spatial dimensions while increasing filter count. Downsampling feature maps twice using max pooling (Layers 1-2). Later convolutional layers (4-6) collect complicated information, and the last layer before flattening is a max pooling layer that reduces spatial dimensions to 1x1x256. The flattening layer converts output into a one-dimensional vector for Random Forest models. The Random Forest, with 7 decision trees, uses this flattened vector to classify. This multi-layered architecture uses convolutional layers and a Random Forest to collect hierarchical characteristics and patterns for reliable canine skin disease categorization.

The confusion matrix provides a comprehensive evaluation of the effectiveness of a multi-class classification model in classifying 10 different types of canine skin disorders. The output displays both the current and projected categorizations, providing valuable information about the model's capabilities and places for improvement. The precision ratings, which range from 75.26% to 82.76%, demonstrate the accuracy of positive forecasts for each class. The model has a commendable overall accuracy of 79.20%, indicating its ability to accurately categorise cases across various skin conditions. The recall measure spans from 74.50% to 91.00%, indicating the model's proficiency in identifying true positive cases. The thorough assessment highlights the model's efficacy in classifying skin diseases in dogs.

TABLE I. PARAMETERS USED TO TRAIN THE MODEL

Layer Type	Filter Size	Stride	Output size	Number of Filters	Activation
Input	—	—	2048x2048x32	—	—
Convolutional Layer 1	3x3	3	683x683x32	32	ReLU
Convolutional Layer 2	3x3	3	228x228x64	64	ReLU
Convolutional Layer 3	3x3	3	76x76x128	128	ReLU
Max Pooling Layer 1	2x2	2	38x38x128	—	—
Convolutional Layer 4	3x3	3	13x13x256	256	ReLU
Convolutional Layer 5	3x3	3	5x5x256	256	ReLU
Convolutional Layer 6	3x3	3	2x2x256	256	ReLU
Max Pooling Layer 2	2x2	2	1x1x256	—	—
Flattening	—	—	256	—	—
Random Forest	—	—	7	—	—

Actual Value	0	476	23	34	14	21	1	4
	1	32	412	2	2	3	2	82
	2	11	43	444	45	45	4	4
	3	3	2	13	435	12	1	12
	4	67	21	16	5	511	45	15
	5	3	5	43	43	14	456	21
	6	12	4	23	34	15	42	476
		0	1	2	3	4	5	6
		Predicted Values						

Fig. 3. Confusion matrix

Table 2 shows illness categorization model performance metrics. True Positives are accurately detected cases for each illness, whereas False Positives are misclassified cases. False Negatives occur when the model missed the illness. The algorithm detects Flea Infestation well with 511 true positives but suffers with Canine Pyoderma with significant false negatives. The metrics show the model's accuracy and areas for development for robust illness categorization across canine skin diseases. A classification model for dog skin

disorders as shown in table 4 is evaluated using these measures. Precision measures positive prediction accuracy, recall measures the model's capacity to catch all positive events, and F1-score combines both. The algorithm accurately detects Flea Infestation (82.29%) and Canine Seborrhea (82.76%). The 91% recall rate of Canine Pyoderma shows its ability to detect genuine positives. The Macro Average and Weighted Average measure performance, with the latter compensating for class inequalities. The Micro Average balances Precision, Recall, and F1-score across courses. These metrics provide a complete assessment of the model's canine skin disease categorization performance.

TABLE II. ASSESSMENT BY PREDICTION

Diseases	True Positive	False Positive	False Negative
Ringworm	476	128	97
Dermoidosis	412	98	123
Canine Atopic Dermatitis	444	131	152
Canine Pyoderma	435	143	43
Flea infestation	511	110	169
Canine Seborrhea	456	95	129
Canine Autoimmune Sin Disorder	476	138	130

TABLE III. RESULTS

Type	Precision	Recall	F1-score
Ringworm	78.81	83.07	80.88
Dermoidosis	80.78	77.01	78.85
Canine Atopic Dermatitis	77.22	74.50	75.83
Canine Pyoderma	75.26	91.00	82.39
Flea infestation	82.29	75.15	78.55
Canine Seborrhea	82.76	77.95	80.55
Canine Autoimmune Sin Disorder	77.52	78.55	78.03
Macro Average	79.23	79.60	76.26
Weighted Average	79.38	79.20	79.15
Micro Average	79.20	79.20	79.20

V. CONCLUSION AND FUTURE SCOPE

Ultimately, this research used sophisticated machine learning methods such as Convolutional Neural Networks and Random Forest to improve the identification and categorization of seven common skin illnesses in dogs. By using a varied dataset consisting of 4,053 photos, our model demonstrated an impressive overall accuracy rate of 79.02%. The precision and recall measures provide valuable insights into the model's performance in relation to various diseases, highlighting its strong points in particular illnesses. The

suggested approach has the potential to assist in veterinary diagnostics. However, continuous improvement and growth of the dataset may make it even more reliable and effective in contributing to better health outcomes for dogs.

REFERENCES

- [1] S. Badotra and S. N. Panda, "SNORT based early DDoS detection system using Opendaylight and open networking operating system in software defined networking.," *Cluster Comput.*, vol. 24, pp. 501–513, 2021.
- [2] V. Kukreja, "Fuzzy AHP-TOPSIS approaches to prioritize teaching solutions for Intellect Errors," *J. Eng. Educ. Transform.*, vol. 35(4), pp. 50–58, 2022.
- [3] V. Kukreja and A. Aggarwal, "Multi-expert and multi-criteria evaluation of online education factors: A fuzzy ahp approach," *J. Eng. Educ. Transform.*, vol. 35(2), pp. 140–148, 2021.
- [4] S. Sharma *et al.*, "Deep learning model for the automatic classification of white blood cells.," *Comput. Intell. Neurosci.*, 2022.
- [5] N. Yanti, M. Mutiara, and A. Syahputri, "Expert System for Diagnosing Skin Diseases in Dogs using the Bayes' Theorem Method.," *J. Mantik*, vol. 5(4), pp. 2549–2555, 2022.
- [6] T. Olivry, "A review of autoimmune skin diseases in domestic animals: I–superficial pemphigus.," *Vet. Dermatol.*, vol. 17(5), pp. 291–305, 2006.
- [7] R. M. N. A. Rathnayaka, K. G. S. N. Anuththara, R. J. P. Wickramasinghe, P. S. Gimhana, L. Weerasinghe, and G. Wimalaratne, "Intelligent System for Skin Disease Detection of Dogs with Ontology Based Clinical Information Extraction.," in *In 2022 IEEE 13th Annual Ubiquitous Computing, Electronics & Mobile Communication Conference (UEMCON)*, pp. 0059–0066.
- [8] T. Olivry and H. A. Jackson, "Diagnosing new autoimmune blistering skin diseases of dogs and cats.," *Clin. Tech. Small Anim. Pract.*, vol. 16(4), pp. 225–229, 2001.
- [9] J. Rybníček, P. J. Lau-Gillard, R. Harvey, and P. B. Hill, "Further validation of a pruritus severity scale for use in dogs.," *Vet. Dermatol.*, vol. 20(2), pp. 115–122, 2009.
- [10] A. Noshad, A. Khonaksar, and M. Mohebbi, "Skinxnet: a dog-based model for automatic detection of skin lesion using deep learning.," in *In 2021 5th International Conference on Pattern Recognition and Image Analysis (IPRIA)*, pp. 1–6.
- [11] A. Upadhyay, G. Singh, S. Mhatre, and P. Nadar, "Dog Skin Diseases Detection and Identification Using Convolutional Neural Networks.," *SN Comput. Sci.*, vol. 4(3), p. 250, 2023.
- [12] B. G. M. Habal, P. E. S. Tiong, J. R. Pasatiempo, M. J. Balen, M. R. Amarga, and L. Juco, "Dog skin disease recognition using image segmentation and GPU enhanced convolutional neural network.," in *In 2021 IEEE 13th International Conference on Humanoid, Nanotechnology, Information Technology, Communication and Control, Environment, and Management (HNICEM)*, pp. 1–5.
- [13] D. M. A. Dissanayaka, K. M. Sifran, and D. I. D. S. Thiviya, J. E. T. A. Wijesinghe, "Skin Disease Detection of Pet Dogs and Identifying Home Remedies Using Machine Learning (SVM, NLP) and AI.," in *In 2022 3rd International Informatics and Software Engineering Conference (IISEC)*,