Designing an Ad Click Aggregator

> Interview-ready walkthrough: requirements → estimates → entities → API → HLD → deep dives (**scale of clicks, exactly-once-style correctness, hot ads, click fraud and dedup, reconciliation**) → trade-offs. The hard parts are **stream aggregation at 10K clicks/s** and **never losing or double counting**.

---

0. Talk track

1. Clarify: record clicks, redirect user, advertiser queries aggregated metrics (per-minute), fraud prevention.
2. Insight: **write-heavy ingest, read of aggregates, durability over low-latency**.
3. HLD: click processor to stream to aggregator to OLAP store.
4. Deep dives: scaling the pipeline, hot shards, idempotency/dedup, batch reconciliation (lambda), query layer.

---

1. Problem

When a user clicks an ad, **redirect** them to the advertiser's site and **record the click**. Advertisers query **aggregated click metrics** (by ad, by time) with up to **1-minute** granularity and low latency.

What makes it hard

- **10K clicks/s average, 100K peak**; no click may be lost.
- Aggregates must be **accurate** (billing) yet **fresh** (near real time).
- **Hot ads** during events; **duplicate/fraudulent clicks** must not be billed.

---

2. Requirements

Functional

- Users click an ad and are redirected to the advertiser's site.
- Advertisers query click metrics over time at **1-minute minimum granularity**.

Out of scope: ad targeting, impression tracking, conversion attribution, cross-device tracking.

Non-functional

- Scale: **10K clicks/s** peak 100K; billions of clicks stored.
- **Low-latency analytics queries** (about 100 ms-1 s).
- **Fault tolerant and accurate**: no data loss.
- **Near real-time** (data within minutes).
- **Idempotent** click tracking (no double counting).

---


3. Estimation

Quantity	Assumption	Result
Clicks	10K/s avg	**864M/day**
Click record	about 100 B	86 GB/day raw, about 30 TB/yr
Peak	10x	100K/s: Kafka partitions needed
Aggregates	10M ads x 1/min active	much smaller; stored as rollups

Consequence: raw log in cheap storage (S3), aggregated rollups in an OLAP/time-series store. Ingest scales through **partitioned stream**.

---

4. Entities



---


5. API

```
GET /click?ad_id=a1&impression_id=<signed token>     -> 302 Location: advertiser URL   # also records
GET /metrics?ad_id=a1&from=...&to=...&granularity=minute -> [{ts, clicks}]
```

Redirect target is **looked up server-side** (cached ad_id to URL), never taken from the client (open-redirect/fraud).


---

6. Architecture



---

7. Flow



---

8. Deep dive 1: ingest and aggregation

Approach	Verdict	Why
Write each click to SQL, aggregate with `GROUP BY`	Bad at scale	Write amplification; slow analytics
Batch only (Spark every N min)	Good	Accurate, but stale
Stream (Kafka + Flink) with windowed aggregation	Great	Near real-time; can combine with batch

Acknowledge the click once it's durably in **Kafka** (acks=all, replication factor 3), then redirect. Redirect shouldn't wait on aggregation. Flink checkpointing plus idempotent sink gives effectively-once.

9. Deep dive 2: hot ads

A viral ad hammers one partition keyed by `ad_id`. Mitigate: **key salting** (`ad_id#0..N`), aggregate partial counts per salt, then merge in a second stage; or pre-aggregate in the click processor in 1 s micro-batches before producing.

10. Deep dive 3: dedup and fraud

- **Impression id**: server issues a **signed, single-use impression token** embedded in the ad; the click must present it. Dedup `(impression_id)` via Redis `SET NX` with TTL (or in Flink state) so repeated clicks on one impression count once.
- Bot detection: rate limit per IP/user, anomaly detection offline; mark clicks invalid but **retain** raw record.
- Ads can be invalidated post hoc (billing correction) via batch recompute.

11. Deep dive 4: accuracy and reconciliation

Lambda-style: stream gives fast, approximate-fresh numbers; **batch from the raw S3 log** recomputes the truth periodically and overwrites rollups. Handles late events, bugs, and replay. Raw log is the **source of truth** (append-only, immutable).

12. Query layer

OLAP stores (columnar, pre-aggregated) answer time-range queries fast. Optional **pre-rollups** at minute, hour, day to avoid scanning; result cache for dashboards; sharded by ad_id/time.

---

13. Failure handling

Failure	Mitigation
Click processor crash	Stateless, LB reroutes; client retry safe via dedup
Kafka broker down	Replication ISR; producer retries with idempotence
Flink job failure	Restart from checkpoint, offsets replay
OLAP write duplicates	Upsert keyed `(ad_id, minute)`
Late/out-of-order	Event-time windows + watermarks + batch fix
Kafka lag	Alert; autoscale consumers

---

14. Trade-offs

Decision	Chosen	Alternative	Given up
Ingest	Kafka	Direct DB write	Extra infra; gains durability and buffering
Aggregation	Stream plus batch	Stream only	Dual pipelines to maintain
Dedup	Signed impression ids	IP heuristics	Needs impression tracking
Storage	Raw S3 + OLAP rollups	OLAP only	Cost for storing raw
Freshness	About 1 min	Sub-second	Window latency

---

15. Level expectations

- **Mid:** click log, redirect, DB aggregation.
- **Senior:** Kafka + Flink, partitioning, OLAP, idempotency, batch backup.
- **Staff+:** hot-key salting, watermarks/late data, fraud pipeline, reconciliation, exactly-once semantics.

16. Follow-ups

Conversion attribution, budget pacing (real-time spend limits), per-user frequency capping, multi-region ingest.

17. Summary checklist

- [ ] Durable Kafka before redirect, partition by ad_id (salt hot)
- [ ] Flink minute windows, idempotent upsert to OLAP
- [ ] Signed impression IDs for dedup
- [ ] Raw S3 log and batch reconciliation
- [ ] Cached query layer on pre-rolled aggregates