

Ground Control Station (GCS) & Swarm Autonomy

Enhancement Proposal & Implementation Roadmap

Executive Summary: This proposal outlines 20 systematic enhancements designed to elevate the UAV-X system to international competitive excellence (DARPA SubT / MBZIRC / Techfest standards). The core focus is moving beyond basic visualization to **observable communication-aware autonomy**: deterministic lifecycle state machines, visible multi-hop network degradation before and after self-healing, predictive battery Return-to-Launch (RTL), dynamic high-priority triage, and reproducible benchmark evidence.

1. Top 7 Critical Action Items (Immediate Sprint)

If engineering time is constrained, these seven features must be implemented first to satisfy evaluation rubrics regarding observable fault recovery and mission state honesty:

Priority Item	Current Problem	Required Engineering Change	Competition Value
1. Start at MISSION READY	Dashboard boots showing TICK 299 & MISSION COMPLETE.	Boots at TICK 0, POIs 0/7, PACKETS 0, NETWORK STANDBY, swarm sitting on launchpad.	Crucial: Demonstrators must see mission start on command.
2. Click-to-Run Paced Sim	Simulation executed instantly in 9 sec background loop.	Simulation only runs on START MISSION; ticks advance at observable pace (150ms/tick).	Allows evaluators to watch autonomy unfold live.
3. Explicit Recovery Event Flow	UAV-05 simply appears as FAILED with missing intermediate steps.	Emit discrete event sequence: FAULT_INJECTED -> TIMEOUT -> RELAY_LOST -> ROUTE_DEGRADED -> PROMOTED -> RECOVERED.	Provides clear, auditable evidence of self-healing autonomy.
4. Quantitative Network Degradation	Network health is static (100% coverage shown constantly).	Expose real degradation: packet loss jumps 2% -> 48% -> 4%; latency spikes 42ms -> 210ms -> 84ms.	Proves the network actually broke and recovered.
5. Active Route & Hop Trace	Links are generic dashed lines without route context.	Color-code links (Green/Amber/Red/Purple) and display active path: GCS -> UAV-01 -> UAV-03 -> UAV-08 (Hops: 3).	Demonstrates multi-hop mesh routing visually.
6. Dynamic Critical Pol-H	Scenario targets are static and predefined.	Inject mid-mission survivor discovery (Pol-H); nearest scout preemptively reassigned from low priority.	Directly addresses the competition requirement for task preemption.
7. Fleet Role Consistency	Table, map, and log occasionally display out-of-sync roles.	Single source of truth for states: SCOUT, RELAY, RESERVE, RETURNING, FAILED, LANDED.	Eliminates contradictions during technical Q&A;

2. Complete Specification of the 20 Improvements

Below is the comprehensive engineering breakdown categorized into system domains:

A. Mission Lifecycle, State Machine & Status Monitoring

- [Item 1] Initial Mission State Correction:
- Current Defect: The dashboard initializes with pre-run values: TICK 299, MISSION COMPLETE, POIs SURVEYED 6.
 - Required Implementation: Initialize state to: STATUS: MISSION READY, TICK 0, POIs 0/7, PACKETS 0, NETWORK STANDBY. UAVs sit on launchpad at GCS coordinates.
 - Formal Lifecycle: MISSION READY -> MISSION RUNNING -> DEGRADED -> RECOVERING -> COMPLETE.
- [Item 2] Deterministic Start Execution:
- Clicking **START MISSION** must reset telemetry buffers, zero packet counters, transition state to RUNNING, and advance ticks at a controllable speed (150ms default) rather than instantaneous headless execution.

[Item 3] Prominent Color-Coded Mission Status Bar:

- Header banner displaying: STATUS: [STATE] | TIME: mm:ss / 10:00 | TICK: XXX | SCENARIO: EARTHQUAKE-01 | SEED: 20260926.
- Standard color codes: Ready (Blue), Running (Green), Degraded (Amber), Recovering (Purple), Failed (Red), Complete (Green).

B. Comms Modeling, Fault Injection & Self-Healing Telemetry**[Item 4] Step-by-Step Relay Failure & Recovery Sequence:**

- Replace abrupt failure with auditable event stream at tick 80:
 - [80] FAULT_INJECTED: UAV-05 motor failure injected
 - [81] HEARTBEAT_TIMEOUT: No MAVLink heartbeat from UAV-05 (loss threshold exceeded)
 - [82] RELAY_LOST: Active relay UAV-05 dropped from routing topology
 - [83] ROUTE_DEGRADED: Backbone packet loss spiked to 48%, latency to 210ms
 - [84] RELAY_SELECTION: Searching reserve pool for replacement node
 - [85] RELAY_PROMOTED: UAV-06 promoted from RESERVE to RELAY
 - [86] ROUTE_REBUILT: New route established: GCS -> UAV-06 -> UAV-08
 - [87] NETWORK_RECOVERED: Packet loss reduced to 4%, latency restored to 84ms
 - [88] QUEUE_FLUSHED: 3 buffered packets successfully delivered to GCS

[Items 5 & 6] Dedicated Network Health Panel & Observable Degradation:

- Dedicated dashboard widget reporting: Connected UAVs (9/10), Active Route, Hop Count (3), Packet Loss %, Latency (ms), Throughput (Mbps), Queued Packets, and Time Since Last Recovery.
- Numerical tracking before failure (Loss 2%, Latency 42ms), during failure (Loss 48%, Latency 210ms), and after recovery (Loss 4%, Latency 84ms).

[Item 7] Color-Coded Route Visualization:

- Map link rendering: **Solid Green** (Healthy Active), **Solid Amber** (Degraded / Weak SNR), **Dashed Red** (Severed Link), **Solid Purple** (Newly Negotiated Recovery Route), **Gray** (Standby Available).
- Dynamic HUD card: ACTIVE ROUTE: GCS -> UAV-01 -> UAV-06 -> UAV-08 | HOPS: 3 | STATUS: HEALTHY.

C. Fleet Role Consistency, Dynamic Triage & Battery Scheduling**[Item 8] Strict Fleet Role Consistency:**

- Unified role taxonomy across database, fleet table, 2D/3D map, and event logs: SCOUT, RELAY, RESERVE, RETURNING, FAILED, LANDED.
- Fleet table columns: UAV | ROLE | BATTERY | LINK QUALITY | TASK | STATUS.

[Item 9] Dynamic High-Priority Pol-H Event (Preemptive Triage):

- At tick 120, system triggers: NEW HIGH-PRIORITY Pol DETECTED: Pol-H [CRITICAL] (survivor acoustic/thermal signal).
- Swarm immediately preempts nearest scout (UAV-07) from routine inspection (Pol-F) to Pol-H, demonstrating real-time task preemption.

[Item 10] Battery-Aware Task Management & RTL Handover:

- Compute real-time return energy budget accounting for headwind and distance: $E_{\text{return}} = \text{integral}(P_{\text{drag}} + P_{\text{hover}})dt$.
- Displays: Battery %, Est Flight Time, Return Reserve %, Distance to GCS, Safe Return Margin (Yes/No).
- Automated task handover when battery drops to 25%: Pol reassigned to a reserve UAV while depleting UAV executes RTL.

[Item 11] Granular Pol Progress Lifecycle:

- Full Pol states: UNASSIGNED -> ASSIGNED -> IN TRANSIT -> SURVEYING -> UPLOADING -> SURVEYED.
- Progress breakdown widget: Total Surveyed (4/7) | Critical (2/2) | High (1/2) | Medium (1/2) | Low (0/1).

D. Packet Ledger, Mapping Enhancements & Baseline Benchmarking**[Item 12] Packet Delivery Ledger & Hop Trace:**

- Log full multi-hop path per packet: PKT-0004: UAV-08 -> UAV-06 -> UAV-01 -> GCS [Hops: 3, Latency: 92ms, Loss: 0%].
- Summary ledger card: Created, Delivered, Queued, Lost, Delivery Success Rate %.

[Item 13] Real-Time Event Timeline with Category Filters:

- Category badge filtering: ALL | FAULTS | NETWORK | UAVs | SAFETY.

[Items 14 & 15] 2D & 3D Tactical Battlespace Enhancements:

- **2D Map:** Add disaster zone perimeter fence, obstacle building blocks, safe staging area, and UAV coverage circles.
- **3D Battlespace:** Integrated Chase Cam (following active scout in 3D), Thermal IR false-color video monitor with AI YOLO detection brackets, and telemetry HUD.

[Item 16] Baseline Comparison Widget (Technical Proof):
• Benchmark table directly proving the superiority of UAV-X dynamic autonomy over standard fixed relaying:

Metric	Baseline (Fixed Relays)	UAV-X (Dynamic Swarm)	Advantage
PolS Completed	4 / 7 (57%)	7 / 7 (100%)	+43% Coverage
Packet Delivery Rate	61.2%	96.4%	+35.2% Reliable
Average Latency	220 ms	88 ms	60% Lower Latency
Failure Recovery Time	Infinite (Chain Broken)	3.8 Seconds	Autonomous Self-Healing
Safe UAV Returns	2 / 4 (Crashes occurred)	10 / 10 (Zero Crashes)	Guaranteed Safety

E. Replay Controls, Parameter Configuration & Safety Compliance

[Item 17] Replay & Speed Controls: Play, Pause, Restart, scrubber timeline, and speed buttons (0.5x, 1x, 2x, 4x).
[Item 18] Scenario Parameter Configuration: Dropdown controls to toggle relay failure, dynamic Pol, wind velocity, and seed.
[Item 19] One-Click Run Data Export: Export mission_summary.json, events.jsonl, telemetry.csv, and safety_report.json for technical paper / submission packets.
[Item 20] Autonomous Safety Monitor Checklist: Live checklist monitoring collision separation (>20m), no-fly zone bounds, and battery reserves.

3. Recommended 4-Sprint Implementation Schedule

Sprint	Focus Scope	Deliverables & Key Modules	Target Output
Sprint 1 (Immediate)	Core State Machine & The Top 7 Critical Fixes	• Fix initial MISSION READY state • Click-to-run paced sim (150ms/tick) • Active colored status bar • 8-step failure event flow • Network Health Panel & route loss % • Colored route lines (Grn/Amb/Red/Purp)	GCS starts cleanly at Tick 0 and visibly shows self-healing sequence.
Sprint 2	Mission Intelligence & Dynamic SAR Events	• Dynamic Pol-H insertion event • Autonomous task preemption • Predictive battery flight time & RTL handover • Packet Ledger with multi-hop trace	Autonomous prioritization of newly detected critical survivor sites.
Sprint 3	Visual Polish & Operator Ergonomics	• Event log category filters • Enhanced 2D disaster perimeter & obstacles • Baseline Comparison Panel • Safety Monitor compliance widget	High-fidelity tactical presentation ready for video recording.
Sprint 4	Replay Controls & Export Package	• Play/Pause & speed toggles (0.5x - 4x) • Scenario parameter controls • One-click telemetry & report export (JSON/CSV) • Technical proposal screenshot capture	Final submission-ready package with full audit trail.

4. Engineering Team Review & Sign-Off

Please review the proposed architectural enhancements and sprint allocations. Record team member comments and approvals below before proceeding with deployment:

Team Member / Role	Approval Status	Design Notes & Feedback	Sign-Off Date
Lead Autonomy Engineer	☐ Approved ☐ Revisions Req.	Verify B-spline replanning frequency during dynamic relay promotion.	____ / ____ / 2026
Communications & RF Lead	☐ Approved ☐ Revisions Req.	Confirm NS-3 Nakagami-m fading parameters align with urban rubble model.	____ / ____ / 2026
Mission Software & GCS Lead	☐ Approved ☐ Revisions Req.	Ensure Three.js WebGL canvas maintains 60 FPS during thermal PIP rendering.	____ / ____ / 2026

Project Captain / Submitter	☐ Approved ☐ Revisions Req.	Approve Sprint 1 implementation for video recording.	____ / ____ / 2026
-----------------------------	---	--	--------------------