

[Explore](#)[Problems](#)[Interview](#)

New

[Contest](#)[Discuss](#)[Store](#)[☆ Premium](#)[Description](#)[Solution](#)[Discuss \(999+\)](#)[Submissions](#)

28. Implement strStr()

Easy

[4430](#)[3765](#)[Add to List](#)[Share](#)

Implement strStr().

Given two strings `needle` and `haystack`, return the index of the first occurrence of `needle` in `haystack`, or `-1` if `needle` is not part of `haystack`.

Clarification:

What should we return when `needle` is an empty string? This is a great question to ask during an interview.

For the purpose of this problem, we will return 0 when `needle` is an empty string. This is consistent to C's `strstr()` and Java's `indexOf()`.

Example 1:

Input: `haystack = "hello", needle = "ll"`

Output: 2

Example 2:

Input: `haystack = "aaaaa", needle = "bba"`

Output: -1

Constraints:

- `1 <= haystack.length, needle.length <= 104`
- `haystack` and `needle` consist of only lowercase English characters.

Accepted 1,310,629

Submissions 3,592,037

Seen this question in a real interview before?

Companies

Related Topics

Similar Questions

[⌵ Problems](#)[✖ Pick One](#)[◀ Prev](#)

28/2329

[Next ▶](#)