

Description

Solution

Discuss (999+)

Submissions

C++

Autocomplete

235. Lowest Common Ancestor of a Binary Search Tree

Easy

6488

207


Add to List

Share

Given a binary search tree (BST), find the lowest common ancestor (LCA) node of two given nodes in the BST.


According to the definition of LCA on Wikipedia: "The lowest common ancestor is defined between two nodes p and q as the lowest node in T that has both p and q as descendants (where we allow **a node to be a descendant of itself**)."

Example 1:



Input: root = [6,2,8,0,4,7,9,null,null,3,5], p = 2, q = 8
Output: 6
Explanation: The LCA of nodes 2 and 8 is 6.

Example 2:



Input: root = [6,2,8,0,4,7,9,null,null,3,5], p = 2, q = 4
Output: 2
Explanation: The LCA of nodes 2 and 4 is 2, since a node can be a descendant of itself according to the LCA definition.

Example 3:

Input: root = [2,1], p = 2, q = 1
Output: 2

Constraints:

- The number of nodes in the tree is in the range $[2, 10^5]$.
- $-10^9 \leq \text{Node.val} \leq 10^9$
- All Node.val are **unique**.
- $p \neq q$
- p and q will exist in the BST.

Accepted 848,204

Submissions 1,457,941

Seen this question in a real interview before?

Yes

No

Companies

Related Topics

```
1  /**
2   * Definition for a binary tree
   * node.
3   * struct TreeNode {
4   *     int val;
5   *     TreeNode *left;
6   *     TreeNode *right;
7   *     TreeNode(int x) : val(x),
   left(NULL), right(NULL) {}
8   * };
9   */
10
11 class Solution {
12 public:
13     TreeNode*
   lowestCommonAncestor(TreeNode*
   root, TreeNode* p, TreeNode* q)
   {
14         if(root == nullptr)
15             return root;
16         TreeNode* l =
   lowestCommonAncestor(root->left,
   p, q);
17         TreeNode* r =
   lowestCommonAncestor(root->right,
   p, q);
18
19         if(root == p || root ==
   q || (l != nullptr and r !=
   nullptr))
20             return root;
21
22         return l == nullptr? r:
   l;
23     }
24 }
```

Testcase

Run Code Result

Debugger

Accepted

Runtime: 4 ms

Your input

[6,2,8,0,4,7,9,null,null,3,5]

Output

6

Diff

Expected

6