DCS API
DCS Seamless wallet API document

Version	Date	Description
1.01	2022-06-30	DCS API document created
1.01	2022-07-17	Adjustment: 2.8 FreeSpin Campaign Player Setup 4.1 DCS API Response Code 4.5 Wager_type
1.02	2022-08-08	Adjustment: 2.1 Login Game，brand_uid String(32) => String(20)
1.10	2022-08-15	Add Special Remarks in: 3.2 Wager 3.3 CancelWager 3.4 AppendWager 3.5 EndWager 3.6 FreeSpinResult Adjustment: 4.1 DCS API Response Code
1.11	2022-08-30	Add Special Remarks in: 3.3 CancelWager Response code
1.12	2022-09-19	Add providers in 4.6 Provider code nlc – Nolimit City png – Play'n Go hs - Hacksaw
1.13	2022-09-29	Adjustment: 3.Brand API endpoints implementation，Response code String(7) => Int
1.14	2022-10-13	Add VES、SSP in 4.2 Currency code List Add providers in 4.6 Provider code: aux - Avatarux
1.15	2022-10-31	Add 5042 to Special Remarks in 3.5 EndWager Change "campaign" description in 4.5 wager_type
1.16	2022-11-09	Add cancelEndWager, promopayout in 4.5 Wager_type Add wager_type property in 3.3 cancelWager, Add bet_type property in 3.2 Wager

		Add tip, game_result property in 2.3 Response Add providers in 4.6 Provider code evo – Evo Play gam – Solid/Gamomat ghg – Solid/Golden Hero psh – Solid/Push ezugi – Ezugi swf – Solid/WinFast ft –FunTa Add 3.8 promoPayout Method Adjustment: 2.3 Report Request restriction
1.17	2022-11-29	1. Delete 2.6 Get Jackpot Information Method 1.1 previous version function no. 2.7 function no. change to 2.6 1.2 previous version function no. 2.8 function no. change to 2.7 1.3 previous version function no. 2.9 function no. change to 2.8 2. Add currency property in 3.3 cancelWager
1.2	2022-12-27	Brand API endpoints implementation: Adjust 3.2 Wager, 3.3CancelWager, 3.4 AppendWager, 3.5EndWager, 3.6FreeSpinResult, adding “is_endround” property
1.21	2023-02-03	1. Adjust 8.3 PromoPayout Sign rule 2. Adjust 3.2 Wager Special Remarks
1.22	2023-04-30	4.1 DCS API Response Code add 5019, 5020 4.6 Provider Code Edit ft To funta Adjustment: 2.1 Login game -> token description Add game_result property in 3.5 Endwager request Add Special remarks in 3.8 promoPayout Adjustment: amount, balance Type Decimal(16,2) into Decimal(16,6)
1.23	2023-06-06	Adjustment: 2.4 Game Replay description 4.1 DCS API Response Code add 5021, 5023, 5024
1.24	2023-07-14	Adjustment: 4.1 DCS API Response Code 5009, 5013 description Add providers in 4.6 Provider code mj – 7Mojos fm - Fantasma ps – Peter & Sons

1.25	2023-10-16	Add providers in 4.6 Provider code sb – Spribe plb – Parlay bay 2.3 Report add “is_endround” parameter in response
1.26	2024-01-10	Remove currency: uBTC, UBC Add provider in 4.6 Provider Code: evl – Evolution btg – Big Time Gaming ne – NetEnt rt – Red Tiger dcace – DCACE tg/tgo – Turbo Games wz – Wazdan Add content property in 2.5 Get Game List response Add freespin_id, freespin_description in 3.6 FreeSpinResult request
1.27	2024-04-22	Add provider in 4.6 Provider Code: tk – Thunderkick
1.30	2024-5-29	Add provider in 4.6 Provider Code: lm – Lucky Monaco yt - Yolted
1.31	2024-7-31	Add provider in 4.6 Provider Code: sa – SA gaming ss – Smartsoft bg –Bgaming
1.32	2024-08-28	1. Add provider in 4.6 Provider Code: nm – Novomatic op – Octoplay bp – BluePrint 2. 3.8 PromoPayout Special Remarks adjustment
1.33	2024-10-30	1. Add provider in 4.6 Provider Code: hso - Hacksaw Gaming ROW hsl - Hacksaw Gaming Latam 2. 4.1 DCS API Response Code add 5025 3. 4.6 Provider description revision: Wazdan => Voltent (Wazdan)

1.34	2025-2-25	1. Add provider in 3.6 Provider Code: 1.1 tq – Tequity 1.2 raw – RAW 2. Remove provider in 3.6 Provider Code : 2.1 ghg – Golden Hero
1.35	2025-03-18	The following method adds an attribute parameter transaction_time VARCHAR(20). 3.2 Wager 3.3 CancelWager 3.4 AppendWager 3.5 EndWager 3.6 FreeSpinResult 3.8 PromoPayout
1.36	2025-03-28	Adjust the following method attribute parameter transaction_time description 3.2 Wager 3.3 CancelWager 3.4 AppendWager 3.5 EndWager 3.6 FreeSpinResult 3.8 PromoPayout
1.37	2025-04-24	1. Adjust the following methods regarding the description of Code 5043 3.2 Wager 3.3 CancelWager 3.4 AppendWager 3.5 EndWager 3.6 FreeSpinResult 3.8 PromoPayout
1.38	2025-07-21	1. Add request parameters, request restriction, response information, and add start_time for the response in 2.8 FreeSpin Campaign Query 2. Add provider in 4.6 Provider Code: bm – Booming Games
1.39	2025-08-12	1. 4.6 Provider description revision: Tequity => Originals (Tequity) 2. 4.2 Remove Currency Code List “TWD”

		3. Add provider in 4.6 Provider Code: ag – PlayACE pts – PlayTech Slot ptc – PlayTech Casino
1.40	2025-09-22	1. Add 2.9 Report Summary 2. Change parameter: brand_id => String(9)

Table of content

1. API information and path 9
2. DCS endpoint 9
   - 2.1 Login Game 10
     - Request 10
     - Response 11
   - 2.2 Try Game 11
     - Request 11
     - Response 12
   - 2.3 Report 13
     - Request restriction 13
     - Request 13
     - Response 13
     - Response information 14
     - Special Remarks 14
   - 2.4 Game Replay 15
     - Request 15
     - Response 15
     - Response information 15
   - 2.5 Get Game List 17
     - Request 17
     - Response 17
   - 2.6 FreeSpin Campaign Setup 18
     - Request 18
     - Response 18
     - Response information 18
   - 2.7 FreeSpin Campaign Player Setup 19
     - Request 19
     - Response 19
   - 2.8 FreeSpin Campaign Query 20
     - Request restriction 20
     - Request 20
     - Response 20
     - Response information 21

2.9 Report Summary 22
Request restriction 22
Request 22
Response 22
Response information 23
Important 24
3. Brand API endpoints implementation 24
3.1 Login Authentication 25
Request 25
Response 25
3.2 Wager 27
Request 27
Response 28
Special Remarks 28
3.3 CancelWager 29
Request 29
Response 29
Special Remarks 30
3.4 AppendWager 31
Request 31
Response 31
Special Remarks 32
3.5 EndWager 33
Request 33
Response 33
Special Remarks 34
3.6 FreeSpinResult 35
Request 35
Response 36
Special Remarks 36
3.7 GetBalance 37
Request 37
Response 37
3.8 PromoPayout 38
Request 38
Response 39
Special Remarks 39
4. Appendix 40
4.1 DCS API Response Code 40

4.2 Currency code List 42
4.3 Language code list 46
4.4 Country_code 48
4.5 Wager_type 48
4.6 Provider List 49

DCS API Description

1. API information and path

Name	Description
api_url	API URL, DC provides to the Operator
getBetData_url	Get bet detail URL, DC provides to the Operator
api_key	Key used for endpoint validation, DC provides to the Operator
brand_id	Brand ID, DC provides to the Operator
brandApi_url	Brand api url, DC provides to the Operator

2. DCS endpoint

Request parameter “sign” is MD5 encrypted containing request info parameters + api_key. When operator calls endpoint, the request info parameters will be different and required. api_key is provided by DC. Additionally, please refer to Appendix 3. for parameters including currency, country, and language.

Endpoint request method and content type：

Method	Content Type
POST	application/json

Endpoint request common parameters：

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID

sign	Yes	String32)	MD5 encryption and transform into CAPITAL Encrypted detail will describe in each endpoint Do not put "+" sign when concatenating messages

Endpoint response common parameters：

Name	Required	Type	Description
code	Yes	Int	Refer to DCS API Response code, check Appendix 4.1
msg	Yes	String(50)	Messages

2.1 Login Game

Login Game method allows players to log into the games. Operator receives launch url with game_url for the game.

Request

EndPoint : {api_url}/dcs/loginGame

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID
sign	Yes	String(32)	Sign = MD5(brand_id+brand_uid+api_key)
brand_uid	Yes	String(20)	Unique User ID from operator (Only support english characters and numbers, case insensitive)
token	Yes	String(32)	Operator provides token for player to launch the games, DC api will request token verification to operator wallet api (Please check login endpoint 3.1), recommend using GUID (or any other unique identifier) to renew token when player launches different game to avoid duplicate.
game_id	Yes	Int	DC Game ID
currency	Yes	String(4)	Player currency code, check Appendix 4.2
language	Yes	String(7)	Language showed in the game, check Appendix 4.3

channel	Yes	String(6)	'pc' or 'mobile'
country_code	Yes	String(2)	Player country code, check Appendix 3.4
return_url	No	String(50)	Use for home button or redirection URL (Only provided in part of games)
full_screen	No	Boolean	Full screen game display (Only provided in part of games)

Response

code	Response
1000	{"code": 1000,"data": {"game_url":"http://xxxxxxxxxxx"},"msg": " Success."}

2.2 Try Game

This method allows players to launch the games in demo mode (without real money)

Request

EndPoint : {api_url}/dcs/tryGame

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID
sign	Yes	String(32)	sign = MD5(brand_id+game_id+api_key)
game_id	Yes	Int	DC Game ID
currency	Yes	String(4)	Player currency code, check Appendix 4.2
language	Yes	String(7)	Language showed in the game, check Appendix 4.3
channel	Yes	String(6)	'pc' or 'mobile'
return_url	No	String(50)	Use for home button or redirection URL (Only provided in pa of games)
full_screen	No	Boolean	Full screen game display (Only provided in part of games)

Response

code	Response
1000	{"code": 1000,"data": {"game_url":"http://xxxxxxxxxxx"},"msg": " Success."}

2.3 Report

Request restriction

The interval between start_time and end_time must be within 24 hours. The data provided is within 6 months. The frequency is 3 sec per request.

The api also supports the paging function. Operator passes the page parameter to 1 in the first request of the same time interval. Each page can provide up to 5000 pieces of data. The total number of pages can be calculated from the total_count parameter in the response information. The calculation method is as follows: page.total_count/5000 unconditional carry to the integer. Reports are generated in UTC time zone.

Request

EndPoint : {getBetData_url}/dcs/getBetData

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID
sign	Yes	String(32)	sign = MD5(brand_id+start_time+end_time+api_key)
page	Yes	Int	Page index
start_time	Yes	String(19)	Starting time format (yyyy-MM-dd HH:mm:ss)
end_time	Yes	String(19)	Ending time format (yyyy-MM-dd HH:mm:ss)
currency	Yes	String(4)	Player currency code, check Appendix 4.2
provider	Yes	String(20)	Game provider code, check Appendix 4.6
brand_uid	No	String(20)	Unique User ID from operator (Only support english characters and numbers, case insensitive)

Response

code	Response
1000	{ "code": 1000, "msg": "Success.",

```
        "data": [
            {
                "brand_uid": "TestUser",
                "currency": "CNY",
                "wager_type": "endWager",
                "amount": 10000.12,
                "before_amount": 806585.06,
                "after_amount": 816585.18,
                "game_id": "7382",
                "game_name": "Lucky Neko",
                "round_id": "1905291058028500001",
                "wager_id": "1905291058028500001",
                "jackpot_contribution": 0.0,
                "jackpot_win ": 0.0,
                "description":"",
                "create_time": "2019-05-29 10:58:24",
                "game_result":"{....}",
                "tip":0.0,
                "is_endround": false
            }
        ],
        "page":{
            "current_page":1,
            "total_count": 1
        }
    }
```


Response information

wager_type：Check Appendix 4.5

page.current_page：Current page index

page.total_count：Total page count (5k results per page)

Special Remarks

When the Provider is SA Gaming and the game is Pok Deng, Player 1 to Player 5 will withhold 2 times of the bet amount.

2.4 Game Replay

The method returns player bet record replay for a specific round. The request restriction is 3 seconds per brand.

Request

EndPoint : {api_url}/dcs/getReplay

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID
sign	Yes	String(32)	sign = MD5(brand_id+round_id+api_key)
brand_uid	Yes	String(20)	Unique User ID from operator (Only support english characters and numbers, case insensitive)
currency	Yes	String(4)	Player currency code, check Appendix 4.2
provider	Yes	String(20)	Game provider code, check Appendix 4.6
round_id	Yes	String(64)	Game round ID

Response

code	Response

1000	{
	"code": 1000,
	"msg": "Success.",
	"data": {
	"record": "http://{xxxxxxxxxx}/replay/{roundid}",
	"record_type": "URL",
	}
	}

Response information

There are three types of data.record_type,

Text：data.record output text format for game result

URL：data.record output URL format, operator needs to check the bet record via certain URL

Html：data.record output in HTML format for game result

2.5 Get Game List

Request

EndPoint : {api_url}/dcs/getGameList

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID
sign	Yes	String(32)	sign = MD5(brand_id+api_key)
provider	No	String(20)	Game provider code, check Appendix 4.6

Response

code	Response

1000	{
	"code": 1000,
	"msg": "Success.",
	"data": [
	{
	"provider": "yg",
	"game_id": 7316,
	"game_name": "Vikings go Wild",
	"game_name_cn": "狂野北欧海盗",
	"release_date": "2015-07-31 ",
	"rtp": "96.30%",
	"game_icon": "https://XXXX?e=tIn7KM",
	"content_type": "Standard",
	"game_type": "SLOT ",
	"content": "Yggdrasil"
	}
	]
	}

2.6 FreeSpin Campaign Setup

This method allows to create FreeSpin Campaign

Request

EndPoint : {api_url}/dcs/createFreeSpin

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID
sign	Yes	String(32)	Sign = MD5(brand_id+end_time+api_key)
game_id	Yes	Int	DC Game ID for assigning freespin
currency	Yes	String(4)	FreeSpin currency, check Appendix 4.2
end_time	Yes	String(19)	Campaign end time, UTC time zone, format: yyyy-MM-dd HH:mm:ss
description	No	String(100)	FreeSpin campaign description

Response

code	Response

1000	{
	"code": 1000,
	"msg": "Success.",
	"data": {
	"freespin_id": 10001,
	"usable_amounts": [0.5, 2.0, 5.5]
	}
	}

Response information

data.usable_amounts: Only provider ‘yg, hs, png, nlc, evo’ responds a list of usable amounts.

2.7 FreeSpin Campaign Player Setup

This method allows operators to bind the FreeSpin Campaign to specific players.

Request

EndPoint : {api_url}/dcs/addFreeSpin

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID
sign	Yes	String(32)	Sign = MD5(brand_id+freespin_id+api_key)
freespin_id	Yes	Long	freespin_id from the response of 2.7 createFreeSpin
round_count	Yes	Int	FreeSpin rounds
amount	Yes	Decimal(16,6)	Bet amount per FreeSpin If the provider is yg, please put one of the values in usable_amounts. No restriction for other provider, but please make sure the amount is in bet limit.
brand_uids	Yes	List<String(20)>	Assign campaign to a list of brand_uid (Only support english characters and numbers, case insensitive) E.g.: "brand_uids": ["DemoUser01","DemoUser02"]

Response

code	Response

1000	{
	"code": 1000,
	"msg": "Success.",
	"data": {
	"result": "Success."
	}
	}

2.8 FreeSpin Campaign Query

Operator can use the api to query details of existing FreeSpin Campaign.

Request restriction

- If start_after and end_before are not filled in, the default query is for FreeSpin created within 7 days.
- If start_after is filled in and end_before is not filled in, the query is 30 days after start_after.
- If start_after is not filled in and end_before is filled in, the query is 30 days before end_before.
- If both start_after and end_before are filled in, the query is up to 30 days; If freespin_uid is filled in, there is no time limit.

Request

EndPoint : {api_url}/dcs/queryFreeSpin

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID
sign	Yes	String(32)	Sign = MD5(brand_id+game_id+api_key)
game_id	Yes	Int	DC Game ID for FreeSpin assigned
currency	No	String(4)	FreeSpin currency, check Appendix 4.2
freespin_id	No	Long	freespin_id from the response of 2.12 createFreeSpin
brand_uid	No	String(20)	Unique User ID from operator
start_after	No	String(19)	Campaign start time, UTC time zone, format: yyyy-MM-dd HH:mm:ss
end_before	No	String(19)	Campaign end time, UTC time zone, format: yyyy-MM-dd HH:mm:ss

Response

code	Response
1000	{ "code": 1000,

```
        "msg": "Success.",
        "data": [
        {
            "freespin_id": 10001,
            "start_time": "2022-08-20 00:00:00",
            "end_time": "2022-08-30 00:00:00",
            "provider": "yg",
            "game_id": 880001,
            "currency": "CNY",
            "status":0,
            "round_count":10,
            "amount":2.65,
            "brand_uids": [
                "DemoUser01",
                "DemoUser02"
            ],
            "create_time" : "2022-07-01 14:50:00"
        }
    ]
}
```


Response information

data.status corresponding status info：

0: Built；1: Players assigned；2: Campaign activated；3: Cancelled；4: Application failed

2.9 Report Summary

Retrieve the daily aggregated betting data per player.

Request restriction

The data provided is within 6 months. The frequency is 3 sec per request.

The api also supports the paging function. Operator passes the page parameter to 1 in the first request of the same time interval. Each page can provide up to 5000 pieces of data. The total number of pages can be calculated from the total_count parameter in the response information. The calculation method is as follows: page.total_count/5000 unconditional carry to the integer. Reports are generated in UTC time zone.

Due to data processing time, if the date is set to today, data from the most recent 10 minutes may not yet be included in the query results.

Request

EndPoint : {getBetData_url}/dcs/getUsersBetSummary

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID
sign	Yes	String(32)	Sign = MD5(brand_id+date+api_key)
page	Yes	Int	Page index
date	Yes	String(10)	format (yyyy-MM-dd)
provider	No	String(20)	Game provider code, check Appendix 3.6
brand_uid	No	String(20)	Unique User ID from operator

Response

code	Response
1000	{ "data": [{ "brand_uid": "TestUser",

```
                "currency": "CNY",
                "provider": "yg",
                "bet_type": "Prepaid bet",
                "bet_count": 2,
                "bet_amt": 4.00,
                "win_amt": 0.00,
                "jackpot_contribution": 0.000000,
                "jackpot_win": 0.00,
                "tip": 0.000000
            },
            {
                "brand_uid": "TestUser",
                "currency": "CNY",
                "provider": "sb",
                "bet_type": "Normal bet",
                "bet_count": 271,
                "bet_amt": 813.00,
                "win_amt": 727.88,
                "jackpot_contribution": 0.000000,
                "jackpot_win": 0.00,
                "tip": 0.000000
            }
        ],
        "page": {
            "current_page": 1,
            "total_count": 2
        },
        "code": 1000,
        "msg": "Success."
    }
```


Response information

- page.current_page：Current page index
- page.total_count：Total page count (5k results per page)

Important

When the Provider is SA Gaming and the game is Pok Deng, Player 1 to Player 5 will withhold 2 times of the bet amount.

3. Brand API endpoints implementation

Operator must implement all API endpoints. Corresponding requests and the response parameters are described in detail.

DC requests operator brand API endpoints in POST method. The sign parameter is MD5 encrypted, operator must affirm the parameters are not tampered.

Method	Content Type
POST	application/json

Endpoint request common parameters：

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID
sign	Yes	String(32)	MD5 encryption and transform into CAPITAL Encrypted detail will describe in each endpoint Do not put “+” sign when concatenating messages

Endpoint response common parameters：

Name	Required	Type	Description
code	Yes	Int	Refer to DCS API Response code, check Appendix 4.1
msg	Yes	String(50)	Messages

3.1 Login Authentication

Operator is obligated to implement login endpoint in order to run gameplay. Token validation is required from providers so operator should respond the corresponding information to the login request.

Request

EndPoint : {brandApi_url}/login

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID
sign	Yes	String(32)	sign = MD5(brand_id+token+api_key)
token	Yes	String(32)	Token is created by operator, only allowed the combination c English letters and numbers
brand_uid	Yes	String(20)	Unique User ID from operator (Only support english characters and numbers, case insensitive)
currency	Yes	String(4)	Player currency code, check Appendix 4.2

Response

Name	Required	Type	Description
code	Yes	Int	DCS API Response Code, check Appendix 4.1
msg	Yes	String(50)	If the request info is valid, please respond with message “Success”.
data.brand_uid	Yes	String(20)	Unique User ID from operator
data.currency	Yes	String(4)	Player currency code, check Appendix 4.2
data.balance	Yes	Decimal(16,6)	Player current balance

code	Response

1000	{
	"code": 1000,
	"msg": "Success.",
	"data": {
	"brand_uid": "testUser",
	"currency": "IDR",
	"balance": 25.55
	}
	}

3.2 Wager

Operator is obliged to implement wager endpoint in order to run gameplay. If there is same wager request (identified by round_id and wager_id), or the wager has been cancelled, operator should not execute but return success response with player current balance. Noted that multiple wager_id may happen in same round_id in case the game has several buy-ins.

Request

EndPoint : {brandApi_url}/wager

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID
sign	Yes	String(32)	sign = MD5(brand_id+wager_id+api_key)
token	Yes	String(32)	Token is created by operator, only allowed the combination of English letters and numbers
brand_uid	Yes	String(20)	Unique User ID from operator (Only support english characters and numbers, case insensitive
currency	Yes	String(4)	Player currency code, check Appendix 4.2
amount	Yes	Decimal(16,6)	Bet amount
jackpot_contribution	Yes	Decimal(16,6)	A portion of player bet amount add to Jackpot feed
game_id	Yes	Int	DC game ID
game_name	Yes	String(50)	DC Game Name
round_id	Yes	String(64)	Unique bet round identifier
wager_id	Yes	String(64)	Unique transaction identifier within a bet round
provider	Yes	String(20)	Game provider code, check Appendix 4.6
bet_type	Yes	Int	1=Normal; 2=Tip
is_endround	Yes	Boolean	false= Unfinished, true= Round Finish
transaction_time	Yes	String(20)	The format is: yyyy-MM-ddTHH:mm:ssZ

Response

Name	Required	Type	Description
code	Yes	Int	DCS API Response Code, check Appendix 4.1
msg	Yes	String(50)	If the request info is valid, please respond with message “Success”.
data.brand_uid	Yes	String(20)	Unique User ID from operator
data.currency	Yes	String(4)	Player currency code, check Appendix 4.2
data.balance	Yes	Decimal(16,6)	Player current balance

code	Response

1000	{
	"code": 1000,
	"msg": "Success.",
	"data": {
	"brand_uid": "testUser",
	"currency": "IDR",
	"balance": 25.55
	}
	}

Special Remarks

1. All communications with the wallet are handled idempotently. If the merchant receives a duplicate wager request that has already been successfully processed (identified by round_id and wager_id), please respond with code: 5043, and return data.brand_uid, data.currency, data.balance without modifying the balance again.
2. Return code: 5003 with data.brand_uid, data.currency, data.balance if player has insufficient balance
3. When the Provider is SA Gaming and the game is Pok Deng, Player 1 to Player 5 will withhold 2 times of the bet amount.

3.3 CancelWager

Operator is obliged to implement cancelWager endpoint in order to run gameplay. If the operator has cancelled the wager (identical round_id and wager_id), operator should not execute the same request but return current balance in the response.

Request

EndPoint : {brandApi_url}/cancelWager

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID
sign	Yes	String(32)	sign = MD5(brand_id+wager_id+api_key)
brand_uid	Yes	String(20)	Unique User ID from operator (Only support english characters and numbers, case insensitive)
currency	Yes	String(4)	Player currency code, check Appendix 4.2
round_id	Yes	String(64)	Unique bet round identifier
wager_id	Yes	String(64)	Unique transaction identifier within a bet round
provider	Yes	String(20)	Game provider code, check Appendix 4.6
wager_type	Yes	Int	1=cancelWager, 2=cancelEndWager
is_endround	Yes	Boolean	false= Unfinished, true= Round Finish
transaction_time	Yes	String(20)	The format is: yyyy-MM-ddTHH:mm:ssZ

Response

Name	Required	Type	Description
code	Yes	Int	DCS API Response Code, check Appendix 4.1
msg	Yes	String(50)	If the request info is valid, please respond with message “Success”.
data.brand_uid	Yes	String(20)	Unique User ID from operator

data.currency	Yes	String(4)	Player currency code, check Appendix 4.2
data.balance	Yes	Decimal(16,6)	Player current balance

code	Response

1000	{
	"code": 1000,
	"msg": "Success.",
	"data": {
	"brand_uid": "testUser",
	"currency": "IDR",
	"balance": 25.55
	}
	}

Special Remarks

1. All communications with the wallet are handled idempotently. If the merchant receives a duplicate cancelWager request that has already been successfully processed (identified by round_id and wager_id), please respond with code: 5043, and return data.brand_uid, data.currency, data.balance without modifying the balance again.
2. Return code:5042 with data.brand_uid, data.currency, and data.balance if operator does not have the wager_id to be cancelled.
3. When the wager_type is 1, the wager round should be cancelled, i.e., return/increase the amount to the player wallet. When wager_type is 2, the endWager round should be cancelled, i.e., deduct/reduce the amount to the player's wallet.

3.4 AppendWager

Operator is obliged to implement AppendWager endpoint in order to run gameplay. This method is used for the result of jackpot game. Operator must payout the bonus unless same appendWager (identical round_id and wager_id) has executed.

Request

EndPoint : {brandApi_url}/appendWager

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID
sign	Yes	String(32)	sign = MD5(brand_id+wager_id+api_key)
brand_uid	Yes	String(20)	Unique User ID from operator (Only support english characters and numbers, case insensitive)
currency	Yes	String(4)	Player currency code, check Appendix 4.2
amount	Yes	Decimal(16,6)	Player jackpot winning amount
game_id	Yes	Int	DC game ID
game_name	Yes	String(50)	DC Game Name
round_id	Yes	String(64)	Unique bet round identifier
wager_id	Yes	String(64)	Unique transaction identifier within a bet round
provider	Yes	String(20)	Game provider code, check Appendix 4.6
description	Yes	String(100)	Description of appendWager
is_endround	Yes	Boolean	false= Unfinished, true= Round Finish
transaction_time	Yes	String(20)	The format is: yyyy-MM-ddTHH:mm:ssZ

Response

Name	Required	Type	Description

code	Yes	Int	DCS API Response Code, check Appendix 4.1
msg	Yes	String(50)	If the request info is valid, please respond with message “Success”.
data.brand_uid	Yes	String(20)	Unique User ID from operator
data.currency	Yes	String(4)	Player currency code, check Appendix 4.2
data.balance	Yes	Decimal(16,6)	Player current balance

code	Response

1000	{
	"code": 1000,
	"msg": "Success.",
	"data": {
	"brand_uid": "testUser",
	"currency": "IDR",
	"balance": 25.55
	}
	}

Special Remarks

1. All communications with the wallet are handled idempotently. If the merchant receives a duplicate appendWager request that has already been successfully processed (identified by round_id and wager_id), please respond with code: 5043, and return data.brand_uid, data.currency, data.balance without modifying the balance again.

3.5 EndWager

Operator is obliged to implement EndWager endpoint in order to run gameplay. This method is used to payout the winning amount for a normal round. If operator has executed the same endWager (identical round_id and wager_id), the current player info will be returned in response.

Request

EndPoint : {brandApi_url}/endWager

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID
sign	Yes	String(32)	sign = MD5(brand_id+wager_id+api_key)
brand_uid	Yes	String(20)	Unique User ID from operator (Only support english characters and numbers, case insensitive)
currency	Yes	String(4)	Player currency code, check Appendix 4.2
amount	Yes	Decimal(16,6)	Player winning amount in normal round
round_id	Yes	String(64)	Unique bet round identifier
wager_id	Yes	String(64)	Unique transaction identifier within a bet round
provider	Yes	String(20)	Game provider code, check Appendix 4.6
is_endround	Yes	Boolean	false= Unfinished, true= Round Finish
game_result	No	String(4000)	Only Ezugi has game result, the other provider will be null
transaction_time	Yes	String(20)	The format is: yyyy-MM-ddTHH:mm:ssZ

Response

Name	Required	Type	Description
code	Yes	Int	DCS API Response Code, check Appendix 4.1

msg	Yes	String(50)	If the request info is valid, please respond with message “Success”.
data.brand_uid	Yes	String(20)	Unique User ID from operator
data.currency	Yes	String(4)	Player currency code, check Appendix 4.2
data.balance	Yes	Decimal(16,6)	Player current balance

code	Response

1000	{
	"code": 1000,
	"msg": "Success.",
	"data": {
	"brand_uid": "testUser",
	"currency": "IDR",
	"balance": 25.55
	}
	}

Special Remarks

1. All communications with the wallet are handled idempotently. If the merchant receives a duplicate endWager request that has already been successfully processed (identified by round_id and wager_id), please respond with code: 5043, and return data.brand_uid, data.currency, data.balance without modifying the balance again.
2. Return code:5042 with data.brand_uid, data.currency, and data.balance if operator does not have the round_id to finish the round.

3.6 FreeSpinResult

Operator is obliged to implement FreeSpinResult endpoint in order to run gameplay. The total winning amount during the campaign will be aggregated in one request.

Request

EndPoint : {brandApi_url}/freeSpinResult

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID
sign	Yes	String(32)	sign = MD5(brand_id+wager_id+api_key)
brand_uid	Yes	String(20)	Unique User ID from operator (Only support english characters and numbers, case insensitive
currency	Yes	String(4)	Player currency code, check Appendix 4.2
amount	Yes	Decimal(16,6)	Player winning amount in campaign
game_id	Yes	Int	DC game ID
game_name	Yes	String(50)	DC Game Name
round_id	Yes	String(64)	Unique bet round identifier
wager_id	Yes	String(64)	Unique transaction identifier within a bet round
provider	Yes	String(20)	Game provider code, check Appendix 4.6
is_endround	Yes	Boolean	false= Unfinished, true= Round Finish
freespin_id	No	Long	freespin_id from the response of 2.7 createFreeSpin
freespin_description	No	String(100)	FreeSpin campaign description
transaction_time	Yes	String(20)	The format is: yyyy-MM-ddTHH:mm:ssZ

Response

Name	Required	Type	Description
code	Yes	Int	DCS API Response Code, check Appendix 4.1
msg	Yes	String(50)	If the request info is valid, please respond with message “Success”.
data.brand_uid	Yes	String(20)	Unique User ID from operator
data.currency	Yes	String(4)	Player currency code, check Appendix 4.2
data.balance	Yes	Decimal(16,6)	Player current balance

code	Response

1000	{
	"code": 1000,
	"msg": "Success.",
	"data": {
	"brand_uid": "testUser",
	"currency": "IDR",
	"balance": 25.55
	}
	}

Special Remarks

1. All communications with the wallet are handled idempotently. If the merchant receives a duplicate freeSpinResult request that has already been successfully processed (identified by round_id and wager_id), please respond with code: 5043, and return data.brand_uid, data.currency, data.balance without modifying the balance again.

3.7 GetBalance

Operator is obliged to implement getBalance endpoint in order to run gameplay. Response will be player current balance.

Request

EndPoint : {brandApi_url}/getBalance

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID
sign	Yes	String(32)	sign = MD5(brand_id+token+api_key)
brand_uid	Yes	String(20)	Unique User ID from operator (Only support english characters and numbers, case insensitive)
currency	Yes	String(4)	Player currency code, check Appendix 4.2
token	Yes	String(32)	Token created by operator, only allowed the combination o English letters and numbers

Response

Name	Required	Type	Description
code	Yes	Int	DCS API Response Code, check Appendix 4.1
msg	Yes	String(50)	If the request info is valid, please respond with message “Success”.
data.brand_uid	Yes	String(20)	Unique User ID from operator
data.currency	Yes	String(4)	Player currency code, check Appendix 4.2
data.balance	Yes	Decimal(16,6)	Player current balance

code	Response
1000	{

```
        "code": 1000,
        "msg": "Success.",
        "data": {
            "brand_uid": "testUser",
            "currency": "IDR",
            "balance": 25.55
        }
}
```


3.8 PromoPayout

This api will be sending promotional bonuses, adding the amount directly to the player wallet

Request

EndPoint : {brandApi_url}/promoPayout

Name	Required	Type	Description
brand_id	Yes	String(9)	Brand ID
sign	Yes	String(32)	sign = MD5(brand_id+promotion_id+trans_id+api_key)
brand_uid	Yes	String(20)	Unique User ID from operator (Only support english characters and numbers, case insensitive)
currency	Yes	String(4)	Player currency code, check Appendix 4.2
amount	Yes	Decimal(16,6)	Promo bonus
promotion_id	Yes	String(36)	Promotion id
trans_id	Yes	String(128)	Trans id
provider	Yes	String(16)	Game provider code, check Appendix 4.6
transaction_time	Yes	String(20)	The format is: yyyy-MM-ddTHH:mm:ssZ

Response

Name	Required	Type	Description
code	Yes	Int	DCS API Response Code, check Appendix 4.1
msg	Yes	String(50)	If the request info is valid, please respond with message “Success”.
data.brand_uid	Yes	String(20)	Unique User ID from operator
data.currency	Yes	String(4)	Player currency code, check Appendix 4.2
data.balance	Yes	Decimal(16,6)	Player current balance

code	Response

1000	{
	"code": 1000,
	"msg": "Success.",
	"data": {
	"brand_uid": "testUser",
	"currency": "IDR",
	"balance": 25.55
	}
	}

Special Remarks

2. All communications with the wallet are handled idempotently. If the merchant receives a duplicate promoPayout request that has already been successfully processed (identified by promotion_id and trans_id), please respond with code: 5043, and return data.brand_uid, data.currency, data.balance without modifying the balance again.

4. Appendix

4.1 DCS API Response Code

Code	Remark	Description
1000	Success.	Success
1001	System error.	System error
1002	Unknown.	Unknown error
5000	Sign error.	Verification code error
5001	Request param error.	Request parameter error
5002	Currency not support.	Currency not supported
5003	Balance insufficient.	Insufficient balance
5005	Brand not exist.	Brand does not exist
5008	Country Code error.	Country code error
5009	Player not exist.	Player's account or token does not exist
5010	Player blocked.	Player blocked
5012	Game id not exist.	Game id does not exist
5013	Not logged in.	Session authentication failed, token does not match with player
5014	Incorrect time format.	Invalid time format
5015	Incorrect provider.	Invalid provider
5016	Incorrect amount.	Invalid amount
5017	Api insufficient permission.	Api has insufficient permission
5018	Incorrect brand uid.	Incorect brand_uid
5040	Request rate limit, once request per 3 seconds.	Request limit reached, once every 3 seconds.

5041	Request date range limit, once request time period can only be within 24 hours. request time can only be within 6 months.	Request segment limit, each request segment must not exceed 24 hours, in addition, the information can be inquired only within 6 months period.
5042	Bet record not exist.	Bet record does not exist.
5043	Bet record duplicate.	Bet record is duplicated/identical.
5070	Free spin ID not exist.	Free spin ID does not exist.
5071	Incorrect round count.	Invalid spin count
5072	The free spin already cancelled.	This free spin has been cancelled.
5073	The free spin already locked.	This free spin has been locked, unable to alter.
5074	The provider does not support free spin.	This provider does not support assigning freespin to players.
5075	The free spin set up error.	The free spin setup has an error.
5019	Provider is maintaining	Provider is under maintenance
5020	Brand locked	Brand locked
5021	No support try game	Try game is not supported
5023	No support get replay	Replay is not supported
5024	Token cannot be used	Token cannot be used
5025	Unsupported method	Unsupported method

4.2 Currency code List

Please refer to ISO 4217 currency codes, different provider supports different currencies.

Code	Remark	Description
AED	United Arab Emirates Dirham	UAE Dirham
AFN	Afghan Afghani	Afghan Afghani
ALL	Albanian Lek	Albanian Lek
AMD	Armenian Dram	Armenian Dram
ANG	Netherlands Antillean Guilder	Netherlands Antillean Guilder
AOA	Angolan Kwanza	Angolan Kwanza
ARS	Argentine Peso	Argentine Peso
AUD	Australian Dollar	Australian Dollar
AZN	Azerbaijan Manat	Azerbaijan Manat
BAM	Bosnia and Herzegovina convertible mark	Bosnia and Herzegovina convertible Mark
BDT	Bangladeshi Taka	Bangladeshi Taka
BGN	Bulgarian Lev	Bulgarian Lev
BHD	Bahrain Dinar	Bahrain Dinar
BND	Brunei Dollar	Brunei Dollar
BOB	Bolivian Boliviano	Bolivian Boliviano
BRL	Brazilian Real	Brazilian Real
BWP	Botswanan Pula	Botswanan Pula
BYN	Belarusian Ruble	Belarusian Ruble
BZD	Belize Dollar	Belize Dollar
CAD	Canadian Dollar	Canadian Dollar
CDF	Congolese Franc	Congolese Franc
CHF	Swiss Franc	Swiss Franc
CLP	Chilean Peso	Chilean Peso
CNY	Chinese Yuan	Chinese Yuan
COP	Colombian Peso	Colombian Peso
CRC	Costa Rican Colón	Costa Rican Colón
CUP	Cuban Peso	Cuban Peso

CZK	Czech Koruna	Czech Koruna
DKK	Danish Krone	Danish Krone
DOP	Dominican Peso	Dominican Peso
DZD	Algerian Dinar	Algerian Dinar
EGP	Egyptian Pound	Egyptian Pound
ETB	Ethiopian Birr	Ethiopian Birr
EUR	Euro	Euro
GBP	Pound Sterling	Pound Sterling
GEL	Georgian Lari	Georgian Lari
GHS	Ghanaian Cedi	Ghanaian Cedi
GMD	Gambian Dalasi	Gambian Dalasi
GNF	Guinean Franc	Guinean Franc
GTQ	Guatemalan Quetzal	Guatemalan Quetzal
HKD	Hong Kong Dollar	Hong Kong Dollar
HNL	Honduran Lempira	Honduran Lempira
HRK	Croatian Kuna	Croatian Kuna
HTG	Haitian Gourde	Haitian Gourde
HUF	Hungarian Forint	Hungarian Forint
IDR	Indonesian Rupiah	Indonesian Rupiah
IDX	Thousand Indonesian Rupiah	Indonesian Rupiah/1000
ILS	Israeli New Shekel	Israeli New Shekel
INR	Indian Rupee	Indian Rupee
IQD	Iraqi Dinar	Iraqi Dinar
IRR	Iranian rial	Iranian rial
ISK	Icelandic Krona	Icelandic Krona
JMD	Jamaican Dollar	Jamaican Dollar
JOD	Jordanian Dinar	Jordanian Dinar
JPY	Japanese Yen	Japanese Yen
KES	Kenyan Shilling	Kenyan Shilling
KGS	Kyrgystani Som	Kyrgyzstani Som

KHR	Cambodian Riel	Cambodian Riel
KRW	South Korean Won	South Korean Won
KWD	Kuwaiti Dinar	Kuwaiti Dinar
KZT	Kazakhstani Tenge	Kazakhstani Tenge
LAK	Lao Kip	Lao Kip
LBP	Lebanese Pound	Lebanese Pound
LKR	Sri Lankan Rupee	Sri Lankan Rupee
LRD	Liberian dollar	Liberian Dollar
LSL	Basotho Loti	Basotho Lotu
LVL	Latvia Lat	Latvia Lat
MAD	Moroccan Dirham	Moroccan Dirham
MDL	Moldovan Leu	Moldovan Leu
MGA	Ariary	Ariary
MKD	Macedonian Denar	Macedonian Denar
MMK	Myanmar Kyat	Myanmar Kyat
MNT	Mongolian Tugrik	Mongolian Tugrik
MOP	Macau Pataca	Macau Pataca
MUR	Mauritian Rupee	Mauritian Rupee
MVR	Maldivian Rufiyaa	Maldivian Rufiyaa
MWK	Malawian kwacha	Malawian Kwacha
MXN	Mexican Peso	Mexican Peso
MYR	Malaysian Ringgit	Malaysian Ringgit
MZN	Mozambican Metical	Mozambican Metical
NAD	Namibian Dollar	Namibian Dollar
NGN	Nigerian Naira	Nigerian Naira
NIO	Nicaraguan Córdoba	Nicaraguan Córdoba
NOK	NOK	Norwegian Krone
NPR	Nepalese Rupee	Nepalese Rupee
NZD	New Zealand Dollar	New Zealand Dollar
OMR	Omani Rial	Omani Rial

PAB	Panamanian Balboa	Panamanian Balboa
PEN	Peruvian Nuevo Sol	Peruvian Nuevo Sol
PHP	Philippine Peso	Philippine Peso
PKR	Pakistan Rupee	Pakistan Rupee
PLN	Polish Zloty	Polish Zloty
PYG	Paraguayan Guarani	Paraguayan Guarani
QAR	Qatari Rial	Qatari Rial
RON	Romanian Dram	Romanian Dram
RSD	Serbian Dinar	Serbian Dinar
RUB	Russian Ruble	Russian Ruble
RWF	Rwandan franc	Rwandan Franc
SAR	Saudi Riyal	Saudi Riyal
SCR	Seychellois Rupee	Seychellois Rupee
SDG	Sudanese Pound	Sudanese Pound
SEK	Swedish Krona	Swedish Krona
SGD	Singapore Dollar	Singapore Dollar
SRD	Surinamese Dollar	Surinamese Dollar
SZL	Swazi Lilangeni	Swazi Lilangeni
TGC	TGC point	TGC point
THB	Thai Baht	Thai Baht
TJS	Tajikistani Somoni	Tajikistani Somoni
TMT	Turkmenistani Manat	Turkmenistani Manat
TND	Tunisian Dinar	Tunisian Dinar
TRY	Turkish Libra	Turkish Libra
TTD	Trinidad and Tobago Dollar	Trinidad and Tobago Dollar
TZS	Tanzanian Shilling	Tanzanian Shilling
UAH	Ukrainian Hryvnia	Ukrainian Hryvnia
USD	United States Dollar	United States Dollar
UYU	Uruguayan Peso	Uruguayan Peso
UZS	Uzbekistani Som	Uzbekistani Som

VND	Vietnamese Dong	Vietnamese Dong
VNX	Thousand Vietnamese Dong	Vietnamese Dong/1000
XAF	Central African CFA Franc	Central African CFA Franc
XCD	East Caribbean Dollar	East Caribbean Dollar
XOF	CFA Franc BCEAO	CFA Franc BCEAO
YER	Yemeni Rial	Yemeni Rial
ZAR	South African Rand	South African Rand
ZM	Zambian Kwacha	Zambian Kwacha
ZWL	Zimbabwean Dollar	Zimbabwean Dollar
BTP	BT Points	BT Points
USDT	Tether	Tether(USDT)
VES	Bolívar Soberano	Bolívar Soberano
SSP	South Sudanese Pound	South Sudanese Pound

4.3 Language code list

Code	Remark	Description
zh_hans	Simplified Chinese	Simplified Chinese
zh_hant	Traditional Chinese	Traditional Chinese
ko	Korean	Korean
kr	Korean	Korean
en	English	English
th	Thai	Thai
vi	Vietnamese	Vietnamese
id	Indonesian	Indonesian
ja	Japanese	Japanese
bg	Bulgarian	Bulgarian
cz	Czech	Czech
de	German	German
el	Greek	Greek
tr	Turkish	Turkish

es	Spanish	Spanish
fi	Finnish	Finnish
fr	French	French
hu	Hungarian	Hungarian
it	Italian	Italian
nl	Dutch	Dutch
no	Norwegian	Norwegian
pl	Polish	Polish
pt	Portuguese	Portuguese
pt-BR	Brazilian-Portuguese	Brazilian-Portuguese
ro	Romanian	Romanian
ru	Russian	Russian
sk	Slovak	Slovak
sv	Swedish	Swedish
da	Danish	Danish
ka	Georgian	Georgian
lv	Latvian	Latvian
uk	Ukrainian	Ukrainian
et	Estonian	Estonian

4.4 Country_code

Please refer to ISO 3166-1 Alpha 2 country coder, below are some examples

Code	Remark	Description
CN	China	China
HK	Hong Kong	Hong Kong
TW	Taiwan	Taiwan
KR	South Korea	South Korea
JP	Japan	Japan
TH	Thailand	Thailand
PH	Philippines	Philippines
ID	Indonesia	Indonesia
IN	India	India
VN	Vietnam	Vietnam
MY	Malaysia	Malaysia
SG	Singapore	Singapore

4.5 Wager_type

Code	Description
wager	Bet
endWager	Finish bet
cancelWager	Cancel bet, due to internal error (bet amount refund to player)
appendWagerResult	Appears in jackpot and prizedrop
campaign	Free Spin Bet record (Only appears in Backoffice)
campaignpayout	Player’s profit from prepaid free spin campaign
cancelEndWager	Cancellation of payout due to internal error (deducting the amount paid to the player from the player's wallet balance)
promopayout	send promotional bonuses, adding the amount directly to the player wallet

4.6 Provider List

Code	Description
dcace	DCACE
yg	Yggdrasil
relax	Relax gaming
nlc	Nolimit City
png	Play'n Go
hs	Hacksaw Gaming
aux	Avatar UX
evo	Evoplay
gam	Gamomat
psh	Push Gaming
ezugi	Ezugi
swf	Win Fast
funta	FunTa Gaming
stm	Slotmill
mj	7Mojos
fm	Fantasma
ps	Peter & Sons
sb	Spribe
plb	Parlay bay
evl	Evolution
btg	Big Time Gaming

ne	NetEnt
rt	Red Tiger
tg tgo	Turbo Games Turbo Games (non-Asian market)
wz	Voltent (Wazdan)
tk	Thunderkick
lm	Lucky Monaco
yt	Yolted
sa	SA Gaming
ss	Smartsoft
bg	Bgaming
nm	Novomatic
op	Octoplay
bp	BluePrint
hso	Hacksaw Gaming ROW
hsl	Hacksaw Gaming Latam
tq	Originals (Tequity)
raw	RAW
bm	Booming Games
ag	PlayACE
pts	Play Tech Slot
ptc	PlayTech Casino