

## ***Solution***      **Section 2.3 - Harmonic Motion**


### ***Exercise***

$$y = \cos 2t + \sin 2t$$

- i.* Plot the function
- ii.* Place the solution in the form  $y = A\cos(\omega_0 t - \phi)$  and compare the graph with the plot in (*i*)

### **Solution**

- i.* Plot the function



- ii.* Place the solution in the form  $y = A\cos(\omega_0 t - \phi)$  and compare the graph with the plot in (*i*)

$$y = 1.\cos 2t + 1.\sin 2t$$


$$= \sqrt{2} \left( \frac{1}{\sqrt{2}} \cos 2t + \frac{1}{\sqrt{2}} \sin 2t \right)$$

$$\cos \phi = \frac{1}{\sqrt{2}} = \sin \phi$$

$$= \sqrt{2} (\cos \phi \cos 2t + \sin \phi \sin 2t)$$

$$= \sqrt{2} \cos(2t - \phi)$$

$$= \sqrt{2} \cos\left(2t - \frac{\pi}{4}\right)$$




### Exercise

$$y = \cos 4t + \sqrt{3} \sin 4t$$

- i. Plot the function
- ii. Place the solution in the form  $y = A \cos(\omega_0 t - \phi)$  and compare the graph with the plot in (i)

### Solution

- i. Plot the function



- ii. Place the solution in the form  $y = A \cos(\omega_0 t - \phi)$  and compare the graph with the plot in (i)

$$y = 1 \cdot \cos 4t + \sqrt{3} \cdot \sin 4t$$

$$= 2 \left( \frac{1}{2} \cos 4t + \frac{\sqrt{3}}{2} \sin 4t \right)$$


$$= 2 (\cos \phi \cos 4t + \sin \phi \sin 4t)$$

$$= 2 \cos(4t - \phi)$$

$$= 2 \cos\left(4t - \frac{\pi}{3}\right)$$

$$= 2 \cos 4\left(t - \frac{\pi}{12}\right)$$

$$\cos \phi = \frac{1}{2} \quad \sin \phi = \frac{\sqrt{3}}{2}$$



### Exercise

A 1-kg mass, when attached to a large spring, stretches the spring a distance of 4.9 m.

- Calculate the spring constant.
- The system is placed in a viscous medium that supplies a damping constant  $\mu = 3 \text{ kg / s}$ . The system is allowed to come to rest. Then the mass is displaced 1 m in the downward direction and given a sharp tap, imparting an instantaneous velocity of 1 m/s in the downward direction. Find the position of the mass as a function of time and plot the solution.

### Solution

a) By Hooke's law:  $k = \frac{F}{y}$

$$= \frac{mg}{y}$$
$$= \frac{(1\text{kg})(9.8\text{m / s}^2)}{4.9\text{m}}$$
$$= \underline{2\text{N / m}}$$

b) **Given:**  $m = 1; \mu = 3; k = 2; y(0) = 1; y'(0) = 1$

$$y'' + 3y' + 2y = 0$$

The characteristic equation is:  $\lambda^2 + 3\lambda + 2 = 0 \Rightarrow \lambda_{1,2} = -1, -2$

The general solution:  $y(t) = C_1 e^{-t} + C_2 e^{-2t}$

### Exercise

The undamped system  $\frac{2}{5}x'' + kx = 0$ ,  $x(0) = 2$   $x'(0) = v_0$  is observed to have period  $\frac{\pi}{2}$  and amplitude 2. Find  $k$  and  $v_0$

### Solution

$$x'' + \frac{5}{2}kx = 0 \Leftrightarrow x'' + \omega_0^2 x = 0 \quad \left( \omega_0^2 = \frac{5k}{2} \right)$$

The characteristic equation is:  $\lambda^2 + \omega_0^2 = 0 \Rightarrow \lambda = \pm \omega_0 i$

It is a complex root, thus we have a complex solution:

$$x'(t) = -C_1 \omega_0 \sin \omega_0 t + C_2 \omega_0 \cos \omega_0 t \quad z(t) = e^{i\omega_0 t} = \cos \omega_0 t + i \sin \omega_0 t = \text{cis } \omega_0 t$$

The general solution:  $x(t) = C_1 \cos \omega_0 t + C_2 \sin \omega_0 t$

This solution is periodic with period  $T = \frac{2\pi}{\omega_0} = \frac{\pi}{2}$  (since the period is  $\frac{\pi}{2}$  given)

$$\omega_0 = 4 \Rightarrow \left| k = \frac{2\omega_0^2}{5} = \frac{32}{5} \right|$$

$$x(0) = C_1 \cos \omega_0 \cdot 0 + C_2 \sin \omega_0 \cdot 0 \Rightarrow \boxed{C_1 = 2}$$

$$x'(0) = -C_1 \omega_0 \sin \omega_0 \cdot 0 + C_2 \omega_0 \cos \omega_0 \cdot 0 \Rightarrow \boxed{C_2 = \frac{v_0}{\omega_0}}$$

$$x(t) = 2 \cos 4t + \frac{v_0}{4} \sin 4t$$

$$x(t) = \sqrt{4 + \frac{v_0^2}{16}} \cos(4t - \phi)$$

$$\tan \phi = \frac{v_0}{8}$$


The amplitude is 2, therefore:

$$\sqrt{4 + \frac{v_0^2}{16}} = 2$$

$$4 + \frac{v_0^2}{16} = 4$$

$$\frac{v_0^2}{16} = 0$$

$$\boxed{v_0 = 0}$$



### Exercise

A body with mass  $m = 0.5 \text{ kg}$  is attached to the end of a spring that is stretched  $2 \text{ m}$  by a force of  $100 \text{ N}$ . It is set in motion with initial position  $x_0 = 1 \text{ m}$  and initial velocity  $v_0 = -5 \text{ m/s}$ . (Note that these initial conditions indicate that the body is displaced to the right and is moving to the left at time  $t = 0$ .) Find the position function of the body as well as the amplitude, frequency, period of oscillation, and time lag of its motion.

### Solution

$$\text{Spring constant: } \left| k = \frac{100 \text{ N}}{2 \text{ m}} = 50 \text{ N/m} \right|$$

$$my'' + \mu y' + ky = F(t)$$

The differential equation can be written as:

$$0.5x'' + 50x = 0 \Rightarrow x'' + 100x = 0$$

$$|\omega_0 = \sqrt{100} = 10 \text{ rad / s}|$$

$$\text{Period: } |T = \frac{2\pi}{\omega_0} = \frac{2\pi}{10} = \frac{\pi}{5} \approx 0.6283 \text{ sec}|$$

$$\text{Frequency: } |\nu = \frac{1}{T} = \frac{5}{\pi} \approx 1.5915 \text{ Hz}|$$

$$\textbf{Given: } x(0) = 1, \quad x'(0) = -5$$

$$x(t) = A \cos 10t + B \sin 10t \rightarrow x(0) = A = 1$$

$$x'(t) = -10A \sin 10t + 10B \cos 10t \rightarrow x'(0) = 10B = -5 \Rightarrow B = -\frac{1}{2}$$

$$x(t) = \cos 10t - \frac{1}{2} \sin 10t$$

$$\text{Amplitude of motion is: } A = \sqrt{1^2 + \left(-\frac{1}{2}\right)^2} = \frac{\sqrt{5}}{2} m$$

Time lag?

$$\begin{aligned} x(t) &= \frac{\sqrt{5}}{2} \left( \frac{2}{\sqrt{5}} \cos 10t - \frac{1}{\sqrt{5}} \sin 10t \right) \\ &= \frac{\sqrt{5}}{2} \cos(10t - \varphi) \end{aligned}$$

$$\text{Phase angle } \varphi: \hat{\varphi} = \tan^{-1} \left( \frac{\frac{1}{\sqrt{5}}}{\frac{2}{\sqrt{5}}} \right) \approx 0.46365$$

$$\text{Since } \cos \varphi = \frac{2}{\sqrt{5}} > 0 \text{ and } \sin \varphi = -\frac{1}{\sqrt{5}} < 0$$

$$\Rightarrow \varphi = 2\pi - 0.46365 = 5.8195$$

Time lag of the motion is:

$$\delta = \frac{\varphi}{\omega_0} \approx \frac{5.8195}{10} \approx 0.58195 \text{ sec}$$

$$x(t) = \frac{\sqrt{5}}{2} \cos(10t - 5.8195)$$

### Exercise

Given the mass, damping, and spring constants of an undriven spring-mass system  $my'' + \mu y' + ky = 0$

$$m = 1 \text{ kg}, \quad \mu = 0 \text{ kg/s}, \quad k = 4 \text{ kg/s}^2, \quad y(0) = -2 \text{ m}, \quad y'(0) = -2 \text{ m/s}$$

- Provide separate plots of the position versus time ( $y$  vs.  $t$ ) and the velocity versus time ( $v$  vs.  $t$ )
- Provide a combined plot of both position and velocity versus time
- Provide a plot of the velocity versus position ( $v$  vs.  $y$ ) in the  $yv$  phase plane.

### Solution

$$my'' = -\mu y' - ky$$





$$y'' = -\frac{\mu}{m} y' - \frac{k}{m} y$$

$$\text{Let } \boxed{v = y'} \Rightarrow v' = -\frac{\mu}{m} v - \frac{k}{m} y$$

$$= -\frac{0}{1} v - \frac{4}{1} y$$

$$\boxed{v' = -4y}$$

$$y(0) = -2, \quad y'(0) = -2 = v(0)$$



## Exercise

Given the mass, damping, and spring constants of an undriven spring-mass system  $my'' + \mu y' + ky = 0$

$$m = 1 \text{ kg}, \quad \mu = 2 \text{ kg/s}, \quad k = 1 \text{ kg/s}^2, \quad y(0) = -3 \text{ m}, \quad y'(0) = -2 \text{ m/s}$$





- Provide separate plots of the position versus time ( $y$  vs.  $t$ ) and the velocity versus time ( $v$  vs.  $t$ )
- Provide a combined plot of both position and velocity versus time
- Provide a plot of the velocity versus position ( $v$  vs.  $y$ ) in the  $yv$  phase plane.

## Solution

$$my'' = -\mu y' - ky \Rightarrow y'' = -\frac{\mu}{m}y' - \frac{k}{m}y$$

$$\begin{aligned} \text{Let } v = y' &\Rightarrow v' = -\frac{\mu}{m}v - \frac{k}{m}y \\ &= -\frac{2}{1}v - \frac{1}{1}y \\ &= -2v - y \end{aligned}$$


The following system of the first-order equations:  $\begin{cases} y' = v \\ v' = -2v - y \end{cases}$  with  $y(0) = -3$   
 $y'(0) = -2 = v(0)$



### Exercise

A  $\frac{1}{4}$ -kg mass is attached to a spring with a stiffness  $k = 4 \text{ N/m}$ . The damping constant  $\mu = 1 \text{ N-sec/m}$ .

If the mass is displaced  $x_0 = \frac{1}{2} \text{ m}$  to the left and given an initial velocity of  $v_0 = 1 \text{ m/s}$  to the left.



- Find the equation of motion.
- What is the maximum displacement that the mass will attain?

### Solution

$$a) \quad \frac{1}{4}x'' + x' + 4x = 0; \quad x(0) = -\frac{1}{2}, \quad x'(0) = -1 \quad mx'' + \mu x' + kx = F(t)$$

$$b) \quad \lambda^2 + 4\lambda + 16 = 0 \rightarrow \lambda_{1,2} = \frac{-4 \pm 4\sqrt{3}}{2} = -2 \pm 2i\sqrt{3}$$

$$x(t) = e^{-2t} (C_1 \cos 2\sqrt{3}t + C_2 \sin 2\sqrt{3}t)$$

$$x(0) = -\frac{1}{2} \rightarrow C_1 = -\frac{1}{2}$$

$$x'(t) = e^{-2t} (-2\sqrt{3}C_1 \sin 2\sqrt{3}t + 2\sqrt{3}C_2 \cos 2\sqrt{3}t - 2C_1 \cos 2\sqrt{3}t - 2C_2 \sin 2\sqrt{3}t)$$

$$x'(0) = -1 \rightarrow 2\sqrt{3}C_2 - 2C_1 = -1 \quad C_2 = -\frac{1}{\sqrt{3}}$$

$$x(t) = e^{-2t} \left( -\frac{1}{2} \cos 2\sqrt{3}t - \frac{1}{\sqrt{3}} \sin 2\sqrt{3}t \right)$$

$$x'(t) = e^{-2t} \left( \sqrt{3} \sin(2\sqrt{3}t) - 2 \cos(2\sqrt{3}t) + \cos(2\sqrt{3}t) + \frac{2}{\sqrt{3}} \sin(2\sqrt{3}t) \right)$$

$$= e^{-2t} \left( \frac{5}{\sqrt{3}} \sin(2\sqrt{3}t) - \cos(2\sqrt{3}t) \right) = 0$$

$$\frac{5}{\sqrt{3}} \sin(2\sqrt{3}t) = \cos(2\sqrt{3}t)$$

$$\tan(2\sqrt{3}t) = \frac{\sqrt{3}}{5} \rightarrow 2\sqrt{3}t = \arctan \frac{\sqrt{3}}{5}$$

$$t = \frac{1}{2\sqrt{3}} \arctan \frac{\sqrt{3}}{5} \approx 0.096$$



$$x(0.096) = e^{-2(0.096)} \left( -\frac{1}{2} \cos 2\sqrt{3}(0.096) - \frac{1}{\sqrt{3}} \sin 2\sqrt{3}(0.096) \right) \\ \approx -0.55 \text{ m}$$

### Exercise

A 2-kg mass is attached to a spring with a stiffness  $k = 50 \text{ N/m}$ . The mass is displaced  $\frac{1}{4} \text{ m}$  to the left of the equilibrium point and given a velocity of  $1 \text{ m/s}$  to the left. Neglecting the damping,

- Find the equation of motion of the mass along with the amplitude, period, and frequency.
- How long after release does the mass pass through the equilibrium position?

### Solution

a) **Given:**  $\mu = 0$

$$2x'' + 50x = 0 ; \quad x(0) = -\frac{1}{4}, \quad x'(0) = -1 \qquad mx'' + \mu x' + kx = 0$$

$$2\lambda^2 + 50 = 0 \rightarrow \lambda_{1,2} = \pm 5i$$

$$x(t) = C_1 \cos 5t + C_2 \sin 5t$$

$$x(0) = -\frac{1}{4} \rightarrow C_1 = -\frac{1}{4}$$

$$x'(t) = -5C_1 \sin 5t + 5C_2 \cos 5t$$

$$x'(0) = -1 \rightarrow 5C_2 = -1 \quad C_2 = -\frac{1}{5}$$

$$x(t) = -\frac{1}{4} \cos 5t - \frac{1}{5} \sin 5t$$

$$\text{Amplitude: } A = \sqrt{\frac{1}{16} + \frac{1}{25}} = \frac{\sqrt{41}}{20}$$

$$\text{The angular velocity: } \omega = \sqrt{\frac{k}{m}} = \sqrt{\frac{50}{2}} = 5$$

$$\text{Period: } T = \frac{2\pi}{\omega} = \frac{2\pi}{5}$$


$$\text{Natural frequency} = \frac{1}{T} = \frac{5}{2\pi}$$

$$b) \quad x(t) = -\frac{1}{4} \cos 5t - \frac{1}{5} \sin 5t = 0$$

$$\frac{1}{5} \sin 5t = -\frac{1}{4} \cos 5t$$

$$\tan 5t = -\frac{5}{4} \rightarrow 5t = \pi - \arctan\left(-\frac{5}{4}\right)$$

$$t = \frac{1}{5} \left( \pi - \arctan\left(\frac{5}{4}\right) \right) \approx 0.45 \text{ sec}$$



### Exercise

A 3-kg mass is attached to a spring with a stiffness  $k = 48 \text{ N/m}$ . The mass is displaced  $\frac{1}{2} \text{ m}$  to the left of the equilibrium point and given a velocity of  $2 \text{ m/s}$  to the left. Neglecting the damping,

- Find the equation of motion of the mass
- Find the amplitude, period, and frequency.
- How long after release does the mass pass through the equilibrium position?

### Solution

a) **Given:**  $\mu = 0$

$$3x'' + 48x = 0 ; \quad x(0) = -\frac{1}{2}, \quad x'(0) = -2 \quad \quad mx'' + \mu x' + kx = 0$$

$$\lambda^2 + 16 = 0 \rightarrow \lambda_{1,2} = \pm 4i$$

$$x(t) = C_1 \cos 4t + C_2 \sin 4t$$

$$x(0) = -\frac{1}{2} \rightarrow C_1 = -\frac{1}{2}$$

$$x'(t) = -4C_1 \sin 4t + 4C_2 \cos 4t$$

$$x'(0) = -2 \rightarrow 4C_2 = -2 \quad C_2 = -\frac{1}{2}$$

$$x(t) = -\frac{1}{2} \cos 4t - \frac{1}{2} \sin 4t$$

b) Amplitude:  $A = \sqrt{\frac{1}{4} + \frac{1}{4}} = \frac{\sqrt{2}}{2} \text{ m}$

The angular velocity:  $\omega = \sqrt{\frac{k}{m}} = \sqrt{\frac{48}{3}} = 4$

Period:  $T = \frac{2\pi}{\omega} = \frac{\pi}{2}$


Natural frequency =  $\frac{1}{T} = \frac{2}{\pi}$

c)  $x(t) = -\frac{1}{2} \cos 4t - \frac{1}{2} \sin 4t = 0$

$$\frac{1}{2} \sin 4t = -\frac{1}{2} \cos 4t$$

$$\tan 4t = -1 \rightarrow 4t = \frac{3\pi}{4}$$

$$t = \frac{3\pi}{16} \approx 0.59 \text{ sec}$$



### Exercise

A 20-kg mass is attached to a spring with a stiffness  $k = 200 \text{ N/m}$ . The damping constant  $\mu = 140 \text{ N} \cdot \text{sec} / \text{m}$ . If the mass is pulled 25 cm to the right of the equilibrium point and given an initial velocity of 1 m/s. Neglecting the damping,

- Find the equation of motion.
- When will it first return to its equilibrium position?

### Solution

$$a) \quad 20x'' + 140x' + 200x = 0 \qquad mx'' + \mu x' + kx = 0$$

$$x'' + 7x' + 10x = 0; \quad x(0) = \frac{1}{4}, \quad x'(0) = -1$$

$$\lambda^2 + 7\lambda + 10 = 0 \rightarrow \lambda_{1,2} = -2, -5$$

$$x(t) = C_1 e^{-2t} + C_2 e^{-5t}$$

$$x(0) = \frac{1}{4} \rightarrow C_1 + C_2 = \frac{1}{4}$$

$$x(t) = -2C_1 e^{-2t} - 5C_2 e^{-5t}$$

$$x'(0) = -1 \rightarrow 2C_1 + 5C_2 = 1$$

$$\begin{cases} C_1 + C_2 = \frac{1}{4} \\ 2C_1 + 5C_2 = 1 \end{cases} \rightarrow 3C_2 = \frac{1}{2} \quad C_2 = \frac{1}{6}, C_1 = \frac{1}{12}$$

$$x(t) = \frac{1}{12} e^{-2t} + \frac{1}{6} e^{-5t}$$

$$b) \quad x(t) = \frac{1}{12} e^{-2t} + \frac{1}{6} e^{-5t} \neq 0$$

The mass will not return to the equilibrium position.

### Exercise

A  $\frac{1}{4}$ -kg mass is attached to a spring with a stiffness  $k = 8 \text{ N/m}$ . The damping constant  $\mu = \frac{1}{4} \text{ N} \cdot \text{sec} / \text{m}$ .

If the mass is displaced  $x_0 = 1 \text{ m}$  to the left of equilibrium and released, what is the maximum displacement to the right that the mass will attain?

### Solution

$$\frac{1}{4}x'' + \frac{1}{4}x' + 8x = 0 \qquad mx'' + \mu x' + kx = 0$$

$$x'' + x' + 32x = 0; \quad x(0) = -1, \quad x'(0) = 0$$

$$\lambda^2 + \lambda + 32 = 0 \rightarrow \lambda_{1,2} = \frac{1}{2} \pm i \frac{\sqrt{127}}{2}$$

$$x(t) = e^{-t/2} \left( C_1 \cos\left(\frac{\sqrt{127}}{2}t\right) + C_2 \sin\left(\frac{\sqrt{127}}{2}t\right) \right)$$

$$x(0) = -1 \rightarrow \underline{C_1 = -1}$$

$$x'(t) = e^{-t/2} \left( -\frac{\sqrt{127}}{2} C_1 \sin\frac{\sqrt{127}}{2}t + \frac{\sqrt{127}}{2} C_2 \cos\frac{\sqrt{127}}{2}t - \frac{1}{2} C_1 \cos\frac{\sqrt{127}}{2}t - \frac{1}{2} C_2 \sin\frac{\sqrt{127}}{2}t \right)$$

$$x'(0) = 0 \rightarrow \frac{\sqrt{127}}{2} C_2 - \frac{1}{2} C_1 = 0 \Rightarrow \underline{C_2 = -\frac{1}{\sqrt{127}}}$$

$$x(t) = e^{-t/2} \left( -\cos\left(\frac{\sqrt{127}}{2}t\right) - \frac{1}{\sqrt{127}} \sin\left(\frac{\sqrt{127}}{2}t\right) \right)$$

$$\begin{aligned} x'(t) &= e^{-t/2} \left( \frac{\sqrt{127}}{2} \sin\frac{\sqrt{127}}{2}t - \frac{1}{2} \cos\frac{\sqrt{127}}{2}t + \frac{1}{2} \cos\frac{\sqrt{127}}{2}t + \frac{1}{2\sqrt{127}} \sin\frac{\sqrt{127}}{2}t \right) \\ &= \frac{64}{\sqrt{127}} e^{-t/2} \sin\frac{\sqrt{127}}{2}t = 0 \end{aligned}$$

$$\frac{\sqrt{127}}{2}t = n\pi \quad (t > 0) \rightarrow n = 1$$

$$t = \frac{2\pi}{\sqrt{127}}$$

$$\begin{aligned} x(t) &= e^{-\pi/\sqrt{127}} \left( -\cos(\pi) - \frac{1}{\sqrt{127}} \sin(\pi) \right) \\ &= \underline{e^{-\pi/\sqrt{127}} \approx 0.7567 \text{ m}} \end{aligned}$$

### Exercise

A  $\frac{1}{4}$ -kg mass is attached to a spring with a stiffness  $k = 8 \text{ N/m}$ . The damping constant  $\mu = 2 \text{ N} \cdot \text{sec} / \text{m}$ .

If the mass is pushed 50 cm to the left of equilibrium and given a leftward velocity of 2 m/sec, when will the mass attain its maximum displacement to the left?

### Solution

$$\frac{1}{4}x'' + 2x' + 8x = 0 \qquad mx'' + \mu x' + kx = 0$$

$$x'' + 8x' + 32x = 0 ; \quad x(0) = -0.5 \text{ m}, \quad x'(0) = -2$$

$$\lambda^2 + 8\lambda + 32 = 0 \rightarrow \lambda_{1,2} = \frac{-8 \pm 8i}{2} = \underline{-4 \pm 4i}$$

$$x(t) = e^{-4t} (C_1 \cos 4t + C_2 \sin 4t)$$

$$x(0) = -\frac{1}{2} \rightarrow \underline{C_1 = -\frac{1}{2}}$$

$$x'(t) = e^{-4t} (-4C_1 \sin 4t + 4C_2 \cos 4t - 4C_1 \cos 4t - 4C_2 \sin 4t)$$

$$x'(0) = -2 \rightarrow 4C_2 - 4C_1 = -2 \Rightarrow \underline{C_2 = -1}$$

$$x(t) = -e^{-4t} \left( \frac{1}{2} \cos 4t + \sin 4t \right)$$

$$\begin{aligned} x'(t) &= e^{-4t} (2 \sin 4t - 4 \cos 4t + 2 \cos 4t + 4 \sin 4t) \\ &= e^{-4t} (6 \sin 4t - 2 \cos 4t) = 0 \end{aligned}$$

$$3 \sin 4t = \cos 4t$$

$$\tan 4t = \frac{1}{3} \rightarrow t = \frac{1}{4} \arctan \frac{1}{3} \approx \underline{0.08 \text{ sec}}$$

### Exercise

A 8-lb mass weight stretches a spring 2 feet. Assuming that a damping force numerically equal to 2 times the instantaneous velocity acts on the system, determine the equation of motion if the mass released from the equilibrium position with an upward velocity of 3 ft/s

### Solution

$$m = \frac{8}{32} = \frac{1}{4} \text{ slug}$$

$$W = mg$$

$$k(2 \text{ ft}) = 8 \rightarrow k = 4$$

$$kx = mg$$

$$\frac{1}{4} x'' + 2x' + 4x = 0$$

$$mx'' + \mu x' + kx = 0$$

$$x'' + 8x' + 16x = 0; \quad x(0) = 0, \quad x'(0) = -3$$

$$\lambda^2 + 8\lambda + 16 = (\lambda + 4)^2 = 0 \rightarrow \underline{\lambda_{1,2} = -4}$$


$$x(t) = (C_1 + C_2 t) e^{-4t}$$

$$x(0) = 0 \rightarrow \underline{C_1 = 0}$$

$$x'(t) = (C_2 - 4C_1 - 4C_2 t) e^{-4t}$$

$$x'(0) = -3 \rightarrow \underline{C_2 = -3}$$

$$\underline{x(t) = -3te^{-4t}}$$



### Exercise

A 8-lb mass weight is attached to the end of a spring, causing the spring to stretch a spring 6 in. beyond its natural length. The block is then pulled down 3 in. and released. Determine the motion of the block, assuming there are no damping or external applied force.

### Solution

$$m = \frac{8}{32} = \frac{1}{4} \text{ slug}$$

$$W = mg$$

$$k \left( 6 \text{ in} \frac{1 \text{ ft}}{12 \text{ in}} \right) = 8 \rightarrow k = 16 \text{ lb/ft} \quad kx = mg$$

$$\frac{1}{4}y'' + 16y = 0; \quad y(0) = \frac{3}{12} = \frac{1}{4}, \quad y'(0) = 0 \quad mx'' + \mu x' + kx = 0$$

$$\frac{1}{4}\lambda^2 + 16 = 0 \rightarrow \lambda^2 = -64 \quad \lambda_{1,2} = -8i$$


$$y(t) = C_1 \cos 8t + C_2 \sin 8t$$

$$y(0) = \frac{1}{4} \rightarrow C_1 = \frac{1}{4}$$

$$y'(t) = -8C_1 \sin 8t + 8C_2 \cos 8t$$

$$y'(0) = 0 \rightarrow C_2 = 0$$

$$y(t) = \frac{1}{4} \cos 8t$$



### Exercise

A 8-lb mass weight is attached to the end of a spring, causing the spring to stretch a spring 6 in. beyond its natural length. The block is then pulled down 3 in. and released. Determine the motion of the block, assuming there damping is present and that the damping coefficient is  $\mu = 1 \text{ lb-sec/ft}$  and external applied force.

### Solution

$$m = \frac{8}{32} = \frac{1}{4} \text{ slug}$$

$$W = mg$$

$$k \left( 6 \text{ in} \frac{1 \text{ ft}}{12 \text{ in}} \right) = 8 \rightarrow k = 16 \text{ lb/ft} \quad kx = mg$$

$$\frac{1}{4}y'' + y' + 16y = 0; \quad y(0) = \frac{3}{12} = \frac{1}{4}, \quad y'(0) = 0 \quad mx'' + \mu x' + kx = 0$$

$$\frac{1}{4}\lambda^2 + \lambda + 16 = 0 \rightarrow \lambda^2 + 4\lambda + 64 = 0$$

$$\lambda_{1,2} = \frac{-4 \pm i\sqrt{240}}{2} = \frac{-4 \pm 4i\sqrt{15}}{2} = -2 \pm 2i\sqrt{15}$$


$$y(t) = e^{-2t} \left( C_1 \cos(2\sqrt{15}t) + C_2 \sin(2\sqrt{15}t) \right)$$

$$y(0) = \frac{1}{4} \rightarrow \underline{C_1 = \frac{1}{4}}$$

$$y'(t) = e^{-2t} \left( -2C_1 \cos(2\sqrt{15}t) - 2C_2 \sin(2\sqrt{15}t) - 2\sqrt{15}C_1 \sin(2\sqrt{15}t) + 2\sqrt{15}C_2 \cos(2\sqrt{15}t) \right)$$

$$y'(0) = 0 \rightarrow -2\left(\frac{1}{4}\right) + 2\sqrt{15}C_2 = 0 \Rightarrow \underline{C_2 = \frac{1}{4\sqrt{15}}}$$

$$\underline{y(t) = e^{-2t} \left( \frac{1}{4} \cos(2\sqrt{15}t) + \frac{1}{4\sqrt{15}} \sin(2\sqrt{15}t) \right)}$$



### Exercise

A 16-lb mass weight is attached to a 5-foot spring. At equilibrium the spring measures 8.2 feet. If the mass is initially released from rest at a point  $x_0 = 2$  ft above the equilibrium position, find the displacements

$x(t)$  if it is further known that the surrounding medium offers a resistance numerically equal to the instantaneous velocity.

### Solution

$$m = \frac{16}{32} = \frac{1}{2} \text{ slug} \quad W = mg$$

$$k(8.2 - 5) = 16 \rightarrow k = \frac{16}{3.2} = 5 \text{ lb/ft} \quad kx = mg$$

$$\frac{1}{2}x'' + x' + 5x = 0 \quad mx'' + \mu x' + kx = 0$$

$$x'' + 2x' + 10x = 0; \quad x(0) = -2, \quad x'(0) = 0$$

$$\lambda^2 + 2\lambda + 10 = 0 \rightarrow \lambda_{1,2} = \frac{-2 \pm 6i}{2} = -1 \pm 3i$$


$$x(t) = e^{-t} (C_1 \cos 3t + C_2 \sin 3t)$$

$$x(0) = -2 \rightarrow \underline{C_1 = -2}$$

$$x'(t) = e^{-t} \left( -3C_1 \sin 3t + 3C_2 \cos 3t - C_1 \cos 3t - C_2 \sin 3t \right)$$

$$x'(0) = 0 \rightarrow 3C_2 - C_1 = 0 \Rightarrow C_2 = -\frac{2}{3}$$

$$x(t) = -e^{-t} \left( 2 \cos 3t + \frac{2}{3} \sin 3t \right)$$



### Exercise

A 16-lb mass weight is attached to a spring, stretches  $\frac{8}{9}$  ft by itself. There is no damping and no external forces acting on the system. The spring is initially displaced 6 inches upwards from its equilibrium position and given an initial velocity of 1 ft/sec downward. Find the displacement  $y(t)$  at any time  $t$ .

### Solution

$$m = \frac{16}{32} = \frac{1}{2} \text{ slug}$$

$$W = mg$$

$$k\left(\frac{8}{9}\right) = 16 \rightarrow k = 18 \text{ lb/ft} \quad kL = mg$$

$$\frac{1}{2}y'' + 18y = 0$$

$$my'' + \mu y' + ky = 0$$

$$y'' + 36y = 0; \quad y(0) = -\frac{6 \text{ in}}{12 \text{ in}} = -\frac{1}{2} \text{ ft}, \quad y'(0) = 1 \text{ ft/sec}$$

$$\lambda^2 + 36 = 0 \rightarrow \lambda_{1,2} = \pm 6i$$

$$y(t) = C_1 \cos 6t + C_2 \sin 6t$$

$$y(0) = -\frac{1}{2} \rightarrow C_1 = -\frac{1}{2}$$

$$y' = -6C_1 \sin 6t + 6C_2 \cos 6t$$

$$y'(0) = 1 \rightarrow 6C_2 = 1 \Rightarrow C_2 = \frac{1}{6}$$




$$y(t) = -\frac{1}{2} \cos 6t + \frac{1}{6} \sin 6t$$

$$A = \sqrt{\frac{1}{4} + \frac{1}{36}} = \frac{\sqrt{10}}{6}$$

$$\varphi = \pi - \tan^{-1} \frac{1}{3} \approx 2.81984$$

$$y(t) = \frac{\sqrt{10}}{6} \cos(6t - 2.81984)$$



### Exercise

A 16-*lb* mass weight is attached to a spring, stretches  $\frac{8}{9}$  *ft* by itself. A damper to the mass that will exert of 12 *lbs*. when the velocity is 2 *ft/sec* . The spring is initially displaced 6 *inches* upwards from its equilibrium position and given an initial velocity of 1 *ft/sec* downward. Find the displacement  $y(t)$  at any time  $t$ .

### Solution

$$m = \frac{16}{32} = \frac{1}{2} \text{ slug}$$

$$W = mg$$

$$k\left(\frac{8}{9}\right) = 16 \rightarrow k = 18 \text{ lb/ft}$$

$$kL = mg$$

$$12 = \mu(2) \rightarrow \mu = 6$$

$$F = \mu v$$

$$\frac{1}{2} y'' + 6y' + 18y = 0$$

$$my'' + \mu y' + ky = 0$$

$$y'' + 12y' + 36y = 0 ; \quad y(0) = -\frac{6 \text{ in}}{12 \text{ in}} = -\frac{1}{2} \text{ ft}, \quad y'(0) = 1 \text{ ft/sec}$$

$$\lambda^2 + 12\lambda + 36 = 0 \rightarrow \lambda_{1,2} = -6, -6$$


$$y(t) = (C_1 + C_2 t) e^{-6t}$$

$$y(0) = -\frac{1}{2} \rightarrow C_1 = -\frac{1}{2}$$

$$y' = (C_2 - 6C_1 - 6C_2 t) e^{-6t}$$

$$y'(0) = 1 \rightarrow C_2 + 3 = 1 \Rightarrow C_2 = -2$$

$$y(t) = \left(-\frac{1}{2} - 2t\right) e^{-6t}$$



### Exercise

A 16-*lb* mass weight is attached to a spring, stretches  $\frac{8}{9}$  *ft* by itself. A damper to the mass that will exert of 5 *lbs*. when the velocity is 2 *ft/sec* . The spring is initially displaced 6 *inches* upwards from its equilibrium position and given an initial velocity of 1 *ft/sec* downward. Find the displacement  $y(t)$  at any time  $t$ .

### Solution

$$m = \frac{16}{32} = \frac{1}{2} \text{ slug} \quad W = mg$$

$$k\left(\frac{8}{9}\right) = 16 \rightarrow k = 18 \text{ lb/ft} \quad kL = mg$$

$$5 = \mu(2) \rightarrow \mu = \frac{5}{2} \quad F = \mu v$$

$$\frac{1}{2}y'' + \frac{5}{2}y' + 18y = 0 \quad my'' + \mu y' + ky = 0$$

$$y'' + 5y' + 36y = 0; \quad y(0) = -\frac{6 \text{ in}}{12 \text{ in}} = -\frac{1}{2} \text{ ft}, \quad y'(0) = 1 \text{ ft/sec}$$

$$\lambda^2 + 5\lambda + 36 = 0 \rightarrow \lambda_{1,2} = \frac{-5 \pm i\sqrt{119}}{2}$$

$$y(t) = \left( C_1 \cos \frac{\sqrt{119}}{2}t + C_2 \sin \frac{\sqrt{119}}{2}t \right) e^{-5t/2}$$

$$y(0) = -\frac{1}{2} \rightarrow C_1 = -\frac{1}{2}$$

$$y' = \left( -\frac{5}{2}C_1 \cos \frac{\sqrt{119}}{2}t - \frac{5}{2}C_2 \sin \frac{\sqrt{119}}{2}t - \frac{\sqrt{119}}{2}C_1 \sin \frac{\sqrt{119}}{2}t + \frac{\sqrt{119}}{2}C_2 \cos \frac{\sqrt{119}}{2}t \right) e^{-5t/2}$$

$$y'(0) = 1 \rightarrow -\frac{5}{2}\left(-\frac{1}{2}\right) + \frac{\sqrt{119}}{2}C_2 = 1 \Rightarrow C_2 = -\frac{1}{2\sqrt{119}}$$

$$y(t) = \left( -\frac{1}{2} \cos \frac{\sqrt{119}}{2}t - \frac{\sqrt{119}}{238} \sin \frac{\sqrt{119}}{2}t \right) e^{-5t/2}$$

$$A = \sqrt{\frac{1}{4} + \frac{119}{238^2}} = 0.502096$$

$$\varphi = \pi + \tan^{-1} \frac{2\sqrt{119}}{238} \approx 3.2321$$

$$y(t) = 0.502096 e^{-5t/2} \cos\left(\frac{\sqrt{119}}{2}t - 3.2321\right)$$

### Exercise

A mass weighing 4-lb is attached to a spring whose spring constant is 16 lb/ft.

- Find the equation of motion.
- What is the period of simple harmonic motion?

### Solution

$$m = \frac{4}{32} = \frac{1}{8}$$

$$W = mg$$

$$a) \quad \frac{1}{8}x'' + 16x = 0 \qquad mx'' + \mu x' + kx = 0$$

$$\frac{1}{8}\lambda^2 + 16 = 0 \Rightarrow \lambda^2 = -128 \rightarrow \lambda_{1,2} = \pm 8i\sqrt{2}$$

$$x(t) = C_1 \cos 5t + C_2 \sin 5t$$

$$b) \quad \text{The angular velocity: } \omega = \sqrt{\frac{k}{m}} = \sqrt{\frac{16}{1/8}} = 8\sqrt{2}$$

$$\text{Period: } T = \frac{2\pi}{\omega} = \frac{2\pi}{8\sqrt{2}} = \frac{\pi\sqrt{2}}{8}$$

### Exercise

A 20-kg mass is attached to a spring. If the frequency of simple harmonic motion is  $\frac{2}{\pi}$  cycles/s.

- What is the spring constant  $k$ ?
- Find the equation of motion.
- What is the frequency of simple harmonic motion if the original mass is replaced with an 80-kg mass.?

### Solution

$$a) \quad 20x'' + kx = 0 \qquad mx'' + \mu x' + kx = 0$$

$$20\lambda^2 + k = 0 \rightarrow \lambda_{1,2} = \pm \frac{1}{2}i\sqrt{\frac{k}{5}} \quad (k > 0)$$

$$x(t) = C_1 \cos \frac{1}{2}\sqrt{\frac{k}{5}}t + C_2 \sin \frac{1}{2}\sqrt{\frac{k}{5}}t$$

$$\omega = \frac{1}{2}\sqrt{\frac{k}{5}} = 2\pi f$$

$$\sqrt{\frac{k}{5}} = 4\pi \frac{2}{\pi} = 8$$

$$k = 5(8^2) = 320 \text{ N/m}$$

$$b) \quad x(t) = C_1 \cos 4t + C_2 \sin 4t$$

$$c) \quad 80x'' + 320x = 0$$

$$\omega = \sqrt{\frac{k}{m}} = \sqrt{\frac{320}{80}} = 2$$

$$\text{Natural frequency} = f = \frac{\omega}{2\pi} = \frac{1}{\pi} \text{ cycle/s}$$

$$80\lambda^2 + 320 = 0 \rightarrow \lambda_{1,2} = \pm 2i$$

$$x(t) = C_1 \cos 2t + C_2 \sin 2t$$

### Exercise

A 24-lb mass weight is attached to the end of a spring, stretches it 4 inches. Initially, the mass is released from rest from a point 3 inches above the equilibrium position.

a) Find the equation of the motion.

b) If the mass is initially released from the equilibrium position with a downward velocity of 2 ft/s

### Solution

$$m = \frac{24}{32} = \frac{3}{4}$$

$$W = mg$$

$$k \left( 4 \text{ in} \frac{1 \text{ ft}}{12 \text{ in}} \right) = 24$$

$$kx = mg$$

$$k = 72 \text{ lb/ft}$$

$$a) \quad \frac{3}{4} y'' + 72y = 0$$

$$my'' + \mu y' + ky = 0$$

$$\frac{3}{4} \lambda^2 + 72 = 0 \Rightarrow \lambda^2 = -96 \rightarrow \lambda_{1,2} = \pm 4i\sqrt{6}$$

$$y(t) = C_1 \cos 4t\sqrt{6} + C_2 \sin 4t\sqrt{6}; \quad y(0) = -\frac{3}{12} = -\frac{1}{4}, \quad y'(0) = 0$$

$$y(0) = -\frac{1}{4} \rightarrow C_1 = -\frac{1}{4}$$

$$y'(t) = -4\sqrt{6}C_1 \sin 4t\sqrt{6} + 4\sqrt{6}C_2 \cos 4t\sqrt{6}$$

$$y'(0) = 0 \rightarrow C_2 = 0$$

$$y(t) = -\frac{1}{4} \cos 4\sqrt{6}t$$

$$b) \quad y(t) = C_1 \cos 4t\sqrt{6} + C_2 \sin 4t\sqrt{6}; \quad y(0) = 0, \quad y'(0) = 2$$

$$y(0) = 0 \rightarrow C_1 = 0$$

$$y'(t) = -4\sqrt{6}C_1 \sin 4t\sqrt{6} + 4\sqrt{6}C_2 \cos 4t\sqrt{6}$$

$$y'(0) = 2 \rightarrow 4\sqrt{6}C_2 = 2 \Rightarrow C_2 = \frac{\sqrt{6}}{12}$$

$$y(t) = \frac{\sqrt{6}}{12} \sin 4\sqrt{6}t$$

### Exercise

The motion of a mass-spring system with damping is given by:

$$y'' + 4y' + ky = 0 ; \quad y(0) = 1, \quad y'(0) = 0$$

Find the equation of motion and sketch its graph for  $k = 2, 4, 6$ , and  $8$ .

### Solution

$$\lambda^2 + 4\lambda + k = 0 \rightarrow \lambda_{1,2} = \frac{-4 \pm \sqrt{16 - 4k}}{2} = \underline{-2 \pm \sqrt{4 - k}}$$

For  $k = 2$

$$\lambda_{1,2} = \underline{-2 \pm \sqrt{2}}$$

$$y(t) = C_1 e^{(-2-\sqrt{2})t} + C_2 e^{(-2+\sqrt{2})t}$$

$$y(0) = 1 \rightarrow C_1 + C_2 = 1$$

$$y'(t) = (-2-\sqrt{2})C_1 e^{(-2-\sqrt{2})t} + (-2+\sqrt{2})C_2 e^{(-2+\sqrt{2})t}$$


$$y'(0) = 0 \rightarrow (-2-\sqrt{2})C_1 + (-2+\sqrt{2})C_2 = 0$$

$$\begin{cases} C_1 + C_2 = 1 \\ (-2-\sqrt{2})C_1 + (-2+\sqrt{2})C_2 = 0 \end{cases}$$

$$\rightarrow \Delta = \begin{vmatrix} 1 & 1 \\ -2-\sqrt{2} & -2+\sqrt{2} \end{vmatrix} = 2\sqrt{2} \quad \Delta_{C_1} = \begin{vmatrix} 1 & 1 \\ 0 & -2+\sqrt{2} \end{vmatrix} = -2+\sqrt{2}$$

$$C_1 = \frac{-2+\sqrt{2}}{2\sqrt{2}} = \underline{\frac{1-\sqrt{2}}{2}} \quad C_2 = \underline{\frac{1+\sqrt{2}}{2}}$$

$$y(t) = \underline{\frac{1-\sqrt{2}}{2} e^{(-2-\sqrt{2})t} + \frac{1+\sqrt{2}}{2} e^{(-2+\sqrt{2})t}}$$



For  $k = 4$

$$\lambda_{1,2} = \underline{-2}$$


$$y(t) = (C_1 + C_2 t) e^{-2t}$$

$$y(0) = 1 \rightarrow \underline{C_1 = 1}$$

$$y'(t) = (C_2 - 2C_1 - 2C_2 t) e^{-2t}$$

$$y'(0) = 0 \rightarrow C_2 - 2C_1 = 0 \quad C_2 = 2$$

$$\underline{y(t) = (1 + 2t) e^{-2t}}$$



For  $k = 6$

$$\underline{\lambda_{1,2} = -2 \pm i\sqrt{2}}$$

$$y(t) = e^{-2t} (C_1 \cos \sqrt{2}t + C_2 \sin \sqrt{2}t)$$

$$y(0) = 1 \rightarrow \underline{C_1 = 1}$$


$$y'(t) = e^{-2t} (-2C_1 \cos \sqrt{2}t - 2C_2 \sin \sqrt{2}t - \sqrt{2}C_1 \sin \sqrt{2}t + \sqrt{2}C_2 \cos \sqrt{2}t)$$

$$y'(0) = 0 \rightarrow -2C_1 + \sqrt{2}C_2 = 0 \quad C_2 = \sqrt{2}$$

$$\underline{y(t) = e^{-2t} (\cos \sqrt{2}t + \sqrt{2} \sin \sqrt{2}t)}$$

$$A = \sqrt{1+2} = \sqrt{3} \quad \& \quad \phi = \tan^{-1} \frac{1}{\sqrt{2}} \approx 0.615$$

$$\underline{y(t) = \sqrt{3} e^{-2t} \sin(\sqrt{2}t - 0.615)}$$



For  $k = 8$

$$\lambda_{1,2} = -2 \pm 2i$$

$$y(t) = e^{-2t} (C_1 \cos 2t + C_2 \sin 2t)$$

$$y(0) = 1 \rightarrow C_1 = 1$$



$$y'(t) = e^{-2t} (-2C_1 \cos 2t - 2C_2 \sin 2t - 2C_1 \sin 2t + 2C_2 \cos 2t)$$

$$y'(0) = 0 \rightarrow -2C_1 + 2C_2 = 0 \quad C_2 = 1$$

$$y(t) = e^{-2t} (\cos 2t + \sin 2t)$$

$$A = \sqrt{1+1} = \sqrt{2} \quad \& \quad \phi = \tan^{-1} \frac{1}{1} = \frac{\pi}{4}$$

$$y(t) = \sqrt{2} e^{-2t} \sin\left(2t - \frac{\pi}{4}\right)$$



### Exercise

A 10-lb mass weight is attached to the end of a spring, stretches it 3 inches. This mass is removed and replaced with a mass of 1.6 slugs, which initially released from a point 4 inches above the equilibrium position with a downward velocity of  $\frac{5}{4}$  ft/s

- Find the equation of the motion.
- Find the amplitude, phase angle, period and the frequency.
- Express the motion equation in amplitude and phase angle form.
- Determine the times the mass attains a displacement below the equilibrium position numerically equal to  $\frac{1}{2}$  the amplitude of motion.

### Solution

$$a) \quad 1.6y'' + 40y = 0; \quad y(0) = -\frac{1}{3}, \quad y'(0) = \frac{5}{4}$$

$$1.6\lambda^2 + 40 = 0 \rightarrow \lambda_{1,2} = \pm 5i$$

$$y(t) = C_1 \cos 5t + C_2 \sin 5t$$

$$y(0) = -\frac{1}{3} \rightarrow C_1 = -\frac{1}{3}$$

$$y'(t) = -5C_1 \sin 5t + 5C_2 \cos 5t$$

$$y'(0) = \frac{5}{4} \rightarrow C_2 = \frac{1}{4}$$

$$y(t) = -\frac{1}{3} \cos 5t + \frac{1}{4} \sin 5t$$

b) Amplitude:  $A = \sqrt{\frac{1}{9} + \frac{1}{16}} = \frac{5}{12}$

Phase angle:  $\phi = \tan^{-1} \left| -\frac{3}{4} \right| \approx 0.9273$

Period:  $T = \frac{2\pi}{5} \quad T = \frac{2\pi}{\omega_0}$

Frequency:  $f = \frac{5}{2\pi} \quad f = \frac{1}{T}$

c)  $y(t) = \frac{5}{12} \sin(5t - 0.9273)$

d)  $y(t) = \frac{1}{2} A = \frac{5}{24}$

$$\frac{5}{24} = \frac{5}{12} \sin(5t - 0.9273) \rightarrow \sin(5t - 0.9273) = \frac{1}{2}$$

$$5t - 0.9273 = \frac{\pi}{6} + 2n\pi \quad \& \quad 5t - 0.9273 = \frac{5\pi}{6} + 2n\pi$$

$$t = \frac{1}{5} \left( \frac{\pi}{6} + 0.9273 + 2n\pi \right) \quad \& \quad t = \frac{1}{5} \left( \frac{5\pi}{6} + 0.9273 + 2n\pi \right)$$

## Exercise

A 64-*lb* mass weight is attached to the end of a spring, stretches it 0.32 *foot*. This mass is initially released from a point 8 *inches* above the equilibrium position with a downward velocity of 5 *ft/s*.

- Find the equation of the motion.
- Find the amplitude, phase angle, period and the frequency.
- Write the motion equation with phase angle form.
- How many complete cycles will the mass have completed at the end of  $3\pi$  *sec*.
- At what time does the mass pass through the equilibrium position heading downward for the second time?
- At what times does the mass attain its extreme displacements on either side of the equilibrium position?
- What is the position of the mass at  $t = 3$  *sec*?
- What is the instantaneous velocity at  $t = 3$  *sec*?
- What is the acceleration at  $t = 3$  *sec*?



- j) What is the instantaneous velocity at the times when the mass passes through the equilibrium position?
- k) At what times is the mass 5 inches below the equilibrium position?
- l) At what times is the mass 5 inches below the equilibrium position heading in the upward direction?

### Solution

$$m = \frac{64}{32} = 2 \text{ slugs}$$

$$W = mg$$

$$k(0.32 f)t = 64 \rightarrow k = 200 \text{ lb/ft}$$

$$kx = mg$$

$$a) \quad 2y'' + 200y = 0; \quad y(0) = -\frac{2}{3}, \quad y'(0) = 5$$

$$my'' + \mu y' + ky = 0$$

$$\lambda^2 + 100 = 0 \rightarrow \lambda_{1,2} = \pm 10i$$

$$y(t) = C_1 \cos 10t + C_2 \sin 10t$$

$$y(0) = -\frac{2}{3} \rightarrow C_1 = -\frac{2}{3}$$

$$y'(t) = -10C_1 \sin 10t + 10C_2 \cos 10t$$

$$y'(0) = 5 \rightarrow C_2 = \frac{1}{2}$$

$$y(t) = -\frac{2}{3} \cos 10t + \frac{1}{2} \sin 10t$$

$$b) \text{ Amplitude: } A = \sqrt{\frac{4}{9} + \frac{1}{4}} = \frac{5}{6}$$

$$\text{Phase angle: } \phi = \tan^{-1} \left| -\frac{4}{3} \right| \approx 0.9273$$

$$\text{Period: } T = \frac{2\pi}{10} = \frac{\pi}{5} \quad T = \frac{2\pi}{\omega_0}$$

$$\text{Frequency: } f = \frac{5}{\pi} \quad f = \frac{1}{T}$$

$$c) \quad y(t) = \frac{5}{6} \sin(10t - 0.9273)$$

$$d) \quad T = \frac{\pi}{5} n = 3\pi \rightarrow n = 15 \text{ cycles}$$

$$e) \text{ Mass passes through the equilibrium position: } y(t) = 0$$

$$y(t) = \frac{5}{6} \sin(10t - 0.9273) = 0$$

$$10t - 0.9273 = n\pi \rightarrow \text{second time } 10t - 0.9273 = 2\pi$$

$$t = \frac{2\pi + 0.9273}{10} \approx 0.721 \text{ sec}$$

$$f) \quad y'(t) = \frac{25}{3} \cos(10t - 0.9273) = 0$$

$$10t - 0.9273 = \frac{\pi}{2} + n\pi$$

$$t = \frac{(2n+1)\pi}{20} + 0.09273$$

$$g) \quad y(t=3) = \frac{5}{6} \sin(30 - 0.9273) \approx -0.597 \text{ ft}$$

$$h) \quad y'(t=3) = \frac{25}{3} \cos(30 - 0.9273) \approx -5.814 \text{ ft/s}$$

$$i) \quad y''(t) = -\frac{250}{3} \sin(10t - 0.9273)$$

$$y''(t=3) = -\frac{250}{3} \sin(30 - 0.9273) \approx -59.685 \text{ ft/s}^2$$

$$j) \quad y(t) = 0 \rightarrow 10t - 0.9273 = n\pi \quad t = \frac{1}{10}(n\pi + 0.9273)$$

$$\begin{aligned} y'\left(t = \frac{1}{10}(n\pi + 0.9273)\right) &= \frac{25}{3} \cos(n\pi + 0.9273 - 0.9273) \\ &= \frac{25}{3} \cos(n\pi) \quad \cos(n\pi) = \pm 1 \\ &\approx \pm 8.33 \text{ ft/s} \end{aligned}$$

$$k) \quad y = 5 \text{ in} \frac{1 \text{ ft}}{12 \text{ in}} = \frac{5}{12} \text{ ft}$$

$$y(t) = \frac{5}{6} \sin(10t - 0.9273) = \frac{5}{12}$$

$$\sin(10t - 0.9273) = \frac{1}{2}$$

$$10t - 0.9273 = \frac{\pi}{6} + 2n\pi \quad \& \quad 10t - 0.9273 = \frac{5\pi}{6} + 2n\pi$$

$$t = \frac{1}{10} \left( \frac{\pi}{6} + 2n\pi + 0.9273 \right) \quad \& \quad t = \frac{1}{10} \left( \frac{5\pi}{6} + 2n\pi + 0.9273 \right)$$

$$l) \quad y = \frac{5}{12} \text{ ft} \quad \& \quad y'(t) < 0$$

$$t = \frac{1}{10} \left( \frac{5\pi}{6} + 2n\pi + 0.9273 \right)$$

## Exercise

If it is underdamped, write the position function in the form  $x(t) = C_1 e^{-pt} \cos(\omega_1 t - \alpha_1)$ .

Also, find the undamped position function  $u(t) = C_0 \cos(\omega_0 t - \alpha_0)$  that would result if the mass on the spring were set in motion with the same initial position and velocity, but with the dashpot disconnected (so  $c = 0$ ). Then, construct a figure that illustrates the effect of damping by comparing the graphs of  $x(t)$  and

$$u(t) \quad m = \frac{1}{2}, \quad c = 3, \quad k = 4; \quad x_0 = 2, \quad v_0 = 0$$

## Solution

### With damping motion

$$\frac{1}{2}x'' + 3x' + 4x = 0 \quad mx'' + cx' + kx = 0$$

$$\lambda^2 + 6\lambda + 8 = 0 \rightarrow \lambda_{1,2} = -4, -2$$

$$x(t) = C_1 e^{-4t} + C_2 e^{-2t}$$

$$x(0) = C_1 + C_2 = 2$$

$$x'(t) = -4C_1 e^{-4t} - 2C_2 e^{-2t} \rightarrow x'(0) = -4C_1 - 2C_2 = 0$$

$$\begin{cases} C_1 + C_2 = 2 \\ -4C_1 - 2C_2 = 0 \end{cases} \rightarrow C_1 = -2 \quad C_2 = 4$$

$$x(t) = -2e^{-4t} + 4e^{-2t} \quad (\text{Overdamped motion})$$

### Without damping ( $c = 0$ )

$$\frac{1}{2}x'' + 4x = 0 \quad mx'' + kx = 0$$

$$\lambda^2 + 8 = 0 \rightarrow \lambda_{1,2} = \pm 2i\sqrt{2}$$


$$u(t) = A \cos(2\sqrt{2}t) + B \sin(2\sqrt{2}t)$$

$$u(0) = A = 2$$

$$u'(t) = -2A\sqrt{2} \sin(2\sqrt{2}t) + 2B\sqrt{2} \cos(2\sqrt{2}t)$$

$$\rightarrow u'(0) = 2B\sqrt{2} = 0 \Rightarrow B = 0$$

$$u(t) = 2 \cos(2\sqrt{2}t)$$



### Exercise

If it is underdamped, write the position function in the form  $x(t) = C_1 e^{-pt} \cos(\omega_1 t - \alpha_1)$ .

Also find the undamped position function  $u(t) = C_0 \cos(\omega_0 t - \alpha_0)$  that would result if the mass on the spring were set in motion with the same initial position and velocity, but with the dashpot disconnected (so  $c = 0$ ). Then, construct a figure that illustrates the effect of damping by comparing the graphs of  $x(t)$  and  $u(t)$

$$m = 1, \quad c = 8, \quad k = 16; \quad x_0 = 5, \quad v_0 = -10$$

### Solution

#### With damping motion

$$x'' + 8x' + 16x = 0 \qquad mx'' + cx' + kx = 0$$

$$\lambda^2 + 8\lambda + 16 = 0 \rightarrow \lambda_{1,2} = -4$$

$$x(t) = (C_1 + C_2 t) e^{-4t}$$

$$x(0) = C_1 = 5$$

$$x'(t) = (C_2 - 4C_1 - 4C_2 t) e^{-4t}$$

$$x'(0) = C_2 - 4C_1 = -10 \Rightarrow C_2 = 10$$

$$x(t) = (5 + 10t) e^{-2t} \quad (\text{Overdamped motion})$$

#### Without damping ( $c = 0$ )

$$x'' + 16x = 0 \qquad mx'' + kx = 0$$

$$\lambda^2 + 16 = 0 \rightarrow \lambda_{1,2} = \pm 4i$$

$$u(t) = A \cos(4t) + B \sin(4t)$$

$$u(0) = A = 5$$


$$u'(t) = -4A \sin(4t) + 4B \cos(4t)$$

$$\rightarrow u'(0) = 4B = -10 \Rightarrow B = -\frac{5}{2}$$

$$A = \sqrt{25 + \frac{25}{4}} = \frac{5\sqrt{5}}{2} \quad \phi = \tan^{-1}\left(-\frac{1}{2}\right) = -0.4636$$

$$u(t) = 5 \cos(4t) - \frac{5}{2} \sin(4t)$$

$$= \frac{5\sqrt{5}}{2} \cos(4t + 0.4636)$$



## Exercise

If it is underdamped, write the position function in the form  $x(t) = C_1 e^{-pt} \cos(\omega_1 t - \alpha_1)$ .

Also find the undamped position function  $u(t) = C_0 \cos(\omega_0 t - \alpha_0)$  that would result if the mass on the spring were set in motion with the same initial position and velocity, but with the dashpot disconnected (so  $c = 0$ ). Then, construct a figure that illustrates the effect of damping by comparing the graphs of  $x(t)$  and  $u(t)$

$$m = 1, \quad c = 10, \quad k = 125; \quad x_0 = 6, \quad v_0 = 50$$

## Solution

### With damping motion

$$x'' + 10x' + 125x = 0 \qquad mx'' + cx' + kx = 0$$

$$\lambda^2 + 10\lambda + 125 = 0 \rightarrow \lambda_{1,2} = -5 \pm 10i$$

$$x(t) = e^{-5t} (A \cos 10t + B \sin 10t) \qquad x(0) = \underline{A = 6}$$

$$x'(t) = (-5A \cos 10t - 5B \sin 10t - 10A \sin 10t + 10B \cos 10t) e^{-5t}$$

$$\rightarrow x'(0) = -5A + 10B = 50 \Rightarrow \underline{B = 8}$$

$$A = \sqrt{36 + 64} = \underline{10} \qquad \phi = \tan^{-1}\left(\frac{4}{3}\right) = \underline{0.9273}$$

$$x(t) = e^{-5t} (6 \cos 10t + 8 \sin 10t) \\ = \underline{10e^{-5t} \cos(10t - 0.9273)} \quad (\text{Overdamped motion})$$

### Without damping ( $c = 0$ )

$$x'' + 125x = 0 \qquad mx'' + kx = 0$$

$$\lambda^2 + 125 = 0 \rightarrow \lambda_{1,2} = \pm 5i\sqrt{5}$$

$$u(t) = A \cos(5\sqrt{5} t) + B \sin(5\sqrt{5} t)$$


$$u(0) = \underline{A = 6}$$

$$u'(t) = -5\sqrt{5}A \sin(5\sqrt{5} t) + 5\sqrt{5}B \cos(5\sqrt{5} t)$$

$$\rightarrow x'(0) = 5\sqrt{5}B = 50 \Rightarrow \underline{B = 2\sqrt{5}}$$

$$A = \sqrt{36 + 20} = \underline{2\sqrt{14}} \qquad \phi = \tan^{-1}\left(\frac{\sqrt{5}}{3}\right) = \underline{0.6405}$$

$$u(t) = 6 \cos(5\sqrt{5} t) + 2\sqrt{5} \sin(5\sqrt{5} t) \\ = \underline{2\sqrt{14} \cos(5\sqrt{5} t - .6405)}$$



## Exercise

If it is underdamped, write the position function in the form  $x(t) = C_1 e^{-pt} \cos(\omega_1 t - \alpha_1)$ .

Also find the undamped position function  $u(t) = C_0 \cos(\omega_0 t - \alpha_0)$  that would result if the mass on the spring were set in motion with the same initial position and velocity, but with the dashpot disconnected (so  $c = 0$ ). Then, construct a figure that illustrates the effect of damping by comparing the graphs of  $x(t)$  and

$$u(t) \quad m = 2, \quad c = 12, \quad k = 50; \quad x_0 = 0, \quad v_0 = -8$$

## Solution

### With damping motion

$$2x'' + 12x' + 50x = 0 \quad mx'' + cx' + kx = 0$$

$$\lambda^2 + 6\lambda + 25 = 0 \rightarrow \lambda_{1,2} = 3 \pm 4i$$

$$x(t) = e^{3t} (A \cos 4t + B \sin 4t)$$

$$x(0) = A = 0$$

$$x'(t) = (3A \cos 4t + 3B \sin 4t - 4A \sin 4t + 4B \cos 4t) e^{3t}$$

$$\rightarrow x'(0) = 3A + 4B = -8 \Rightarrow B = -2$$

$$x(t) = -2e^{3t} \sin 4t$$

$$= 2e^{3t} \cos\left(4t - \frac{3\pi}{2}\right) \quad (\text{Overdamped motion})$$

### Without damping ( $c = 0$ )

$$2x'' + 50x = 0 \quad mx'' + kx = 0$$

$$2\lambda^2 + 50 = 0 \rightarrow \lambda_{1,2} = \pm 5i$$

$$u(t) = A \cos(5t) + B \sin(5t)$$


$$u(0) = A = 0$$

$$u'(t) = -5A \sin(t) + 5B \cos(5t)$$

$$\rightarrow u'(0) = 5B = -8 \Rightarrow B = -\frac{8}{5}$$

$$u(t) = -\frac{8}{5} \sin(5t)$$

$$= \frac{8}{5} \cos\left(5t - \frac{3\pi}{2}\right)$$



## Exercise

If it is underdamped, write the position function in the form  $x(t) = C_1 e^{-pt} \cos(\omega_1 t - \alpha_1)$ .

Also find the undamped position function  $u(t) = C_0 \cos(\omega_0 t - \alpha_0)$  that would result if the mass on the spring were set in motion with the same initial position and velocity, but with the dashpot disconnected (so  $c = 0$ ). Then, construct a figure that illustrates the effect of damping by comparing the graphs of  $x(t)$  and

$$u(t) \quad m = 2, \quad c = 16, \quad k = 40; \quad x_0 = 5, \quad v_0 = 4$$

## Solution

### With damping motion

$$2x'' + 16x' + 40x = 0 \quad mx'' + cx' + kx = 0$$

$$\lambda^2 + 8\lambda + 20 = 0 \rightarrow \lambda_{1,2} = -4 \pm 2i$$

$$x(t) = e^{-4t} (A \cos 2t + B \sin 2t)$$

$$x(0) = A = 5$$

$$x'(t) = (-4A \cos 2t - 4B \sin 2t - 2A \sin 2t + 2B \cos 2t) e^{-4t}$$

$$\rightarrow x'(0) = -4A + 2B = 4 \Rightarrow B = 12$$

$$A = \sqrt{25 + 144} = 13 \quad \phi = \tan^{-1}\left(\frac{12}{5}\right) = 1.176$$

$$x(t) = e^{-4t} (5 \cos 2t + 12 \sin 2t) \\ = 12e^{-4t} \cos(2t - 1.176) \quad (\text{Overdamped motion})$$

### Without damping ( $c = 0$ )

$$2x'' + 40x = 0 \quad mx'' + kx = 0$$

$$\lambda^2 + 20 = 0 \rightarrow \lambda_{1,2} = \pm 2\sqrt{5}i$$

$$u(t) = A \cos(2\sqrt{5} t) + B \sin(2\sqrt{5} t)$$


$$u(0) = A = 5$$

$$u'(t) = -2\sqrt{5}A \sin(2\sqrt{5} t) + 2\sqrt{5}B \cos(2\sqrt{5} t)$$

$$\rightarrow x'(0) = 2\sqrt{5}B = 4 \Rightarrow B = \frac{2\sqrt{5}}{5}$$

$$A = \sqrt{25 + \frac{4}{5}} = \sqrt{\frac{129}{5}} \quad \phi = \tan^{-1}\left(\frac{2\sqrt{5}}{25}\right) = 0.177$$

$$u(t) = 5 \cos(2\sqrt{5} t) - \frac{2\sqrt{5}}{5} \sin(2\sqrt{5} t) \\ = \sqrt{\frac{129}{5}} \cos(2\sqrt{5} t - 0.177)$$



### Exercise

If it is underdamped, write the position function in the form  $x(t) = C_1 e^{-pt} \cos(\omega_1 t - \alpha_1)$ .

Also find the undamped position function  $u(t) = C_0 \cos(\omega_0 t - \alpha_0)$  that would result if the mass on the spring were set in motion with the same initial position and velocity, but with the dashpot disconnected (so  $c = 0$ ). Then, construct a figure that illustrates the effect of damping by comparing the graphs of  $x(t)$  and

$$u(t) \quad m = 3, \quad c = 30, \quad k = 63; \quad x_0 = 2, \quad v_0 = 2$$

### Solution

#### With damping motion

$$3x'' + 30x' + 63x = 0 \quad mx'' + cx' + kx = 0$$

$$\lambda^2 + 10\lambda + 21 = 0 \rightarrow \lambda_{1,2} = -7, -3$$

$$x(t) = C_1 e^{-7t} + C_2 e^{-3t}$$

$$x(0) = C_1 + C_2 = 2$$

$$x'(t) = -7C_1 e^{-7t} - 3C_2 e^{-3t}$$

$$\rightarrow x'(0) = -7C_1 - 3C_2 = 2$$

$$\begin{cases} C_1 + C_2 = 2 \\ -7C_1 - 3C_2 = 2 \end{cases} \rightarrow \underline{C_1 = -2} \quad \underline{C_2 = 4}$$

$$x(t) = 4e^{-3t} - 2e^{-7t} \quad (\text{Overdamped motion})$$

#### Without damping ( $c = 0$ )

$$3x'' + 63x = 0 \quad mx'' + kx = 0$$

$$\lambda^2 + 21 = 0 \rightarrow \lambda_{1,2} = \pm i\sqrt{21}$$

$$u(t) = A \cos(\sqrt{21} t) + B \sin(\sqrt{21} t)$$

$$u(0) = A = 2$$


$$u'(t) = -A\sqrt{21} \sin(\sqrt{21} t) + B\sqrt{21} \cos(\sqrt{21} t)$$

$$\rightarrow u'(0) = \sqrt{21}B = 2 \Rightarrow B = \frac{2}{\sqrt{21}}$$

$$A = \sqrt{4 + \frac{4}{21}} = 2\sqrt{\frac{22}{21}} \quad \phi = \tan^{-1}\left(\frac{1}{\sqrt{21}}\right) = 0.2149$$

$$u(t) = 2\cos(\sqrt{21} t) + \frac{2}{\sqrt{21}}\sin(\sqrt{21} t)$$

$$= 2\sqrt{\frac{22}{21}} \cos(\sqrt{21} t - 0.2149)$$





## Exercise

If it is underdamped, write the position function in the form  $x(t) = C_1 e^{-pt} \cos(\omega_1 t - \alpha_1)$ .

Also find the undamped position function  $u(t) = C_0 \cos(\omega_0 t - \alpha_0)$  that would result if the mass on the spring were set in motion with the same initial position and velocity, but with the dashpot disconnected (so  $c = 0$ ). Finally, construct a figure that illustrates the effect of damping by comparing the graphs of  $x(t)$  and  $u(t)$

$m = 4, \quad c = 20, \quad k = 169; \quad x_0 = 4, \quad v_0 = 16$

## Solution

### With damping motion

$$4x'' + 20x' + 169x = 0 \qquad mx'' + cx' + kx = 0$$

$$4\lambda^2 + 20\lambda + 169 = 0 \rightarrow \lambda_{1,2} = -\frac{5}{2} \pm 6i$$

$$x(t) = e^{-\frac{5}{2}t} (A \cos 6t + B \sin 6t)$$

$$x(0) = A = 5$$

$$x'(t) = \left( -\frac{5}{2} A \cos 6t - \frac{5}{2} B \sin 6t - 6A \sin 6t + 6B \cos 6t \right) e^{-\frac{5}{2}t}$$

$$\rightarrow x'(0) = -\frac{5}{2} A + 6B = 16 \Rightarrow 6B = 16 + 10 \rightarrow B = \frac{13}{3}$$

$$A = \sqrt{16 + \frac{169}{9}} = \frac{\sqrt{313}}{3} \quad \phi = \tan^{-1}\left(\frac{13}{12}\right) = 0.8254$$

$$x(t) = e^{-\frac{5}{2}t} \left( 4 \cos 6t + \frac{13}{3} \sin 6t \right)$$

$$= \frac{\sqrt{313}}{3} e^{-\frac{5}{2}t} \cos(6t - 0.8254) \quad (\text{Overdamped motion})$$

### Without damping ( $c = 0$ )

$$4x'' + 169x = 0 \qquad mx'' + kx = 0$$


$$4\lambda^2 + 169 = 0 \rightarrow \lambda_{1,2} = \pm \frac{13}{2}i$$

$$u(t) = A \cos\left(\frac{13}{2}t\right) + B \sin\left(\frac{13}{2}t\right)$$

$$u(0) = A = 4$$

$$u'(t) = -\frac{13}{2} A \sin\left(\frac{13}{2}t\right) + \frac{13}{2} B \cos\left(\frac{13}{2}t\right)$$

$$\rightarrow x'(0) = \frac{13}{2} B = 16 \Rightarrow B = \frac{32}{13}$$



$$A = \sqrt{16 + \frac{1,024}{169}} = \frac{4\sqrt{233}}{13} \quad \phi = \tan^{-1}\left(\frac{8}{13}\right) = 0.5517$$

$$u(t) = 4\cos\left(\frac{13}{2}t\right) + \frac{32}{13}\sin\left(\frac{13}{2}t\right) \\ = \frac{4\sqrt{233}}{13}\cos\left(\frac{13}{2}t - 0.5517\right)$$

### Exercise

Suppose that the mass in a mass–spring–dashpot system with  $m = 10$ ,  $c = 9$ , and  $k = 2$  is set in motion with  $x(0) = 0$  and  $x'(0) = 5$

- Find the position function  $x(t)$  and graph the function
- Find how far the mass moves to the right before starting back toward the origin.

### Solution

$$a) \quad 10x'' + 9x' + 2x = 0 \qquad mx'' + cx' + kx = 0$$

$$\text{The characteristic equation: } 10\lambda^2 + 9\lambda + 2 = 0 \rightarrow \lambda_{1,2} = \frac{-9 \pm 1}{20} = \underline{\underline{-\frac{1}{2}, -\frac{2}{5}}}$$

$$x(t) = C_1 e^{-t/2} + C_2 e^{-2t/5}$$

$$x(0) = 0 \rightarrow C_1 + C_2 = 0$$

$$x'(t) = -\frac{1}{2}C_1 e^{-t/2} - \frac{2}{5}C_2 e^{-2t/5}$$

$$x'(0) = 5 \rightarrow -\frac{1}{2}C_1 - \frac{2}{5}C_2 = 5 \Rightarrow 5C_1 + 4C_2 = -50$$

$$-4 \begin{cases} C_1 + C_2 = 0 \\ 5C_1 + 4C_2 = -50 \end{cases} \rightarrow \underline{\underline{C_1 = -50, C_2 = 50}}$$

$$x(t) = \underline{\underline{-50e^{-t/2} + 50e^{-2t/5}}}$$

$$b) \quad x'(t) = 25e^{-t/2} - 20e^{-2t/5} = 0$$


$$5e^{-t/2} = 4e^{-2t/5}$$

$$e^{-t/10} = \frac{4}{5}$$

$$\underline{\underline{t = -10 \ln \frac{4}{5} \approx 2.2314}}$$

The farthest distance to the right of the mass is:

$$x\left(t = -10 \ln \frac{4}{5}\right) = -50e^{5 \ln 4/5} + 50e^{4 \ln 4/5} \\ = 50 \left( -\left(\frac{4}{5}\right)^5 + \left(\frac{4}{5}\right)^4 \right)$$



$$= 50 \left( \frac{4}{5} \right)^4 \left( 1 - \frac{4}{5} \right)$$

$$\underline{= 10 \left( \frac{4}{5} \right)^4 = 4.096}$$

### Exercise

Suppose that the mass in a mass–spring–dashpot system with  $m = 25$ ,  $c = 10$ , and  $k = 226$  is set in motion with  $x(0) = 20$  and  $x'(0) = 41$

- Find the position function  $x(t)$  and graph the function
- Find the pseudoperiod of the oscillations and the equations of the “envelope curves” that are dashed.

### Solution

$$a) \quad 25x'' + 10x' + 226x = 0 \qquad mx'' + cx' + kx = 0$$

$$\text{The characteristic equation: } 25\lambda^2 + 10\lambda + 226 = 0 \rightarrow \lambda_{1,2} = \frac{-10 \pm 150}{50} = \underline{-\frac{1}{5} \pm 3i}$$

$$x(t) = e^{-t/5} (C_1 \cos 3t + C_2 \sin 3t)$$

$$\underline{x(0) = 20 \rightarrow C_1 = 20}$$

$$x(t) = e^{-t/5} \left( -\frac{1}{5}C_1 \cos 3t - \frac{1}{5}C_2 \sin 3t - 3C_1 \sin 3t + 3C_2 \cos 3t \right)$$


$$\underline{x'(0) = 41 \rightarrow -\frac{1}{5}C_1 + 3C_2 = 41 \Rightarrow C_2 = 15}$$

$$\underline{x(t) = e^{-t/5} (20 \cos 3t + 15 \sin 3t)}$$

$$A = \sqrt{20^2 + 15^2} = \underline{25}$$

$$\phi = \tan^{-1} \frac{3}{4} \approx \underline{0.6435}$$

$$\underline{x(t) = 25e^{-t/5} \cos(3t - 0.6435)}$$



b) Since  $-1 \leq \cos \theta \leq 1$ , then the oscillation are bounded by the curves  $x(t) = \pm 25e^{-t/5}$  and

pseudoperiod:  $T = \frac{2\pi}{\omega} = \frac{2\pi}{3}$

### Exercise

A mass of 1 *slug* is suspended from a spring, the spring constant is 9 *lb/ft*. The mass is initially released from a point 1 *foot* above the equilibrium position with an upward velocity of  $\sqrt{3}$  *ft/s*. Find the times at which the mass is heading downward at a velocity of 3 *ft/s*

### Solution

$$y'' + 9y = 0 ; \quad y(0) = -1, \quad y'(0) = -\sqrt{3}$$

$$mx'' + \mu x' + kx = 0$$

$$\lambda^2 + 9 = 0 \rightarrow \lambda_{1,2} = \pm 3i$$

$$y_h = C_1 \cos 3t + C_2 \sin 3t$$

$$y(0) = -1 \rightarrow C_1 = -1$$

$$y'_h = -3C_1 \sin 3t + 3C_2 \cos 3t$$

$$y'(0) = -\sqrt{3} \rightarrow C_2 = -\frac{\sqrt{3}}{3}$$

$$y(t) = -\cos 3t + \frac{\sqrt{3}}{3} \sin 3t$$

$$A = \sqrt{(-1)^2 + \left(\frac{\sqrt{3}}{3}\right)^2} = \frac{2}{\sqrt{3}}$$

$$\phi = \tan^{-1} \frac{-\sqrt{3}}{3} = -\frac{\pi}{6}$$

$$y(t) = \frac{2}{\sqrt{3}} \cos\left(3t + \frac{\pi}{6}\right)$$

$$y'(t) = -2\sqrt{3} \sin\left(3t + \frac{\pi}{6}\right) = 3$$

$$\sin\left(3t + \frac{\pi}{6}\right) = -\frac{\sqrt{3}}{2}$$

$$3t + \frac{\pi}{6} = \frac{4\pi}{3} + 2n\pi$$

$$3t + \frac{\pi}{6} = \frac{5\pi}{3} + 2n\pi$$

$$t = \frac{7\pi}{18} + \frac{2n\pi}{3}$$

$$t = \frac{\pi}{2} + \frac{2n\pi}{3}$$

## Exercise

Two parallel springs, with constants  $k_1$  and  $k_2$ , support a single mass, the effective spring constant of the system is given by  $k = \frac{4k_1 k_2}{k_1 + k_2}$ .

A mass weight 20 pounds stretches one spring 6 inches and another spring 2 inches. The springs are attached to a common rigid support and then to a metal plate. The mass is attached to the center of the plate in the double-spring constant arrangement.

- Determine the effective spring constant of this system.
- Find the equation of motion if the mass is initially released from the equilibrium position with a downward velocity of 2 ft/s.

## Solution

$$m = \frac{20}{32} = \frac{5}{8} \text{ slug}$$

$$W = mg$$

$$a) \quad k_1 (0.5 \text{ ft}) = 20 \rightarrow k_1 = 40 \text{ lb/ft} \quad kx = mg$$

$$k_2 \left( \frac{2}{12} \text{ ft} \right) = 20 \rightarrow k_2 = 120 \text{ lb/ft}$$

$$k = \frac{4(40)(120)}{40 + 120} = 120 \text{ lb/ft}$$

$$k = \frac{4k_1 k_2}{k_1 + k_2}$$

$$b) \quad \frac{5}{8} x'' + 120x = 0$$

$$x'' + 192x = 0; \quad x(0) = 0, \quad x'(0) = 2$$

$$\lambda^2 + 192 = 0 \rightarrow \lambda_{1,2} = \pm 8i\sqrt{3}$$


$$x(t) = C_1 \cos 8\sqrt{3}t + C_2 \sin 8\sqrt{3}t$$

$$x(0) = 0 \rightarrow C_1 = 0$$

$$x'(t) = -8\sqrt{3}C_1 \sin 8\sqrt{3}t + 8\sqrt{3}C_2 \cos 8\sqrt{3}t$$

$$x'(0) = 2 \rightarrow 8\sqrt{3}C_2 = 2 \quad C_2 = \frac{\sqrt{3}}{12}$$

$$x(t) = \frac{\sqrt{3}}{12} \sin 8\sqrt{3}t$$



### Exercise

A 12-lb weight is attached both to a vertically suspended spring that it stretches 6 in. and to a dashpot that provides 3 lb. of resistance for every foot per second of velocity.

- a) If the weight is pulled down 1 foot. below its static equilibrium position and then released from rest at time  $t = 0$ , find its position function  $x(t)$ .
- b) Find the frequency, time-varying amplitude, and phase angle of the motion.

### Solution

**Given:**  $c = 3$  lb-sec/ft

$$m = \frac{12}{32} = \frac{3}{8} \text{ slug} \qquad W = mg$$

$$k\left(\frac{6}{12} \text{ ft}\right) = 12 \rightarrow k = 24 \text{ lb/ft} \qquad kx = mg$$

a)  $\frac{3}{8}x'' + 3x + 24 = 0$

$$x'' + 8x + 64 = 0; \quad x(0) = 1, \quad x'(0) = 0$$

$$\lambda^2 + 8\lambda + 64 = 0 \rightarrow \lambda_{1,2} = \frac{-8 \pm 8i\sqrt{3}}{2} = -4 \pm 4i\sqrt{3}$$

$$x(t) = (C_1 \cos 4\sqrt{3}t + C_2 \sin 4\sqrt{3}t)e^{-4t}$$

$$x(0) = 1 \rightarrow C_1 = 1$$

$$x'(t) = (-4\sqrt{3}C_1 \sin 4\sqrt{3}t + 4\sqrt{3}C_2 \cos 4\sqrt{3}t - 4C_1 \cos 4\sqrt{3}t - 4C_2 \sin 4\sqrt{3}t)e^{-4t}$$

$$x'(0) = 0 \rightarrow 4\sqrt{3}C_2 - 4C_1 = 0 \Rightarrow C_2 = \frac{\sqrt{3}}{3}$$

$$x(t) = e^{-4t} \left( \cos 4\sqrt{3}t + \frac{\sqrt{3}}{3} \sin 4\sqrt{3}t \right)$$

b) Frequency:  $4\sqrt{3} \approx 6.93 \text{ rad/sec}$

Time-varying amplitude  $A = \sqrt{1 + \frac{1}{3}} = \frac{2}{\sqrt{3}}$

Phase angle  $\phi = \tan^{-1} \frac{\sqrt{3}}{3} = \frac{\pi}{6}$

$$x(t) = \frac{2}{\sqrt{3}} e^{-4t} \cos\left(4\sqrt{3}t - \frac{\pi}{6}\right)$$

### Exercise

A  $\frac{1}{8}$ -kg mass is attached to a spring with a spring constant  $k = 16 \text{ N/m}$ . The mass is displaced  $\frac{1}{2} \text{ m}$  to the right of the equilibrium point and given an outward velocity (to the right) of  $\sqrt{2} \text{ m/sec}$ . Neglecting any damping or external forces that may be present,

- Determine the equation of motion of the mass
- Determine the equation of motion amplitude, period, and natural frequency.
- How long after release does the mass pass through the equilibrium position?

### Solution

$$a) \quad \frac{1}{8}x'' + 16x = 0 \qquad mx'' + \mu x' + kx = 0$$

$$x'' + 128x = 0; \quad x(0) = \frac{1}{2}, \quad x'(0) = \sqrt{2}$$

$$\lambda^2 + 128 = 0 \rightarrow \lambda_{1,2} = \pm 8i\sqrt{2}$$

$$x_h = C_1 \cos 8\sqrt{2}t + C_2 \sin 8\sqrt{2}t$$

$$x(0) = \frac{1}{2} \rightarrow C_1 = \frac{1}{2}$$

$$x'_h = -8\sqrt{2}C_1 \sin 8\sqrt{2}t + 8\sqrt{2}C_2 \cos 8\sqrt{2}t$$

$$x'(0) = \sqrt{2} \rightarrow 8\sqrt{2}C_2 = \sqrt{2} \Rightarrow C_2 = \frac{1}{8}$$

$$x(t) = \frac{1}{2} \cos 8\sqrt{2}t + \frac{1}{8} \sin 8\sqrt{2}t$$

$$b) \text{ Amplitude: } A = \sqrt{\frac{1}{4} + \frac{1}{64}} = \frac{\sqrt{17}}{8}$$

$$\text{Phase angle: } \phi = \tan^{-1} 4 \approx 1.326 \quad C_1 \text{ and } C_2 \in \mathbb{QI}$$

$$x(t) = \frac{\sqrt{17}}{8} \sin(8\sqrt{2}t + 1.326)$$

$$\text{Period: } P = \frac{2\pi}{\omega} = \frac{\pi\sqrt{2}}{8}$$

$$\text{Natural Frequency: } \frac{1}{P} = \frac{8}{\pi\sqrt{2}}$$

$$c) \quad x(t) = \frac{\sqrt{17}}{8} \sin(8\sqrt{2}t + 1.326) = 0$$

$$8\sqrt{2}t + 1.326 = n\pi$$

$$t = \frac{n\pi - 1.326}{8\sqrt{2}}$$

$$n = 1 \rightarrow t = \frac{\pi - 1.326}{8\sqrt{2}} \approx 0.16 \text{ sec}$$

### Exercise

A 3-kg mass is attached to a spring with a spring constant 75 N/m. The mass is displaced  $\frac{1}{4}$  m to the left and given a velocity of 1 m/sec to the right. The damping force is negligible.

- Determine the equation of motion of the mass
- Determine the equation of motion amplitude, period, and natural frequency.
- How long after release does the mass pass through the equilibrium position?

### Solution

Given:  $m = 3$   $k = 75$   $c = 0$

a)  $3x'' + 75x = 0$  ;  $x(0) = -\frac{1}{4}$ ,  $x'(0) = 1$   $mx'' + \mu x' + kx = 0$

$$3\lambda^2 + 75 = 0 \rightarrow \lambda_{1,2} = \pm 5i$$

$$x_h = C_1 \cos 5t + C_2 \sin 5t$$

$$x(0) = -\frac{1}{4} \rightarrow C_1 = -\frac{1}{4}$$

$$x'_h = -5C_1 \sin 5t + 5C_2 \cos 5t$$

$$x'(0) = 1 \rightarrow 5C_2 = 1 \Rightarrow C_2 = \frac{1}{5}$$

$$x(t) = -\frac{1}{4} \cos 5t + \frac{1}{5} \sin 5t$$

d) Amplitude:  $A = \sqrt{\frac{1}{16} + \frac{1}{25}} = \frac{\sqrt{41}}{20}$

Phase angle:  $\phi = \pi - \tan^{-1} \frac{5}{4} \approx 2.246$   $C_1$  and  $C_2 \in QII$

$$x(t) = \frac{\sqrt{41}}{20} \sin(5t + 2.246)$$

Period:  $P = \frac{2\pi}{\omega} = \frac{2\pi}{5}$

Natural Frequency:  $\frac{1}{P} = \frac{5}{2\pi}$

e)  $x(t) = \frac{\sqrt{41}}{20} \sin(5t + 2.246) = 0$

$$5t + 2.246 = n\pi$$

$$t = \frac{n\pi - 2.246}{5}$$

$$n = 1 \rightarrow t = \frac{\pi - 2.246}{5} \approx 0.179 \text{ sec}$$



### Exercise

A 3-kg mass is attached to a spring with a spring constant 300 N/m. The mass is pulled down 10 cm and released with downward velocity of 1 m/sec. The damping force is negligible.

- Determine the equation of motion of the mass
- Solve the equation to find the time when the maximum downward displacement of the mass from its equilibrium position is first achieved.
- What is the maximum downward displacement?

### Solution

Given:  $m = 3$   $k = 300$   $\mu = 0$

a)  $3y'' + 300y = 0$  ;  $y(0) = 0.1$ ,  $y'(0) = 1$   $my'' + \mu y' + ky = 0$

$$3\lambda^2 + 300 = 0 \rightarrow \lambda^2 = -100 \quad \lambda_{1,2} = \pm 10i$$


$$y(t) = C_1 \cos 10t + C_2 \sin 10t$$

$$x(0) = \frac{1}{10} \rightarrow C_1 = \frac{1}{10}$$

$$y'(t) = -10C_1 \sin 10t + 10C_2 \cos 10t$$

$$y'(0) = 1 \rightarrow 10C_2 = 1 \Rightarrow C_2 = \frac{1}{10}$$

$$y(t) = \frac{1}{10}(\cos 10t + \sin 10t)$$



b)  $y'(t) = \cos 10t - \sin 10t = 0$

$$\cos 10t = \sin 10t \rightarrow 10t = \frac{\pi}{4}$$

The time when the maximum downward displacement of the mass from its equilibrium position is first achieved  $t = \frac{\pi}{40}$

c)  $y\left(t = \frac{\pi}{40}\right) = \frac{1}{10}\left(\cos \frac{\pi}{4} + \sin \frac{\pi}{4}\right)$   
 $= \frac{1}{10}\left(\frac{\sqrt{2}}{2} + \frac{\sqrt{2}}{2}\right)$   
 $= \frac{\sqrt{2}}{10}$

### Exercise

A 10-*kg* mass is attached to the end of a spring hanging vertically, stretches the spring 0.03 *m*. The mass is pulled down another 7 *cm* and released (with no initial velocity).

- Determine the spring constant  $k$ .
- Determine the equation of motion of the mass

### Solution

$$a) \quad k = \frac{10(9.8)}{0.03} = \underline{3,266.67 \text{ N/m}} \quad ky = mg$$

$$b) \quad 10y'' + 3266.67y = 0 ; \quad y(0) = .07, \quad y'(0) = 0 \quad my'' + cy' + ky = F(t)$$

$$10\lambda^2 + 3266.67 = 0 \rightarrow \underline{\lambda = \pm 18.07i}$$

$$y_h = C_1 \cos 18.07t + C_2 \sin 18.07t$$

$$y(0) = 0.07 \rightarrow \underline{C_1 = 0.07}$$

$$y'_h = -18.07C_1 \sin 18.07t + 18.07C_2 \cos 18.07t$$

$$y'(0) = 0 \rightarrow \underline{C_2 = 0}$$

$$\underline{y(t) = 0.07 \cos 18.07t}$$

### Exercise

A 10-*kg* mass is attached to a spring with spring constant  $k = 300 \text{ N/m}$ . At time  $t = 0$ , the mass is pulled down another 10 *cm* and released with a downward velocity of 100 *cm/sec*.

- Determine the equation of motion.
- What is the maximum downward displacement?

### Solution

$$a) \quad 3y'' + 300y = 0 ; \quad y(0) = 0.1, \quad y'(0) = 1$$

$$\lambda^2 + 100 = 0 \rightarrow \underline{\lambda_{1,2} = \pm 10i}$$

$$y_h = C_1 \cos 10t + C_2 \sin 10t$$

$$y(0) = 0.1 \rightarrow \underline{C_1 = 0.1}$$

$$y'_h = -10C_1 \sin 10t + 10C_2 \cos 10t$$

$$y'(0) = 1 \rightarrow \underline{C_2 = 0.1}$$

$$\underline{y(t) = 0.1 \cos 10t + 0.1 \sin 10t}$$

$$b) \quad y'(t) = -\sin 10t + \cos 10t = 0$$

$$\sin 10t = \cos 10t \rightarrow \tan 10t = 1 \Rightarrow 10t = \frac{\pi}{4}$$

$$\underline{t = \frac{\pi}{40}}$$

$$\begin{aligned} y\left(t = \frac{\pi}{40}\right) &= \frac{1}{10} \cos \frac{\pi}{4} + \frac{1}{10} \sin \frac{\pi}{4} \\ &= \frac{\sqrt{2}}{20} + \frac{\sqrt{2}}{20} \\ &= \frac{\sqrt{2}}{10} \end{aligned}$$

### Exercise

A 10-*kg* mass is attached to the end of a spring hanging vertically at rest. The mass is pulled down another 7 *cm* and released (with no initial velocity).

- Determine the spring constant  $k$ .
- Determine the equation of motion of the mass

### Solution

$$a) \quad k = \frac{10(9.8)}{0.03} = \underline{3,266.67 \text{ N/m}} \quad ky = mg$$

$$b) \quad 10y'' + 3266.67y = 0; \quad y(0) = .07, \quad y'(0) = 0 \quad my'' + cy' + ky = F(t)$$

$$10\lambda^2 + 3266.67 = 0 \rightarrow \underline{\lambda_{1,2} = \pm 18.07i}$$

$$y_h = C_1 \cos 18.07t + C_2 \sin 18.07t$$

$$\underline{y(0) = 0.07 \rightarrow C_1 = 0.07}$$

$$y'_h = -18.07C_1 \sin 18.07t + 18.07C_2 \cos 18.07t$$

$$\underline{y'(0) = 0 \rightarrow C_2 = 0}$$

$$\underline{y(t) = 0.07 \cos 18.07t}$$

### Exercise

A 10-*kg* mass is attached to the end of a spring hanging vertically, stretches the spring 0.7 *m*. The mass is started in motion from the equilibrium position with an initial velocity 1 *m/sec* in the upward direction. If the force due to air resistance is  $-90y' \text{ N}$

- Determine the spring constant  $k$ .
- Determine the equation of motion of the mass

### Solution

$$a) \quad k = \frac{10(9.8)}{0.7} = \underline{140 \text{ N/m}} \quad ky = mg$$

$$b) \quad 10y'' + 90y' + 140y = 0 ; \quad y(0) = 0, \quad y'(0) = 1 \quad my'' + cy' + ky = F(t)$$

$$\lambda^2 + 9\lambda + 14 = 0 \rightarrow \underline{\lambda_{1,2} = -2, -7}$$

$$y(t) = C_1 e^{-2t} + C_2 e^{-7t}$$

$$y(0) = 0 \rightarrow C_1 + C_2 = 0$$

$$y' = -2C_1 e^{-2t} - 7C_2 e^{-7t}$$

$$y'(0) = 1 \rightarrow -2C_1 - 7C_2 = 1$$

$$\Delta = \begin{vmatrix} 1 & 1 \\ -2 & -7 \end{vmatrix} = -5 \quad \Delta_{C_1} = \begin{vmatrix} 0 & 1 \\ 1 & -7 \end{vmatrix} = -1 \quad \Delta_{C_2} = \begin{vmatrix} 1 & 0 \\ -2 & 1 \end{vmatrix} = 1$$

$$\underline{C_1 = \frac{1}{5}, \quad C_2 = -\frac{1}{5}}$$

$$\underline{y(t) = \frac{1}{5}e^{-2t} - \frac{1}{5}e^{-7t}}$$

### Exercise

A  $\frac{1}{4}$ -slug mass is attached to the end of a spring hanging vertically, stretches the spring 1.28 ft. The mass is started in motion from the equilibrium position with an initial velocity 4 ft/sec in the downward direction. If the force due to air resistance is  $-2y'$  lb

a) Determine the spring constant  $k$ .

b) Determine the equation of motion of the mass

### Solution

$$a) \quad k = \frac{1}{4} \frac{32}{1.28} = \underline{6.25 \text{ lb/ft}} \quad ky = mg$$

$$b) \quad \frac{1}{4} y'' + 2y' + 6.25y = 0 \quad my'' + cy' + ky = F(t)$$

$$y'' + 8y' + 25y = 0 ; \quad y(0) = 0, \quad y'(0) = 4$$

$$\lambda^2 + 8\lambda + 25 = 0 \rightarrow \underline{\lambda_{1,2} = -4 \pm 3i}$$

$$y(t) = e^{-4t} (C_1 \cos 3t + C_2 \sin 3t)$$

$$y(0) = 0 \rightarrow C_1 = 0$$

$$y' = e^{-4t} (-4C_1 \cos 3t - 4C_2 \sin 3t - 3C_1 \sin 3t + 3C_2 \cos 3t)$$

$$y'(0) = 4 \rightarrow \underline{C_2 = \frac{4}{3}}$$

$$\underline{y(t) = \frac{4}{3} e^{-4t} \sin 3t}$$

### Exercise

A 20-*kg* mass is attached to the end of a spring hanging vertically at rest. When given an initial downward velocity of 2 *m/s* from its equilibrium position the mass was observed to attain a maximum displacement of 0.2 *m* from its equilibrium position.

- Determine the spring constant  $k$ .
- Determine the equation of motion of the mass

### Solution

$$a) \quad 20y'' + ky = 0 ; \quad y(0) = 0, \quad y'(0) = 2 \qquad my'' + cy' + ky = F(t)$$

$$20\lambda^2 + k = 0 \rightarrow \lambda_{1,2} = \pm \frac{1}{2}\sqrt{\frac{k}{5}}i$$

$$y_h = C_1 \cos \frac{1}{2}\sqrt{\frac{k}{5}}t + C_2 \sin \frac{1}{2}\sqrt{\frac{k}{5}}t$$

$$y(0) = 0 \rightarrow C_1 = 0$$

$$y'_h = -\frac{1}{2}\sqrt{\frac{k}{5}}C_1 \sin \frac{1}{2}\sqrt{\frac{k}{5}}t + \frac{1}{2}\sqrt{\frac{k}{5}}C_2 \cos \frac{1}{2}\sqrt{\frac{k}{5}}t$$

$$y'(0) = 2 \rightarrow \frac{1}{2}\sqrt{\frac{k}{5}}C_2 = 2 \quad C_2 = 4\sqrt{\frac{5}{k}}$$

$$y(t) = 4\sqrt{\frac{5}{k}} \sin \frac{1}{2}\sqrt{\frac{k}{5}}t$$

$$y'(t) = 2 \cos \frac{1}{2}\sqrt{\frac{k}{5}}t = 0 \rightarrow t = \frac{\pi}{2}$$

$$y_{max} = 4\sqrt{\frac{5}{k}} = 0.2$$

$$\sqrt{\frac{5}{k}} = \frac{5}{100}$$

$$\frac{k}{5} = \left(\frac{100}{5}\right)^2 = 400$$

$$k = 2,000 \text{ N/m}$$

$$b) \quad y(t) = \frac{1}{5} \sin 10t$$

### Exercise

A steel ball weighing 128-*lb* is attached to the end of a spring, stretches 2 *ft* from its natural length. The ball is started in motion with no initial velocity by displacing it 6 *in* above the equilibrium position. Assuming no air resistance.

- Determine the spring constant  $k$ .
- Find the equation of the ball position at time  $t$ .

c) Find the position of the ball at  $t = \frac{\pi}{12}$  sec

### Solution

$$a) \quad m = \frac{128}{32} = 4 \text{ slugs} \quad w = mg$$

$$k = \frac{128}{2} = 64 \text{ N/m} \quad ky = mg$$

$$b) \quad 4y'' + 64y = 0; \quad y(0) = -\frac{6}{12} = -\frac{1}{2}, \quad y'(0) = 0 \quad my'' + cy' + ky = F(t)$$

$$4\lambda^2 + 64 = 0 \rightarrow \lambda_{1,2} = \pm 4i$$

$$y(t) = C_1 \cos 4t + C_2 \sin 4t$$

$$y(0) = -\frac{1}{2} \rightarrow C_1 = -\frac{1}{2}$$

$$y' = -4C_1 \sin 4t + 4C_2 \cos 4t$$

$$y'(0) = 0 \rightarrow C_2 = 0$$

$$y(t) = -\frac{1}{2} \cos 4t$$

$$c) \quad y\left(t = \frac{\pi}{12}\right) = -\frac{1}{2} \cos \frac{\pi}{3}$$

$$= -\frac{1}{4} \text{ ft}$$

$$= 3 \text{ in}$$

### **Exercise**

A 9-lb mass is attached to the end of a spring hanging vertically with spring constant  $k = 32 \text{ lb/ft}$ , is perturbed from its equilibrium position with a certain upward initial velocity. The amplitude of the resulting vibrations is observed to be 4 in.

- Determine the equation of motion.
- What is the initial velocity?
- Determine the period and frequency of the vibrations?

### Solution

$$a) \quad \frac{9}{32} y'' + 32y = 0; \quad y(0) = 0, \quad y'(0) = y'_0 < 0 \text{ (upward)} \quad my'' + cy' + ky = F(t)$$

$$9\lambda^2 + 32^2 = 0 \rightarrow \lambda_{1,2} = \pm \frac{32}{3}i$$

$$y_h = C_1 \cos \frac{32}{3}t + C_2 \sin \frac{32}{3}t$$

$$y(0) = 0 \rightarrow C_1 = 0$$

$$y(t) = C_2 \sin \frac{32}{3} t$$

$$\text{Amplitude: } |A| = \frac{4}{12} = \frac{1}{3} \rightarrow \underline{C_2 = -\frac{1}{3}}$$

$$\underline{y(t) = -\frac{1}{3} \sin \frac{32}{3} t}$$

$$b) \quad y'(t) = -\frac{32}{9} \cos \frac{32}{3} t$$

$$\underline{y'(0) = -\frac{32}{9} \text{ ft/sec}}$$

$$c) \quad \text{Period:} \quad P = \frac{2\pi}{\omega} = \underline{\frac{3\pi}{16}}$$

$$\text{Frequency:} \quad f = \frac{1}{P} = \underline{\frac{16}{3\pi} \text{ Hz}}$$

### Exercise

A 2-kg mass is suspended from a spring with a spring constant of 10 N/m. The mass is started in motion from the equilibrium position with an initial velocity 1.5 m/sec. Assuming no air resistance

- Determine the equation of motion of the mass.
- Determine the circular frequency, natural frequency, and period.

### Solution

$$a) \quad 2x'' + 10x = 0$$

$$x'' + 5x = 0; \quad x(0) = 0; \quad x'(0) = 1.5$$

$$\lambda^2 + 5 = 0 \rightarrow \underline{\lambda_{1,2} = \pm i\sqrt{5}}$$

$$x(t) = C_1 \cos \sqrt{5}t + C_2 \sin \sqrt{5}t$$

$$\underline{x(0) = 0 \rightarrow C_1 = 0}$$

$$x' = -\sqrt{5}C_1 \sin \sqrt{5}t + \sqrt{5}C_2 \cos \sqrt{5}t$$

$$\underline{x'(0) = 1.5 \rightarrow C_2 = \frac{3}{2\sqrt{5}}}$$

$$\underline{x(t) = \frac{3\sqrt{5}}{10} \sin \sqrt{5}t}$$

$$b) \quad \text{Circular frequency:} \quad \underline{\omega = \sqrt{5} \approx 2.236 \text{ Hz}}$$

$$\text{Natural frequency:} \quad f = \frac{\omega}{2\pi} = \underline{\frac{\sqrt{5}}{2\pi} \approx 0.3559 \text{ Hz}}$$

$$\text{Period:} \quad T = \frac{1}{f} = \underline{\frac{2\pi}{\sqrt{5}} \approx 2.81 \text{ sec}}$$

### Exercise

A  $\frac{1}{4}$ -slug mass is attached to a spring having a spring constant of 1 lb/ft. The mass is started in motion initially displacing it 2 ft in the downward direction with an initial velocity 2 ft/sec in the upward direction. If the force due to air resistance is  $-1x'$  lb. Find the subsequent motion of the mass

### Solution

$$\frac{1}{4}x'' + x' + 1 = 0 ; \quad x(0) = 2, \quad x'(0) = -2$$

$$\lambda^2 + 4\lambda + 4 = 0 \rightarrow \lambda_{1,2} = -2$$

$$x(t) = (C_1 + C_2 t)e^{-2t}$$

$$x(0) = 2 \rightarrow C_1 = 2$$

$$x' = (C_2 - 2C_1 - 2C_2 t)e^{-2t}$$

$$x'(0) = -2 \rightarrow C_2 - 2C_1 = -2 \Rightarrow C_2 = 2$$

$$x(t) = (2 - 2t)e^{-2t}$$

### Exercise

A spring with a mass of 2-kg has natural length 0.5 m. A force of 25.6 N is required to maintain it stretched to a length of 0.7 m. If the spring is stretched to a length of 0.7 m and then released with initial velocity zero. Find the position of the mass at any time  $t$ .

### Solution

$$k = \frac{25.6}{0.7 - 0.5} = 128 \quad k(x_2 - x_1) = F$$

$$2x'' + 128 = 0 ; \quad x(0) = 0.2, \quad x'(0) = 0$$

$$\lambda^2 + 64 = 0 \rightarrow \lambda_{1,2} = \pm 8i$$

$$x(t) = C_1 \cos 8t + C_2 \sin 8t$$

$$x(0) = 0.2 \rightarrow C_1 = \frac{1}{5}$$

$$x' = -8C_1 \sin 8t + 8C_2 \cos 8t$$

$$x'(0) = 0 \rightarrow C_2 = 0$$

$$x(t) = \frac{1}{5} \cos 8t$$



### Exercise

A spring with a mass of 2-kg has natural length 0.5 m . A force of 25.6 N is required to maintain it stretched to a length of 0.7 m . The spring is immersed in a fluid with damping constant  $c = 40$  . If the spring is started from the equilibrium position and is given a push to start it with initial velocity 0.6 m/s . Find the position of the mass at any time  $t$  .

### Solution

$$k = \frac{25.6}{0.7 - 0.5} = 128 \quad k(x_2 - x_1) = F$$

$$2x'' + 40x + 128 = 0 ; \quad x(0) = 0, \quad x'(0) = 0.6$$

$$\lambda^2 + 20\lambda + 64 = 0 \rightarrow \lambda_{1,2} = -10 \pm 6 = -16, -4$$

$$x(t) = C_1 e^{-16t} + C_2 e^{-4t}$$

$$x(0) = 0 \rightarrow C_1 + C_2 = 0$$

$$x' = -16C_1 e^{-16t} - 4C_2 e^{-4t}$$

$$x'(0) = 0.6 \rightarrow -16C_1 - 4C_2 = 0.6$$

$$\Rightarrow -16C_1 + 4C_1 = 0.6 \rightarrow C_1 = -0.05, C_2 = 0.05$$

$$x(t) = -0.05e^{-16t} + 0.05e^{-4t}$$

### Exercise

A spring with a mass of 3-kg is held stretched 0.6 m beyond its natural length by a force of 20 N . If the spring begins at its equilibrium and with initial velocity 1.2 m/s . Find the position of the mass.

### Solution

$$k = \frac{20}{0.6} = \frac{100}{3} \quad kx = F$$

$$3x'' + \frac{100}{3}x = 0 ; \quad x(0) = 0, \quad x'(0) = 1.2 \quad mx'' + cx' + kx = F(t)$$

$$3\lambda^2 + \frac{100}{3} = 0 \rightarrow \lambda = \pm \frac{10}{3}i$$

$$x(t) = C_1 \cos \frac{10}{3}t + C_2 \sin \frac{10}{3}t$$

$$x(0) = 0 \rightarrow C_1 = 0$$

$$x' = -\frac{10}{3}C_1 \sin \frac{10}{3}t + \frac{10}{3}C_2 \cos \frac{10}{3}t$$

$$x'(0) = \frac{6}{5} \rightarrow \frac{10}{3}C_2 = \frac{6}{5} \Rightarrow C_2 = \frac{9}{25}$$

$$\underline{x(t) = \frac{9}{25} \sin \frac{10}{3} t}$$

### Exercise

A spring with a mass of  $2\text{-kg}$  is held stretched  $0.5\text{ m}$ , has damping constant  $14$ , and a force of  $6\text{ N}$ . If the spring is stretched  $1\text{ m}$  beyond at its equilibrium and with no initial velocity.

- Find the position of the mass at any time  $t$ .
- Find the mass that would produce critical damping.

### Solution

$$a) \quad k = \frac{6}{.5} = 12$$

$$kx = F$$

$$2x'' + 14x' + 12x = 0; \quad x(0) = 1, \quad x'(0) = 0$$

$$mx'' + cx' + kx = F(t)$$

$$\lambda^2 + 7\lambda + 6 = 0 \rightarrow \underline{\lambda_1 = -6, \lambda_2 = -1}$$

$$x(t) = C_1 e^{-6t} + C_2 e^{-t}$$

$$x(0) = 1 \rightarrow C_1 + C_2 = 1$$

$$x(t) = -6C_1 e^{-6t} - C_2 e^{-t}$$

$$x'(0) = 0 \rightarrow -6C_1 - C_2 = 0$$

$$\Delta = \begin{vmatrix} 1 & 1 \\ -6 & -1 \end{vmatrix} = 5 \quad \Delta_{C_1} = \begin{vmatrix} 1 & 1 \\ 0 & -1 \end{vmatrix} = -1 \quad \Delta_{C_2} = \begin{vmatrix} 1 & 1 \\ -6 & 0 \end{vmatrix} = 6$$

$$\underline{C_1 = -\frac{1}{5}, C_2 = \frac{6}{5}}$$

$$\underline{x(t) = -\frac{1}{5}e^{-6t} + \frac{6}{5}e^{-t}}$$

$$b) \quad m\lambda^2 + 14\lambda + 12 = 0 \rightarrow \lambda_{1,2} = \frac{-14 \pm \sqrt{196 - 48m}}{2m}$$

For critical damping:  $196 - 48m = 0$

$$\underline{m = \frac{196}{48} = \frac{49}{12} \text{ kg}}$$

### Exercise

A spring has a mass of  $1\text{-kg}$  and its spring constant  $k = 100$ . The spring is released at a point  $0.1\text{ m}$  above its equilibrium position. Graph the position function for the following values of damping constant  $c$ : 10, 15, 20, 25, 30. What type of damping occurs each case?

### Solution

**Given:**  $m = 1, \quad k = 100, \quad x(0) = -0.1, \quad x'(0) = 0$

$$x'' + cx' + 100x = 0; \quad x(0) = -0.1, \quad x'(0) = 0$$

$$mx'' + cx' + kx = F(t)$$

For  $c = 10$

$$\lambda^2 + 10\lambda + 100 = 0 \rightarrow \lambda_{1,2} = -5 \pm 5i\sqrt{3}$$

$\therefore$  The motion is *underdamped*

$$x(t) = e^{-5t} (C_1 \cos 5\sqrt{3}t + C_2 \sin 5\sqrt{3}t)$$

$$x(0) = -0.1 \rightarrow C_1 = -0.1 = -\frac{1}{10}$$

$$x' = e^{-5t} (-5C_1 \cos 5\sqrt{3}t - 5C_2 \sin 5\sqrt{3}t - 5\sqrt{3}C_1 \sin 5\sqrt{3}t + 5\sqrt{3}C_2 \cos 5\sqrt{3}t)$$

$$x'(0) = 0 \rightarrow -5C_1 + 5\sqrt{3}C_2 = 0 \quad C_2 = -\frac{1}{10\sqrt{3}}$$

$$x(t) = -\frac{1}{10} e^{-5t} \left( \cos 5\sqrt{3}t + \frac{\sqrt{3}}{3} \sin 5\sqrt{3}t \right)$$

For  $c = 15$

$$\lambda^2 + 15\lambda + 100 = 0 \rightarrow \lambda_{1,2} = -\frac{15}{2} \pm i\frac{5\sqrt{7}}{2}$$

$\therefore$  The motion is *underdamped*

$$x(t) = e^{-15t/2} \left( C_1 \cos \frac{5\sqrt{7}}{2}t + C_2 \sin \frac{5\sqrt{7}}{2}t \right)$$

$$x(0) = -0.1 \rightarrow C_1 = -0.1 = -\frac{1}{10}$$

$$x' = e^{-15t/2} \left( -\frac{15}{2}C_1 \cos \frac{5\sqrt{7}}{2}t - \frac{15}{2}C_2 \sin \frac{5\sqrt{7}}{2}t - \frac{5\sqrt{7}}{2}C_1 \sin \frac{5\sqrt{7}}{2}t + \frac{5\sqrt{7}}{2}C_2 \cos \frac{5\sqrt{7}}{2}t \right)$$

$$x'(0) = 0 \rightarrow -\frac{15}{2}C_1 + \frac{5\sqrt{7}}{2}C_2 = 0 \quad C_2 = -\frac{3}{10\sqrt{7}}$$

$$x(t) = e^{-15t/2} \left( -\frac{1}{10} \cos \frac{5\sqrt{7}}{2}t - \frac{3}{10\sqrt{7}} \sin \frac{5\sqrt{7}}{2}t \right)$$

For  $c = 20$

$$\lambda^2 + 20\lambda + 100 = 0 \rightarrow \lambda_{1,2} = -10$$

$\therefore$  The motion is *critically damped*

$$x(t) = (C_1 + C_2 t) e^{-10t}$$

$$x(0) = -0.1 \rightarrow C_1 = -0.1 = -\frac{1}{10}$$

$$x' = (C_2 - 10C_1 - 10C_2 t)e^{-10t}$$

$$x'(0) = 0 \rightarrow C_2 + 1 = 0 \quad \underline{C_2 = -1}$$

$$\underline{x(t) = (-0.1 - t)e^{-10t}}$$

For  $c = 25$

$$\lambda^2 + 25\lambda + 100 = 0 \rightarrow \lambda_{1,2} = \frac{-25 \pm 15}{2} = \underline{-20, -5}$$

$\therefore$  The motion is *overdamped*

$$x(t) = C_1 e^{-20t} + C_2 e^{-5t}$$

$$x(0) = -0.1 \rightarrow C_1 + C_2 = -0.1$$

$$x' = -20C_1 e^{-20t} - 5C_2 e^{-5t}$$

$$x'(0) = 0 \rightarrow -20C_1 - 5C_2 = 0 \Rightarrow 4C_1 + C_2 = 0$$

$$\Delta = \begin{vmatrix} 1 & 1 \\ 4 & 1 \end{vmatrix} = -3 \quad \Delta_{C_1} = \begin{vmatrix} -0.1 & 1 \\ 0 & 1 \end{vmatrix} = -0.1 \quad \Delta_{C_2} = \begin{vmatrix} 1 & -0.1 \\ 4 & 0 \end{vmatrix} = 0.4$$

$$\underline{C_1 = \frac{1}{30}, \quad C_2 = -\frac{4}{30} = -\frac{2}{15}}$$

$$\underline{x(t) = \frac{1}{10}e^{-10t} - \frac{1}{5}e^{-5t}}$$

For  $c = 30$

$$\lambda^2 + 30\lambda + 100 = 0 \rightarrow \lambda_{1,2} = \underline{-15 \pm 5\sqrt{5}}$$

$\therefore$  The motion is *overdamped*

$$x(t) = C_1 e^{(-15-5\sqrt{5})t} + C_2 e^{(-15+5\sqrt{5})t}$$

$$x(0) = -0.1 \rightarrow C_1 + C_2 = -0.1$$

$$x' = (-15-5\sqrt{5})C_1 e^{(-15-5\sqrt{5})t} + (-15+5\sqrt{5})C_2 e^{(-15+5\sqrt{5})t}$$


$$x'(0) = 0 \rightarrow (-15-5\sqrt{5})C_1 + (-15+5\sqrt{5})C_2 = 0$$

$$\Delta = \begin{vmatrix} 1 & 1 \\ -15-5\sqrt{5} & -15+5\sqrt{5} \end{vmatrix} = 10\sqrt{5}$$

$$\Delta_{C_1} = \begin{vmatrix} -0.1 & 1 \\ 0 & -15+5\sqrt{5} \end{vmatrix} = 1.5 - .5\sqrt{5} \quad \Delta_{C_2} = \begin{vmatrix} 1 & -0.1 \\ -15-5\sqrt{5} & 0 \end{vmatrix} = -1.5 - .5\sqrt{5}$$

$$\underline{C_1 = \frac{15-5\sqrt{5}}{100\sqrt{5}} = \frac{5-3\sqrt{5}}{100} \quad C_2 = \frac{-15-5\sqrt{5}}{100\sqrt{5}} = \frac{-5-3\sqrt{5}}{100}}$$

$$x(t) = \frac{5-3\sqrt{5}}{100} e^{(-15-5\sqrt{5})t} + \frac{-5-3\sqrt{5}}{100} e^{(-15+5\sqrt{5})t}$$



### Exercise

A 4-kg mass is attached to a spring and set in motion. A record of the displacements was made and found to be described by  $y(t) = 25 \cos\left(2t - \frac{\pi}{6}\right)$ , with displacement measured in centimeters and time in seconds.

- Determine the displacement  $y_0$ .
- Determine the initial velocity  $y'_0$ ?
- Determine the spring constant  $k$ .
- Determine the period and frequency of the vibrations?

### Solution

$$a) \quad 4y'' + ky = 0 ; \quad y(0) = y_0, \quad y'(0) = y'_0$$

$$my'' + cy' + ky = F(t)$$

$$\text{Given: } y(t) = 25 \cos\left(2t - \frac{\pi}{6}\right) \text{ cm}$$

$$= 0.25 \cos\left(2t - \frac{\pi}{6}\right) \text{ m}$$

$$y(0) = \frac{1}{4} \cos\left(-\frac{\pi}{6}\right)$$

$$y_0 = \frac{\sqrt{3}}{8} \text{ m}$$

$$b) \quad y' = -\frac{1}{2} \sin\left(2t - \frac{\pi}{6}\right)$$

$$y'(0) = -\frac{1}{2} \sin\left(-\frac{\pi}{6}\right) = \frac{1}{4} = .25 \text{ m/s}$$

$$c) \quad 2 = \sqrt{\frac{k}{4}} \rightarrow k = 16 \text{ N/m} \quad \omega = \sqrt{\frac{k}{m}}$$

$$d) \quad P = \frac{2\pi}{2} = \pi \text{ sec}$$

$$f = \frac{1}{P} = \frac{1}{\pi} \text{ Hz}$$

### Exercise

A 10-kg mass is attached to a spring with a spring constant  $k = 100 \text{ N/m}$ ; the dashpot has damping constant  $7 \text{ kg/sec}$ . At time  $t = 0$ , the system is set into motion by pulling the mass down  $0.5 \text{ m}$  from its equilibrium rest position while simultaneously giving it an initial downward velocity of  $1 \text{ m/s}$

a) Solve the equation of motion.

b) What is the  $\lim_{t \rightarrow \infty} y(t)$

c) Plot the solution.

d) How long it takes for the magnitude of the vibrations to be reduced to  $0.1 \text{ m}$ .

(Estimate the smallest time,  $\tau$ , for which  $|y(t)| \leq 0.1 \text{ m}$ ,  $\tau \leq t < \infty$ )

### Solution

$$a) \quad 10y'' + 7y' + 100y = 0; \quad y(0) = 0.5, \quad y'(0) = 1 \quad my'' + cy' + ky = 0$$

$$10\lambda^2 + 7\lambda + 100 = 0 \rightarrow \lambda_{1,2} = -\frac{7}{20} \pm i \frac{3\sqrt{439}}{20}$$

$$y(t) = e^{-7t/20} \left( C_1 \cos \frac{3\sqrt{439}}{20} t + C_2 \sin \frac{3\sqrt{439}}{20} t \right)$$

$$y(0) = \frac{1}{2} \rightarrow C_1 = \frac{1}{2}$$

$$y' = e^{-7t/20} \left( -\frac{7}{20} C_1 \cos \frac{3\sqrt{439}}{20} t - \frac{7}{20} C_2 \sin \frac{3\sqrt{439}}{20} t - \frac{3\sqrt{439}}{20} C_1 \sin \frac{3\sqrt{439}}{20} t + \frac{3\sqrt{439}}{20} C_2 \cos \frac{3\sqrt{439}}{20} t \right)$$


$$y'(0) = 1 \rightarrow -\frac{7}{20} \frac{1}{2} + \frac{3\sqrt{439}}{20} C_2 = 1 \quad C_2 = \frac{47}{6\sqrt{439}}$$

$$y(t) = e^{-7t/20} \left( \frac{1}{2} \cos \frac{3\sqrt{439}}{20} t + \frac{47}{6\sqrt{439}} \sin \frac{3\sqrt{439}}{20} t \right)$$


$$y(t) = e^{-0.35t} (0.5 \cos 3.14285t + 0.37386 \sin 3.14285t)$$

$$b) \quad \lim_{t \rightarrow \infty} y(t) = 0$$

c)



d)



From the graph:

$\tau$	$y$
0.63960	0.10046
0.64000	0.09983

### Exercise

A spring and dashpot system is to be designed for a 32-*lb* weight so that the overall system is critically damped

- How must the damping constant  $c$  and the spring constant  $k$  be related?
- Assume the system is to be designed so that the mass, when given initial velocity of 4 *ft/sec* from its rest position, will have a maximum displacement of 6 *in*. What values of damping constant  $c$  and spring constant  $k$  are required?
- It is observed that the time interval between successive zero crossing is 20% larger for the damped vibration displacement than for the undamped vibration displacement. What is the damping constant  $c$ ? (Spring constant  $k$  remains same from part (b)).

### Solution

$$a) \quad \frac{32}{32} y'' + cy' + ky = 0$$

$$y'' + cy' + ky = 0$$

$$my'' + cy' + ky = F(t)$$

$$\lambda^2 + c\lambda + k = 0 \rightarrow \lambda_{1,2} = \frac{-c \pm \sqrt{c^2 - 4k}}{2}$$

Since the system is critically damped, then:

$$c^2 - 4k = 0 \rightarrow \underline{c^2 = 4k} \quad c = 2\sqrt{k}$$

b)  $y'' + 2\sqrt{k}y' + ky = 0$  ;  $y(0) = 0$ ,  $y'(0) = 4$

$$\rightarrow \underline{\lambda_{1,2} = -\frac{c}{2}}$$

$$y(t) = (C_1 + C_2 t)e^{-ct/2}$$

$$\underline{y(0) = 0 \rightarrow C_1 = 0}$$

$$y'(t) = (C_2 - \frac{c}{2}C_1 - \frac{c}{2}C_2 t)e^{-ct/2}$$

$$\underline{y'(0) = 4 \rightarrow C_2 - \frac{c}{2}C_1 = 4 \quad C_2 = 4}$$

$$\underline{y(t) = 4te^{-ct/2}}$$

$$y'(t) = (4 - 2ct)e^{-ct/2} = 0 \rightarrow \underline{t = \frac{2}{c}}$$

$$y\left(t = \frac{2}{c}\right) = \frac{8}{c}e^{-1} = \frac{6}{12} = \underline{\frac{1}{2}}$$

$$\underline{c = \frac{16}{e} \approx 5.886 \text{ lb.sec/ft}}$$

$$\underline{k = \frac{64}{e^2} \approx 8.66 \text{ lb/ft}}$$

c) Since, the time interval ( $\tau$ ) between successive zero crossing is 20% larger of undamped .

$$\lambda_{1,2} = \frac{-c \pm \sqrt{c^2 - 4k}}{2} = -\frac{c}{2} \pm i \frac{\sqrt{4k - c^2}}{2}$$

$$1.2 \text{ damped} = \text{undamped} (c = 0)$$

$$\frac{\sqrt{4k - c^2}}{2} (1.2\tau) = \frac{\sqrt{4k}}{2} \tau$$

$$0.6\sqrt{4k - c^2} = \sqrt{k}$$

$$\frac{1}{e}\sqrt{256 - e^2 c^2} = \frac{8}{0.6e} = \frac{40}{3e}$$

$$\sqrt{256 - c^2} = \frac{40}{3}$$

$$256 - e^2 c^2 = \frac{1600}{9}$$

$$\underline{e^2 c^2 = \frac{704}{9} \rightarrow c = \frac{8\sqrt{11}}{3e} \approx 3.254 \text{ lb.sec/ft}}$$



### Exercise

Find the charge  $q(t)$  on the capacitor in an  $LRC$ -series circuit when  $L = 0.25 \text{ H}$ ,  $R = 10 \text{ } \Omega$ ,  $C = 0.001 \text{ F}$ ,  $E(t) = 0$ ,  $q(0) = q_0 \text{ C}$ , and  $i(0) = 0$ .

### Solution

$$0.25q'' + 10q' + \frac{1}{0.001}q = 0 \quad Lq'' + Rq' + \frac{1}{C}q = E(t)$$

$$q'' + 40q' + 4,000q = 0$$

$$\lambda^2 + 40\lambda + 4000 = 0 \rightarrow \lambda_{1,2} = \frac{-40 \pm 120i}{2} = -20 \pm i60$$

$$q(t) = e^{-20t} (C_1 \cos 60t + C_2 \sin 60t)$$

$$q(0) = q_0 \rightarrow \underline{C_1 = q_0}$$

$$q'(t) = e^{-20t} (-20C_1 \cos 60t - 20C_2 \sin 60t - 60C_1 \sin 60t + 60C_2 \cos 60t)$$

$$q'(0) = i(0) = 0 \rightarrow -20C_1 + 60C_2 = 0 \quad \underline{C_2 = \frac{1}{3}q_0}$$

$$\underline{q(t) = q_0 e^{-20t} \left( \cos 60t + \frac{1}{3} \sin 60t \right)}$$

$$A = \sqrt{1 + \frac{1}{9}} = \underline{\frac{\sqrt{10}}{3}}$$

$$\phi = \tan^{-1} 3 \approx \underline{1.249}$$

$$\underline{q(t) = \frac{q_0 \sqrt{10}}{3} e^{-20t} \sin(60t + 1.249)}$$

### Exercise

Find the charge  $q(t)$  on the capacitor in an  $LRC$ -series circuit at  $t = 0.01 \text{ sec}$  when  $L = 0.05 \text{ h}$ ,  $R = 2 \text{ } \Omega$ ,  $C = 0.01 \text{ f}$ ,  $E(t) = 0$ ,  $q(0) = 5 \text{ C}$ , and  $i(0) = 0 \text{ A}$ . Determine the first time at which the charge on the capacitor is equal to zero.

### Solution

$$0.05q'' + 2q' + \frac{1}{0.01}q = 0 \quad Lq'' + Rq' + \frac{1}{C}q = E(t)$$

$$q'' + 40q' + 2,000q = 0$$

$$\lambda^2 + 40\lambda + 2000 = 0 \rightarrow \lambda_{1,2} = \underline{-20 \pm i40}$$

$$q(t) = e^{-20t} (C_1 \cos 40t + C_2 \sin 40t)$$

$$q(0) = 5 \rightarrow \underline{C_1 = 5}$$

$$q'(t) = e^{-20t} \left( -20C_1 \cos 40t - 20C_2 \sin 40t - 40C_1 \sin 40t + 40C_2 \cos 40t \right)$$

$$q'(0) = i(0) = 0 \rightarrow -20C_1 + 40C_2 = 0 \quad \underline{C_2 = \frac{5}{2}}$$

$$\underline{q(t) = e^{-20t} \left( 5 \cos 40t + \frac{5}{2} \sin 40t \right)}$$

$$A = \sqrt{25 + \frac{25}{4}} = \frac{5\sqrt{5}}{2}$$

$$\phi = \tan^{-1} 2 \approx 1.1071 \quad \phi = \tan^{-1} \frac{a}{b}$$

$$\underline{q(t) = \frac{5\sqrt{5}}{2} e^{-20t} \sin(40t + 1.1071)}$$

$$q(0.01) = \frac{5\sqrt{5}}{2} e^{-20t} \sin(40(.01) + 1.1071) \approx \underline{4.5676 \text{ C}}$$

$$q(t) = \frac{5\sqrt{5}}{2} e^{-20t} \sin(40t + 1.1071) = 0$$

$$40t + 1.1071 = \pi$$

$$\underline{t \approx 0.0509 \text{ sec}}$$

### Exercise

Find the charge  $q(t)$  on the capacitor in an  $LRC$ -series circuit when  $L = 0.25 \text{ h}$ ,  $R = 20 \Omega$ ,  $C = \frac{1}{300} \text{ f}$ ,

$E(t) = 0$ ,  $q(0) = 4 \text{ C}$ , and  $i(0) = 0 \text{ A}$ . Is the charge on the capacitor ever equal to zero.

### Solution

$$\frac{1}{4} q'' + 20q' + 300q = 0 \quad Lq'' + Rq' + \frac{1}{C}q = E(t)$$

$$q'' + 80q' + 1,200q = 0$$

$$\lambda^2 + 80\lambda + 1200 = 0 \rightarrow \lambda_{1,2} = -40 \pm 20 = \underline{-60, -20}$$

$$q(t) = C_1 e^{-60t} + C_2 e^{-20t}$$

$$q(0) = 4 \rightarrow C_1 + C_2 = 4$$

$$q'(t) = -60C_1 e^{-60t} - 20C_2 e^{-20t}$$

$$q'(0) = i(0) = 0 \rightarrow -60C_1 - 20C_2 = 0$$

$$\begin{cases} C_1 + C_2 = 4 \\ 3C_1 + C_2 = 0 \end{cases} \rightarrow \underline{C_1 = -2, C_2 = 6}$$

$$\underline{q(t) = 6e^{-20t} - 2e^{-60t}}$$

$$q(t) = 6e^{-20t} - 2e^{-60t} = 0$$

$$3e^{-20t} = e^{-60t}$$

$$e^{40t} = \frac{1}{3}$$

$$t = \frac{1}{40} \ln \frac{1}{3} \approx \underline{-0.0275 < 0}$$

Therefore; the charge will never equal to zero.

### ***Exercise***

Find the charge  $q(t)$  on the capacitor in an  $LRC$ -series circuit when  $L = \frac{5}{3} \text{ h}$ ,  $R = 10 \text{ } \Omega$ ,  $C = \frac{1}{30} \text{ f}$ ,

$E(t) = 0$ ,  $q(0) = 4 \text{ C}$ , and  $i(0) = 0 \text{ A}$ .

### **Solution**

$$\frac{5}{3}q'' + 10q' + 30q = 0$$

$$Lq'' + Rq' + \frac{1}{C}q = E(t)$$

$$q'' + 6q' + 18q = 0$$

$$\lambda^2 + 6\lambda + 18 = 0 \rightarrow \underline{\lambda_{1,2} = -3 \pm 3i}$$

$$q(t) = e^{-3t} (C_1 \cos 3t + C_2 \sin 3t)$$

$$\underline{q(0) = 4 \rightarrow C_1 = 4}$$

$$q'(t) = e^{-3t} (-3C_1 \cos 3t - 3C_2 \sin 3t - 3C_1 \sin 3t + 3C_2 \cos 3t)$$

$$\underline{q'(0) = i(0) = 0 \rightarrow -3C_1 + 3C_2 = 0 \quad C_2 = 4}$$

$$\underline{q(t) = e^{-3t} (4 \cos 3t + 4 \sin 3t)}$$