

GEOG 432/832: Programming, Scripting, and Automation for GIS

Week 11.01: Spatial data and intro to viz

Dr. Bitterman

Today's schedule

- Open discussion
- Project update presentation(s)
- Slides, discussion and exercises
- For next class

Open discussion

Today's prep:

- We'll use *unit10inclass.zip* from Canvas
- Open Anaconda
- Wait

Packages/modules we'll need today

- geopandas
- matplotlib

Reading spatial data

What are some possible forms (and sources) of spatial data?

Package setup

```
%matplotlib inline  
import geopandas  
import matplotlib
```

Reading spatial data

A zip file from the web (you may want to copy-paste the URL)

```
# reading from the web
# this is a zip file hosted on the GitHub page. The zip contains a .shp file
county_url = "https://github.com/pjbitterman/UNL_geog432/blob/main/data/county_boundaries.zip?raw=true"
county_boundaries = geopandas.read_file(county_url)
```

```
county_boundaries.plot()
county_boundaries.crs
```

What happened?

Reading from geojson

Wait, what's a geojson?

What's a "json"?

Open street_centerlines_lc.geojson in a text editor and see for yourself

Reading a geojson

```
# Read from geojson
streets_path = "../unit10data/street_centerlines_lc.geojson"

streets = geopandas.read_file(streets_path)
```

display

```
streets.plot() # may take a while
streets.crs
```

Be careful with geojson, files get HUGE

And shapefiles too

```
# Read a bog standard shapefile
schools_path = "./unit10data/Public_Schools.shp"
schools = geopandas.read_file(schools_path)
schools
```

display

```
schools.plot()
```

Anything notable about how we read these 3 file types into memory?

geopandas dataframes are a LOT like non-spatial dataframes

ESDA is ALWAYS a good idea... what's "ESDA"?

- all the operations we've used before still work:
- try some:

- `head()`

- `tail()`

- `describe()`

-

Slicing a spatial dataframe

- just like aspatial dataframes, we can look at a subset
- let's try a few:

```
streets.loc[2500, 'geometry'] # you don't always get a good look the geometry, depending on scale
```

```
muni_boundaries.loc[577, 'geometry']
```

What happened?

Some basic styling

Setting an alpha value

```
schools.plot(alpha = 0.1)
```

What happened?

Super simple mapping

```
# Setup figure and axis
f, ax = matplotlib.pyplot.subplots(1)

# Plot layer of polygons on the axis
county_boundaries.plot(ax = ax)

# Remove axis frames
ax.set_axis_off()

# Add figure title
f.suptitle("Counties in Nebraska")

# Display
matplotlib.pyplot.show()
```


What did we just do?

1. Created a figure named `f` with one axis named `ax` by using the command `matplotlib.pyplot.subplots` *(Note: the method is returning two elements and we assigned each of them to objects with different name (`f` and `ax`) by listing them at the front of the statement)*
2. Plotted the geographies, telling the function that to draw the polygons on the axis we passed, `ax`. This method returns the axis with the geographies in them, so we stored it on an object with the same name, `ax`.
3. Removed the box with coordinates
4. Set a title
5. Displayed the figure by calling `matplotlib.pyplot.show()`

A quick multilayer example

- We can do some simple multilayer mapping by adding layers one at a time to a figure
- For example:

```
lc_path = "../unit10data/lancaster_county.shp"
lc = geopandas.read_file(lc_path)

# Setup figure and axis
f, ax = matplotlib.pyplot.subplots(1)

# Add a layer with polygon on to axis `ax`
lc.plot(ax = ax, color = "green")

# Add a layer with lines on top in axis `ax`
streets.plot(ax = ax, color = "yellow")

# give it a title
f.suptitle("What a horrible color scheme")

# save it to disk
#matplotlib.pyplot.savefig('lc_streets.png')
```

We can also do some basic spatial calculations...

Calculate area

```
county_areas = county_boundaries.area  
county_areas.head()
```

what happened? Does it make sense?

Always project your data!!!

What does this code do?

```
counties_14n = county_boundaries.to_crs(epsg=26914) # EPSG for NAD84 UTM 14N  
county_areas = counties_14n.area  
county_areas.head()
```

What are the units now?

Lengths, too:

```
street_length = streets.to_crs(epsg=26914).length  
street_length.head()
```

Garbage in, garbage out (know your datasets and data types)... this works:

```
streets.to_crs(epsg=26914).area.head()
```

What's wrong with it?

And buffers are straightforward:

Break it down:

```
schools14n = schools.to_crs(munis_14n.crs) # set to the CRS of an existing layer  
schools14n.crs
```

```
school_buff = schools14n.buffer(500) # 500m buffer  
school_buff.head()
```

```
school_buff.plot() # at this scale, maybe a bit tough to tell they're buffers
```

For next class

- Lab 5 starts Friday
- Readings are linked/posted on Canvas
- HOMEWORK: review https://darribas.org/gds_course/content/bC/lab_C.html (the framework for today's slides)