

Class10

Patricia Chen A16138722

4. Comparative structure analysis of Adenylate Kinase (ADK)

ADK is an important drug target and we would love to know how it works ie. molecular mechanism. There has been a lot of work done on this protein due to its importance including lots of crystal structures.

We will begin with getting an example ADK sequence from the database, we will then use this to find all ADK structures in the pDB

Install packages in the R console NOT your Rmd/Quarto file

```
#install.packages("bio3d")
#install.packages("devtools")
#install.packages("BiocManager")

#BiocManager::install("msa")
#devtools::install_bitbucket("Grantlab/bio3d-view")
```

Q10. Which of the packages above is found only on BioConductor and not CRAN?
Answer: MSA

Q11. Which of the above packages is not found on BioConductor or CRAN?:
Answer: The bottom package, bio3d-view, is not found on the BioConductor or CRAN.

Q12. True or False? Functions from the devtools package can be used to install packages from GitHub and BitBucket? Answer: True.

Search and retrieve ADK structures

```
library(bio3d)
aa <- get.seq("lake_A")
```

Warning in get.seq("lake_A"): Removing existing file: seqs.fasta

Fetching... Please wait. Done.

```
aa
```

```

      1      .      .      .      .      .      .      60
pdb|1AKE|A MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMMLRAAVKSGSELGKQAKDIMDAGKLV
      1      .      .      .      .      .      .      60

      61      .      .      .      .      .      .      120
pdb|1AKE|A DELVIALVKERIAQEDCRNGFLLDGFPRTIPQADAMKEAGINVDYVLEFDVPDELIVDRI
      61      .      .      .      .      .      .      120

      121      .      .      .      .      .      .      180
pdb|1AKE|A VGRRVHAPSGRVYHVKNPPKVEGKDDVTGEELTRKDDQEETVRKRLVEYHQMTAPLIG
      121      .      .      .      .      .      .      180

      181      .      .      .      214
pdb|1AKE|A YYSKEAEAGNTKYAKVDGTPVAEVRADLEKILG
      181      .      .      .      214
```

Call:

```
read.fasta(file = outfile)
```

Class:

```
fasta
```

Alignment dimensions:

```
1 sequence rows; 214 position columns (214 non-gap, 0 gap)
```

```
+ attr: id, ali, call
```

We can now run BLAST

```
#b<- blast.pdb(aa)
```

```
#hits<-plot(b)
```

Let's see what is in our 'hits' object

```
#hits$pdb.id
```

```
hits$pdb.id
```

Q13. How many amino acids are in this sequence, i.e. how long is this sequence?

Answer: There are 214 amino acids in this sequence.

```
# Blast or hmmer search
```

```
#b <- blast.pdb(aa)
```

```
# Plot a summary of search results
```

```
#hits <- plot(b)
```

```
# List out some 'top hits'
```

```
#head(hits$pdb.id)
```

```
hits <- NULL
```

```
hits$pdb.id <- c('1AKE_A','6S36_A','6RZE_A','3HPR_A','1E4V_A','5EJE_A','1E4Y_A','3X2S_A',
```

We can now use function `get.pdb()` and `pdbslit()` to fetch and parse the identified structures.

```
# Download related PDB files - Skipping downloads (already exists)
```

```
files <- get.pdb(hits$pdb.id, path="pdb", split=TRUE, gzip=TRUE)
```

```
Warning in get.pdb(hits$pdb.id, path = "pdb", split = TRUE, gzip = TRUE):  
pdb/1AKE.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdb", split = TRUE, gzip = TRUE):  
pdb/6S36.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdb", split = TRUE, gzip = TRUE):  
pdb/6RZE.pdb.gz exists. Skipping download
```

```
Warning in get.pdb(hits$pdb.id, path = "pdb", split = TRUE, gzip = TRUE):  
pdb/3HPR.pdb.gz exists. Skipping download
```

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1E4V.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/5EJE.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/1E4Y.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3X2S.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6HAP.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/6HAM.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4K46.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/3GMT.pdb.gz exists. Skipping download

Warning in get.pdb(hits\$pdb.id, path = "pdbs", split = TRUE, gzip = TRUE):
pdbs/4PZL.pdb.gz exists. Skipping download

	0%
=====	8%
=====	15%
=====	23%
=====	31%
=====	38%

	=====	46%
	=====	54%
	=====	62%
	=====	69%
	=====	77%
	=====	85%
	=====	92%
	=====	100%

Alignment: Align and superpose structures

Next we will use the `pdbaln()` function to align and also optionally fit (i.e. superpose) the identified PDB structures. Now I want to align and supersose theses structures which are all over the place

```
# Align releated PDBs
pdbs <- pdbaln(files, fit = TRUE, exefile="msa")
```

Reading PDB files:

```
pdbs/split_chain/1AKE_A.pdb
pdbs/split_chain/6S36_A.pdb
pdbs/split_chain/6RZE_A.pdb
pdbs/split_chain/3HPR_A.pdb
pdbs/split_chain/1E4V_A.pdb
pdbs/split_chain/5EJE_A.pdb
pdbs/split_chain/1E4Y_A.pdb
pdbs/split_chain/3X2S_A.pdb
pdbs/split_chain/6HAP_A.pdb
pdbs/split_chain/6HAM_A.pdb
pdbs/split_chain/4K46_A.pdb
pdbs/split_chain/3GMT_A.pdb
pdbs/split_chain/4PZL_A.pdb
```

```
PDB has ALT records, taking A only, rm.alt=TRUE
```

```

.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
..  PDB has ALT records, taking A only, rm.alt=TRUE
.... PDB has ALT records, taking A only, rm.alt=TRUE
.   PDB has ALT records, taking A only, rm.alt=TRUE
...

```

Extracting sequences

```

pdb/seq: 1   name: pdbs/split_chain/1AKE_A.pdb
           PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 2   name: pdbs/split_chain/6S36_A.pdb
           PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 3   name: pdbs/split_chain/6RZE_A.pdb
           PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 4   name: pdbs/split_chain/3HPR_A.pdb
           PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 5   name: pdbs/split_chain/1E4V_A.pdb
pdb/seq: 6   name: pdbs/split_chain/5EJE_A.pdb
           PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 7   name: pdbs/split_chain/1E4Y_A.pdb
pdb/seq: 8   name: pdbs/split_chain/3X2S_A.pdb
pdb/seq: 9   name: pdbs/split_chain/6HAP_A.pdb
pdb/seq: 10  name: pdbs/split_chain/6HAM_A.pdb
           PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 11  name: pdbs/split_chain/4K46_A.pdb
           PDB has ALT records, taking A only, rm.alt=TRUE
pdb/seq: 12  name: pdbs/split_chain/3GMT_A.pdb
pdb/seq: 13  name: pdbs/split_chain/4PZL_A.pdb

```

Let's have a look at our 'pdbs' object

```
pdbs
```

	1	.	.	.	40
[Truncated_Name:1] 1AKE_A.pdb	-----	MRIILLGAPGAGKGTQAQFIMEKYGIPQIS			
[Truncated_Name:2] 6S36_A.pdb	-----	MRIILLGAPGAGKGTQAQFIMEKYGIPQIS			
[Truncated_Name:3] 6RZE_A.pdb	-----	MRIILLGAPGAGKGTQAQFIMEKYGIPQIS			
[Truncated_Name:4] 3HPR_A.pdb	-----	MRIILLGAPGAGKGTQAQFIMEKYGIPQIS			
[Truncated_Name:5] 1E4V_A.pdb	-----	MRIILLGAPVAGKGTQAQFIMEKYGIPQIS			
[Truncated_Name:6] 5EJE_A.pdb	-----	MRIILLGAPGAGKGTQAQFIMEKYGIPQIS			

[Truncated_Name:7] 1E4Y_A.pdb	-----MRIILLGALVAGKGTQAQFIMEKYGIPQIS
[Truncated_Name:8] 3X2S_A.pdb	-----MRIILLGAPGAGKGTQAQFIMEKYGIPQIS
[Truncated_Name:9] 6HAP_A.pdb	-----MRIILLGAPGAGKGTQAQFIMEKYGIPQIS
[Truncated_Name:10] 6HAM_A.pdb	-----MRIILLGAPGAGKGTQAQFIMEKYGIPQIS
[Truncated_Name:11] 4K46_A.pdb	-----MRIILLGAPGAGKGTQAQFIMAKFGIPQIS
[Truncated_Name:12] 3GMT_A.pdb	-----MRLILLGAPGAGKGTQANFIKEKFGIPQIS
[Truncated_Name:13] 4PZL_A.pdb	TENLYFQSNAMRIILLGAPGAGKGTQAKIIEQYKYNIAHIS
	~*** ***** * *~* **
	1 . . . 40
	41 . . . 80
[Truncated_Name:1] 1AKE_A.pdb	TGDMMLRAAVKSGSELGKQAKDIMDAGKLVTDDELVIALVKE
[Truncated_Name:2] 6S36_A.pdb	TGDMMLRAAVKSGSELGKQAKDIMDAGKLVTDDELVIALVKE
[Truncated_Name:3] 6RZE_A.pdb	TGDMMLRAAVKSGSELGKQAKDIMDAGKLVTDDELVIALVKE
[Truncated_Name:4] 3HPR_A.pdb	TGDMMLRAAVKSGSELGKQAKDIMDAGKLVTDDELVIALVKE
[Truncated_Name:5] 1E4V_A.pdb	TGDMMLRAAVKSGSELGKQAKDIMDAGKLVTDDELVIALVKE
[Truncated_Name:6] 5EJE_A.pdb	TGDMMLRAAVKSGSELGKQAKDIMDACKLVTDDELVIALVKE
[Truncated_Name:7] 1E4Y_A.pdb	TGDMMLRAAVKSGSELGKQAKDIMDAGKLVTDDELVIALVKE
[Truncated_Name:8] 3X2S_A.pdb	TGDMMLRAAVKSGSELGKQAKDIMDCGKLVTDDELVIALVKE
[Truncated_Name:9] 6HAP_A.pdb	TGDMMLRAAVKSGSELGKQAKDIMDAGKLVTDDELVIALVRE
[Truncated_Name:10] 6HAM_A.pdb	TGDMMLRAAIKSGSELGKQAKDIMDAGKLVTDDEIIIALVKE
[Truncated_Name:11] 4K46_A.pdb	TGDMMLRAAIKAGTELGKQAKSVIDAGQLVSDDIILGLVKE
[Truncated_Name:12] 3GMT_A.pdb	TGDMMLRAAVKAGTPLGVEAKTYMDEGKLVPSLIIGLVKE
[Truncated_Name:13] 4PZL_A.pdb	TGDMIRETIKSGSALGQELKKVLDAGELVSDEFIIKIVKD
	****~* ~* *~** * ~* ** * ^^ ~*^^
	41 . . . 80
	81 . . . 120
[Truncated_Name:1] 1AKE_A.pdb	RIAQEDCRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD
[Truncated_Name:2] 6S36_A.pdb	RIAQEDCRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD
[Truncated_Name:3] 6RZE_A.pdb	RIAQEDCRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD
[Truncated_Name:4] 3HPR_A.pdb	RIAQEDCRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD
[Truncated_Name:5] 1E4V_A.pdb	RIAQEDCRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD
[Truncated_Name:6] 5EJE_A.pdb	RIAQEDCRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD
[Truncated_Name:7] 1E4Y_A.pdb	RIAQEDCRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD
[Truncated_Name:8] 3X2S_A.pdb	RIAQEDSRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD
[Truncated_Name:9] 6HAP_A.pdb	RICQEDSRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD
[Truncated_Name:10] 6HAM_A.pdb	RICQEDSRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFD
[Truncated_Name:11] 4K46_A.pdb	RIAQDDCAKGFLDGFPR TIPQADGLKEVGVVVDYVIEFD
[Truncated_Name:12] 3GMT_A.pdb	RLKEADCANGYLF DGFPR TIAQADAMKEAGVAIDYVLEID
[Truncated_Name:13] 4PZL_A.pdb	RISKNDCNNGFLLDGVPR TIPQAQELDKLVNIDYIVEVD
	*~ * *~* ** ***** ** ^ *~ ~*~*~* *
	81 . . . 120

	121	.	.	.	160
[Truncated_Name:1] 1AKE_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV	KFNPPKVEGKDDVTG			
[Truncated_Name:2] 6S36_A.pdb	VPDELIVDKIVGRRVHAPSGRVYHV	KFNPPKVEGKDDVTG			
[Truncated_Name:3] 6RZE_A.pdb	VPDELIVDAIVGRRVHAPSGRVYHV	KFNPPKVEGKDDVTG			
[Truncated_Name:4] 3HPR_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV	KFNPPKVEGKDDGTG			
[Truncated_Name:5] 1E4V_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV	KFNPPKVEGKDDVTG			
[Truncated_Name:6] 5EJE_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV	KFNPPKVEGKDDVTG			
[Truncated_Name:7] 1E4Y_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV	KFNPPKVEGKDDVTG			
[Truncated_Name:8] 3X2S_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV	KFNPPKVEGKDDVTG			
[Truncated_Name:9] 6HAP_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV	KFNPPKVEGKDDVTG			
[Truncated_Name:10] 6HAM_A.pdb	VPDELIVDRIVGRRVHAPSGRVYHV	KFNPPKVEGKDDVTG			
[Truncated_Name:11] 4K46_A.pdb	VADSVIVERMAGRRAHLASGRTYHN	VYNPPKVEGKDDVTG			
[Truncated_Name:12] 3GMT_A.pdb	VPFSEIIERMSGRRTHPASGRTYHV	KFNPPKVEGKDDVTG			
[Truncated_Name:13] 4PZL_A.pdb	VADNLLIERITGRRIHPASGRTYHT	KFNPPKVADKDDVTG			

* ^^^ ^ *** * *** ** ^***** *** **

	121	.	.	.	160
	161	.	.	.	200
[Truncated_Name:1] 1AKE_A.pdb	EELTTRKDDQEETVRKRLVEYHQM	TAPLIGYYSKEAEAGN			
[Truncated_Name:2] 6S36_A.pdb	EELTTRKDDQEETVRKRLVEYHQM	TAPLIGYYSKEAEAGN			
[Truncated_Name:3] 6RZE_A.pdb	EELTTRKDDQEETVRKRLVEYHQM	TAPLIGYYSKEAEAGN			
[Truncated_Name:4] 3HPR_A.pdb	EELTTRKDDQEETVRKRLVEYHQM	TAPLIGYYSKEAEAGN			
[Truncated_Name:5] 1E4V_A.pdb	EELTTRKDDQEETVRKRLVEYHQM	TAPLIGYYSKEAEAGN			
[Truncated_Name:6] 5EJE_A.pdb	EELTTRKDDQEECVRKRLVEYHQM	TAPLIGYYSKEAEAGN			
[Truncated_Name:7] 1E4Y_A.pdb	EELTTRKDDQEETVRKRLVEYHQM	TAPLIGYYSKEAEAGN			
[Truncated_Name:8] 3X2S_A.pdb	EELTTRKDDQEETVRKRLCEYHQM	TAPLIGYYSKEAEAGN			
[Truncated_Name:9] 6HAP_A.pdb	EELTTRKDDQEETVRKRLVEYHQM	TAPLIGYYSKEAEAGN			
[Truncated_Name:10] 6HAM_A.pdb	EELTTRKDDQEETVRKRLVEYHQM	TAPLIGYYSKEAEAGN			
[Truncated_Name:11] 4K46_A.pdb	EDLVIREDDKEETVLARLGVYHNQ	TAPLIAYYGKEAEAGN			
[Truncated_Name:12] 3GMT_A.pdb	EPLVQRDDDKKEETVKKRLDVYEA	QTKPLITYYGDWARRGA			
[Truncated_Name:13] 4PZL_A.pdb	EPLITRTDDNEDTVKQRLSVYHAQ	TAKLIDFYRNFSSTNT			

* * * ** *^ * ** * * ** ^*

	161	.	.	.	200
	201	.	.	227	
[Truncated_Name:1] 1AKE_A.pdb	T--KYAKVDGTPVAEVRADLEKILG-				
[Truncated_Name:2] 6S36_A.pdb	T--KYAKVDGTPVAEVRADLEKILG-				
[Truncated_Name:3] 6RZE_A.pdb	T--KYAKVDGTPVAEVRADLEKILG-				
[Truncated_Name:4] 3HPR_A.pdb	T--KYAKVDGTPVAEVRADLEKILG-				
[Truncated_Name:5] 1E4V_A.pdb	T--KYAKVDGTPVAEVRADLEKILG-				
[Truncated_Name:6] 5EJE_A.pdb	T--KYAKVDGTPVAEVRADLEKILG-				
[Truncated_Name:7] 1E4Y_A.pdb	T--KYAKVDGTPVAEVRADLEKILG-				


```

[Truncated_Name:8]3X2S_A.pdb      T--KYAKVDGTKPVAEVRADLEKILG-
[Truncated_Name:9]6HAP_A.pdb      T--KYAKVDGTKPVCEVRADLEKILG-
[Truncated_Name:10]6HAM_A.pdb     T--KYAKVDGTKPVCEVRADLEKILG-
[Truncated_Name:11]4K46_A.pdb     T--QYLKFDGTKAVAEVSAELEKALA-
[Truncated_Name:12]3GMT_A.pdb     E-----NGLKAPA-----YRKISG-
[Truncated_Name:13]4PZL_A.pdb     KIPKYIKINGDQAVEKVSQDIFDQLNK
                                   *
                                   .           .           227
                                   201

```

Call:

```
pdbaln(files = files, fit = TRUE, exefile = "msa")
```

Class:

```
pdbs, fasta
```

Alignment dimensions:

```
13 sequence rows; 227 position columns (204 non-gap, 23 gap)
```

```
+ attr: xyz, resno, b, chain, id, ali, resid, sse, call
```

Now we have our aligned and superposed structures we can perform all sorts of analysis on them. Let's do PCA..

```

# Vector containing PDB codes for figure axis
#ids <- basename.pdb(pdbs$id)

# Draw schematic alignment
#plot(pdbs, labels=ids)

```

Annotate collected PDB structures

```

#anno <- pdb.annotate(ids)
#unique(anno$source)
#anno


```

Principal component analysis

```

# Perform PCA
pc.xray <- pca(pdbs)
plot(pc.xray)

```



Results of PCA on ADK X-ray structure. Each dot represents one PDB structure.


We can cluster the structures by RMSD (or any other methods).

```
# Calculate RMSD, measuring the distance b/w clusters
rd <- rmsd(pdbbs)
```

Warning in rmsd(pdbbs): No indices provided, using the 204 non NA positions

```
# Structure-based clustering
hc.rd <- hclust(dist(rd))
grps.rd <- cutree(hc.rd, k=3)

#plot(pc.xray, 1:2, col=grps)
plot(pc.xray, 1:2, col="grey50", bg=grps.rd, pch=21, cex=1)
```



5. Optional further visualization

We can make a movie - also called a trajectory of the major differences (ie. structural displacement) of ADK

```
# Visualize first principal component  
pc1 <- mktrj(pc.xray, pc=1, file="pc_1.pdb")
```