

idea项目配置连接池为阿里云上的mysql

```
datasource:
  type: com.alibaba.druid.pool.DruidDataSource
  username: root
  password: 111111
  url: jdbc:mysql://47.100.178.135:3306/vhr?useUnicode=true&characterEncoding=UTF-8&serverTimezone=Asia/Shanghai
```

只要将这里改成阿里云的ip地址

如果出现报错The last packet sent successfully to the server was 0 milliseconds ago. The driver has not received any packets from the server.

解决办法如下:

1. 阿里云安全组开放3306端口

入方向

出方向

手动添加

快速添加

Q 输入端口或者授权对象进行搜索

不合并

授权策略	优先级 ①	协议类型	端口范围 ①	授权对象 ①	描述	创建时间	操作
<div><div><input type="checkbox"/></div><div>允许</div></div>	1	自定义 TCP	目的: 3306/3306	源: 0.0.0.0/0	mysql	2023年1月20日 19:04:03	<div>编辑 复制 删除</div>

2. 防火墙开放3306端口

```
sudo firewall-cmd --zone=public --permanent --add-port=3306/tcp
```

```
[ecs-user@patrick ~]$ sudo firewall-cmd --zone=public --permanent --add-port=3306/tcp
success
```

```
sudo firewall-cmd --reload
```

```
[ecs-user@patrick ~]$ sudo firewall-cmd --reload
success
```

sudo firewall-cmd --list-all (如下图所示, 说明3306端口是否已经开放)

```
[ecs-user@patrick ~]$ sudo firewall-cmd --list-all
public
target: default
icmp-block-inversion: no
interfaces:
sources:
services: dhcpv6-client ssh
ports: 8080/tcp 15672/tcp 3306/tcp
protocols:
masquerade: no
forward-ports:
source-ports:
icmp-blocks:
rich rules:
```

3. 重启阿里云上的mysql

```
[ecs-user@patrick ~]$ sudo service mysqld stop
Shutting down MySQL. SUCCESS!
[ecs-user@patrick ~]$ sudo service mysqld status
ERROR! MySQL is not running
[ecs-user@patrick ~]$ sudo service mysqld start
Starting MySQL.. SUCCESS!
[ecs-user@patrick ~]$ sudo service mysqld status
SUCCESS! MySQL running (26289)
```