



Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

Database Management Systems

Module 12: Intermediate SQL/1

Partha Pratim Das

Department of Computer Science and Engineering
Indian Institute of Technology, Kharagpur

ppd@cse.iitkgp.ac.in



Module 12

Partha Pratim
Das

Objectives & Outline

Nested Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of the Database

Module Summary

- SQL Examples Practiced



Module 12

Partha Pratim
Das

Objectives & Outline

Nested Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of the Database

Module Summary

- To understand nested subquery in SQL
- To understand processes for data modification



Module 12

Partha Pratim
Das

Objectives & Outline

Nested Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of the Database

Module Summary

- Nested Subqueries
- Modifications of the Database



Module 12

Partha Pratim
Das

Objectives &
Outline

**Nested
Subqueries**

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

Nested Subqueries



Nested Subqueries

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- SQL provides a mechanism for the nesting of subqueries
- A **subquery** is a **select-from-where** expression that is nested within another query
- The nesting can be done in the following SQL query

```
select  $A_1, A_2, \dots, A_n$   
from  $r_1, r_2, \dots, r_m$   
where  $P$ 
```

as follows:

- A_i can be replaced by a subquery that generates a single value
- r_i can be replaced by any valid subquery
- P can be replaced with an expression of the form:

$B \langle \text{operation} \rangle (\text{subquery})$

where B is an attribute and $\langle \text{operation} \rangle$ to be defined later



Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

**Subqueries in the
Where Clause**

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

Subqueries in the Where Clause



Subqueries in the Where Clause

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

**Subqueries in the
Where Clause**

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- Typical use of subqueries is to perform tests:
 - For set membership
 - For set comparisons
 - For set cardinality



Set Membership

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- Find courses offered in Fall 2009 and in Spring 2010. (**intersect** example)

```
select distinct course_id  
from section  
where semester = 'Fall' and year = 2009 and  
       course_id in (select course_id  
                      from section  
                      where semester = 'Spring' and year = 2010);
```

- Find courses offered in Fall 2009 but not in Spring 2010. (**except** example)

```
select distinct course_id  
from section  
where semester = 'Fall' and year = 2009 and  
       course_id not in (select course_id  
                          from section  
                          where semester = 'Spring' and year = 2010);
```



Set Membership (2)

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- Find the total number of (distinct) students who have taken course sections taught by the instructor with ID 10101

```
select count (distinct ID)
from takes
where (course_id, sec_id, semester, year) in
      (select course_id, sec_id, semester, year
       from teaches
       where teaches.ID = 10101);
```

- Note: Above query can be written in simpler manner. The formulation above is simply to illustrate SQL features.



Set Comparison – “some” Clause

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- Find names of instructors with salary greater than that of some (at least one) instructor in the Biology department

```
select distinct T.name  
from instructor as T, instructor as S  
where T.salary > S.salary and S.dept name = 'Biology';
```

- Same query using **some** clause

```
select name  
from instructor  
where salary > some (select salary  
                        from instructor  
                        where dept_name = 'Biology');
```



Set Comparison – “some” Clause

```
postgres=# select distinct T.name  
from instructor as T, instructor as S  
where T.salary > S.salary and S.dept_name = 'Biology' limit 20 ;  
name
```

```
-----  
Bertolino  
Yin  
Tung  
Dusserre  
Jaekel  
Liley  
Atanassov  
Sakurai  
Pingr  
Valtchev  
Arias  
Moreira  
Mingoz  
DAgostino  
Bondi  
Yazdi  
Soisalon-Soininen  
Gustafsson  
Bawa  
Sarkar  
(20 rows)
```

```
postgres=# SELECT DISTINCT T.name  
FROM instructor AS T  
WHERE T.salary > (SELECT MIN(salary) FROM instructor WHERE dept_name = 'Biology') LIMIT 20;  
name
```

```
-----  
Bertolino  
Yin  
Tung  
Dusserre  
Jaekel  
Liley  
Atanassov  
Sakurai  
Pingr  
Valtchev  
Arias  
Moreira  
Mingoz  
DAgostino  
Bondi  
Yazdi  
Soisalon-Soininen  
Gustafsson  
Bawa  
Sarkar  
(20 rows)
```

from instructor
where dept_name = 'Biology');



Definition of "some" Clause

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- $F <\text{comp}> \text{some } r \Leftrightarrow \exists t \in r \text{ such that } (F <\text{comp}> t)$
where $<\text{comp}>$ can be: $<, \leq, >, \geq, =, \neq$
- **some** represents existential quantification

$$(5 < \text{some } \begin{array}{|c|} \hline 0 \\ \hline 5 \\ \hline 6 \\ \hline \end{array}) = \text{true} \quad (\text{read: } 5 < \text{some tuple in the relation})$$

$$(5 < \text{some } \begin{array}{|c|} \hline 0 \\ \hline 5 \\ \hline \end{array}) = \text{false}$$

$$(5 = \text{some } \begin{array}{|c|} \hline 0 \\ \hline 5 \\ \hline \end{array}) = \text{true}$$

$$(5 \neq \text{some } \begin{array}{|c|} \hline 0 \\ \hline 5 \\ \hline \end{array}) = \text{true (since } 0 \neq 5)$$

$(= \text{some}) \equiv \text{in}$

However, $(\neq \text{some}) \neq \text{not in}$



Set Comparison – “all” Clause

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- Find the names of all instructors whose salary is greater than the salary of all instructors in the Biology department

```
select name
from instructor
where salary > all (select salary
                    from instructor
                    where dept_name = 'Biology');
```

```
postgres=# select name from instructor where salary > all (select salary from instructor where dept_name = 'Biology') limit 20;
 name
-----
McKinnon
MTrd
Luo
Levine
Shumling
Sullivan
Voronina
Arlas
MIngoz
Yazdi
Kenje
Jaekel
Sarkar
Bancilhon
Lilley
Gustafsson
Bondi
Lent
Pimenta
Bourrier
(20 rows)

postgres=#
```



Definition of “all” Clause

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- $F \text{ <comp> all } r \Leftrightarrow \forall t \in r \text{ such that } (F \text{ <comp> } t)$
Where <comp> can be: $<, \leq, >, \geq, =, \neq$
- **all** represents universal quantification

$$(5 < \text{all } \begin{array}{|c|} \hline 0 \\ \hline 5 \\ \hline 6 \\ \hline \end{array}) = \text{false}$$

$$(5 < \text{all } \begin{array}{|c|} \hline 6 \\ \hline 10 \\ \hline \end{array}) = \text{true}$$

$$(5 = \text{all } \begin{array}{|c|} \hline 4 \\ \hline 5 \\ \hline \end{array}) = \text{false}$$

$$(5 \neq \text{all } \begin{array}{|c|} \hline 4 \\ \hline 6 \\ \hline \end{array}) = \text{true (since } 5 \neq 4 \text{ and } 5 \neq 6)$$

$(\neq \text{all}) \equiv \text{not in}$
However, $(= \text{all}) \neq \text{in}$



Test for Empty Relations: “exists”

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- The **exists** construct returns the value **true** if the argument subquery is nonempty
 - **exists** $r \Leftrightarrow r \neq \emptyset$
 - **not exists** $r \Leftrightarrow r = \emptyset$



Use of “exists” Clause

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- Yet another way of specifying the query “Find all courses taught in both the Fall 2009 semester and in the Spring 2010 semester”

```
select course_id
from section as S
where semester = 'Fall' and year = 2009 and
      exists (select *
              from section as T
              where semester = 'Spring' and year = 2010
              and S.course_id = T.course_id);
```

- **Correlation name** – variable S in the outer query
- **Correlated subquery** – the inner query



Use of “not exists” Clause

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- Find all students who have taken all courses offered in the Biology department.

```
select distinct S.ID, S.name  
from student as S  
where not exists (select course_id  
                    from course  
                    where dept_name = 'Biology')  
except  
(select T.course_id  
   from takes as T  
   where S.ID = T.ID));
```

- First nested query lists all courses offered in Biology
- Second nested query lists all courses a particular student took
- Note: $X - Y = \emptyset \Leftrightarrow X \subseteq Y$
- Note: Cannot write this query using **= all** and its variants



Test for Absence of Duplicate Tuples: “unique”

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- The **unique** construct tests whether a subquery has any duplicate tuples in its result
- The **unique** construct evaluates to “true” if a given subquery contains no duplicates
- Find all courses that were offered at most once in 2009

```
select  T.course_id
from    course as T
where   unique (select R.course_id
                 from section as R
                 where T.course_id = R.course_id
                 and R.year = 2009);
```



Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

**Subqueries in the
From Clause**

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

Subqueries in the From Clause



Subqueries in the From Clause

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- SQL allows a subquery expression to be used in the **from** clause
- Find the average instructors' salaries of those departments where the average salary is greater than \$42,000

```
select dept_name, avg_salary
from (select dept_name, avg(salary) as avg_salary
      from instructor
      group by dept_name)
where avg_salary > 42000;
```

- Note that we do not need to use the **having** clause
- Another way to write above query

```
select dept_name, avg_salary
from (select dept_name, avg(salary)
      from instructor
      group by dept_name) as dept_avg(dept_name, avg_salary)
where avg_salary > 42000;
```



With Clause

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- The **with** clause provides a way of defining a temporary relation whose definition is available only to the query in which the **with** clause occurs
- Find all departments with the maximum budget

```
with max_budget(value) as  
      (select max(budget)  
      from department)  
select department.name  
from department, max_budget  
where department.budget=max_budget.value;
```



Complex Queries using With Clause

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- Find all departments where the total salary is greater than the average of the total salary at all departments

```
with dept_total (dept_name, value) as  
    select dept_name, sum(salary)  
    from instructor  
    group by dept_name,  
    dept_total_avg(value) as  
        (select avg(value)  
        from dept_total)  
select dept_name  
from dept_total, dept_total_avg  
where dept_total.value > dept_total_avg.value;
```



Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

Subqueries in the Select Clause



Scalar Subquery

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- Scalar subquery is one which is used where a single value is expected
- List all departments along with the number of instructors in each department

```
select dept_name,  
      (select count(*)  
       from instructor  
       where department.dept_name = instructor.dept_name)  
       as num_instructors  
       from department;
```

- Runtime error if subquery returns more than one result tuple



Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

Modifications of the Database



Modification of the Database

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

**Modifications of
the Database**

Module Summary

- Deletion of tuples from a given relation
- Insertion of new tuples into a given relation
- Updating of values in some tuples in a given relation



Deletion

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- Delete all instructors
delete from *instructor*
- Delete all instructors from the Finance department
delete from *instructor*
where *dept_name* = 'Finance';
- Delete all tuples in the *instructor* relation for those instructors associated with a department located in the Watson building
delete from *instructor*
where *dept_name* in (select *dept_name*
from *department*
where *building* = 'Watson');



Deletion (2)

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- Delete all instructors whose salary is less than the average salary of instructors

delete from *instructor*

where *salary* < (select avg (*salary*)
from *instructor*);

- **Problem:** as we delete tuples from deposit, the average salary changes
- Solution used in SQL:
 - a) First, compute **avg** (*salary*) and find all tuples to delete
 - b) Next, delete all tuples found above (without recomputing **avg** or retesting the tuples)



Insertion

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- Add a new tuple to course
insert into *course*
values ('CS-437', 'Database Systems', 'Comp. Sci.', 4);
- or equivalently:
insert into *course* (*course_id*, *title*, *dept_name*, *credits*)
values ('CS-437', 'Database Systems', 'Comp. Sci.', 4);
- Add a new tuple to student with *tot_creds* set to null
insert into *student*
values ('3003', 'Green', 'Finance', *null*);



Insertion (2)

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- Add all instructors to the *student* relation with *tot_creds* set to 0

```
insert into student
```

```
select ID, name, dept_name, 0
```

```
from instructor
```

- The **select from where** statement is evaluated fully before any of its results are inserted into the relation

- Otherwise queries like

```
insert into table1 select * from table1
```

would cause problem



Updates

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- Increase salaries of instructors whose salary is over \$100,000 by 3%, and all others by a 5%

- Write two **update** statements:

```
update instructor
```

```
set salary = salary * 1.03
```

```
where salary > 100000;
```

```
update instructor
```

```
set salary = salary * 1.05
```

```
where salary <= 100000;
```

- The order is important
- Can be done better using the **case** statement (next slide)



Case Statement for Conditional Updates

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- Same query as before but with **case** statement

```
update instructor
```

```
set salary = case
```

```
  when salary <= 100000
```

```
  then salary * 1.05
```

```
  else salary * 1.03
```

```
end
```



Updates with Scalar Subqueries

Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- Recompute and update `tot_creds` value for all students

update student S

set `tot_creds` = (select sum(`credits`)

from `takes, course`

where `takes.course_id` = `course.course_id` and

`S.ID` = `takes.ID` and

`takes.grade` <> 'F' and

`takes.grade` is not null);

- Sets `tot_creds` to null for students who have not taken any course

- Instead of `sum(credits)`, use:

case

when `sum(credits)` is not null then `sum(credits)`

else 0

end



Module 12

Partha Pratim
Das

Objectives &
Outline

Nested
Subqueries

Subqueries in the
Where Clause

Subqueries in the
From Clause

Subqueries in the
Select Clause

Modifications of
the Database

Module Summary

- Introduced nested subquery in SQL
- Introduced data modification

Slides used in this presentation are borrowed from <http://db-book.com/> with kind permission of the authors.

Edited and new slides are marked with “PPD”.