

IIT Madras BSc Degree

Copyright and terms of use

IIT Madras is the sole owner of the content available in this portal - onlinedegree.iitm.ac.in and the content is copyrighted to IIT Madras.

- Learners may download copyrighted material for their use for the purpose of the online program only.
- Except as otherwise expressly permitted under copyright law, no use other than for the purpose of the online program is permitted.
- No copying, redistribution, retransmission, publication or exploitation, commercial or otherwise of material will be permitted without the express permission of IIT Madras.
- Learner acknowledges that he/she does not acquire any ownership rights by downloading copyrighted material.
- Learners may not modify, publish, transmit, participate in the transfer or sale, create derivative works, or in any way exploit, any of the content, in whole or in part.

REST and APIs

API Design

- Web architecture - REST
- API Examples
- OpenAPI specification

Distributed Software Architecture

- Servers - Clients
- Standard “protocols” needed for communication
- Assumptions?
 - Server always on?
 - Server knows what client is doing?
 - Client authentication?
 - Network latency?


The Web

- Client - Server may be far apart
- Different networks, latencies, quality
- Authentication? Not core part of protocol
- State?
 - Server does not know what state client is in
 - Client cannot be sure what state server is in

Architecture for the Web

- Roy Fielding, PhD thesis 2000 UC Irvine
- “REpresentational State Transfer” - REST
 - Take into account limitations of the Web
 - Provide guidelines or constraints
- Software Architecture Style
 - Not a set of rules!


Constraint 1: Client - Server




Constraint 2: Stateless

- Server cannot assume state of client:
 - which page are you looking at
 - is a request coming from an already logged in user just because of the address?
- Client cannot assume state of server:
 - did server reboot since last request?
 - is this request being answered by same server?

Constraint 3: Layered System



Constraint 4: Cacheability



Constraint 5: Uniform Interface

- Client and Server interact in a uniform and predictable manner
- Server exposes “resources”

Hypertext/media used to convey the available resources and functionality - can be discovered by client through hypertext information from server

(Optional) Constraint 6: Code on Demand

- Server can extend client functionality
 - Javascript
 - Java applets

Part of the overall architecture - these are not hard rules

REST

- REpresentational State Transfer

REST

- REpresentational State Transfer

What does that mean?

- State information between client and server explicitly transferred with every communication

Sequence

- Client accesses a Resource Identifier from server
 - Usually URI - superset of URL
 - Typically start from home page of application
 - No initial state assumed

Sequence

- Client accesses a Resource Identifier from server
 - Usually URI - superset of URL
 - Typically start from home page of application
 - No initial state assumed
- Resource Operation specified as part of access
 - If HTTP, then GET, POST etc.
 - Not fundamentally tied to protocol

Sequence

- Client accesses a Resource Identifier from server
 - Usually URI - superset of URL
 - Typically start from home page of application
 - No initial state assumed
- Resource Operation specified as part of access
 - If HTTP, then GET, POST etc.
 - Not fundamentally tied to protocol
- Server responds with new Resource Identifier
 - New state of system; new links to follow etc.

Sequence

- Client accesses a Resource Identifier from server
 - Usually URI - superset of URL
 - Typically start from home page of application
 - No initial state assumed
- Resource Operation specified as part of access
 - If HTTP, then GET, POST etc.
 - Not fundamentally tied to protocol
- Server responds with new Resource Identifier
 - New state of system; new links to follow etc.

State of interaction transferred back and forth

HTTP

- One possible protocol to carry REST messages
- Use the HTTP verbs to indicate actions
- Standardize some types of functionality

HTTP

- GET: Retrieve representation of target resource's state
- POST: Enclose data in request: target resource “processes” it
- PUT: Create a target resource with data enclosed
- DELETE: Delete the target resource

Idempotent operations

- Repeated application of the operation is not a problem

Idempotent operations

- Repeated application of the operation is not a problem
- Example: GET is always safe - read-only operation

Idempotent operations

- Repeated application of the operation is not a problem
- Example: GET is always safe - read-only operation
- Example:
 - PUT: will always create the same new resource. If already exists, may give error

Idempotent operations

- Repeated application of the operation is not a problem
- Example: GET is always safe - read-only operation
- Example:
 - PUT: will always create the same new resource. If already exists, may give error
 - DELETE: can delete only once. may error on repeated deletion, but won't change data

Idempotent operations

- Repeated application of the operation is not a problem
- Example: GET is always safe - read-only operation
- Example:
 - PUT: will always create the same new resource. If already exists, may give error
 - DELETE: can delete only once. may error on repeated deletion, but won't change data
- POST: May NOT be idempotent
 - Example: Add comment to blog - repeat will cause multiple copies

CRUD

- CRUD - database operations
- Typically a common set of operations needed in most web applications
 - Good candidate for REST based functionality

REST != CRUD

But they do work well together

Data Encoding

- Basic HTML: for simple responses
- XML: Structured data response
- JSON: simpler form of structured data

Data serialization for transferring complex data types over text based format

JSON

- JavaScript Object Notation
- Nested arrays:
 - Serialize complex data structures like dictionaries, arrays etc.

JSON

- JavaScript Object Notation
- Nested arrays:
 - Serialize complex data structures like dictionaries, arrays etc.

```
{  
  "firstName": "John",  
  "lastName": "Smith",  
  "age": 27,  
  "address": {  
    "streetAddress": "21 2nd Street",  
    "postalCode": "10021-3100"  
  },  
  "phoneNumbers": [  
    {  
      "type": "home",  
      "number": "212 555-1234"  
    },  
    {  
      "type": "office",  
      "number": "646 555-4567"  
    }  
  ],  
  "children": [],  
  "spouse": null  
}
```

API data transfer format

- Input to API: text - HTTP
- Output: complex data types - JSON, XML, YAML etc.
 - JSON most commonly used
- Different from internal server representation
- Different from final view presentation

YAML

- Yet Another Markup Language - common alternative, especially for documentation and configuration