

1. ConvertAudioEngine-Keep71.ps1 v3.0.5

Retains TrueHD 7.1 and AAC 7.1 audio tracks

- Keep original TrueHD 7.1 / AAC 7.1 and add a **DDP 5.1 (EAC3) compatibility track at 1152k** (Pass+Copy)
- Downmix all other 7.1 audio to **DDP 5.1 (1152k)**
- Re-encode 5.1 audio to **DDP 5.1 (768k)**
- DTS-HD MA/HRA re-encodes at **DDP 5.1 (1024k)**
- All **2.0 stereo tracks are removed** — stereo output is handled by ConvertAudioEngine-Stereo
- Maintain perfect sync on long-duration files
- Normalize malformed channel layouts
- Remove 2-channel commentary tracks

1 To Adjust Bitrate (line 68-72)

```
You can safely adjust these numbers, within **'....k'**  
Common EAC3 5.1: 384, 448, 512, 640, 768 — industry-standard streaming bitrates  
Pipeline-specific: 1024, 1152, 1280, 1408, 1536 — used for DTS-HD re-encode & 7.1→5.1 downmix  
  
$BitRateConfig = @{  
    Downmix51      = '1152k'    # << Change your Bitrate  
    ReEncode51     = '768k'     # << Change your Bitrate  
    PassCopy51     = '1152k'    # << Change your Bitrate  
    EncodeDTSHD    = '1024k'    # << Change your Bitrate
```

Remember to save the file after making changes.

All four values can be adjusted safely — changes apply automatically throughout the script.

Key	Default	Used for
Downmix51	1152k	All 7.1 sources downmixed to 5.1 (EAC3/DTS/PCM/FLAC)
ReEncode51	768k	5.1 sources re-encoded to DD+
PassCopy51	1152k	DDP 5.1 compatibility track added alongside TrueHD 7.1 / AAC 7.1
EncodeDTSHD	1024k	DTS-HD MA and HRA sources (5.1 and 7.1)

Requirements

PowerShell 7.6 - [Click here to Download PS 7.6 \(Windows x64 .msi\)](#)

FFmpeg 8.1 - <https://ffmpeg.org/download.html>

Quick Start (Windows 11)

1. Place **ConvertAudioEngine-Keep71.ps1**, **ffmpeg.exe**, and **ffprobe.exe** in the same folder.
2. Run the script:

```
pwsh -ExecutionPolicy Bypass -File .\ConvertAudioEngine-Keep71.ps1 ".\YourMovie.mkv"
```

The -ExecutionPolicy Bypass only applies to this single run and doesn't change your system settings.

macOS / Linux

1. Place the script, **ffmpeg**, and **ffprobe** in the same folder.
2. Make the binaries executable (first time only):

```
chmod +x ffmpeg ffprobe
```

3. Run:

```
pwsh -File ./ConvertAudioEngine-Keep71.ps1 "./YourMovie.mkv"
```

Output filename: The program saves a new file in the same folder, adding a codec suffix like **_keep71mix.mkv**. Your original file stays untouched.

Supported Audio Codecs

The engine supports and processes the following codec families:

Codec Family	Formats Included
AAC	AAC LC, HE-AAC, AAC 5.1, AAC 7.1
EAC3 / Atmos	EAC3, EAC3-JOC (Atmos)
TrueHD	TrueHD 5.1, TrueHD 7.1, TrueHD+Atmos
DTS	DTS Core, DTS-HD MA, DTS-HD HRA
PCM	pcm_s16le, pcm_s24le, pcm_f32le, pcm_f32be
FLAC	All FLAC channel layouts

2. FFmpeg Global Options

These are global flags to ensure FFmpeg handles large, high-resolution files without data corruption or sync drift.

- **-y**
 - **What:** Overwrites the output file without asking.
 - **Why:** Allows the script to re-run cleanly without manual prompts.
- **-loglevel error**
 - **What:** Suppresses all FFmpeg output except actual errors.
 - **Why:** Keeps the console clean. Real errors still surface.
- **-stats**
 - **What:** Shows encoding progress (time, bitrate, speed) in the console.
 - **Why:** Gives the user live feedback during what can be a long encode.
- **-threads 8** — User-adjustable (4–16)
 - **What:** Sets the number of CPU threads the encoder is allowed to use.
 - **Why:** Helps balance encoding speed and system stability.
- **-analyzeduration 200M** & **-probesize 200M**
 - **What:** Increases the initial data analysis buffer to 200 Megabytes.
 - **Why:** High-bitrate audio like TrueHD with Atmos metadata or AAC 7.1 requires a deep probe to fully parse the channel layout.
- **-err_detect ignore_err**
 - **What:** Instructs FFmpeg to bypass minor bitstream errors.
 - **Why:** Prevents a single corrupted audio frame from aborting a multi-hour conversion.
- **-drc_scale 0**
 - **What:** Disables Dynamic Range Compression (DRC).
 - **Why:** Ensures the output audio maintains the full dynamic range of the source.

2.5 ScanThrottle + ThreadCount

Sets how many CPU threads the encoder uses (line 55).

```
$ThreadCount = 8    # User-adjustable (4-16).
```

Limits how many peak-scan tasks run at the same time (line 56).

```
$ScanThrottle = [Math]::Max(1, [int]([Environment]::ProcessorCount /  
$ThreadCount))  
# Recommended overrides: 1, 2, 3, or 4
```

What ScanThrottle does:

- Limits parallel SPN scans to avoid CPU overload.
- Keeps the system responsive during peak detection.
- Does not affect encoding speed.
- SSD/NVMe: safe to override up to 4. Spinning disk: keep at 1.

3. The "De-Sync" Safeguard

These flags are applied after the input to maintain perfect alignment on long-duration files.

- **-avoid_negative_ts make_zero**
 - **What:** Forces all stream timestamps to start at absolute zero.
 - **Why:** Many digital files contain negative initial "Presentation Time Stamps" (PTS); this clamps them to zero to prevent audio lag or lead.
- **-max_muxing_queue_size 14000** *(1024-100000) recommended range
 - **What:** Increases the muxing buffer headroom.
 - **Why:** Pass+Copy mode creates 3 streams (video c, 7.1 pass, 7.1→EAC3 enc). One copy (video) and one pass (7.1 audio) streams flood the muxer while the encode pipeline catches up; 14000 buffer prevents de-sync on 3+ hour files.
- **-map 0:v? -c:v copy**
 - **What:** Maps all video tracks and sets them to stream-copy mode.
 - **Why:** Ensures zero quality loss for the video while moving at maximum speed.
- **-map_metadata 0 -map_chapters 0**
 - **What:** Copies global metadata and chapter markers from the source.
 - **Why:** Preserves the original file's organizational structure (Title, Year, Scene markers).

3.2 Safe-Peak Normalizer (SPN)

- **What:** Safe-Peak Normalizer checks each audio track before processing and only steps in when the volume is too close to clipping (above -0.5 dBFS).
- **Why:** Some movies arrive with peaks already above 0 dBFS. When that happens, even simple mixing of the channels can push those peaks higher and cause distortion in the final encode. SPN catches this early so the issue never reaches the rest of the audio processing.

- **How:** Safe-Peak Normalizer runs after rule matching and before filters are built. (Encode, Downmix, etc.). If the peak scan shows the track is too hot, a light loudness-correction step is added at the very start of that track's filter chain.
- **Clean Sources:** Nothing is changed — the original loudness and dynamics stay exactly the same.
- **Passthrough tracks:** — Peak detection is skipped entirely. Copied streams cannot have filters applied.
- **Dirty Sources:** SPN fixes unsafe peaks without making the movie sound compressed or “over-normalized.”
- **Result:** More consistent, safer audio across all movies, keeping clean sources untouched.

Threshold (line 57)

These are the values Safe-Peak Normalizer uses to decide when to step in.

```
$PeakThresholdDB = -0.5 # SPN: loudnorm triggers when source peak exceeds this (dBFS)
```

- Valid range: **−1.5 dBFS to −0.3 dBFS** (recommended: −0.5 dBFS)
- Lower values (e.g. −1.5) normalize more tracks — more conservative.
- Higher values (e.g. −0.3) normalize fewer tracks — only the hottest sources.

Setting	Value
loudnorm target	−23 LUFS
Loudness range target	LRA=11 LU
True peak ceiling	−1.5 dBTP

4. Stereo (2.0) Tracks — Removed

All 2.0 stereo tracks are removed by this script, regardless of codec. Stereo output is delegated to **ConvertAudioEngine-Stereo**, which handles 2.0 encoding with the correct stereo-specific flags and bitrates.

5. Encoding & Downmix Execution

These parameters determine how the audio is shaped and processed during encoding.

- `-filter:a:$i $panFilter`
 - **What:** Applies the custom channel-mapping matrix (the Pan Filter).
 - **Why:** Necessary for downmixing 7.1 or 5.1 to smaller layouts. It ensures that "lost" channels (like back-surrounds) are projected into the remaining speakers rather than simply deleted.
- `-c:a:$i eac3`

- **What:** Sets the codec for audio stream `$i` to Dolby Digital Plus (EAC3).
- **Why:** Chosen for its high efficiency and broad compatibility with modern smart TVs and home theater receivers.
- **-ac 6**
 - **What:** Forces the output to exactly 6 channels (5.1).
 - **Why:** Applied on the 5.1 re-encode path to guarantee the correct channel count, even if the source reports a non-standard layout.
- **-b:a:\$i \$t.Bitrate**
 - **What:** Sets the target bitrate (e.g., 1152k for 7.1 downmix/Pass+Copy, 768k for 5.1 re-encode, 1024k for DTS-HD).
 - **Why:** High bitrates ensure the "transparency" of the encode, making it difficult to distinguish from the lossless original.
- **-dialnorm -31**
 - **What:** Sets Dialogue Normalization to the reference "off" position.
 - **Why:** Prevents the playback device from applying its own internal volume leveling, preserving the original mix's intended loudness.
- **-cutoff 20000**
 - **What:** Sets the low-pass filter frequency to 20kHz.
 - **Why:** Preserves the high-frequency clarity of the audio that standard encoders sometimes discard to save space.
 - **Applies to:** Downmix and Pass+Copy DDP duplicate paths, and 5.1 re-encode path only — not passthrough.
- **-metadata:s:a:\$i "title=..."**
 - **What:** Injects a custom string into the stream title metadata.
 - **Why:** Allows users to see exactly what the track is (e.g., "DD+ 5.1 Downmix") in their media player's audio selection menu.

6. Audio Rules & Priority

The audio-engine uses a **Priority Mapping (0-110)** to evaluate tracks based on quality and codec type.

The "Pass+Copy" Strategy

- **Action:** Specifically for **TrueHD 7.1** and **AAC 7.1**.
- **What:** It performs a **Passthrough** of the original 7.1 master while creating a **new EAC3 (DD+) 5.1** duplicate at **1152k** (`PassCopy51`).

- **Why:** This future-proofs the file for high-end theaters while providing a high-quality fallback for standard devices that cannot decode 7.1 layouts.
- **Summary Visualization:** This action generates **two rows** in the final summary report for a single input track:
 - **Row 1:** The original 7.1 Passthrough (Master).
 - **Row 2:** The new DDP 5.1 Copy (Compatibility track).

TrueHD Rules (Priority 110)

Priority	Channels	Action	Output
110	8ch (7.1)	Pass+Copy	TrueHD 7.1 kept + DDP 5.1 @ 1152k
81	6ch (5.1)	Passthrough	Original TrueHD 5.1

EAC3 / Atmos Rules

Priority	Condition	Action	Output
100	EAC3 Atmos (JOC)	Passthrough	Original EAC3 Atmos — preserves object metadata
99	EAC3 7.1	Downmix	DDP 5.1 @ 1152k
98	EAC3 5.1	Passthrough	Original EAC3 5.1
97	EAC3 2.0	Removed	Delegated to ConvertAudioEngine-Stereo

AAC Rules

Priority	Channels	Action	Output
93	7.1 (8ch)	Pass+Copy	AAC 7.1 kept + DDP 5.1 @ 1152k
91	5.1 (6ch)	Encode	DDP 5.1 @ 768k
90	2.0 (2ch)	Removed	Delegated to ConvertAudioEngine-Stereo

Malformed AAC 7ch → corrected to 6ch before rule matching.

DTS Rules

Priority	Variant	Action	Output
73	DTS-HD MA/HRA (any ch > 2)	Encode	DDP 5.1 @ 1024k
72	DTS Core (any ch > 2)	Encode	DDP 5.1 @ 768k

71	DTS-HD 2.0	Removed	Delegated to ConvertAudioEngine-Stereo
70	DTS 2.0	Removed	Delegated to ConvertAudioEngine-Stereo

PCM / FLAC Rules

Priority	Channels	Action	Output
62	7.1 (8ch)	Downmix	DDP 5.1 @ 1152k
61	5.1 (6ch)	Encode	DDP 5.1 @ 768k
60	2.0 (2ch)	Removed	Delegated to ConvertAudioEngine-Stereo

Master Codec Rules

Priority	Feature/Codec	Action	Why?
110	TrueHD 7.1	Pass+Copy	Preserves lossless master + adds compatible fallback.
100	EAC3 Atmos	Passthrough	Keeps Atmos metadata intact for object-based audio.
93	AAC 7.1	Pass+Copy	Keeps high-channel source + adds DDP 5.1 duplicate.
73	DTS-HD	Encode	Converts high-bitrate DTS to EAC3 5.1 for compatibility.
0	Commentary	Removed	Filters out unwanted 2.0 director/cast tracks to save space.

Fallback Rules

If no specific rule matches, the following logic is applied:

Channels	Fallback Action	Bitrate
2 Channels or fewer	Removed	— (delegated to ConvertAudioEngine-Stereo)
3 to 6	Encode	768k
Over 6	Downmix	1152k

7. Spatial Audio: The Pan Filter Matrix

When 7.1 audio is reduced to 5.1, standard downmixing often loses spatial detail from the side channels.

The Formula

```
aformat=channel_layouts=7.1,pan=5.1|FL=FL|FR=FR|FC=FC|LFE=LFE|BL=BL+0.707SL|BR=BR+0.707SR  
alimiter=limit=0.948:attack=5:release=50:level=disabled:latency=1
```

Layout Locking (aformat)

What: Forces the decoder to output a strict 8-channel 7.1 layout *before* the Pan Filter runs.

Why: Some codecs (TrueHD, AAC, EAC3) may decode into non-standard 7.1 variants.

Locking the layout ensures:

- SL really is the Side Left channel, BL really is the Back Left channel
- No channel swapping, No silent corruption of the downmix

The Math (0.707)

What: Applies a -3 dB coefficient to the Side Surrounds (SL/SR).

Why: Prevents the side channels from overpowering the rear soundstage and avoids digital clipping.

Limiter (0.948) — For All 7.1 Codecs

```
alimiter=limit=0.948:attack=5:release=50:level=disabled:latency=1
```

latency=1 allows the limiter a 1-sample look-ahead window to catch post-downmix peaks without adding audible delay.

Why: Any 7.1 track that is downmixed or duplicated into 5.1 can produce true-peak overshoots after decoding:

- AAC 7.1 > when creating the DDP 5.1 copy
- TrueHD 7.1 > when creating the DDP 5.1 copy
- DTS-HD MA > during 7.1 → 5.1 downmix
- PCM/FLAC > during 7.1 → 5.1 downmix
- EAC3 7.1 > during 7.1 → 5.1 downmix

Important:

- If the source audio already contains true-peak or inter-sample peaks (“clips”), these will also appear in analysis of the downmix.
- The limiter prevents new clipping during downmixing and encoding, but it does not remove overshoots inherent in the source mix.

8. Commentary Filtering

- **Only 2-channel commentary tracks** are removed to save space while preserving primary content.
- **Detection Methods:** Title matching, keyword detection, and case-insensitive search.
- **Keywords:** commentary, director, producer, writer, cast, behind, bonus, alt, interview.
- **Why 5.1 Commentary is NOT removed:**
 - It is extremely rare in retail media.
 - Hard to tell apart from "Alternate Mixes" or "Home Theater Optimized" tracks.
 - Removing it carries a high risk of "False Positives" (deleting real movie content).

9. Malformed Layout Guards

The script corrects illegal 7-channel layouts before rule matching runs:

- **AAC 7ch** → 6ch (treated as 5.1)
- **EAC3 7ch** → 6ch (treated as 5.1)
- **TrueHD 7ch** → 8ch (treated as 7.1)
- **PCM/FLAC 7ch** → 8ch (treated as 7.1)
- **AC3 7ch** → Removed (no valid AC3 7-channel layout exists)

10. Audio Processing Summary

- For Pass+Copy tracks, \ - - Copy appears as Action and output identifies it as DDP5.1 audio.

Column	Description
Index	The original stream number (e.g., 1, 2).
Codec	The source format (e.g., TrueHD, DTS).
Channels	The detected number of channels (e.g., 7.1, 5.1).
Action	Green: Passthrough / Pass, Yellow: Downmix / Copy, Blue: Encode, Red: Removed.
Output	The final codec and bitrate configuration.
Priority	The assigned priority level (0–110). Removed tracks show —.
Rule	The logical rule that was matched during processing.

Subtitles and attachments are always carried through unchanged. The script maps `-map 0:s?` (all subtitles) and `-map 0:t?` (all attachments — fonts, cover art) with stream copy. There is no toggle to disable this.

11. Re-Enabling 2.0 Encoding (Optional)

All 2.0 rules are present in the engine but set to `Action = "Removed"` by default. This is intentional — stereo output is delegated to **ConvertAudioEngine-Stereo**. If you want this script to encode 2.0 tracks instead of removing them, you can re-enable any rule by changing three fields.

Example — re-enabling AAC 2.0 at 256k:

```
# Find this block in $Rules_AAC (Rule3):
Action      = "Removed"
Bitrate     = $null
Rule        = "AAC_2.0_Removed"

# Change it to:
Action      = "Encode"
Bitrate     = "256k"
Rule        = "AAC_2.0_Encode_256k"
```

Only those three fields need to change. Nothing else in the engine requires modification.

Apply the same pattern to re-enable any other 2.0 rule:

Rule block	Location	Default	Suggested bitrate
AAC 2.0	Rule3 in \$Rules_AAC	Removed	256k
EAC3 2.0	Rule4 in \$Rules_EAC3_Atmos	Removed	384k
DTS-HD 2.0	Rule3 in \$Rules_DTS	Removed	384k
DTS 2.0	Rule4 in \$Rules_DTS	Removed	256k
PCM/FLAC 2.0	Rule3 in \$Rules_PCMFLAC	Removed	384k

12. Non-Critical FFmpeg Warnings (**Safe to Ignore**)

During processing, FFmpeg may display one or more of the following messages.

These warnings are **normal**, and do not affect audio quality, sync, or re-encode.

They come from FFmpeg's internal decoders and subtitle parsers — not from the script!

“quant_step_size larger than huff_lsbs”

- **Cause:** Printed by the TrueHD decoder during the initial probe phase.
- **Impact:** Safe to ignore. Does not affect decoding, channel layout, or the Pass+Copy path.

“Codec AVOption drc_scale ... has not been used for any stream”

- **Cause:** (`-drc_scale`) applies only to AC-3/EAC3 decoders.
FFmpeg prints this when the input track is not AC-3 (e.g., TrueHD, DTS, FLAC).
- **Impact:** Safe to ignore. The script disables DRC intentionally for consistent output.

“(Subtitle: hdmv_pgs_subtitle) unspecified size”

- **Cause:** PGS (Blu-ray) subtitles do not declare width/height in the container.
FFmpeg warns until the first subtitle packet is decoded.
- **Impact:** Safe to ignore. Subtitles are copied untouched (`-c:s copy`).

“Assuming an incorrectly encoded 7.1 channel layout...instead of 7.1(wide)”

- **Cause:** AAC has two 7.1 layouts. Most encoders use the common (non-spec) layout.
FFmpeg prints this when the file does not use the strict 7.1(wide) AAC layout.
- **Impact:** Safe to ignore. The script already corrects and pins the layout using
(`aformat=channel_layouts=7.1`)

Disclaimer

- Always test on a few files before batch-processing your library.
- Keep backups of original media.
- Results may vary depending on source quality and hardware.