Approximating Hair Scattering Function for Interactive Rendering

Pramook Khungurn

December 11, 2019

This document is written as a companion to reading "Interactive Hair Rendering under Environment Lighting" by Ren et al. [2] and "Interative Hair Rendering and Appearance Editing under Environment Lighting" by Xu et al. [3].

We focus on these two papers approximate the hair scattering function $S(\omega_i, \omega_o)$ for interactive rendering under environment lighting. We begin with a tutorial on the sphecial radial basis function, which is central to both papers.

1 Spherical Radial Basis Functions

- Let \mathbb{S}^m denote the unit sphere in \mathbb{R}^{m+1} .
- Let ω and ξ be two points on \mathbb{S}^m . We set θ be the geodesic distance between the two points. In other words, $\theta = \arccos(\omega \cdot \xi)$.
- A spherical radial basis function (SBRF) $G(\omega)$ is a function from $\mathbb{S}^m \to \mathbb{R}$ that depends only on $\omega \cdot \xi$ where ξ is a fixed point on the sphere. That is:

$$G(\omega) = G(\omega \cdot \xi) = G(\cos \theta).$$

We call ξ the center of the SRBF. When writing an SBRF, we will write $G(\omega \cdot \xi)$ instead of $G(\omega)$.

• Most of the time, SRBFs are represented in terms of expansions in Legendre polynomials:

$$G(\omega \cdot \xi) = \sum_{l=0}^{\infty} G_l P_l(\omega \cdot \xi)$$

where $P_l(x)$ is the normalized Legendre polynomial of degree l. The **Legendre coefficients** G_l satisfy the property that $G_l \ge 0$ and $\sum_{l=0}^{\infty} G_l < \infty$.

• Let G be an SRBF with center ξ_g , and H be another SBRF with center ξ_h . The convolution of G and H are given by the following equation:

$$G *_m H = \int_{\mathbb{S}^m} G(\omega \cdot \xi_g) H(\omega \cdot \xi_h) \, d\omega(\omega) = \sum_{l=0}^{\infty} G_l H_l \frac{\Omega_m}{d_{m,l}} P_l(\xi_g \cdot \xi_h).$$

Here, Ω_m is the volume of \mathbb{S}^m :

$$\Omega_m = \frac{(2\pi)^{(m+1)/2}}{\Gamma((m+1)/2)},$$

and $d_{m,l}$ i the imension of the space of the order-l spherical harmonics on \mathbb{S}^m :

$$d_{m,l} = \begin{cases} \frac{(2l+m-1)!(l+m-2)!}{l!(m-l)!}, & \text{if } l \ge 1\\ 1, & \text{if } l = 0 \end{cases}$$

- There are two examples of SBRFs.
 - The **Abel-Poisson SRBF kernel** is defined as:

$$G^{\text{Abel}}(\omega \cdot \xi; \lambda) = \frac{1 - \lambda^2}{[1 - 2\lambda(\omega \cdot \xi) + \lambda^2]^{3/2}}$$

for $0 < \lambda < 1$.

- The Gaussian SRBF kernel is defined as:

$$G^{Gau}(\omega \cdot \xi; \lambda) = e^{-\lambda} e^{\lambda(\omega \cdot \xi)}$$

for $\lambda > 0$.

In both of these functions, λ denotes the "bandwidth" parameter which controls the width of the lobes.

• Let G^{Abel} be an Abel-Poisson SBRF kernel with center ξ_g and bandwidth λ_g . Let H^{Abel} be the same with center ξ_h and λ_h . We have that

$$G^{\mathrm{Abel}} *_m H^{\mathrm{Abel}} = \frac{1 - (\lambda_g \lambda_h)^2}{[1 - 2(\lambda_g \lambda_h)(\xi_g \cdot \xi_h) + (\lambda_g \lambda_h)^2]^{3/2}}.$$

It's interesting to note that, if we view $G^{\text{Abel}} *_m H^{\text{Abel}}$ as a function of $\xi_g \cdot \xi_h$, then it is an Abel–Poisson SBRF kernel.

• Define G^{Gau} and H^{Gau} similarly as the previous item but with the Gaussian SRBF kernel. We have that:

$$G^{\text{Gau}} *_m H^{\text{Gau}} = e^{-(\lambda + \lambda_h)} \Omega_m \Gamma\left(\frac{m+1}{2}\right) I_{\frac{m-1}{2}}(\|r\|) \left(\frac{2}{\|r\|}\right)^{\frac{m-1}{2}}.$$

where $r = \lambda_g \xi_g + \lambda_h \xi_h$ and I_{ν} is the modified Bessel function of the first kind of order ν :

$$I_{\nu}(x) = \frac{(x/2)^{\nu}}{\Gamma(\nu + 1/2)\Gamma(1/2)} \int_{-1}^{1} e^{-xz} (1 - z^{2})^{\nu - 1/2} dz.$$

For the special case of m=2 (sphere in 3D), we can simplify the convolution to:

$$G^{\text{Gau}} *_2 H^{\text{Gau}} = 4\pi \frac{\sinh(\|r\|)}{\|r\|}.$$

• Given a spherical function $F(\omega)$, its **SRBF kernel expansion** is basically an approximation of F as a linear combination of a finite number of SRBF kernels:

$$F(\omega) \approx \sum_{k=1}^{n} F_k G(\omega \cdot \xi_k; \lambda_k).$$

If the centers $\xi_1, \xi_2, \dots, \xi_n$ and bandwidths $\lambda_1, \lambda_2, \dots, \lambda_n$ are given, the coefficient F_1, F_2, \dots, F_n can be obtained by least squares.

2 Ren et al. [2]

• Following [1], the outgoing curve intensity can be written as:

$$\overline{L}(\omega_o) = D \int_{\mathbb{S}^2} L(\omega_i) T(\omega_i) S(\omega_i, \omega_o) \cos \theta_i \, d\omega_i$$

where

- D is the diameter of the hair fiber,
- $L(\omega_i)$ is the incoming radiance,
- $-T(\omega_i)$ is the transmittance in the incident direction generated by the hair volume:

$$T(\omega_i) = T(x, \omega_i) = \exp\left(-\sigma_a \int_x^\infty \rho(x') dx'\right)$$

where $\rho(x)$ is the density function at x, and

 $-S(\omega_i,\omega_o)$ is the bidirectional curve radiance distribution function.

Note that the positional dependence of each term is omitted for brevity.

- It's important to distinguish between curved intensity $\overline{L}(\omega)$ and radiance $L(\omega)$. Curved intensity is energy per unit length of the fiber along a direction, but radiance is energy per unit area of the fiber's surface along a direction.
- In a physically based renderer, we are concerned with radiance, not curved intensity. The formula that relates outgoing radiance to incoming radiance is:

$$L(\omega_o) = \int_{\mathbb{S}^2} L(\omega_i) T(\omega_i) S(\omega_i, \omega_o) \cos \theta_i \, d\omega_i.$$

Notice that there is no D here.

 The environment light is approximate as a linear combination of a finite number of Gaussian SRBF kernels:

$$L(\omega_i) \approx \sum_{j=1}^{N} L_j G(\omega_i \cdot \xi_j; \lambda_j).$$

Using $G_i(\omega_i)$ to denote $G(\omega_i \cdot \xi_i; \lambda_i)$, this means that the outgoing curve intensity is given by:

$$\overline{L}(\omega_i) \approx D \sum_{j=1}^{N} L_j \int_{\mathbb{S}^2} G_j(\omega_i) T(\omega_i) S(\omega_i, \omega_o) \cos \theta_i \, d\omega_i$$

 \bullet The transmittance term is also factored out as the effective transmittance \widetilde{T} :

$$\overline{L}(\omega_o) \approx D \sum_{j=1}^{N} L_j \widetilde{T}(\xi_j, \lambda_j) \int_{\mathbb{S}^2} G_j(\omega_i) S(\omega_i, \omega_o) \cos \theta_i \, d\omega_i.$$

where

$$\widetilde{T}(\xi_j, \lambda_j) = \frac{\int_{\mathbb{S}^2} G_j(\omega_i) T(\omega_i) S(\omega_i, \omega_o) \cos \theta_i \ \mathrm{d}\omega_i}{\int_{\mathbb{S}^2} G_j(\omega_i) S(\omega_i, \omega_o) \cos \theta_i \ \mathrm{d}\omega_i}.$$

- The effective transmittance depends on the position x and is approximated exponentiating the optical depth at x averaged over the directions covered by the SRBF light. We will not cover the details in this document.
- Note that after factoring out the effective transmittance, the term

$$I(\omega_o; \xi, \lambda) = \int_{\mathbb{S}^2} G(\omega_i \cdot \xi; \lambda) S(\omega_i, \omega_o) \cos \theta_i \, d\omega_i,$$

which the paper calls the *convolution term*, is independent of the hair geometry. The paper precomputes this term for a set of ω_o , ξ , and λ parameters and stores the results in a table for run-time lookup.

• If we use the Marschner model (or any other scattering model with circular cross section), then the above table is a 4D table $\mathbf{I}_{M}(\cos\theta_{\xi},\cos\theta_{o},\cos(\phi_{\xi}-\phi_{o}),1/\lambda)$.

Ren et al. chooses to use $1/\lambda$ instead of λ because it is proportional to the width of the SRBF. The cosines are used to avoid the computation of inverse trigonometric functions.

3 Xu et al. [3]

- The paper approximates the Marschner model with SRBF kernels.
- We will not give a complete formulation of the Marschner model here. Please refer to the Marschner model note written earlier.
- As a matter of notational different, the original Marschner paper uses p to denote a scattering mode. However, the Xu paper uses the variable t. Therefore, the scattering function for Mode t is denoted by $S_t(\omega_i, \omega_o)$.
- The paper also changes the definition of the Gaussian SRBF a little. It defines:

$$G(\omega_i \cdot \xi_i; \lambda_i) = e^{-2(\omega_i \cdot \xi_j - 1)/\lambda_j^2}$$
.

It does this to be consistent with the 1D Gaussian:

$$g^{u}(x;\mu,\lambda) = \frac{1}{\sqrt{\pi}\lambda}e^{-(x-\mu)^{2}/\lambda^{2}}.$$

• Define $\mathcal{M}_t(\xi_j, \lambda_j)$ to be the result of convolving $S_t(\omega_i, \omega_o)$ with $G_j(\omega_i) = G(\omega_i \cdot \xi_j; \lambda_j)$:

$$\mathcal{M}_t(\xi_j, \lambda_j) = \int_{\mathbb{S}^2} G_j(\omega_i) S_t(\omega_i, \omega_o) \cos \theta_i \, d\omega_i$$
$$= \int_{\mathbb{S}^2} G_j(\omega_i) M_t(\theta_h) N_t(\theta_d, \phi) \cos \theta_i / \cos^2 \theta_d \, d\omega_i$$

where $\theta_h = (\theta_i + \theta_o)/2$, and $\theta_d = ||\theta_i - \theta_o||/2$, and $\phi = \phi_o - \phi_i$.

• We write ω_i and ξ_j in Cartesian coordinates:

$$\omega_i = (\sin \theta_i, \cos \theta_i \cos \phi_i, \cos \theta_i \sin \phi_i)$$

$$\xi_i = (\sin \theta_i, \cos \theta_i \cos \phi_i, \cos \theta_i \sin \phi_i).$$

Their dot product minus one is given by:

$$\omega_i \cdot \xi_j - 1 = [\cos(\theta_i - \theta_j) - 1] + \cos\theta_i \cos\theta_j [\cos(\phi_i - \phi_j) - 1].$$

Hence,

$$\begin{split} G(\omega_i \cdot \xi_j; \lambda_j) &= e^{-2([\cos(\theta_i - \theta_j) - 1] + \cos\theta_i \cos\theta_j [\cos(\phi_i - \phi_j) - 1])/\lambda_j^2} \\ &= e^{-2[\cos(\theta_i - \theta_j) - 1]/\lambda_j^2} e^{-2\cos\theta_i \cos\theta_j [\cos(\phi_i - \phi_j) - 1]/\lambda_j^2} \\ &= g^c(\theta_i; \theta_j, \lambda_j) g^c(\phi_i; \phi_j, \lambda_i / \sqrt{\cos\theta_i \cos\theta_j}) \end{split}$$

where $q^c(x; \mu, \lambda) = e^{2[\cos(x-\mu)-1]/\lambda^2}$. To make the notation even shorter, let

$$g_j^c(\theta_i) = g^c(\theta_i; \theta_j, \lambda_j), \text{ and}$$

 $g_i^c(\phi_i) = g^c(\phi_i; \phi_j, \lambda_j / \sqrt{\cos \theta_i \cos \theta_j}),$

so that we can write $G_i(\omega_i) = g_i^c(\theta_i)g_i^c(\phi_i)$.

• Now that we have factored the SRBF, we can write:

$$\mathcal{M}_{t}(\xi_{j}, \lambda_{j}) = \int_{-\pi/2}^{\pi/2} \int_{0}^{2\pi} g_{j}^{c}(\theta_{i}) g_{j}^{c}(\phi_{i}) M_{t}(\theta_{h}) N_{t}(\theta_{d}, \phi) \frac{\cos^{2} \theta_{i}}{\cos^{2} \theta_{d}} d\phi_{i} d\theta_{i}$$
$$= \int_{-\pi/2}^{\pi/2} g_{j}^{c}(\theta_{i}) M_{t}(\theta_{h}) \frac{\cos^{2} \theta_{i}}{\cos^{2} \theta_{d}} \left(\int_{0}^{2\pi} g_{j}^{c}(\phi_{i}) N_{t}(\theta_{d}, \phi) d\phi_{i} \right) d\theta_{i}.$$

• Now consider the azimuthal integral:

$$\int_0^{2\pi} g_j^c(\phi_i) N_t(\theta_d, \phi) \, d\phi_i = \int_0^{2\pi} g^c(\phi_i; \phi_j, \lambda_j / \sqrt{\cos \theta_i \cos \theta_j}) N_t(\theta_d, \phi_o - \phi_i) \, d\phi_i.$$

Let $\phi_i' = \phi_i - \phi_j$ and $\lambda_j' = \lambda_j / \sqrt{\cos \theta_i \cos \theta_j}$. We can write the above integral in terms of ϕ_i' :

$$\int_0^{2\pi} g^c(\phi_i; \phi_j, \lambda'_j) N_t(\theta_d, \phi_o - \phi_i) \, d\phi_i = \int_0^{2\pi} g^c(\phi'_i; 0, \lambda'_j) N_t(\theta_d, (\phi_o - \phi_j) - \phi'_i) \, d\phi'_i.$$

We shall abbreviate the RHS as $\mathcal{N}_t(\lambda'_j, \phi_o - \phi_j, \theta_d)$.

• Now make the following approximations:

$$g_i^c(\theta_i) \approx e^{-(\theta_i - \theta_j)^2/\lambda_j} = g(\theta_i; \theta_j, \lambda_j) = g_j(\theta_i).$$

Therefore,

$$\mathcal{M}_t(\xi_j, \lambda_j) = \int_{-\pi/2}^{\pi/2} g_j(\theta_i) M_t(\theta_h) \frac{\cos^2 \theta_i}{\cos^2 \theta_d} \mathcal{N}_t(\lambda_j', \phi_o - \phi_j, \theta_d) d\theta_i$$

That task now is to evaluate the inner integral \mathcal{N}_t and the outer integral \mathcal{M}_t for each of the three modes.

3.1 Approximating the R Mode

• For the R mode, we have

$$N_R(\eta, \theta_d, \phi) = \frac{1}{4} |\cos(\phi/2)| F(\eta, \theta_d, -\sin(\phi/2))$$

were $F(\eta, \theta_d, h)$ is the Fresnel reflectance.

• We approximate the Fresnel term with Schlick's approximation:

$$F(\eta, \theta_d, h) \approx F_0 + (1 - F_0)(1 - \cos \theta_d \sqrt{1 - h^2})^5$$

where $F_0 = (1 - \eta)^2 / (1 + \eta)^2$.

• Substituting $h = -\sin(\phi/2)$, we have

$$F(\eta, \theta_d, -\sin(\phi/2)) \approx F_0 + (1 - F_0)(1 - \cos\theta_d \sqrt{1 - \sin^2(\phi/2)})^5$$
$$= F_0 + (1 - F_0)(1 - \cos\theta_d |\cos(\phi/2)|)^5.$$

Now, N_R becomes a polynomial of $|\cos(\phi/2)|$ of degree 6. Let us write:

$$N_R(\eta, \theta_d, \phi) \approx \sum_{k=0}^{6} C_k(\theta_d, \eta) |\cos^k(\phi/2)|.$$

• As such, the inner integral can be approximate as:

$$\mathcal{N}_{R}(\lambda'_{j}, \phi_{o} - \phi_{j}, \theta_{d}) = \sum_{k=0}^{6} C_{k}(\theta_{d}, \eta) \int_{0}^{2\pi} \left| \cos^{k} \left(\frac{\phi_{o} - \phi_{j} - \phi'_{i}}{2} \right) \right| g^{c}(\phi'_{i}; 0, \lambda'_{j}) d\phi'_{i}$$

$$= \sum_{k=0}^{6} C_{k}(\theta_{d}, \eta) C_{k}(\lambda'_{j}, \phi_{o} - \phi_{j})$$

where $C_k(\lambda'_j, \phi_o - \phi_j)$ stands for the integral in the RHS. The paper precomputes this for various values of λ'_i and $\phi_o - \phi_j$ and look up its value in run time.

• Now, we need to figure out the outer integral $\mathcal{M}_R(\xi_j,\lambda_j)$. Consider the term $M_R(\theta_h)$. We have that

$$M_R(\theta_h) = g^u(\theta_h; \alpha_R, \beta_R) = 2g^u(\theta_i; 2\alpha_R - \theta_o, 2\beta_R).$$

Therefore, the term $g_j(\theta_i)M_R(\theta_h)$ is a product of two 1D Gaussians, which means that it is also a Gaussian. Hence, $\mathcal{M}_R(\xi_j, \lambda_j)$ is an integral of a product of the function $\frac{\cos^2 \theta_i}{\cos^2 \theta_d} \mathcal{N}_t(\lambda'_j, \phi_o - \phi_j, \theta_d)$ with a Gaussian. The paper estimates this product integral with a numerical quadrature procedure that we will detail in the next section.

3.2 Approximate Product Integral with 1D Gaussian

• Given a Guassian $g(x;\mu,\lambda)$ and an arbitrary function f(x), we would like to approximate the integral

$$\int_{r_0}^{r_1} g(x; \mu, \lambda) f(x) \, \mathrm{d}x,$$

which generally has no analytic solution.

- We assume that f(x) is smooth and approximate it as being piecewise linear. To do so:
 - We take m+1 samples $r_0 = x_0 < x_1 < x_2 < \ldots < x_m = r_1$ from the interval $[r_0, r_1]$.
 - We approximate f(x) on the interval $[x_s, x_{s_1}]$ as $f(x) \approx b_s x + c_s$. Here, b_s and c_s are linear coefficients computed from $f(x_s)$ and $f(x_{s+1})$.
- The product integral becomes:

$$\sum_{s=0}^{m-1} \int_{x_s}^{x_{s+1}} g(x; \mu, \lambda) (b_s x + c_s) \, dx$$

which can be computed analytically because the product of a Gaussian with a linear function has an analytic solution involving the error function. (See the supplement material of the paper for details.)

- To compute $\mathcal{M}_t(\xi_j, \lambda_j)$ is to compute the product integral over the interval $[-\pi/2, \pi/2]$. The paper picks m+1 samples by:
 - Pick the two end points $-\pi/2$ and $\pi/2$.
 - Pick m-1 samples uniformly from the interval $[u-(m-2)\lambda/2, \mu+(m-2)\lambda/2]$.

The paper found that using m = 4 is enough.

3.3 Approximating the TT Mode

 \bullet For the TT mode, we have that

$$N_{TT}(\eta, \theta_d, \sigma_a, \phi) = \frac{1}{2} \left| \frac{\mathrm{d}\phi}{\mathrm{d}h} \right|^{-1} (1 - F(\eta, \theta_d, h))^2 T(\sigma_a, \theta_d, h).$$

• The paper approximates the above function by a single circular Gaussian centered at $\phi = \pi$ (apparently because the TT mode is forward scattering):

$$N_{TT}(\eta, \theta_d, \sigma_a, \phi) \approx b_{TT}(\eta, \sigma_d, \sigma_a) g^c(\phi; \pi, \lambda_{TT}(\eta, \theta_d, \sigma_a))$$

where $b_T T$ and $\lambda_T T$ denote the scaling factor and the width of the Gaussian. Both depends on η , θ_d , and σ_a .

- b_{TT} is set to be the value of N_{TT} at $\phi = \pi$.
- $\lambda_T T$ is defined as:

$$\lambda_{TT}(\eta, \theta_d, \sigma_a) = \frac{1}{\sqrt{\pi}b_{TT}(\eta, \theta_d, \sigma_a)} \int_{-\pi}^{\pi} N_{TT}(\eta, \theta_d, \sigma_a, \phi) d\phi.$$

Thus, our task comes down to approximating the integral of N_{TT} over $[-\pi, \pi]$.

• To approximate the integral, we first approximate the transmittance function $T(\sigma_a, \theta_d, h)$ with a fourth order Taylor expansion:

$$T(\sigma_a, \theta_d, h) \approx \sum_{k \in \{0, 2, 4\}} a_k(\theta_d, \sigma_a) h^k$$

where $a_k(\theta_d, \sigma_a)$ is a Taylor expansion coefficient which has an analytic expression.

• Now, we have that

$$\int_{-\pi}^{\pi} N_{TT}(\eta, \theta_d, \sigma_a, \phi) d\phi = \int_{-\pi}^{\pi} \frac{1}{2} \left| \frac{d\phi}{dh} \right|^{-1} (1 - F(\eta, \theta_d, h))^2 T(\sigma_a, \theta_d, h) d\phi$$

$$= \frac{1}{2} \int_{-1}^{1} (1 - F(\eta, \theta_d, h))^2 T(\sigma_a, \theta_d, h) dh$$

$$\approx \frac{1}{2} \int_{-1}^{1} (1 - F(\eta, \theta_d, h))^2 \left(\sum_{k \in \{0, 2, 4\}} a_k(\theta_d, \sigma_a) h^k \right) dh$$

$$= \frac{1}{2} \sum_{k \in \{0, 2, 4\}} a_k(\theta_d, \sigma_a) \left(\int_{-1}^{1} (1 - F(\eta, \theta_d, h))^2 h^k dh \right).$$

Let us the denote the integral $\int_{-1}^{1} (1 - F(\eta, \theta_d, h))^2 h^k dh$ as $\mathcal{K}_k^{TT}(\eta, \theta_d)$. The paper precomputes these integrals for various values of η and θ_d and stores the results in a 2D table for run-time lookups.

• Now that we have approximated N_{TT} , our next task is to evaluate the integral

$$\mathcal{N}_{TT}(\lambda_j', \phi_o - \phi_j, \theta_d) = \int_0^{2\pi} g^c(\phi_i'; 0, \lambda_j') N_{TT}(\theta_d, (\phi_o - \phi_j) - \phi_i') d\phi_i'.$$

Note that we have approximated N_{TT} as a circular Gaussian, we have that the integrand is a product of two circular Gaussians, which is still a circular Gaussian. The integral has an analytic solution which can be easily computed.

• The outer integral \mathcal{M}_{TT} is a product integral between a Gaussian and the function $\mathcal{N}_{TT}\cos^2\theta_i/\cos^2\theta_d$, which is smooth. We evaluate this integral the same way we evaluated the integral for the R mode.

3.4 Approximating the TRT Mode

- In the Marschner model, the TRT has two types of behavior. When $\eta' < 2$, the azimuthal scattering function has two peaks. When $\eta' \geq 2$, it has no peaks.
- When $\eta' < 2$, Xu et al. approximates the azimuthal scattering function as the sum of three Gaussians:

$$N_{TRT} \approx b_1(g^c(\phi; \phi^*, w_c) + g^c(\phi; -\phi^*, w_c)) + b_2g^c(\phi; 0, \phi^*).$$

where ϕ^* is the peak location which is given by:

$$\phi^* = \phi(h^*) = \phi\left(\sqrt{\frac{4 - {\eta'}^2}{3}}\right),$$

and w_c is the width of the peak, which the user sets.

• The coefficient b_2 is set to:

$$b_2 = (1 - g^c(0; \phi^*, w_c))^2 N_{TRT}(0).$$

• The coefficient b_1 is set to:

$$b_1 = \frac{\int_{-\pi}^{\pi} N_{TRT}(\phi) \, d\phi - \int_{-\pi}^{\pi} b_2 g^c(\phi) \, d\phi}{2 \int_{-\pi}^{\pi} g^c(\phi; \phi^2, w_c) \, d\phi} = \frac{\int_{-\pi}^{\pi} N_{TRT}(\phi) \, d\phi - b_2 \sqrt{\pi} \phi^*}{2\sqrt{\pi} w_c}.$$

• To approximate the $\int_{-\pi}^{\pi} N_{TRT} d\phi$ term, we use the same technique used to apprixmate $\int_{-\pi}^{\pi} N_{TT} d\phi$. First, we write:

$$\int_{-\pi}^{\pi} N_{TRT}(\phi) d\phi = \frac{1}{2} \int_{-1}^{1} (1 - F(\eta, \theta_d, h))^2 F(\eta, \theta_d, h) T^2(\sigma_a, \theta_d, h) dh$$

Then, we approximate

$$T^2(\sigma_a, \theta_d, h) \approx \sum_{k \in \{0, 2, 4\}} c_k(\theta_d, \sigma_a) h^k$$

where each $c_k(\theta_d, \sigma_a)$ is a Taylor series expansion coefficient that has analytic expressions.

Thus, we have that

$$\int_{-\pi}^{\pi} N_{TRT}(\phi) \, d\phi \approx \frac{1}{2} \sum_{k \in \{0,2,4\}} c_k(\theta_d, \sigma_a) \left(\int_{-1}^{1} (1 - F(\eta, \theta_d, h))^2 F(\eta, \theta_d, h) h^k \, dh \right)$$

Let $\mathcal{K}^{TRT}(\eta, \theta_d)$ denote the integral $\int_{-1}^{1} (1 - F(\eta, \theta_d, h))^2 F(\eta, \theta_d, h) h^k dh$. We precompute a table of $\mathcal{K}^{TRT}(\eta, \theta_d)$ for real-time lookups.

• When $\eta' \geq 2$, N_{TRT} is approximated using a single Guassian:

$$N_{TRT} \approx b_3 g^c(\phi; 0, \lambda_3).$$

The coefficient b_3 is set to the value of N_{TRT} at $\phi = 0$, and λ_3 is determined by trying to preserve the energy just like in the TT mode case:

$$\lambda_3 = \frac{1}{\sqrt{\pi}b_3} \int_{-\pi}^{\pi} N_{TRT}(\phi) \, d\phi.$$

• The approximation of N_{TRT} when $\eta' \geq 2$ might lead to discontinuity when η' changes across 2. This is a problem because, when $\eta' < 2$, the center Gaussian bandwidth is w_c . However, when $\eta' \geq 2$, when Gaussian bandwidth is λ_3 .

Xu et al. interpolates the bandwidth of the center Gaussian between w_c and λ_3 over a small range of $\Delta \eta'$:

$$\lambda_3' = \text{interp}(w_c, \lambda_3, \text{smoothstep}(2, 2 + \Delta \eta', \eta')).$$

The coefficient b' is modified to $b_3\lambda_3/\lambda_3'$ to preserve the energy of the lobe.

• The outer integral \mathcal{M}_{TRT} is approximate using linear quadrature as was done in the TT mode.

3.5 Handling Eccentricity in the TRT Mode

• Marschner proposed using varying refraction index η^* that depends on the azimuthal half angle ϕ_h to simulate hair eccentricity:

$$\eta_1^* = 2(\eta - 1)a^2 - \eta + 2$$

$$\eta_2^* = 2(\eta - 1)a^{-2} - \eta + 2$$

$$\eta^*(\phi_h) = ((\eta_1^* + \eta_2^*) + \cos(2\phi_h)(\eta_1^* - \eta_2^*))/2$$

where a is the eccentricity parameter.

• To incorporate eccentricity, the inner integral \mathcal{N}_{TRT} is changed to:

$$\mathcal{N}_{TRT} = \int g^c(\phi_i'; 0, \lambda_j') N_{TRT}(\eta^*(\phi_h), \theta_d, \phi_o - \phi_j - \phi_i') \, d\phi_i'$$

$$\approx \int g^c(\phi_i'; 0, \lambda_j') N_{TRT}(\overline{\eta^*}, \theta_d, \phi_o - \phi_j - \phi_i') \, d\phi_i'$$

where

$$\overline{\eta^*} = \frac{\int g^c(\phi_i'; 0, \lambda_j) \eta^*(\phi_h) \, d\phi_i'}{\int g^c(\phi_i'; 0, \lambda_i) \, d\phi_i'}.$$

The average index of refraction $\overline{\eta}^*$ can be efficiently computed on the fly by reusing the precomputed $C_k(\lambda'_j, \phi_o - \phi_j)$. This because we have that $\cos(2\phi_h) = 2\cos^2(\phi_h) - 1 = 2\cos^2((\phi'_i - \phi_j + \phi_o)/2) - 1$, which means we only need C_0 and C_2 .

References

- [1] Stephen R. Marschner, Henrik Wann Jensen, Mike Cammarano, Steve Worley, and Pat Hanrahan. Light scattering from human hair fibers. In *ACM SIGGRAPH 2003 Papers*, SIGGRAPH '03, pages 780–791, New York, NY, USA, 2003. ACM.
- [2] Zhong Ren, Kun Zhou, Tengfei Li, Wei Hua, and Baining Guo. Interactive hair rendering under environment lighting. In *ACM SIGGRAPH 2010 papers*, SIGGRAPH '10, pages 55:1–55:8, New York, NY, USA, 2010. ACM.
- [3] Kun Xu, Li-Qian Ma, Bo Ren, Rui Wang, and Shi-Min Hu. Interactive hair rendering and appearance editing under environment lighting. In *Proceedings of the 2011 SIGGRAPH Asia Conference*, SA '11, pages 173:1–173:10, New York, NY, USA, 2011. ACM.