

C++ Course

Materials for Students

Paweł Kisielewicz pkisiel@gmail.com

Krakow, 19 June 2026

Contents

1	Introduction	4
2	English Version Plan	5
2.1	Goal	5
2.2	Learning Path	5
2.3	Translation Batches	5
2.3.1	Batch 1	5
2.3.2	Batch 2	5
2.3.3	Batch 3	5
2.3.4	Batch 4	6
2.3.5	Batch 5	6
2.3.6	Batch 6	6
2.4	Editorial Rules	6
2.5	YouTube Support	6
2.6	First Downloadable English Draft	6
3	00 - Start	8
3.1	Learning Goals	8
3.2	What You Need	8
3.3	First Compiler Check	8
3.4	First Program	8
3.5	Editor	9
3.6	Git Basics	9
3.7	CMake in One Sentence	9
3.8	Student Checklist	9
3.9	Next Step	9
4	01 - C++ Basics	10
4.1	Learning Goals	10
4.2	Minimal Program Structure	10
4.3	Output	10
4.4	Input	11
4.5	Basic Types	11
4.6	Simple Calculation	11
4.7	Formatting Output	12
4.8	Common Mistakes	12
4.9	Practice Tasks	12
4.10	Student Checklist	12
4.11	Next Step	13
5	02 - Control Flow and Loops	14
5.1	Learning Goals	14
5.2	Conditions	14
5.3	Multiple Conditions	15
5.4	<code>switch</code>	15
5.5	<code>for</code> Loop	16

5.6	<code>while</code> Loop	16
5.7	<code>do while</code> Loop	16
5.8	<code>break</code> and <code>continue</code>	17
5.9	Common Mistakes	17
5.10	Bridge Exercise: Minimum, Maximum, and Average	17
	5.10.1 Requirements	17
	5.10.2 Suggested Work Plan	18
	5.10.3 Check Scenarios	18
5.11	Practice Tasks	18
5.12	Student Checklist	18
6	03 - Functions, Arrays, and Strings	19
6.1	Learning Goals	19
6.2	Why Functions Matter	19
6.3	Declaration and Definition	19
6.4	Parameters and Return Values	20
6.5	Local Variables and Scope	20
6.6	One-Dimensional Arrays	20
6.7	Array Minimum and Maximum	20
6.8	Two-Dimensional Arrays	21
6.9	Strings	21
6.10	Reading a Full Line	21
6.11	Bridge Exercise: GADERYPOLUKI Cipher	22
6.12	Required Function	22
6.13	Suggested Work Plan	22
6.14	Check Scenarios	22
6.15	Extra Tasks	23
6.16	Common Mistakes	23
6.17	Practice Tasks	23
6.18	Student Checklist	23
7	04 - Pointers, References, and Memory	24
7.1	Learning Goals	24
7.2	Value and Address	24
7.3	Pointers	24
7.4	<code>nullptr</code>	25
7.5	References	25
7.6	Pointer or Reference	25
7.7	Passing to Functions	25
7.8	<code>const</code> References	26
7.9	Arrays and Pointers	26
7.10	Memory Safety Rules	26
7.11	Practice Tasks	27
7.12	Checklist	27
8	05 - Files and Exceptions	28
8.1	Learning Goals	28
8.2	Writing a Text File	28
8.3	Appending Data	28
8.4	Reading a Text File	29
8.5	Reading Numbers with Validation	29
8.6	Simple Configuration Format	30
8.7	Exceptions	30
8.8	Error-Handling Strategy	30
8.9	Bridge Exercise: File Menu	30
8.10	Practice Tasks	31
8.11	Checklist	31
9	06 - Object-Oriented Programming	32

9.1	Learning Goals	32
9.2	Classes and Objects	32
9.3	Encapsulation	33
9.4	Constructors	33
9.5	<code>const</code> Methods and <code>this</code>	33
9.6	Inheritance	34
9.7	Virtual Methods and Polymorphism	34
9.8	Why the Virtual Destructor Matters	35
9.9	Operator Overloading	35
9.10	Bridge Exercise: Shapes and Polymorphism	36
9.11	Checklist	36
10	07 - STL and Data Structures	37
10.1	Learning Goals	37
10.2	Why STL Matters	37
10.3	<code>std::vector</code>	37
10.4	Vector of Records	38
10.5	Sorting	38
10.6	Searching with <code>std::find_if</code>	39
10.7	<code>std::map</code>	39
10.8	Stack, Queue, and List	40
10.9	Choosing a Container	40
10.10	Mini Project: HRMS	40
10.11	Practice Tasks	41
10.12	Checklist	41
11	08 - Project Structure, Build, and Tests	42
11.1	Learning Goals	42
11.2	From One File to Several Files	42
11.3	Headers and Source Files	42
11.4	Include Guards	43
11.5	Compiling Multiple Files	43
11.6	Build Script	43
11.7	Syntax Checks	44
11.8	Simple Tests Without a Framework	44
11.9	Basic CI/CD Idea	44
11.10	Bridge Exercise: RPN Calculator	45
11.11	Practice Tasks	46
11.12	Checklist	46

Chapter 1

Introduction

- Author: Paweł Kisielewicz <pkisiel@gmail.com>
- Place and date: Krakow, 19 June 2026
- Version: 0.6.0-en

This ebook is the first English draft based on the Polish C++ learning materials. The Polish version remains the source of truth for now. The English version starts with the course structure, learning path, and translation plan.

The full course is organized from environment setup and C++ basics to functions, arrays, strings, files, exceptions, object-oriented programming, STL, build systems, testing, and final projects.

Chapter 2

English Version Plan

2.1 Goal

The English edition should become a downloadable version of the C++ course for students who want to learn from the same material as the Polish course.

The first release should focus on readability and navigation. The code examples can stay close to the Polish repository at the beginning, while explanations, chapter introductions, exercises, and project descriptions are translated in batches.

2.2 Learning Path

1. `00-start` - development environment, compiler, editor, Git, and CMake.
2. `01-basics` - first program, input/output, types, variables, and operators.
3. `02-control-flow-loops` - conditions, `switch`, loops, `break`, `continue`.
4. `03-functions-arrays-strings` - functions, arrays, matrices, and strings.
5. `04-pointers-references-memory` - addresses, pointers, references, and safe memory habits.
6. `05-files-exceptions` - text files, validation, and exceptions.
7. `06-oop` - classes, objects, constructors, encapsulation, inheritance, and operators.
8. `07-stl-data-structures` - STL containers, algorithms, maps, stacks, queues, and lists.
9. `08-project-build-tests` - multi-file projects, build scripts, tests, and CI.
10. `09-modern-cpp` - selected modern C++ features, lambdas, move semantics, namespaces, and threads.
11. `10-projects` - final project topics, grading checklists, and project planning.

2.3 Translation Batches

2.3.1 Batch 1

- Main repository introduction - draft added.
- Ebook front matter - draft added.
- `00-start` - first English chapter added.
- `01-basics` - first English chapter added.

2.3.2 Batch 2

- `02-control-flow-loops` - first English chapter added.
- Bridge exercise: minimum, maximum, and average - included in the chapter.

2.3.3 Batch 3

- `03-functions-arrays-strings` - first English chapter added.
- Bridge exercise: GADERYPOLUKI cipher - included in the chapter.

2.3.4 Batch 4

- 04-pointers-references-memory - first English chapter added.
- 05-files-exceptions - first English chapter added.
- 06-oop - first English chapter added.
- Bridge exercise: figures and polymorphism - included in the chapter.

2.3.5 Batch 5

- 07-stl-data-structures - first English chapter added.
- 08-project-build-tests - first English chapter added.
- Bridge exercise: RPN calculator - included in the chapter.

2.3.6 Batch 6

- 09-modern-cpp.
- 10-projects.
- Project checklist and grading card.

2.4 Editorial Rules

- Keep the English text simple and practical.
- Do not translate code identifiers unless the example itself is rewritten.
- Prefer short paragraphs and clear section titles.
- Keep exercises close to the Polish version, but adjust wording for an English-speaking student.
- Do not include archive materials in the ebook.
- Keep the Polish and English ebook versions buildable by the same script.

2.5 YouTube Support

The first bilingual video format should be short quizzes:

- Polish question first.
- English question second.
- One C++ concept per video.
- Link to the repository and both ebook downloads in the description.

Example:

C++ Quiz #1

What will this program print?

```
int x = 5;
std::cout << x++ << " " << x;
```

- A) 5 5
- B) 5 6
- C) 6 6

Answer: B) 5 6, because postfix `x++` returns the current value first and increments the variable afterwards.

2.6 First Downloadable English Draft

The first downloadable English file should be marked clearly as a draft:

- title: C++ Course
- version: 0.1.0-en
- scope: plan, learning path, and translation roadmap
- output files:

- `ebook/download/cpp-course-en.pdf`
- `ebook/download/cpp-course-en.epub`

Chapter 3

00 - Start

This chapter prepares the technical environment for learning C++. It is meant for students who are starting with a compiler, code editor, terminal, Git, and simple project structure.

3.1 Learning Goals

After this chapter you should be able to:

- explain what a C++ compiler does,
- compile and run a simple `.cpp` file,
- use a terminal for basic commands,
- open and edit source files in Visual Studio Code or another editor,
- understand why Git is useful during programming exercises,
- understand the role of `CMakeLists.txt` in larger projects,
- move safely to the first C++ programming chapter.

3.2 What You Need

You need:

- a C++ compiler with C++17 support,
- a text editor or IDE,
- a terminal,
- Git,
- access to this repository.

On macOS and Linux, the compiler is often available as `c++`, `clang++`, or `g++`. On Windows, students usually use MSYS2, Visual Studio Build Tools, or an IDE configured by the teacher.

3.3 First Compiler Check

Open a terminal and run:

```
c++ --version
```

If the command prints compiler information, you can continue. If it says that the command is missing, install a compiler before moving forward.

3.4 First Program

Create a file named `hello.cpp`:

```
#include <iostream>
```

```
int main() {
    std::cout << "Hello, C++!" << std::endl;
    return 0;
}
```

Compile it:

```
c++ -std=c++17 -Wall -Wextra -pedantic hello.cpp -o hello
```

Run it:

```
./hello
```

Expected output:

```
Hello, C++!
```

3.5 Editor

Use an editor that lets you:

- open folders,
- edit `.cpp` files,
- open an integrated terminal,
- see compiler errors clearly.

Visual Studio Code is a practical default for beginners, but the course does not depend on one specific editor.

3.6 Git Basics

Git helps you save progress and review changes. For this course, the most important commands are:

```
git status
git add file.cpp
git commit -m "Describe the change"
```

At the beginning, treat Git as a history of your learning steps. Commit small, working changes.

3.7 CMake in One Sentence

CMake is a build configuration tool. In small exercises you can compile one file manually. In larger projects, CMake or a build script describes how many source files should be compiled together.

3.8 Student Checklist

Before going to the next chapter, make sure you can:

- open a terminal,
- check the compiler version,
- compile `hello.cpp`,
- run the generated program,
- explain what source file and executable mean,
- check Git status in a repository.

3.9 Next Step

Go to chapter 01 - Basics and write your first simple console programs.

Chapter 4

01 - C++ Basics

This chapter is the first programming block of the course. It introduces the structure of a C++ program, input and output, basic data types, variables, operators, and simple console tasks.

4.1 Learning Goals

After this chapter you should be able to:

- describe the role of an algorithm, a program, and the `main` function,
- write, compile, and run a simple C++ program,
- use `std::cout`, `std::cin`, and `std::getline`,
- choose basic data types for a simple problem,
- declare and initialize variables,
- perform simple calculations,
- format basic text output,
- solve small console exercises.

4.2 Minimal Program Structure

Most beginner programs in this course start like this:

```
#include <iostream>

int main() {
    std::cout << "Hello" << std::endl;
    return 0;
}
```

Important parts:

- `#include <iostream>` makes console input/output available,
- `int main()` is the starting point of the program,
- statements inside `{ }` are executed in order,
- `return 0;` means the program finished successfully.

4.3 Output

Use `std::cout` to print text:

```
#include <iostream>

int main() {
    std::cout << "C++ basics" << std::endl;
}
```

```
    std::cout << "Second line" << std::endl;
}
```

`std::endl` ends the current line.

4.4 Input

Use `std::cin` to read a value:

```
#include <iostream>
#include <string>

int main() {
    std::string name;

    std::cout << "Your name: ";
    std::cin >> name;

    std::cout << "Hello, " << name << "!" << std::endl;
}
```

Use `std::getline` when you want to read a full line with spaces:

```
#include <iostream>
#include <string>

int main() {
    std::string fullName;

    std::cout << "Full name: ";
    std::getline(std::cin, fullName);

    std::cout << "Hello, " << fullName << "!" << std::endl;
}
```

4.5 Basic Types

Common beginner types:

Type	Example use
<code>int</code>	whole numbers
<code>double</code>	decimal numbers
<code>char</code>	one character
<code>bool</code>	true or false
<code>std::string</code>	text

Example:

```
int age = 20;
double price = 19.99;
bool active = true;
std::string city = "Krakow";
```

4.6 Simple Calculation

```
#include <iostream>

int main() {
```

```

double a = 0.0;
double b = 0.0;

std::cout << "First number: ";
std::cin >> a;

std::cout << "Second number: ";
std::cin >> b;

std::cout << "Sum: " << a + b << std::endl;
std::cout << "Product: " << a * b << std::endl;
}

```

4.7 Formatting Output

For decimal precision, use `<iomanip>`:

```

#include <iomanip>
#include <iostream>

int main() {
    double value = 10.0 / 3.0;
    std::cout << std::fixed << std::setprecision(2);
    std::cout << value << std::endl;
}

```

Expected output:

3.33

4.8 Common Mistakes

- forgetting `#include <iostream>`,
- missing semicolon at the end of a statement,
- using `int` when the result should contain decimals,
- mixing `std::cin >> value` and `std::getline` without understanding how input is buffered,
- ignoring compiler warnings.

4.9 Practice Tasks

1. Print your name, city, and favorite programming topic.
2. Read two integers and print their sum, difference, and product.
3. Read a rectangle width and height, then print its area.
4. Read a temperature in Celsius and print the value in Fahrenheit.
5. Read a full name with spaces and print a greeting.

4.10 Student Checklist

Before moving to control flow and loops, make sure you can:

- write a minimal C++ program,
- compile it with `-std=c++17 -Wall -Wextra -pedantic`,
- read one value from the user,
- read one full line from the user,
- choose between `int`, `double`, `bool`, and `std::string`,
- format a decimal number with two digits after the decimal point.

4.11 Next Step

The next topic is control flow: `if`, `else`, `switch`, and loops.

Chapter 5

02 - Control Flow and Loops

This chapter teaches how a program makes decisions and repeats instructions. These tools are necessary for almost every non-trivial console program.

5.1 Learning Goals

After this chapter you should be able to:

- use `if`, `else if`, and `else`,
- use comparison and logical operators,
- use `switch` for simple menu-like choices,
- use the conditional operator `?:` in simple expressions,
- write loops with `for`, `while`, and `do while`,
- choose the right loop type for a problem,
- use `break` and `continue` in simple cases,
- solve tasks that require decisions and repetition.

5.2 Conditions

Use `if` when the program should execute code only in some situations:

```
#include <iostream>

int main() {
    int age = 0;

    std::cout << "Age: ";
    std::cin >> age;

    if (age >= 18) {
        std::cout << "Adult" << std::endl;
    } else {
        std::cout << "Minor" << std::endl;
    }
}
```

Common comparison operators:

Operator	Meaning
<code>==</code>	equal
<code>!=</code>	not equal
<code><</code>	less than
<code><=</code>	less than or equal

Operator	Meaning
>	greater than
>=	greater than or equal

Logical operators:

Operator	Meaning
&&	and
	or
!	not

5.3 Multiple Conditions

Use `else if` when there are several possible ranges or categories:

```
#include <iostream>

int main() {
    int points = 0;

    std::cout << "Points: ";
    std::cin >> points;

    if (points >= 90) {
        std::cout << "Very good" << std::endl;
    } else if (points >= 60) {
        std::cout << "Passed" << std::endl;
    } else {
        std::cout << "Failed" << std::endl;
    }
}
```

5.4 switch

Use `switch` for simple choices based on one value:

```
#include <iostream>

int main() {
    int option = 0;

    std::cout << "1. Add\n";
    std::cout << "2. Remove\n";
    std::cout << "Option: ";
    std::cin >> option;

    switch (option) {
        case 1:
            std::cout << "Add selected" << std::endl;
            break;
        case 2:
            std::cout << "Remove selected" << std::endl;
            break;
        default:
            std::cout << "Unknown option" << std::endl;
    }
}
```

```

        break;
    }
}

```

Remember `break`. Without it, execution continues into the next case.

5.5 for Loop

Use `for` when you know how many times the loop should run:

```

#include <iostream>

int main() {
    for (int i = 1; i <= 5; ++i) {
        std::cout << i << std::endl;
    }
}

```

Typical uses:

- counting from 1 to `n`,
- summing numbers,
- printing a table,
- iterating over an index range.

5.6 while Loop

Use `while` when the loop depends on a condition that may change during input:

```

#include <iostream>

int main() {
    int number = 0;

    while (number != 5) {
        std::cout << "Enter 5 to stop: ";
        std::cin >> number;
    }
}

```

This loop may execute zero times if the condition is false at the beginning.

5.7 do while Loop

Use `do while` when the body should run at least once:

```

#include <iostream>

int main() {
    int option = 0;

    do {
        std::cout << "1. Continue\n";
        std::cout << "0. Exit\n";
        std::cout << "Option: ";
        std::cin >> option;
    } while (option != 0);
}

```

This is useful for simple console menus.

5.8 break and continue

`break` exits a loop:

```
for (int i = 1; i <= 10; ++i) {
    if (i == 5) {
        break;
    }
    std::cout << i << std::endl;
}
```

`continue` skips the rest of the current iteration:

```
for (int i = 1; i <= 10; ++i) {
    if (i % 2 == 0) {
        continue;
    }
    std::cout << i << std::endl;
}
```

5.9 Common Mistakes

- writing `=` instead of `==` in a condition,
- adding an accidental semicolon after `if` or `while`,
- forgetting `break` in `switch`,
- creating an infinite loop because the loop variable never changes,
- dividing by zero when no valid input was provided,
- using `for` for input that should end based on user command.

5.10 Bridge Exercise: Minimum, Maximum, and Average

Write a console program that reads real numbers from the user and calculates:

- minimum value,
- maximum value,
- arithmetic average,
- number of valid values.

The user should be able to finish input with a portable text command, for example `q`, `end`, or an empty line.

Example session:

```
Enter a number or q to finish: 10
Enter a number or q to finish: -2.5
Enter a number or q to finish: 4.5
Enter a number or q to finish: q
```

```
Count: 3
Minimum: -2.5
Maximum: 10
Average: 4
```

5.10.1 Requirements

The program should:

- use C++17,
- use a `while` or `do while` loop,
- store the sum in a `double`,
- count valid values,

- update minimum and maximum after each valid value,
- detect invalid input,
- avoid division by zero when no numbers were entered,
- compile with `-Wall -Wextra -pedantic`.

5.10.2 Suggested Work Plan

1. Write a loop that reads text until the user enters `q`.
2. Add a counter for valid numbers.
3. Add sum and average calculation.
4. Add minimum and maximum.
5. Add a message for the empty data case.
6. Add invalid input handling, for example for `abc`.

5.10.3 Check Scenarios

1. Enter 10, -2.5, 4.5, then `q`.
2. Enter only one number and check that minimum, maximum, and average are the same.
3. Finish without entering any number and check the message.
4. Enter invalid text such as `abc` and check that the program asks again.
5. Enter several negative numbers and verify minimum and maximum.

5.11 Practice Tasks

1. Read a number and print whether it is positive, negative, or zero.
2. Read a menu option and handle it with `switch`.
3. Print numbers from 1 to 100 with a `for` loop.
4. Sum numbers from 1 to `n`.
5. Read numbers until the user enters 0.
6. Print a multiplication table.
7. Skip even numbers using `continue`.
8. Stop searching when a target value is found using `break`.

5.12 Student Checklist

Before moving to functions, arrays, and strings, make sure you can:

- write an `if/else` condition,
- use comparison and logical operators,
- use a `switch` with `break`,
- choose between `for`, `while`, and `do while`,
- write a loop that depends on user input,
- explain when `break` and `continue` are useful,
- solve the minimum, maximum, and average bridge exercise.

Chapter 6

03 - Functions, Arrays, and Strings

This chapter teaches how to split a program into smaller parts and how to work with simple collections of data. You will use functions, one-dimensional arrays, two-dimensional arrays, and `std::string`.

6.1 Learning Goals

After this chapter you should be able to:

- declare and define your own functions,
- pass arguments to functions,
- return values from functions,
- understand the difference between a declaration and a definition,
- use one-dimensional arrays,
- use simple two-dimensional arrays,
- iterate over array elements,
- perform basic operations on `std::string`,
- split a larger task into smaller functions.

6.2 Why Functions Matter

A function gives a name to a piece of logic. Instead of writing everything in `main`, you can move a calculation into a separate function:

```
#include <iostream>

int add(int a, int b) {
    return a + b;
}

int main() {
    std::cout << add(2, 3) << std::endl;
}
```

This makes code easier to read, test, and reuse.

6.3 Declaration and Definition

A declaration tells the compiler that a function exists:

```
int add(int a, int b);
```

A definition contains the function body:

```
int add(int a, int b) {
    return a + b;
}
```

In small programs, both can be in one file. In larger projects, declarations often go into header files and definitions go into `.cpp` files.

6.4 Parameters and Return Values

Parameters are input values for a function. `return` sends a result back:

```
double rectangleArea(double width, double height) {
    return width * height;
}
```

Use clear names. A function named `rectangleArea` is easier to understand than one named `calc`.

6.5 Local Variables and Scope

Variables declared inside a function are local to that function:

```
int square(int value) {
    int result = value * value;
    return result;
}
```

`result` cannot be used outside `square`. This is useful because it prevents unrelated parts of the program from accidentally changing each other.

6.6 One-Dimensional Arrays

An array stores several values of the same type:

```
#include <iostream>

int main() {
    int numbers[5] = {4, 2, 9, 1, 7};

    for (int i = 0; i < 5; ++i) {
        std::cout << numbers[i] << std::endl;
    }
}
```

Array indexes start at 0. For an array of size 5, valid indexes are 0, 1, 2, 3, and 4.

6.7 Array Minimum and Maximum

```
#include <iostream>

int main() {
    int numbers[5] = {4, 2, 9, 1, 7};
    int minimum = numbers[0];
    int maximum = numbers[0];

    for (int i = 1; i < 5; ++i) {
        if (numbers[i] < minimum) {
            minimum = numbers[i];
        }
        if (numbers[i] > maximum) {
```

```

        maximum = numbers[i];
    }
}

std::cout << "Minimum: " << minimum << std::endl;
std::cout << "Maximum: " << maximum << std::endl;
}

```

The first element is a practical initial value when the array is not empty.

6.8 Two-Dimensional Arrays

A two-dimensional array can represent a table or a small matrix:

```

#include <iostream>

int main() {
    int matrix[2][3] = {
        {1, 2, 3},
        {4, 5, 6}
    };

    for (int row = 0; row < 2; ++row) {
        for (int col = 0; col < 3; ++col) {
            std::cout << matrix[row][col] << " ";
        }
        std::cout << std::endl;
    }
}

```

Nested loops are the usual way to process rows and columns.

6.9 Strings

`std::string` stores text:

```

#include <iostream>
#include <string>

int main() {
    std::string text = "C++";

    std::cout << text << std::endl;
    std::cout << "Length: " << text.size() << std::endl;
}

```

You can iterate over characters:

```

for (char ch : text) {
    std::cout << ch << std::endl;
}

```

6.10 Reading a Full Line

Use `std::getline` when the text may contain spaces:

```

#include <iostream>
#include <string>

int main() {

```

```

    std::string sentence;

    std::cout << "Enter text: ";
    std::getline(std::cin, sentence);

    std::cout << "You entered: " << sentence << std::endl;
}

```

6.11 Bridge Exercise: GADERYPOLUKI Cipher

Write a console program that encrypts text with the GADERYPOLUKI substitution cipher.

The cipher uses replacement pairs:

GA DE RY PO LU KI

Rules:

- G becomes A,
- A becomes G,
- D becomes E,
- E becomes D,
- the same rule applies to every pair,
- characters not present in the key stay unchanged.

Example:

PROGRAM -> OYPAYGM

6.12 Required Function

The program should contain a function:

```
std::string encryptGaderypoluki(const std::string& text);
```

The function should:

- take the input text as `std::string`,
- return a new encrypted `std::string`,
- not modify the input text directly,
- keep characters outside the key unchanged.

6.13 Suggested Work Plan

1. Write a helper function that replaces one character.
2. Test the pair G and A.
3. Add all remaining key pairs.
4. Write a function that loops over the whole string.
5. Read input with `std::getline`.
6. Test text containing spaces, digits, and punctuation.

6.14 Check Scenarios

1. Input PROGRAM; expected result: OYPAYGM.
2. Input GADERYPOLUKI; every letter should be replaced by its pair.
3. Input ALA 123; digits and spaces should stay unchanged.
4. Input an empty string; the program should not crash.

6.15 Extra Tasks

After the basic version works, add:

- lowercase support,
- preserving letter case,
- automatic decryption with the same function,
- tests for the encryption function,
- reading text from a file,
- writing encrypted text to a file,
- a custom substitution key.

6.16 Common Mistakes

- printing from the encryption function instead of returning a value,
- changing only one pair and forgetting the rest of the key,
- using `std::cin >> text` when the text may contain spaces,
- modifying the original string when a returned result would be clearer,
- mixing input/output code with encryption logic.

6.17 Practice Tasks

1. Write a function `isEven`.
2. Write a function `maxOfTwo`.
3. Calculate the average of an array.
4. Find the minimum and maximum in an array.
5. Print a two-dimensional array as a table.
6. Count letters in a string.
7. Check whether a string is a palindrome.
8. Implement the GADERYPOLUKI cipher.

6.18 Student Checklist

Before moving to pointers, references, and memory, make sure you can:

- write a function with parameters and a return value,
- explain local variable scope,
- iterate over an array by index,
- process a two-dimensional array with nested loops,
- read a full line with `std::getline`,
- iterate over characters in `std::string`,
- split a string-processing task into small functions.

Chapter 7

04 - Pointers, References, and Memory

This chapter introduces addresses, pointers, references, and basic memory safety habits. These topics are powerful, but they require discipline because small mistakes can produce hard-to-diagnose bugs.

7.1 Learning Goals

After this chapter you should be able to:

- distinguish a variable value from its address,
- use the address-of operator `&`,
- declare and initialize pointers,
- understand `nullptr`,
- dereference a pointer with `*`,
- use references,
- pass data to functions by value, pointer, and reference,
- recognize common memory safety problems.

7.2 Value and Address

A variable has a value and an address in memory:

```
#include <iostream>

int main() {
    int number = 42;

    std::cout << "Value: " << number << std::endl;
    std::cout << "Address: " << &number << std::endl;
}
```

`number` reads the value. `&number` reads the address.

7.3 Pointers

A pointer stores an address:

```
#include <iostream>

int main() {
    int number = 42;
    int* pointer = &number;
```

```

    std::cout << pointer << std::endl;
    std::cout << *pointer << std::endl;
}

```

`pointer` stores the address. `*pointer` reads the value stored at that address. This is called dereferencing.

7.4 nullptr

If a pointer does not point to a valid object, initialize it with `nullptr`:

```
int* pointer = nullptr;
```

Before dereferencing a pointer, check whether it is not empty:

```

if (pointer != nullptr) {
    std::cout << *pointer << std::endl;
}

```

This habit prevents many beginner-level pointer mistakes.

7.5 References

A reference is another name for an existing object:

```

#include <iostream>

int main() {
    int value = 10;
    int& ref = value;

    ref = 20;

    std::cout << value << std::endl;
}

```

The program prints 20 because `ref` refers to `value`.

7.6 Pointer or Reference

Use a reference when the argument must exist:

```

void increment(int& value) {
    ++value;
}

```

Use a pointer when the argument may be missing:

```

void incrementIfPresent(int* value) {
    if (value != nullptr) {
        ++(*value);
    }
}

```

This is a practical rule for beginner code. It makes the intent visible in the function signature.

7.7 Passing to Functions

Passing by value copies the argument:

```
void changeCopy(int value) {
    value = 100;
}
```

Passing by reference can modify the original value:

```
void changeOriginal(int& value) {
    value = 100;
}
```

Passing by pointer can also modify the original value, but the function should handle `nullptr`:

```
void changeIfPresent(int* value) {
    if (value != nullptr) {
        *value = 100;
    }
}
```

7.8 const References

Use `const` references when a function should read a larger object without copying it:

```
#include <iostream>
#include <string>

void printName(const std::string& name) {
    std::cout << name << std::endl;
}
```

The function cannot modify `name`, and it avoids copying the string.

7.9 Arrays and Pointers

An array name can be used as a pointer to the first element:

```
#include <iostream>

int main() {
    int numbers[3] = {10, 20, 30};
    int* p = numbers;

    for (int i = 0; i < 3; ++i) {
        std::cout << p[i] << std::endl;
    }
}
```

Valid indexes for this array are 0, 1, and 2. Accessing `p[3]` is outside the array and is an error.

7.10 Memory Safety Rules

Use these rules consistently:

- initialize pointers,
- prefer `nullptr` for an empty pointer,
- check a pointer before dereferencing it,
- do not return the address of a local variable,
- do not access an array outside its valid range,
- prefer references when a value is required,
- prefer `const` references for read-only larger objects,
- keep variables close to the place where they are used.

Do not write code like this:

```
int* invalid() {  
    int local = 10;  
    return &local;  
}
```

`local` stops existing when the function ends. The returned pointer does not point to a valid object.

7.11 Practice Tasks

1. Write `printIfPresent`, which takes `int*` and prints the value only when the pointer is not `nullptr`.
2. Write `incrementIfPresent`, which takes `int*` and increments the value only when the pointer is not `nullptr`.
3. Write `increment`, which takes `int&`, and compare it with the pointer version.
4. Write a function that reads an array through a pointer and a size.
5. Find one previous function where `const std::string&` would be better than passing a string by value.

7.12 Checklist

Before moving on, make sure that your code:

- initializes every pointer,
- checks optional pointers before dereferencing,
- does not return addresses of local variables,
- does not read past the end of an array,
- uses references when a value is required,
- compiles without warnings.

Chapter 8

05 - Files and Exceptions

This chapter shows how a program can store data outside memory and how it can react to error situations. You will work with text files, input validation, and basic exceptions.

8.1 Learning Goals

After this chapter you should be able to:

- open a text file for writing,
- append data to a text file,
- open a text file for reading,
- read a file line by line,
- check whether a file operation succeeded,
- validate simple input data,
- use `try`, `throw`, and `catch`,
- choose a simple error-handling strategy for a small program.

8.2 Writing a Text File

Use `std::ofstream` to write to a file:

```
#include <fstream>
#include <iostream>

int main() {
    std::ofstream file("notes.txt");

    if (!file) {
        std::cout << "Cannot open file for writing." << std::endl;
        return 1;
    }

    file << "First line" << std::endl;
    file << "Second line" << std::endl;
}
```

Opening a file this way replaces the previous content.

8.3 Appending Data

Use `std::ios::app` to append data at the end:

```

#include <fstream>

int main() {
    std::ofstream file("notes.txt", std::ios::app);
    file << "Another line" << std::endl;
}

```

This is useful for logs, notes, and simple history files.

8.4 Reading a Text File

Use `std::ifstream` and `std::getline`:

```

#include <fstream>
#include <iostream>
#include <string>

int main() {
    std::ifstream file("notes.txt");

    if (!file) {
        std::cout << "Cannot open file for reading." << std::endl;
        return 1;
    }

    std::string line;
    while (std::getline(file, line)) {
        std::cout << line << std::endl;
    }
}

```

Always check whether the file was opened correctly before reading from it.

8.5 Reading Numbers with Validation

Input from a file can be invalid. Keep parsing and validation separate from the rest of the program:

```

#include <iostream>
#include <sstream>
#include <string>

bool parseInt(const std::string& text, int& result) {
    std::istringstream input(text);
    input >> result;
    return input && input.eof();
}

int main() {
    int value = 0;

    if (parseInt("123", value)) {
        std::cout << value << std::endl;
    } else {
        std::cout << "Invalid number" << std::endl;
    }
}

```

This design is easy to test because `parseInt` does not depend on a real file.

8.6 Simple Configuration Format

A practical beginner exercise is a small **key=value** file:

```
name=Alice
level=3
active=true
```

Read the file line by line, split each line at **=**, and validate the result. Empty lines and malformed lines should be handled deliberately.

8.7 Exceptions

An exception reports an error that cannot be handled at the current place in the code:

```
#include <iostream>
#include <stdexcept>

int divide(int a, int b) {
    if (b == 0) {
        throw std::runtime_error("division by zero");
    }

    return a / b;
}

int main() {
    try {
        std::cout << divide(10, 0) << std::endl;
    } catch (const std::runtime_error& error) {
        std::cout << "Error: " << error.what() << std::endl;
    }
}
```

Use exceptions for situations where normal execution cannot continue in the current function. Do not use them as a replacement for simple **if** statements.

8.8 Error-Handling Strategy

For small student programs, use this order:

1. Check expected problems with **if**, for example missing input or an empty value.
2. Return a status value when a function can fail in a normal way.
3. Throw an exception when the current function cannot sensibly continue.
4. Catch exceptions near the program boundary, for example in **main**.

The goal is not to use advanced error handling. The goal is to make failures visible and predictable.

8.9 Bridge Exercise: File Menu

Write a console program with a simple menu:

1. Add note
2. Show notes
3. Clear notes
0. Exit

Requirements:

- store notes in a text file,
- append new notes instead of replacing the whole file,

- read and print all notes,
- handle a missing file,
- validate the menu choice,
- keep file operations in separate functions.

8.10 Practice Tasks

1. Write a program that saves three lines to a file.
2. Modify it so that new lines are appended instead of overwriting the file.
3. Write a program that reads a file line by line and counts non-empty lines.
4. Write a function that parses one integer from a string.
5. Write a function that throws an exception for division by zero.

8.11 Checklist

Before moving on, make sure that your code:

- checks whether files open successfully,
- separates parsing from file reading,
- handles invalid input,
- catches exceptions by `const` reference,
- keeps user-facing error messages clear,
- compiles without warnings.

Chapter 9

06 - Object-Oriented Programming

This chapter introduces classes, objects, constructors, encapsulation, inheritance, and polymorphism. The goal is not to make every program object-oriented. The goal is to understand when objects help organize data and behavior.

9.1 Learning Goals

After this chapter you should be able to:

- define a class,
- create objects,
- use private fields,
- write constructors,
- write `const` methods,
- understand `this`,
- explain basic inheritance,
- use virtual methods,
- use `override`,
- overload a simple operator,
- build a small polymorphic program.

9.2 Classes and Objects

A class defines a type. An object is a value of that type:

```
#include <iostream>
#include <string>

class Student {
public:
    Student(const std::string& name, int points)
        : name_(name), points_(points) {}

    void print() const {
        std::cout << name_ << ": " << points_ << std::endl;
    }

private:
    std::string name_;
    int points_;
};
```

```
int main() {
    Student student("Alice", 42);
    student.print();
}
```

The public part is the interface. The private part is implementation detail.

9.3 Encapsulation

Encapsulation means that the class protects its own data. Instead of making fields public, provide methods that keep the object valid:

```
class Counter {
public:
    void increment() {
        ++value_;
    }

    int value() const {
        return value_;
    }

private:
    int value_ = 0;
};
```

Code outside the class cannot accidentally assign an invalid internal state.

9.4 Constructors

A constructor prepares an object for use:

```
class Rectangle {
public:
    Rectangle(double width, double height)
        : width_(width), height_(height) {

    }

    double area() const {
        return width_ * height_;
    }

private:
    double width_;
    double height_;
};
```

Prefer initializing fields in the initializer list.

9.5 const Methods and this

A method marked with `const` promises not to modify the object:

```
double area() const {
    return width_ * height_;
}
```

Inside a method, `this` points to the current object. You rarely need to write `this` explicitly in beginner code, but it helps explain what method calls do.

9.6 Inheritance

Inheritance lets one class reuse or specialize another class:

```
#include <iostream>
#include <string>

class Person {
public:
    explicit Person(const std::string& name) : name_(name) {
    }

    void printName() const {
        std::cout << name_ << std::endl;
    }

private:
    std::string name_;
};

class Teacher : public Person {
public:
    Teacher(const std::string& name, const std::string& subject)
        : Person(name), subject_(subject) {
    }

private:
    std::string subject_;
};
```

Use inheritance carefully. If one class is not a real specialized version of another class, composition is often clearer.

9.7 Virtual Methods and Polymorphism

Polymorphism means that code can call the same method through a base interface, while the actual implementation depends on the object type:

```
#include <iostream>
#include <memory>
#include <string>
#include <vector>

class Shape {
public:
    virtual ~Shape() = default;
    virtual double area() const = 0;
    virtual std::string description() const = 0;
};

class Square : public Shape {
public:
    explicit Square(double side) : side_(side) {
    }

    double area() const override {
        return side_ * side_;
    }
};
```

```

    std::string description() const override {
        return "square";
    }

private:
    double side_;
};

class Circle : public Shape {
public:
    explicit Circle(double radius) : radius_(radius) {

        double area() const override {
            return 3.14159 * radius_ * radius_;
        }

        std::string description() const override {
            return "circle";
        }

private:
    double radius_;
};

int main() {
    std::vector<std::unique_ptr<Shape>> shapes;
    shapes.push_back(std::make_unique<Square>(4.0));
    shapes.push_back(std::make_unique<Circle>(2.0));

    for (const auto& shape : shapes) {
        std::cout << shape->description()
                    << " : " << shape->area() << std::endl;
    }
}

```

Shape is abstract because it has pure virtual methods. Square and Circle provide concrete implementations.

9.8 Why the Virtual Destructor Matters

When a derived object is deleted through a base pointer, the base class should have a virtual destructor:

```
virtual ~Shape() = default;
```

This is a standard safety rule for base classes used polymorphically.

9.9 Operator Overloading

Operator overloading lets a class define how an operator works for its objects:

```

class Point {
public:
    Point(int x, int y) : x_(x), y_(y) {

        Point operator+(const Point& other) const {
            return Point(x_ + other.x_, y_ + other.y_);
        }
    }
}

```

```
private:
    int x_;
    int y_;
};
```

Use operator overloading only when the operator has a natural meaning for the type.

9.10 Bridge Exercise: Shapes and Polymorphism

Write a console program that:

- defines an abstract base class **Shape**,
- defines derived classes **Square** and **Circle**,
- calculates the area of each shape,
- returns a description of each shape,
- stores different shapes through base-class pointers,
- iterates over the collection and calls methods polymorphically.

Minimum technical requirements:

- C++17,
- pure virtual methods,
- virtual destructor in the base class,
- private fields in derived classes,
- **const** methods for read-only operations,
- **override** in derived classes,
- **std::vector** for the collection,
- **std::unique_ptr<Shape>** for ownership,
- compilation with **-Wall -Wextra -pedantic**.

Suggested steps:

1. Write the abstract class **Shape**.
2. Add **Square** and test area calculation.
3. Add **Circle** and a constant for pi.
4. Add **description** to every derived class.
5. Store shapes in one collection through base-class pointers.
6. Print every description and area in a loop.
7. Add validation for dimensions.

Extra tasks:

- add **Rectangle**,
- add **Triangle**,
- add perimeter calculation,
- sort shapes by area,
- calculate total area,
- save the shape list to a file.

9.11 Checklist

Before moving on, make sure that your code:

- keeps fields private,
- initializes objects through constructors,
- marks read-only methods as **const**,
- uses **override** for overridden virtual methods,
- uses a virtual destructor in polymorphic base classes,
- separates object logic from input/output when possible,
- compiles without warnings.

Chapter 10

07 - STL and Data Structures

This chapter introduces the Standard Template Library containers and a few common algorithms. You will learn how to choose a container, store records, search data, sort values, and combine containers in a small program.

10.1 Learning Goals

After this chapter you should be able to:

- choose a container for a simple task,
- use `std::vector` for lists of values,
- iterate over containers with a range-based `for` loop,
- add, remove, and search elements,
- use `std::map` for key-value data,
- use `std::stack` and `std::queue`,
- use basic STL algorithms such as `std::sort` and `std::find_if`,
- combine containers with classes or structs.

10.2 Why STL Matters

The STL gives you tested building blocks. Instead of writing your own dynamic array, map, stack, or queue, use the standard container that matches the task.

For beginner projects, this usually means:

- `std::vector` for a list,
- `std::map` for lookup by key,
- `std::queue` for first-in-first-out processing,
- `std::stack` for last-in-first-out processing,
- algorithms from `<algorithm>` for searching, sorting, and filtering.

10.3 `std::vector`

`std::vector` stores a sequence of values:

```
#include <iostream>
#include <vector>

int main() {
    std::vector<int> numbers;

    numbers.push_back(10);
    numbers.push_back(20);
```

```

    numbers.push_back(30);

    for (int value : numbers) {
        std::cout << value << std::endl;
    }
}

```

Use `push_back` to add an element at the end. Use `size` to check how many elements are stored.

10.4 Vector of Records

Containers become more useful when they store structured data:

```

#include <iostream>
#include <string>
#include <vector>

struct Student {
    std::string name;
    int points;
};

int main() {
    std::vector<Student> students = {
        {"Alice", 42},
        {"Bob", 35},
        {"Carol", 50}
    };

    for (const Student& student : students) {
        std::cout << student.name << ": "
                  << student.points << std::endl;
    }
}

```

Use `const Student&` in the loop when you only read the element and do not want to copy it.

10.5 Sorting

Use `std::sort` from `<algorithm>`:

```

#include <algorithm>
#include <iostream>
#include <vector>

int main() {
    std::vector<int> numbers = {5, 2, 9, 1};

    std::sort(numbers.begin(), numbers.end());

    for (int value : numbers) {
        std::cout << value << std::endl;
    }
}

```

For records, pass a comparison function or a lambda:

```

std::sort(students.begin(), students.end(),
    [](const Student& a, const Student& b) {

```

```
        return a.points > b.points;
    });
```

This sorts students by points from highest to lowest.

10.6 Searching with `std::find_if`

Use `std::find_if` when the search condition is more complex than equality:

```
#include <algorithm>
#include <iostream>
#include <string>
#include <vector>

struct Student {
    std::string name;
    int points;
};

int main() {
    std::vector<Student> students = {
        {"Alice", 42},
        {"Bob", 35}
    };

    auto found = std::find_if(students.begin(), students.end(),
        [](const Student& student) {
            return student.name == "Bob";
        });

    if (found != students.end()) {
        std::cout << found->points << std::endl;
    }
}
```

The result is an iterator. Compare it with `end()` before using it.

10.7 `std::map`

`std::map` stores key-value pairs:

```
#include <iostream>
#include <map>
#include <string>

int main() {
    std::map<std::string, int> points;

    points["Alice"] = 42;
    points["Bob"] = 35;

    std::cout << points["Alice"] << std::endl;
}
```

Use `find` when you want to check whether a key exists:

```
auto it = points.find("Carol");
if (it != points.end()) {
    std::cout << it->second << std::endl;
}
```

This avoids accidentally creating a new entry.

10.8 Stack, Queue, and List

Use `std::stack` when the last value added should be processed first:

```
#include <iostream>
#include <stack>

int main() {
    std::stack<int> values;
    values.push(1);
    values.push(2);

    std::cout << values.top() << std::endl;
    values.pop();
}
```

Use `std::queue` when the first value added should be processed first:

```
#include <iostream>
#include <queue>

int main() {
    std::queue<std::string> tasks;
    tasks.push("compile");
    tasks.push("test");

    std::cout << tasks.front() << std::endl;
    tasks.pop();
}
```

Use `std::list` only when you really need frequent insertions and removals in the middle. For many beginner tasks, `std::vector` is the better default.

10.9 Choosing a Container

Use these practical rules:

- choose `std::vector` for ordered data and simple iteration,
- choose `std::map` when lookup by key is important,
- choose `std::queue` for tasks processed in arrival order,
- choose `std::stack` for reverse-order processing,
- choose `std::list` only when its insertion and removal behavior matters.

Start with the simplest container that matches the problem.

10.10 Mini Project: HRMS

Build a small human resources management program.

Minimum version:

- store employees in `std::vector`,
- each employee has an id, name, department, and salary,
- print all employees,
- find an employee by id,
- sort employees by salary,
- group or count employees by department with `std::map`.

Suggested structure:

```
struct Employee {  
    int id;  
    std::string name;  
    std::string department;  
    double salary;  
};
```

Keep operations in separate functions. This prepares the code for the next chapter, where projects are split into multiple files and tested.

10.11 Practice Tasks

1. Store five numbers in a vector and print them in sorted order.
2. Store students in a vector and find the student with the highest score.
3. Build a `std::map<std::string, int>` that counts words.
4. Simulate a queue of tasks with `std::queue`.
5. Use `std::stack` to reverse a sequence of values.
6. Extend the HRMS mini project with a department filter.

10.12 Checklist

Before moving on, make sure that your code:

- uses standard containers instead of manual arrays when appropriate,
- checks iterators before dereferencing,
- uses `const` references for read-only records,
- keeps container choice simple and justified,
- separates data operations into functions,
- compiles without warnings.

Chapter 11

08 - Project Structure, Build, and Tests

This chapter shows how to move from one `.cpp` file to a small C++ project with headers, source files, build commands, syntax checks, tests, and basic automation.

11.1 Learning Goals

After this chapter you should be able to:

- split a program into header and source files,
- explain the role of the preprocessor and `#include`,
- protect headers against multiple inclusion,
- create a minimal project structure,
- compile a project made of several files,
- check syntax without building a full program,
- write simple tests without an external framework,
- explain the basic idea of CI/CD.

11.2 From One File to Several Files

A one-file program is fine at the beginning. As the code grows, split it into:

- headers with declarations,
- source files with definitions,
- tests that check selected functions,
- a build directory for generated files.

A small structure can look like this:

```
calculator/  
  include/calculator.h  
  src/calculator.cpp  
  src/main.cpp  
  tests/calculator_tests.cpp  
  build/  
  build.sh
```

The exact layout can vary. The important rule is that source code and generated files are not mixed.

11.3 Headers and Source Files

A header declares what exists:

```
// include/calculator.h
#ifndef CALCULATOR_H
#define CALCULATOR_H

int add(int a, int b);

#endif
```

A source file defines how it works:

```
// src/calculator.cpp
#include "calculator.h"

int add(int a, int b) {
    return a + b;
}
```

main.cpp can use the function through the header:

```
#include <iostream>
#include "calculator.h"

int main() {
    std::cout << add(2, 3) << std::endl;
}
```

11.4 Include Guards

Include guards prevent the same header from being included more than once in a single translation unit:

```
#ifndef CALCULATOR_H
#define CALCULATOR_H

// declarations

#endif
```

You may also see `#pragma once` in real projects. Include guards are explicit and portable, so they are a good teaching default.

11.5 Compiling Multiple Files

A simple manual compile command can look like this:

```
c++ -std=c++17 -Wall -Wextra -pedantic \
    -Iinclude \
    src/main.cpp src/calculator.cpp \
    -o build/calculator
```

Important parts:

- `-std=c++17` selects the language version,
- `-Wall -Wextra -pedantic` enables useful warnings,
- `-Iinclude` tells the compiler where to find project headers,
- several `.cpp` files are compiled and linked into one program.

11.6 Build Script

A small `build.sh` keeps commands repeatable:

```
#!/bin/sh
set -eu
```

```
mkdir -p build
```

```
c++ -std=c++17 -Wall -Wextra -pedantic \  
    -Iinclude \  
    src/main.cpp src/calculator.cpp \  
    -o build/calculator
```

```
c++ -std=c++17 -Wall -Wextra -pedantic \  
    -Iinclude \  
    tests/calculator_tests.cpp src/calculator.cpp \  
    -o build/calculator_tests
```

```
./build/calculator_tests
```

Generated files should stay in build/ and should not be committed.

11.7 Syntax Checks

Use `-fsyntax-only` when you want the compiler to check code without producing an executable:

```
c++ -std=c++17 -Wall -Wextra -pedantic -fsyntax-only src/main.cpp
```

This is useful for quick feedback and for checking starter files.

11.8 Simple Tests Without a Framework

A minimal test program can return 0 for success and non-zero for failure:

```
#include "calculator.h"
```

```
int main() {  
    if (add(2, 3) != 5) {  
        return 1;  
    }  
  
    if (add(-2, 2) != 0) {  
        return 1;  
    }  
  
    return 0;  
}
```

The build script can run the test executable. If the test returns 1, the script fails.

11.9 Basic CI/CD Idea

CI means that checks are run automatically after a change is pushed to the repository. For this course, a useful first CI setup would:

- install a compiler,
- compile examples,
- run simple tests,
- fail when a command returns an error.

CD is about automatic delivery or deployment. For this repository, CI is the more important concept for students.

11.10 Bridge Exercise: RPN Calculator

Build a small multi-file project that calculates arithmetic expressions by converting them to Reverse Polish Notation.

The program should:

- read one text expression,
- support real numbers,
- support +, -, *, /,
- respect multiplication and division precedence,
- support parentheses,
- convert the expression to Reverse Polish Notation,
- evaluate the result with a stack,
- report clear errors for invalid expressions.

Examples:

```
2 + 2 * 2 = 6
(2 + 2) * 2 = 8
10 / 2 + 3 = 8
```

Suggested structure:

```
rpn-calculator/
  include/rpn/
    token.h
    tokenizer.h
    rpn.h
    evaluator.h
  src/
    tokenizer.cpp
    rpn.cpp
    evaluator.cpp
    main.cpp
  tests/
    rpn_tests.cpp
  build/
    .gitignore
    build.sh
    README.md
```

Suggested functions:

```
std::vector<Token> tokenize(const std::string& expression);
std::vector<Token> toReversePolishNotation(const std::vector<Token>& tokens);
double evaluateReversePolishNotation(const std::vector<Token>& tokens);
```

Minimum requirements:

- C++17,
- separate tokenization from evaluation,
- use `std::vector<Token>`,
- use `std::vector` or `std::stack` as the evaluation stack,
- handle division by zero,
- detect invalid parentheses,
- include tests for at least three valid expressions,
- include a `build.sh` script that builds the app and tests,
- compile with `-Wall -Wextra -pedantic`.

Suggested work order:

1. Create the project directory structure.
2. Add `build.sh` that compiles an empty program.

3. Define `Token`.
4. Implement tokenization for numbers and operators.
5. Convert tokens to Reverse Polish Notation.
6. Evaluate the RPN expression with a stack.
7. Add tests for valid expressions.
8. Add error handling and tests for invalid expressions.

Extra tasks:

- negative numbers,
- exponentiation,
- constants `pi` and `e`,
- repeated calculations in a loop,
- calculation history,
- comparison with a recursive parser.

11.11 Practice Tasks

1. Split a one-file calculator into `calculator.h`, `calculator.cpp`, and `main.cpp`.
2. Add a `build.sh` script for the calculator.
3. Add a test program that checks three functions.
4. Add a syntax-only command for one starter file.
5. Add a `README.md` section that explains how to build and test the project.
6. Start the RPN calculator with only tokenization and tests.

11.12 Checklist

Before moving on, make sure that your project:

- has headers and source files in clear directories,
- keeps generated files in `build/`,
- has a repeatable build command or script,
- compiles with warnings enabled,
- has tests that return non-zero on failure,
- separates parsing, calculation, and user interaction,
- documents build and test commands.