

Configure Database Vault

Container Database CDB\$ROOT

Verify if Label Security and Database Vault are Installed & Configured

```
col DESCRIPTION format a40

set lines 900

SELECT * FROM SYS.DBA_DV_STATUS;

SELECT * FROM DBA_OLS_STATUS;
```

Create new Users for Database Vault

```
GRANT CREATE SESSION, SET CONTAINER TO c##dv_owner_root IDENTIFIED BY
ORacle1234## CONTAINER = ALL;

GRANT CREATE SESSION, SET CONTAINER TO c##dv_acctmgr_root IDENTIFIED BY
ORacle1234## CONTAINER = ALL;
```

#Configure Database Vault (Connect as root admin)

```
BEGIN
CONFIGURE_DV (
  dvowner_username    => 'c##dv_owner_root',
  dvacctmgr_username  => 'c##dv_acctmgr_root',
  force_local_dvowner => FALSE);
END;
/

exec CONFIGURE_DV('c##dv_owner_root','c##dv_acctmgr_root');
```

Recompile Invalid Objects

```
@?/rdbms/admin/utlrp.sql
```

Connect to root as DV Owner User(c##dv_owner_root)

```
EXEC DBMS_MACADM.ENABLE_DV;
```

Restart the Database

```
SQL> conn / as sysdba
```

```
Shutdown immediate
```

```
Startup
```

Verify if Label Security and Database Vault are Installed & Configured

```
SELECT * FROM SYS.DBA_DV_STATUS;
```

```
SELECT * FROM DBA_OLS_STATUS;
```