

TO:

SUBJECT:

CategoryName	Item	Model	Quantity	Rate	Amount
Total					

in Words :

AirCooled Chiller

CGAJ

- * Chiller Selection: The chiller shall be selected in accordance with the manufacturer's technical catalogue, ensuring compliance with performance and capacity requirements.
- * Country of Origin: The proposed chiller shall be manufactured in China.
- * Compressor Type: Equipped with hermetic scroll compressors for compact design, low maintenance, and reliable performance.
- * Power Supply: Designed for 400V / 50Hz / 3-phase electrical power.
- * Compressor Motor Starter: Features a star-delta starter for the compressor motor to reduce inrush current during start-up.
- * Compressor Motor Starter: Features a star-delta starter for the compressor motor to reduce inrush current during start-up.
- * Electrical Protection: Includes under-voltage and over-voltage protection for enhanced electrical safety and system reliability.
- * User Interface: LCD display panel with a user-friendly human-machine interface (HMI) for easy operation and system monitoring.
- * Safety Devices: Supplied with flow switches for system protection and operational safety.
- * Refrigerant and Oil Charge: Supplied with a full operating charge of R-410A refrigerant and compressor oil, factory-charged for immediate operation.

Close Control Unit

- * asfasdf
- * asdasdfasdf
- * asdfasdf

TO:

SUBJECT:

AirCooled Chiller
yee

AirCooled Chiller
ddd