

TO: SUBJECT:

CategoryName	Item	Model	Quantity	Rate	Amount

Total

in Words:

Scope of Work

AirCooled Chiller CGAJ

- Chiller Selection: The chiller shall be selected in accordance with the manufacturer's technical catalogue, ensuring compliance with performance and capacity requirements.
- Country of Origin: The proposed chiller shall be manufactured in China.
- Compressor Type: Equipped with hermetic scroll compressors for compact design, low maintenance, and reliable performance.
- Power Supply: Designed for 400V / 50Hz / 3-phase electrical power.
- Compressor Motor Starter: Features a star-delta starter for the compressor motor to reduce inrush current during start-up.
- Compressor Motor Starter: Features a star-delta starter for the compressor motor to reduce inrush current during
- Electrical Protection: Includes under-voltage and over-voltage protection for enhanced electrical safety and system reliability.
- User Interface: LCD display panel with a user-friendly human-machine interface (HMI) for easy operation and system monitoring.
- Safety Devices: Supplied with flow switches for system protection and operational safety.
- Refrigerant and Oil Charge: Supplied with a full operating charge of R-410A refrigerant and compressor oil, factory-charged for immediate operation.

Close Control Unit

- asfasdf
- asdasdfasdf
- asdfasdf



TO:	SUBJECT:

Warranty

AirCooled Chiller yee

Exclusions

AirCooled Chiller ddd