

TO:

SUBJECT:

CategoryName	Item	Model	Quantity	Rate	Amount
Total					

in Words :

#### AirCooled Chiller

#### CGAJ

Chiller Selection: The chiller shall be selected in accordance with the manufacturer's technical catalogue, ensuring compliance with performance and capacity requirements.

Country of Origin: The proposed chiller shall be manufactured in China.

Compressor Type: Equipped with hermetic scroll compressors for compact design, low maintenance, and reliable performance.

Power Supply: Designed for 400V / 50Hz / 3-phase electrical power.

Compressor Motor Starter: Features a star-delta starter for the compressor motor to reduce inrush current during start-up.

Compressor Motor Starter: Features a star-delta starter for the compressor motor to reduce inrush current during start-up.

Electrical Protection: Includes under-voltage and over-voltage protection for enhanced electrical safety and system reliability.

User Interface: LCD display panel with a user-friendly human-machine interface (HMI) for easy operation and system monitoring.

Safety Devices: Supplied with flow switches for system protection and operational safety.

Refrigerant and Oil Charge: Supplied with a full operating charge of R-410A refrigerant and compressor oil, factory-charged for immediate operation.

#### Close Control Unit

asfasdf

asdasdfasdf

asdfasdf

TO:

SUBJECT:

**AirCooled Chiller**  
yee

**AirCooled Chiller**  
ddd