

Peer-to-Peer Systems and Applications



TECHNISCHE
UNIVERSITÄT
DARMSTADT

Lecture 9: P2P Testbeds, EMANICSLab, and PlanetLab

* Original slides for this lecture provided by David Hausheer (TU Darmstadt, Germany), Larry Peterson, Vivek S. Pai et al. (Princeton University) and Timothy Roscoe (Intel Research Berkeley)

0. Lecture Overview



1. Introduction to PlanetLab
 1. Idea and Concept
 2. Relation to P2P
 3. Services
 4. Tools
 5. PlanetLab @ TUD
 6. References
2. EmanicsLab
 1. Overview
 2. Monitoring
 3. Management
3. Mobile Testbeds
 1. Motivation
 2. Requirements
 3. CrowdLab
 4. PhoneLab
 5. SmartNets Lab
 6. Federation



1. PlanetLab

Idea, Concept, Relation to P2P,
Services and Tools

*Based partially on original slides by Larry Peterson, Vivek S. Pai et al. (Princeton University) and Timothy Roscoe (Intel Research Berkeley)

1. PlanetLab - What it is

- ❖ Large collection of machines spread around the world for distributed systems research
- ❖ Established in 2002 by UC Berkeley, Princeton University, and University of Washington
- ❖ Now a consortium of companies and universities
 - E.g. Intel, HP, and Google

1. PlanetLab - Value Proposition

- ❖ Institutions join, provide 2 nodes at minimum
 - Hosted outside the firewall
- ❖ In exchange, researchers get a small slice of many machines worldwide
 - High benefit from a small entry fee

1. PlanetLab Today



- ❖ 1171 nodes spanning 552 sites and over 35 countries
 - Nodes within a LAN-hop of over 3M users
- ❖ Supports *distributed virtualization*
 - Each of over 500 network services running in their own *slice*
- ❖ Carries real user traffic
 - Generating over 4 TB / contacting over 1M unique IP addresses every day

1.1. PlanetLab Idea

- ❖ New paradigm for network research infrastructure
 - Support experimental validation of new services
 - Simultaneously support real users and clean slate designs
 - Provide plausible deployment path
- ❖ Key ideas
 - Virtualization
 - Multiple architectures on a shared infrastructure
 - Programmable
 - Virtually no limit on new designs
 - Opt-in on a per-user / per-application basis
 - Attract real users
 - Demand drives deployment / adoption




1.1. PlanetLab Entities and Roles

- ❖ Sites
- ❖ Nodes
- ❖ Users
 - Administrator
 - Principal Investigator
 - Technical Contact
 - User
- ❖ Slices (and Slivers)


1.1. PlanetLab Concept: Slices

- ❖ Services run in *slices*
 - Slice: set of virtual machines (*slivers*)
 - Slivers provide „root access“ to service manager
 - Created by *slices creation service*




- ❖ VMM: Virtual Machine Monitor
 - Isolates the virtual machines from each other
 - Currently Linux with vserver extensions
 - Could eventually be Xen


1.1. PlanetLab Concept: Slices




1.1. PlanetLab Service Example 1



1.1. PlanetLab Service Example 2



1.1. PlanetLab Concept: User Opt-in



1.1. Permissions of User Roles

- ❖ Administrator
 - Enable, disable sites
- ❖ Principal Investigator
 - Enable, disable, and delete user accounts
 - Create / delete slices
 - Assign users to slices
 - Allocate resources to slices
- ❖ Technical Contact
 - Add, configure, maintain nodes
- ❖ User
 - Add nodes to slices

1.1. PlanetLab Concept: Management

❖ PlanetLab Central (PLC)

- Trusted intermediary between node owners and node users
- Control of operating systems on nodes
- Access permissions and resource allocation to services
- Operated by PlanetLab administrators at Princeton University
- Accessible via PLC API (XML-RPC) or <http://www.planet-lab.org/>

❖ MyPLC

- A complete PlanetLab Central (PLC) installation
- Includes the core components of PLC: a web server, an XML-RPC API server, a boot server, and a database server
- Allows users to deploy their own “private” PlanetLab
- Next step: Federation of private PlanetLabs

1.2. PlanetLab: What does it have to do with P2P

- ❖ PlanetLab is a hybrid P2P system
 - Nodes are relatively autonomous
 - Local control through admin slice
- ❖ PlanetLab enables
 - Deployment of P2P applications at planetary scale
 - Across jurisdictional and administrative boundaries
 - Evaluation of P2P applications in a realistic setting
 - Real latencies between nodes, nodes may be unreliable
 - Nothing works as expected at scale!
- ❖ Many P2P applications are tested on PlanetLab
 - E.g. OceanStore, Bamboo, Chord, PeerMart
- ❖ PlanetLab Challenge
 - Remove PlanetLab Central entirely

1.3. Services based on PlanetLab



Planetflow2 - Traffic Search Results - Mozilla Firefox

File Edit View History Bookmarks Tools Help

Planetflow2 - Traffic Search Results +

http://planetflow.planet-lab.org/search.php?nodeip=130.83.166.246

Traffic details

The following is a breakup of the traffic you specified by the "slice" (i.e., the PlanetLab experiment) that generated it. If the list is long, then it may help to go back and refine your search by specifying additional details such as the destination IP address. If you find that 1 or 2 slices account for most of the traffic, then email them to find out what they're doing by clicking on the slice id, putting PlanetLab support on cc. We'll make sure that your query is responded to promptly.


The node 130.83.166.246 is part of peer PlanetLab Central of the PlanetLab federation.

Packets	slice	Bytes
2614409	princeton_codeen	935319350
133922	ufl_svpn	18931324
109754	ufl_ipop3	13912832
42362	princeton_comon	3395334
1723	tauple_DIMES_test	212481
167	uka_p2pns	66961
645	umd_scriptroute	53234
16856222	uw_oneswarm	2622187010
429617	0	39967581
152285	princeton_coblitz	12576781
57822	ufpr_vaphds	2017964

1.3. PlanetLab: Example Service – CoDeeN

- ❖ A Content Distribution Network (CDN)
 - Redirects/caches HTTP requests
- ❖ An Open Proxy Network
 - Probably the largest in existence

- ❖ How Does It Work?
 - Clients specify proxy to use
 - Cache hits served locally
 - Cache misses forwarded to CoDeeN nodes
 - Maybe forwarded to origin servers



1.3. CoDeeN: Malicious Traffic

❖ Spammers

- SMTP tunnels, POST forms, IRC channels

Restrict ports & HTTP methods

❖ Bandwidth hogs

- Google crawls, steganographers, X-Pacific

Multi-scale req & bw accounting

❖ Hackers & Spreaders

- Yahoo dictionary attacks, IIS vuln tests

Signature database & Robot test

❖ Content thieves

- E-journals/databases, local content

Determine location & privilege

1.4. PlanetLab Tools

- ❖ Pssh: Parallel ssh
 - Provides the parallel versions of the *openssh* tools
 - Can be used to control large collections of nodes in a network
 - <http://www.theether.org/pssh/>
- ❖ PLDeploy: PlanetLab Slice Deploy Toolkit
 - A set of Perl scripts to help users manage their slices
 - Allocating a sliver, pushing code to multiple slivers and pulling results back
 - <http://psepr.org/tools/>
- ❖ Many more: Plush, PIMan, vxargs, ...
- ❖ <https://www.planet-lab.org/tools>

1.5. PlanetLab @ TUD

- ❖ TUD is a member of PlanetLab
- ❖ Currently, TUD hosts 3 PlanetLab nodes:
 - host1.planetlab.informatik.tu-darmstadt.de
 - host2.planetlab.informatik.tu-darmstadt.de
 - host3.planetlab.informatik.tu-darmstadt.de
- ❖ TUD staff members and students are eligible for a PlanetLab account.
- ❖ In order to apply for an account, you have to register:
 - <https://www.planet-lab.eu/db/persons/register.php> **Changed!**
 - Select site "Technische Universität Darmstadt"
- ❖ Contact Principal Investigator (PI) to get a slice
 - **Robert Rehner** <rehner@dvs.tu-darmstadt.de>

1.6. References

- ❖ L. Peterson, T. Anderson, D. Culler, and T. Roscoe: *A Blueprint for Introducing Disruptive Technology into the Internet*; First ACM Workshop on Hot Topics in Networking (HotNets), October 2002.
- ❖ A. Bavier, M. Bowman, B. Chun, et al.: *Operating System Support for Planetary-Scale Services*; First Symposium on Network Systems Design and Implementation (NSDI), March 2004.
- ❖ L. Peterson, A. Bavier, M. Fiuczynski, and S. Muir: *Experiences Building PlanetLab*; Seventh Symposium on Operating System Design and Implementation (OSDI), November 2006.
- ❖ <http://www.planet-lab.org/>



2. EmanicsLab

Overview, Monitoring, Management,
Future Extensions

2. Drawbacks of PlanetLab

- ❖ PlanetLab configuration and control is done centrally by PlanetLab administrators
 - Users needs cannot always be accommodated
 - Could be a problem if strong trust relationships and access protection mechanisms are required
 - E.g., for trace repositories

- ❖ Resources in PlanetLab are limited
 - Standard disk quota only 5GB per user on each node
 - Distributed flow collection requires much more storage
 - A load average of 7 is not uncommon on PlanetLab nodes

2. EmanicsLab

- ❖ European research network initiated in 2007
- ❖ Funded from 2007-2009 by the EU NoE EMANICS
- ❖ Based on myPLC - backend management infrastructure of PlanetLab
- ❖ Maintained by the Communication Systems Group (CSG) at the University of Zurich (UZH).

- ❖ Since 2010 governed by the EmanicsLab Steering Committee
- ❖ EmanicsLab currently consists of 22 nodes at 11 sites across Europe
- ❖ EmanicsLab partners use the network for research activities in the area of network and service management, including
 - Distributed flow collection and analysis systems
 - Distributed intrusion detection systems
 - Distributed monitoring and accounting systems

2.1. Benefits of EmanicsLab


- ❖ EmanicsLab is dedicated to its members
 - Enables the flexible allocation of resources to research activities
 - Ensures that the control of the testbed stays within the EmanicsLab consortium
 - Access to the testbed can be restricted if necessary
 - Extensions or changes to the testbed can be done
 - E.g., use of a different virtualization platform
 - Specific services supporting research on network and service management can be provided
 - E.g., distributed trace repositories

2.1. EmanicsLab Sites

Total:


- 11 sites
- 22 nodes
- 75 users
- 10 slices

June 2013



2.1. EmanicsLab Administrator

- ❖ Trusted institution running myPLC for EmanicsLab
- ❖ Primary contact for any technical and administrative questions
- ❖ Responsible for the execution of peerings with other organizations such as PlanetLab Europe
- ❖ Currently: UZH/
David Hausheer
- ❖ EmanicsLab's administrators can be contacted at emanicslab@ifi.uzh.ch



2.1. Acceptable Use Policy

- ❖ Usage of the EmanicsLab infrastructure is regulated by an acceptable use policy
- ❖ EmanicsLab - due to its federation with PlanetLab Europe (PLE) - is a part of the overall world-wide PlanetLab infrastructure
- ❖ This implies that all EmanicsLab sites have to be members of either PLE or PlanetLab Central (PLC) and as a result are bound by a PlanetLab acceptable use policy (AUP)
- ❖ For the latest PlanetLab acceptable use policy (AUP), please visit: <http://www.planet-lab.eu/doc/aup>
- ❖ Read the AUP carefully, before running an experiment on any EmanicsLab or PlanetLab nodes.
- ❖ To report a suspected violation of this policy, contact EmanicsLab Support (emanicslab@ifi.uzh.ch).

2.1. Federation with PlanetLab Europe (PLE)

- ❖ Since March 2011 EmanicsLab federates with PlanetLab Europe (PLE)
 - PlanetLab Europe is the European branch of the global PlanetLab system
 - Federation governed by a Memorandum of Understanding (MoU)
cf. <https://www.emanicslab.org/?q=node/11>
- ❖ EmanicsLab users can access hundreds of PLE nodes and vice-versa
- ❖ Central management of EmanicsLab nodes remains under control of EmanicsLab administrator
- ❖ Federation achieved using Slice-based Federation Architecture (SFA)
- ❖ For further information see
<http://onelab.eu/index.php/services/testbed-federation.html>
- ❖ Description of the EmanicsLab use case:
<http://onelab.eu/index.php/services/testbed-federation/use-cases/485-emanicslab.html>

2.1. Mailing Lists

- ❖ All EmanicsLab users are required to subscribe to the EmanicsLab mailing list:
<https://lists.ifi.uzh.ch/listinfo/emanicslab>
- ❖ The mailing list is used for announcements such as node down times
- ❖ EmanicsLab's administrators can be contacted at emanicslab@ifi.uzh.ch

2.1. EmanicsLab Nodes (1)

Site	Hostname	RAM	HDD	CPU
UZH	emanicslab1.csg.uzh.ch	3 GB	500 GB	Pentium 4, 3.6 GHz
	emanicslab2.csg.uzh.ch	3 GB	120 GB	Pentium 4, 3.6 GHz
JUB	emanicslab1.eecs.jacobs-university.de	1 GB	80 GB	Pentium D, 2.8 GHz
	emanicslab2.eecs.jacobs-university.de	1 GB	500 GB	Pentium D, 2.8 GHz
TUD	emanicslab1.ps.tu-darmstadt.de	4 GB	750 GB	Dual Core Xeon, 1.6 GHz
	emanicslab2.ps.tu-darmstadt.de	4 GB	1000 GB	Dual Core Xeon, 2 GHz
UniBW	emanicslab1.informatik.unibw-muenchen.de	2 GB	150 GB	Dual Core Xeon, 3.0 GHz
	emanicslab2.informatik.unibw-muenchen.de	2 GB	150 GB	Dual Core Xeon, 3.0 GHz
UPC	moscu.upc.es	4 GB	500 GB	Dual Core i5, 3.2 GHz
	muro.upc.es	1 GB	250 GB	Core 2, 2.13 GHz
INRIA	host1-plb.loria.fr	2 GB	160 GB	Pentium 4, 3.0 GHz
	host2-plb.loria.fr	4 GB	750 GB	Core 2, 2.93 GHz

2.1. EmanicsLab Nodes (2)

Site	Hostname	RAM	HDD	CPU
UT	emanicslab1.ewi.utwente.nl	4 GB	2000 GB	Xeon, 2.66 GHz
	emanicslab2.ewi.utwente.nl	4 GB	2000 GB	Xeon, 2.66 GHz
IBBT	planck232ple.test.iminds.be	12 GB	1000 GB	Dual Core Xeon, 2.4 GHz
	planck233ple.test.iminds.be	12 GB	1000 GB	Dual Core Xeon, 2.4 GHz
PSNC	emanicslab1.man.poznan.pl	1 GB	500 GB	Xeon, 2.66 GHz
	emanicslab2.man.poznan.pl	1 GB	500 GB	Xeon, 2.66 GHz
UCL	emanics1.ee.ucl.ac.uk	4 GB	750 GB	Dual Core 2, 2.5 GHz
	emanics2.ee.ucl.ac.uk	4 GB	750 GB	Dual Core 2, 2.5 GHz
UPI	emanicslab1.upit.ro	3 GB		
	emanicslab2.upit.ro	4 GB		
Total		80 GB	13.4 TB	


2.1. EmanicsLab Slices

Sites	Principal Investigator	Slices	Users
TUD	David Hausheer	tud_fkaup tud_btlive	Fabian Kaup, Florian Jomrich, Matthias Wichtlhuber, Björn Scheurich Tamara Knierim
JUB	Juergen Schoenwaelder	iub_discaria iub_tcpprobe	Ha Manh Tran Jürgen Schönwälder
UPC	Jose Antonio Astorga Rivera	upc_sblomars	Josep M Tomas
UZH	Guilherme Sperb Machado	uzh_btcollector	Andri Lareida
PSNC	Szymon Trocha	psnc_flow3	Robert Szuman, Szymon Trocha
UT	Ramin Sadre	ut_snid_ut	Ramin Sadre, Anna Sperotto
ELC	David Hausheer	pl_elabmoni	Andrei Vancea, Cristian Morariu

2.2. EmanicsLab Monitoring: Ganglia




TECHNISCHE
UNIVERSITÄT
DARMSTADT



<http://www.emanicslab.org/ganglia/>

2.3. Account Creation



EmanicsLab - Mozilla Firefox

File Edit View History Bookmarks Tools Help

www.emanicslab.org

Add Link Leo Dict Zope Manage Bing UZH CSG Google LEO Milkyway SBB SRF SF UT Yahoo! Import to Mendeley

EmanicsLab

Submitted by drupal on Sun, 06/28/2009 - 01:24.

EmanicsLab is a European research network initiated in 2007 and funded from 2007-2009 by the **European Network of Excellence for the Management of Internet Technologies and Complex Services (EMANICS)**. EmanicsLab is based on myPLC, the backend management infrastructure of **PlanetLab**. It is maintained by the **Communication Systems Group (CSG)** at the **University of Zurich (UZH)**. Since 2010 EmanicsLab is governed by the EmanicsLab Steering Committee.

UCL

University of Twente

JACOBS UNIVERSITY

POZNAŃ

iMinds

INRIA

TECHNISCHE UNIVERSITÄT DARMSTADT

der Bundeswehr

EmanicsLab login

E-mail: *

Password: *

Log in

[Forgot your password?](#)

[Create an account](#)

[File a site registration](#)

Services

- [EmanicsLab Grid Report](#)
- [Monitoring by Sblomars](#)
- [Trouble Tickets](#)

Documentation

- [AUP](#)
- [Charter](#)
- [Federation](#)

2.3. Registration



TECHNISCHE
UNIVERSITÄT
DARMSTADT

[Home](#)

Account Registration

Register

First name: *

Last name: *

Title:

Telephone:

Your E-mail address must be able to receive e-mail and will be used as your username:

E-mail: *

Password: *

Select the site where you belong :


Site:

Select a site


▼

Register


2.3. Verify Account (User)



2.3. Confirmation (User)



2.3. Login



EmanicsLab - Mozilla Firefox

File Edit View History Bookmarks Tools Help

www.emanicslab.org

Add Link Leo Dict Zope Manage Bing UZH CSG Google LEO Milkyway SBB SRF SF UT Yahoo! Import to Mendeley

EmanicsLab

Submitted by drupal on Sun, 06/28/2009 - 01:24.

EmanicsLab is a European research network initiated in 2007 and funded from 2007-2009 by the [European Network of Excellence for the Management of Internet Technologies and Complex Services \(EMANICS\)](#). EmanicsLab is based on myPLC, the backend management infrastructure of [PlanetLab](#). It is maintained by the [Communication Systems Group \(CSG\)](#) at the [University of Zurich \(UZH\)](#). Since 2010 EmanicsLab is governed by the EmanicsLab Steering Committee.

EmanicsLab login

E-mail: *

Password: *

Login

[Forgot your password?](#)

[Create an account](#)

[File a site registration](#)

Services

- [EmanicsLab Grid Report](#)
- [Monitoring by Sblomars](#)
- [Trouble Tickets](#)

Documentation

- [AUP](#)
- [Charter](#)
- [Federation](#)

UCL

University of Twente

JACOBS UNIVERSITY

POZNAN

TECHNISCHE UNIVERSITÄT DARMSTADT

iMinds


INRIA

der Bundeswehr

2.3. EmanicsLab Web Interface



TECHNISCHE
UNIVERSITÄT
DARMSTADT



EmanicsLab

david.hausheer@ps.tu-darmstadt...

- Logout
- My Account
- Sites
 - My Site
- Nodes
 - My Site Nodes
- My Slices
 - Sirius
- About MyPLC
 - PLCAPI doc
 - NMAPI doc

Services

- EmanicsLab Grid Report
- Monitoring by Sblomars
- Trouble Tickets


Documentation

- AUP
- Charter
- Federation
- Guides
- Incident Response
- Mailing Lists
- MoU

EmanicsLab

Submitted by drupal on Sun, 06/28/2009 - 01:24.

EmanicsLab is a European research network initiated in 2007 and funded from 2007-2009 by the [European Network of Excellence for the Management of Internet Technologies and Complex Services \(EMANICS\)](#). EmanicsLab is based on myPLC, the backend management infrastructure of PlanetLab. It is maintained by the [Communication Systems Group \(CSG\)](#) at the [University of Zurich \(UZH\)](#). Since 2010 EmanicsLab is governed by the EmanicsLab Steering Committee.



- UCL
- University of Twente
- JACOBS UNIVERSITY
- POZNAN
- TECHNISCHE UNIVERSITÄT DARMSTADT
- der Bundeswehr Universität München
- UNIVERSITAT POLITÈCNICA DE CATALUNYA
- INRIA
- iMinds

2.3. Generate Key



```
hausheer@myhost ~  
$ ssh-keygen.exe -t rsa  
Generating public/private rsa key pair.  
Enter file in which to save the key (/home/hausheer/.ssh/id_rsa):  
Enter passphrase (empty for no passphrase):  
Enter same passphrase again:  
Your identification has been saved in /home/hausheer/.ssh/id_rsa.  
Your public key has been saved in /home/hausheer/.ssh/id_rsa.pub.  
The key fingerprint is:  
49:8a:29:11:b8:97:9a:4c:b4:46:05:5c:05:f5:7b:3b hausheer@myhost  
  
hausheer@myhost ~  
$
```

2.3. Manage Keys



EMANICS EmanicsLab

david.hausheer@ps.tu-darmstadt...

Home

Details for account testuser Test

▼ Details

Title

First Name

Last Name

Email

Phone

URL

Bio

Password

Repeat

Update Account

Enabled Yes

No slice !!

No kev !!

Warning This user has no known key

TYPE KEY

Upload new key Browse... Upload key

One site

One role

Logout

My Account

Sites

- My Site

Nodes

- My Site Nodes

My Slices

- Sirius

About MyPLC

- PLCAPI doc
- NMAPI doc

Services

- EmanicsLab Grid Report
- Monitoring by Sblomars
- Trouble Tickets


Documentation

- AUP
- Charter
- Federation
- Guides
- Incident Response
- Mailing Lists
- MoU
- Tutorial

2.3. Slice Profile (User)



TECHNISCHE
UNIVERSITÄT
DARMSTADT



EmanicsLab

david.hausheer@ps.tu-darmstadt...

- ▼ Logout
- ▼ My Account
- ▼ Sites
 - My Site
- ▼ Nodes
 - My Site Nodes
- ▼ **My Slices**
 - Slices
- ▼ About MyPLC
 - PLCAPI doc
 - NMAPI doc

Services

- **EmanicsLab Grid Report**
- **Monitoring by Sblomars**
- **Trouble Tickets**

Home

Slices - all peers

My slices **My site slices**

Search and ☒

PEER	NAME	USERS	U	N	EXP. D/M/Y
ELC	tud_testtest	david.hausheer@ps.tu-darmstadt.de	1	0	09/07/2013

Notes
U = number of users
N = number of nodes
Hold down the shift key to select multiple columns to sort
Enter & or | in the search area to switch between **AND** and **OR** search modes

2.3. Add Nodes to a Slice (User)

▼ 26 more nodes available

1 2

Search and ☒ Items/page

HOSTNAME	AU	ST	RES	+
emanicslab2.upit.ro	ELC	failboot...		<input type="checkbox"/>
emanicslab1.upit.ro	ELC	boot...		<input type="checkbox"/>
emanicslab2.lab.ifi.lmu.de	ELC	boot...		<input type="checkbox"/>
test.ps.tu-darmstadt.de	ELC	failboot...		<input type="checkbox"/>
emanicslab1.unige.ch	ELC	safeboot...		<input type="checkbox"/>
emanicslab2.unige.ch	ELC	safeboot...		<input type="checkbox"/>
emanicslab1.informatik.unibw-muenchen.de	ELC	boot		<input type="checkbox"/>
emanicslab2.csg.uzh.ch	ELC	boot		<input type="checkbox"/>
emanics1.ee.ucl.ac.uk	ELC	boot		<input type="checkbox"/>
emanicslab1.csg.uzh.ch	ELC	boot		<input type="checkbox"/>
host2-plb.loria.fr	ELC	boot		<input type="checkbox"/>
emanicslab1.eecs.jacobs-university.de	ELC	boot		<input type="checkbox"/>
host1-plb.loria.fr	ELC	boot		<input type="checkbox"/>
planck233ple.test.iminds.be	ELC	boot		<input type="checkbox"/>
moscu.upc.es	ELC	boot		<input type="checkbox"/>
emanicslab2.eecs.jacobs-university.de	ELC	boot		<input type="checkbox"/>
emanicslab1.man.poznan.pl	ELC	boot		<input type="checkbox"/>
emanicslab1.ewi.utwente.nl	ELC	boot		<input type="checkbox"/>
emanicslab2.ewi.utwente.nl	ELC	boot		<input type="checkbox"/>
emanicslab2.man.poznan.pl	ELC	boot		<input type="checkbox"/>

1 2

Items [1 - 20] of 26 -- Page 1 of 2

Add selected

2.3. Add Attributes (User)



▼ No initscript ?

Update initscripts

shared initscript name none ▼

slice initscript

Update initscripts

▼ No tag !!

Search and ☒

NAME	VALUE	NODE	NODEGROUP	
Choose Tag				

Remove selected

All Nodes ▼ No Nodegroup ▼ Set Tag

2.3. Renew Slice (User)

▼ Expires Tuesday Jul-09-13 13:13:50 GMT - Renew this slice

Important: Please take this opportunity to review and update your slice information in the Details tab.


PlanetLab's security model requires that anyone who is concerned about a slice's activity be able to immediately learn about that slice. The details that you provide are your public explanation about why the slice behaves as it does. Be sure to describe the **kind of traffic** that your slice generates, and how it handles material that is under **copyright**, if relevant.

The PlanetLab Operations Centres regularly respond to concerns raised by third parties about site behaviour. Most incidents are resolved rapidly based upon the publicly posted slice details. However, when these details are not sufficiently clear or accurate, and we cannot immediately reach the slice owner, we must delete the slice.

Duration: One more month (Tuesday Aug-06-13 13:13:50 GMT) ▼ Renew

NOTE: Slices cannot be renewed beyond another 4 week(s) (Tuesday Aug-06-13 13:13:50 GMT).

2.3. Login to a Node (User)



```
uzh_debian@emanicslab1:~  
  
hausheer@myhost ~  
$ ssh -l uzh_test -i /home/hausheer/.ssh/id_rsa emanicslab1.csg.uzh.ch  
Last login: Mon Jan 14 00:30:43 2008 from 21-90.79-83.cust.bluewin.ch  
[uzh_test@emanicslab1 ~]$
```


2.3. Install Software (User)



```
uzh_debian@emanicslab1:~$ su
bash-3.00# yum install joe
Setting up Install Process
Setting up repositories
Reading repository metadata in from local files
Parsing package install arguments
Resolving Dependencies

Dependencies Resolved

=====
Package                Arch      Version      Repository    Size
=====
Installing:
joe                    i386      3.3-2        core          320 k
Updating for dependencies:
glibc                  i686      2.4-11       updates       4.9 M
glibc-common           i386      2.4-11       updates       16 M

Transaction Summary
=====
Install      1 Package(s)
Update      2 Package(s)
Remove      0 Package(s)
Total download size: 21 M
Is this ok [y/N]: y
```

2.3. Further Guides

❖ <http://www.planet-lab.eu/doc/guides>

- User's Guide
- Principal Investigator's Guide (PI Guide)
- Technical Contact's Guide (Tech Guide)
- Site Migration Guide




3. Mobile Testbeds

Motivation, Requirements, CrowdLab, PhoneLab,
SmartNets Lab, Federation

3.1. Observations

- ❖ Access from anywhere and anytime
- ❖ Mobile applications become increasingly large-scale and traffic-intensive
 - E.g. mobile video streaming
- ❖ Smart phone users become service providers themselves
 - E.g. opportunistic / participatory sensing



3.1. Motivation

- ❖ Planet Lab Benefit: Geographic diversity
- ❖ Mobile Testbed: Mobility, Sensing
- ❖ Mobile experimentation is hard
 - Mobility is fundamental but difficult to model
 - Location affects system behavior
 - Connectivity can be unpredictable
 - Devices are power constrained
- ❖ Existing Approaches
 - Programmed mobility
 - e.g., Orbit => Limited mobility
 - Vehicular mobility
 - e.g., CarTel, DieselNet => Limited locations
 - Human mobility
 - e.g., AnonySense => Limited access to resources



3.2. Requirements

What do we want?

- ❖ Want experiments in any location
 - Cafes, shops, airports, etc
- ❖ Want to observe all levels of the stack
 - OS, drivers and applications
- ❖ Want local interactions
 - Ad-hoc network, sensing

How can we get there?

- ❖ Want experiments in any location
 - Rely on volunteer devices
- ❖ Want to observe all levels of the stack
 - Rely on hypervisor for isolation
- ❖ Want local interactions
 - Need coordination among devices

3.3. CrowdLab: An Architecture for Volunteer Mobile Testbeds

- ❖ Expose mobile apps to real mobile human contexts like PlanetLab exposes systems to the real Internet
- ❖ Low-level access to wireless state
- ❖ Dual mode wireless abstraction
- ❖ Supports gang-scheduled instances
- ❖ Can support multiple architectures (x86 & ARM)

3.4. PhoneLab: A Participatory Smartphone Testbed

- ❖ Scale: 1000 Nexus S 4G Smartphones
 - Providing an order of magnitude more participants than typical smartphone experiments
 - Enabling large-scale experiments

- ❖ Realism: Used by Real People
 - Distributed to students, staff, and faculty, enabling realistic experiments
 - Eliminating the need to recruit participants
 - Providing up to 1000 participants in the same area

- ❖ Power: Kernel & App Experimentation
 - Providing access to both the kernel layer and the app layer
 - Enabling low-level smartphone experimentation
 - Overcoming limitations of App Store or Android Market


3.5. SmartNets

❖ SmartNets: A mobile testbed at TU Darmstadt

- 12 Android smart phones (Type: Google Nexus S)
- 3 wireless access points
- Core switch running OpenFlow

❖ Purpose

- Experimentation with large-scale distributed mobile applications
- Evaluation of energy-efficiency and scalability aspects
- Integration of smart networking concepts
 - P2P & service overlay networks (SON)
 - Programmable networks (OpenFlow)
- Federation with other mobile testbeds



3.5. SmartNets Application Use Case: P2P-based Live Streaming


- ❖ Functional requirements:
 - Setup and sharing of a new live video stream by any of the clients
 - Discovery and retrieving of the stream by a potentially large number of other clients
 - Decentralized (based on P2P techniques), not based on IP multicast
- ❖ Non-functional requirements:
 - Performance: fluid playback
 - Delay: small differences in the playback delay
 - Energy consumption: consume as less energy as possible, balanced over all clients
 - Robust against peer churn: peers (except the source) may leave the overlay



3.5. Measuring Energy Consumption on Smartphones





- ❖ Hardware usually does not provide this information
- ❖ Hardware consists of many different components (WiFi, GPS, CPU, ...)
 - Each component might be in a different state (awake, asleep, ...)
 - Single components may provide multiple services
- ❖ Usually models are used




3.5. Example App: PowerTutor

- ❖ Enables fine-grained measurements:
 - Per app consumption
 - Consumption of different components




3.5. Example App: PowerTutor

- ❖ A modified version of PowerTutor has been integrated into SmartNets
 - Centralized measurement of all the phones in the overlay
 - Monitoring via web interface




Starts
profiler
service



3.6. Federation of Mobile Testbeds

- ❖ Combination of diverse mobile nodes into a large-scale testbed
- ❖ Integration of fixed and mobile nodes
 - E.g. mobile access to cloud services
- ❖ Issues
 - PlanetLab integration
 - High dynamicity of nodes
 - Scarcity of resources
 - Exchange policies



3.6. Federation: Issues

❖ High dynamicity

- Asynchronous sliver creation and experiment setup needed
 - Enqueue experiment, execute when enough resources are available
 - Dynamic adaptation of slivers during experiments

❖ Scarcity of resources

- Maximum slice resources need to be redefined
 - Idea: New maximum energy budget per slice

❖ Exchange Policies

- Integration of fixed and mobile nodes: need to define equivalent of sliver in fixed and mobile testbed
- Energy consumption as an additional metric for exchange
 - Time-invariant, correlates with induced costs