# **Network Security (NetSec)**



Summer 2015

**Chapter 01: Fundamentals** 

Module 02: Networking 101



**Prof. Dr.-Ing. Matthias Hollick** 

Technische Universität Darmstadt Secure Mobile Networking Lab - SEEMOO Department of Computer Science Center for Advanced Security Research Darmstadt - CASED

Mornewegstr. 32 D-64293 Darmstadt, Germany Tel.+49 6151 16-70922, Fax. +49 6151 16-70921 http://seemoo.de or http://www.seemoo.tu-darmstadt.de

Prof. Dr.-Ing. Matthias Hollick matthias.hollick@seemoo.tu-darmstadt.de





# Networking 101



# **Learning Objectives**



Obtain a common understanding of communication networks

- Identify the most important basic concepts of communication networking
- Understand layering, services, protocols, etc.
- Have some idea of the philosophy behind the Internet and understand its fundamental design principles
- Identify networking aspects that might be directly security related

"The shortest distance between two points is usually under repair."

—Anonymous





# **Overview of this Module**



- (1) What we consider to be a network throughout the lecture
- (2) Layered architectures (including the Internet architecture)
- (3) Basic network primitives and interaction with security
- (4) Recommended readings

Chapter 01, Module 02






# Computer and Communication Networks



#### Computer and communication networks

- Several autonomous computers/end-systems/processors interconnected with the aim to exchange information
- Here "interconnected" means: data can be exchanged, resources can be shared





# **Scope of Networks**



Distance between Processors	CPUs jointly located on/in	Example		
<= 0,1 m	Boards	usually tightly coupled multi- processor system		
1 m	Systems	e.g. body area network e.g. sensor area network e.g. storage area network		
10 m	Rooms			
100 m	Buildings	LAN		
1 km	Campuses			
10 km	Cities	MAN		
100 km	Countries (national)			
1.000 km	Continents (intern.)	WAN		
>= 10.000 km	Planets			

• Structure: point-to-point vs. point-to-multipoint

• Media: wireline vs. wireless





# **Motivating Layers**




Problem: communication engineering means

- Multitude of partially very complex tasks
- Interaction of differing systems and components

#### Simplification:

- To introduce abstraction levels of varying functionalities
- General module, preferable: layer, level

See example







# **Layers**



#### ISO-OSI (Open Systems Interconnection) Reference Model

- Model for layered communication systems
- Defines fundamental concepts and terminology
- Defines 7 layers and their functionalities (see textbook for details)

#### ISO-OSI Reference Model


- Layer 1: physical (PHY)
- Layer 2: data link (MAC)
  - Has neighbor-neighbor revelance
- Layer 3: network (NET)
  - Has relevance on entire path between systems
- Layer 4: transport (TRANS)
  - Has end-to-end revelance
- Layer 5-7: application, presentation, session (APP)





# **Data Flow**







# **Protocols, Services**




#### Protocol:

 Communication between same-layer entities

#### Service:

Communication between adjacent Layers



Implementation: each layer provides some API (or SAP – Service Access Point) to that above it; the provided service can be

- Reliable: bit stream or packets, arrive in same order at other end
- Datagram: send chunk of data, maybe it gets there, possibly lost, duplicated, out-of-order; usually detects nonmalicious errors






# **Protocol**

# **Communication between same-layer Entities**





#### **Protocol**


- rules for syntax (format) and semantics (contents)
  - of the data transfer (frames, packet, message) occurring between the respective, active peer entities
- analogy: programming, protocol corresponds to
  - realization of the data type (procedures, etc.)
  - the "interior" of the object





# **Service**Communication between adjacent Layers





#### Service

- multiple of primitives/operations/functions
  - which one layer offers to the upper next layer
- characterized by the "interface"
- does not reveal anything about the implementation
- analogy: programming, service corresponds to
  - abstract data type, object





# Connection-oriented vs. **Connectionless Service**



#### Connection-oriented:

- 3 phases:
  - 1. to connect
  - 2. to transfer data
  - 3. to disconnect
- Analogy: telephony
- Applications such as:
  - Regularly recurring data units, longer duration
  - Quality of service guarantees (time, bandwidth)

#### Connectionless (Datagram Service)

- Transfer of isolated data units
- Analogy: letter delivery
- Applications such as one-time data transfer, short duration



13





# **Confirmed and Unconfirmed Service**





#### Service primitives

- Define a service in an abstract manner
- Are usually parameterized

#### Types:

- service.REQUEST
- Service.INDICATION
- service.RESPONSE
- service.CONFIRMATION









# Reliability (a cousin to Security)



# **Integrity Checks**



# Nonmalicious integrity checks

- Send it multiple times
- VRC (vertical redundancy check) parity within byte
- LRC (parity over a bit of all the bytes in a block)
- LRC+VRC catches what bit errors?

	Data							Parity
Row 1	1	1	0	1	0	1	1	1
Row 2	1	1	1	1	1	1	1	1
Row 3	0	1	0	1	0	1	0	1
Row 4	0	0	1	1	0	0	1	1
Parity Row	0	1	0	0	1	1	1	0

- CRC (make message + checksum divisible by the "CRC polynomial")
- Cryptographic integrity check





### Intuition behind CRC



CRC (make message + checksum divisible by the "CRC polynomial")

# CRC Example

- Pretend message is long number
- Suppose "CRC polynomial" is some number, say 17
- Suppose message is 5283
- Multiply it by 100=528300
- 528300 is 8 mod 17
- Subtract 8 from 528300=528292. Send that
- Rcvr checks divisibility by 17. If not, error. If so, round to nearest 100, then truncate to get message





# (Two-way Reliable) Protocols



Those of you who attended KN or TK or NCS: which protocols do you know to be reliable/unreliable?

#### Two-way reliable protocols

- Used sometimes in layer 2, sometimes in layer 4 (e.g., TCP, but not UDP)
- Was more popular in layer 2 when lossy links
- Basic idea the same, sequence number on data, sequence number on ack, pipelining
- If n sequence numbers (and wrap around), how many can you send?

Where to put reliability: L2? L4?





# **Summary**





# **Acks & Recommended Reading**



#### Selected slides of this chapter courtesy of

- Radia Perlman
- Andrew Tanenbaum
- Lars Wolf, Ralf Steinmetz and the KN-team at KOM

#### Recommended reading

- Networking textbook, including the one by Kurose et al., the one by Tanenbaum, etc.
- [KuRo2010] James F. Kurose, Keith W. Ross: Computer Networking: A Top-Down Approach, 5th Edition, Addison Wesley, 2010, ISBN: 9780136079675





# **Copyright Notice**



This document has been distributed by the contributing authors as a means to ensure timely dissemination of scholarly and technical work on a non-commercial basis. Copyright and all rights therein are maintained by the authors or by other copyright holders, notwithstanding that they have offered their works here electronically.

It is understood that all persons copying this information will adhere to the terms and constraints invoked by each author's copyright. These works may not be reposted without the explicit permission of the copyright holder.



# **Contact**





