


Speculative Decoding


K-V Cache



Speculative Decoding

title={Fast Inference from Transformers
via Speculative Decoding},
arXiv={2211.17192},
citations={152}

[START] japan ' s benchmark ~~bond~~ n
[START] japan ' s benchmark nikkei 22 ~~7~~ 5
[START] japan ' s benchmark nikkei 225 index rose 22 ~~7~~ 6
[START] japan ' s benchmark nikkei 225 index rose 226 . 69 ~~7~~ points
[START] japan ' s benchmark nikkei 225 index rose 226 . 69 points , or 1 . 5 percent , to 10 , 98 ~~5~~ 9
[START] japan ' s benchmark nikkei 225 index rose 226 . 69 points , or 1 . 5 percent , to 10 , 989 . 79 ~~7~~ in
[START] japan ' s benchmark nikkei 225 index rose 226 . 69 points , or 1 . 5 percent , to 10 , 989 . 79 in ~~tokyo~~ late
[START] japan ' s benchmark nikkei 225 index rose 226 . 69 points , or 1 . 5 percent , to 10 , 989 . 79 in late morning trading . [END]



Speculative Decoding

$$q(x) \leq p(x) \quad \text{OK}$$

Random Sample

$$q(x) > p(x) \quad 1 - \frac{p(x)}{q(x)} \quad \text{If reject: resample} \quad p'(x) = \text{norm}(\max(0, p(x) - q(x)))$$

Proof:

$$\text{Note that as } p'(x) = \text{norm}(\max(0, p(x) - q(x))) = \frac{p(x) - \min(q(x), p(x))}{\sum_{x'} (p(x') - \min(q(x'), p(x')))} = \frac{p(x) - \min(q(x), p(x))}{1 - \beta},$$

$$P(x = x') = P(\text{guess accepted}, x = x') + P(\text{guess rejected}, x = x')$$

$$P(\text{guess accepted}, x = x') = q(x') \min(1, \frac{p(x')}{q(x')}) = \min(q(x'), p(x'))$$

$$P(\text{guess rejected}, x = x') = (1 - \beta)p'(x') = p(x') - \min(q(x'), p(x'))$$

$$P(x = x') = \min(p(x'), q(x')) + p(x') - \min(p(x'), q(x')) = p(x').$$

Speculative Decoding

$$E(\# \text{ generated tokens}) = \frac{1 - \alpha^{\gamma+1}}{1 - \alpha}$$

$$\alpha = 1 - E(D_{LK}(p, q)) = E(\min(p, q))$$

α	γ	OPERATIONS	SPEED
0.6	2	1.53X	1.96X
0.7	3	1.58X	2.53X
0.8	2	1.23X	2.44X
0.8	5	1.63X	3.69X
0.9	2	1.11X	2.71X
0.9	10	1.60X	6.86X


TASK	M_q	TEMP	γ	α	SPEED
ENDE	T5-SMALL ★	0	7	0.75	3.4X
ENDE	T5-BASE	0	7	0.8	2.8X
ENDE	T5-LARGE	0	7	0.82	1.7X
ENDE	T5-SMALL ★	1	7	0.62	2.6X
ENDE	T5-BASE	1	5	0.68	2.4X
ENDE	T5-LARGE	1	3	0.71	1.4X
CNNDM	T5-SMALL ★	0	5	0.65	3.1X
CNNDM	T5-BASE	0	5	0.73	3.0X
CNNDM	T5-LARGE	0	3	0.74	2.2X
CNNDM	T5-SMALL ★	1	5	0.53	2.3X
CNNDM	T5-BASE	1	3	0.55	2.2X
CNNDM	T5-LARGE	1	3	0.56	1.7X

Speculative Decoding


M_p	M_q	SMPL	α
GPT-LIKE (97M)	UNIGRAM	T=0	0.03
GPT-LIKE (97M)	BIGRAM	T=0	0.05
GPT-LIKE (97M)	GPT-LIKE (6M)	T=0	0.88
GPT-LIKE (97M)	UNIGRAM	T=1	0.03
GPT-LIKE (97M)	BIGRAM	T=1	0.05
GPT-LIKE (97M)	GPT-LIKE (6M)	T=1	0.89
T5-XXL (EnDe)	UNIGRAM	T=0	0.08
T5-XXL (EnDe)	BIGRAM	T=0	0.20
T5-XXL (EnDe)	T5-SMALL	T=0	0.75
T5-XXL (EnDe)	T5-BASE	T=0	0.80
T5-XXL (EnDe)	T5-LARGE	T=0	0.82
T5-XXL (EnDe)	UNIGRAM	T=1	0.07
T5-XXL (EnDe)	BIGRAM	T=1	0.19
T5-XXL (EnDe)	T5-SMALL	T=1	0.62
T5-XXL (EnDe)	T5-BASE	T=1	0.68
T5-XXL (EnDe)	T5-LARGE	T=1	0.71

T5-XXL (CNNDM)	UNIGRAM	T=0	0.13
T5-XXL (CNNDM)	BIGRAM	T=0	0.23
T5-XXL (CNNDM)	T5-SMALL	T=0	0.65
T5-XXL (CNNDM)	T5-BASE	T=0	0.73
T5-XXL (CNNDM)	T5-LARGE	T=0	0.74
T5-XXL (CNNDM)	UNIGRAM	T=1	0.08
T5-XXL (CNNDM)	BIGRAM	T=1	0.16
T5-XXL (CNNDM)	T5-SMALL	T=1	0.53
T5-XXL (CNNDM)	T5-BASE	T=1	0.55
T5-XXL (CNNDM)	T5-LARGE	T=1	0.56
LAMDA (137B)	LAMDA (100M)	T=0	0.61
LAMDA (137B)	LAMDA (2B)	T=0	0.71
LAMDA (137B)	LAMDA (8B)	T=0	0.75
LAMDA (137B)	LAMDA (100M)	T=1	0.57
LAMDA (137B)	LAMDA (2B)	T=1	0.71
LAMDA (137B)	LAMDA (8B)	T=1	0.74


Medusa



Medusa




Medusa



(a)

Speedup on different categories for 7B model



(b)

Medusa

Model Name	Vicuna-7B	Zephyr-7B	Vicuna-13B	Vicuna-33B
Acc. rate	3.47	3.14	3.51	3.01
Overhead	1.22	1.18	1.23	1.27
Quality	6.18 (+0.01)	7.25 (-0.07)	6.43 (-0.14)	7.18 (+0.05)

title={Medusa: Simple LLM Inference Acceleration Framework with Multiple Decoding Heads},
arXiv={2401.10774},
citations={23}

Thank You