RotorNet: A Scalable, Low-complexity, Optical Datacenter Network

William “Max” Mellette

Rob McGuinness, Arjun Roy, Alex Forencich,
George Papen, Alex C. Snoeren, and George Porter

UC San Diego

Toward 100+ Petabit/second datacenters

Challenge: deliver (very) low-cost bandwidth at scale

Co-design:
Protocol
Topology
Hardware



- **New protocols**
  Load balancing, congestion control, …
- **New topologies**
  Jellyfish, Longhop, Slimfly, …
- **New hardware**
  Optical circuit switching, RF/optical wireless, …
- ~~**Same switching model**~~

New "Rotor" switching model

RotorNet → "Future-proof" bandwidth (2× today) + simple control + …

Don’t packet switches work fine?

Electronic Packet Switch



Fat Tree (Sigcomm ‘08)



Packet switch capacity growth:
~ 2× / 2 years

<

Network capacity growth:
~ 2× / year

(A. Singh et al., SIGCOMM 2015)

Optical switching – benefits & barriers

Electronic Packet Switch

Copper:
25 Gb/s



I/O limits bandwidth

$$$



Optical Circuit Switch

Fiber:
> 1 Tb/s



Cheap, future-proof bandwidth

Optical switching – benefits & barriers



Data plane doesn't scale to entire datacenter!



Rotor switching model simplifies control



Rotor switches have a simpler implementation

Optical Crossbar:



Optical Rotor switch:



- Cost and complexity scale with:

	Ports	Matchings (<< Ports)
Ex. 2,048 ports:	4,096 mirrors 2,048 directions	2 mirrors 16 directions

RotorNet architecture overview



1-hop forwarding over Rotor switch

- Wait for direct path:



Uniform traffic → 100% throughput

- But datacenter traffic can be sparse …

1-hop forwarding & sparse traffic = low throughput

- Wait for direct path:

Node 1 → 4



Problem: single flow → 33% throughput

- Hint at improvement: network is underutilized

2-hop forwarding better for sparse traffic

- Not new: Valiant (’82) & Chang et al. (’02)



Throughput: **Single flow** **33% (1-hop)** → **100% (2-hop)**

Uniform traffic **100% (1-hop)** → **50% (2-hop)**

- Optimization: can we adapt between **1-hop** and **2-hop** forwarding?

RotorLB: adapting between 1 & 2-hop forwarding

RotorLB (Load Balancing) overview:

- Default to 1-hop forwarding
- Send traffic over 2 hops only when there is extra capacity
- Discover capacity using in-band pairwise protocol:



→ **RotorLB is fully distributed**

Throughput of forwarding approaches (256 ports)



[1] Ghobadi et al. Sigcomm '16
[2] Roy et al. Sigcomm '15

Throughput of forwarding approaches (256 ports)



[1] Ghobadi et al. Sigcomm '16
[2] Roy et al. Sigcomm '15

RotorNet architecture overview



- RotorLB → **Distributed, high throughput**
- **Topology?**
- Optical Rotor switch → **More scalable**
- Rotor switching model → **Simpler control**

How should we build a network from Rotor switches?

UCSDCSE

At large scale:

- **High latency:** Sequentially step through many matchings
- **Fabrication challenge:** Monolithic Rotor switch with many matchings
- **Single point of failure**



Distributing Rotor matchings = lower latency

Fault tolerant

Reduced latency:

- Access matchings in parallel

Simplifies Rotor switches:

- Matchings << ports
- More scalable, less expensive



Rotor switching is feasible today

Validated feasibility of entire architecture:
(8 endpoints)



100× faster switching than crossbar

Prototype Rotor switch



RotorNet scales to 1,000s of racks

- Rotor switch design point: 2,048 ports, 1,000× faster switching than crossbar

  Details in: W. Mellette et al., *Journal of Lightwave Technology* ’16
  W. Mellette et al., *OFC* ’16

- 2,048-rack data center:
  → **Latency (cycle time) = 3.2 ms**
- Faster than 10 ms crossbar reconfiguration time
- Hybrid network for low-latency applications



RotorNet component comparison

Network	# Packet switches	# Transceivers	# Rotor switches	Bandwidth
3:1 Fat Tree	2.6 k	103 k	0	**33 %**
RotorNet, 10% packet	2.3 k	84 k	128	**70 %**
RotorNet, 20% packet	2.5 k	96 k	128	**70 %**

RotorNet delivers:

- Today: Bandwidth 2× less expensive
- Future: Cost advantage grows with bandwidth
- **Benefits of optical switching without control complexity**

A scalable, low-complexity optical datacenter network

RotorNet architecture:







- **RotorLB** → Distributed, high throughput
- **RotorNet topology** → Fast cycle time
- **Optical Rotor switch** → More scalable
- **Rotor switching model** → Simpler control

This work was supported by the NSF and a gift from Facebook