


Adaptive Large Neighborhood Search applied to mixed vehicle routing problems

David Pisinger, Stefan R pke

NEXT workshop 2006



Vehicle Routing Problem

Depot	Multiple depots
Customers	Site dependant
Vehicles	Pickup-delivery
Capacity of vehicle	Backhauls
Time windows	Open VRP

Storeroom optimization (MBS)


Exact methods (Jepsen, Petersen, Spoorendonk)

Heuristic methods (Pisinger, R pke)


- Unified algorithm, several VRP variants
- Automatic parameter tuning

Adaptive Large Neighborhood Search

- Framework for combining several solution approaches
- Based on Large Neighborhood Search
- Applied to 12 variants of VRP
- Encouraging results (improved 40% instances)




Adaptive Large Neighborhood Search




- Local search framework
- Simple algorithms compete to modify current solution
- Choose algorithm to *destroy* solution
- Choose algorithm to *repair* solution
- Accept new solution according to local search framework
- Choose *destroy* and *repair* alg. based on past score

Extension of LNS (Shaw [1998]) VNS (Hansen and Mladenovic [1999])




Properties of ALNS

Large Neighborhood Search



- Suited for tightly coupled problems where small neighborhoods cannot escape local minima
- Robust to changes in input, structure of instances
- Calibration quite limited
- The more reasonable neighborhoods the better performance
- Not “either-or” but “both-and”


Destroy Neighborhoods



Given a solution x remove q requests

- Random removal
- Worst removal (remove request)
- Related removal (distance between PD requests)
- Cluster removal (related removal, few routes)
- Time-oriented removal (requests served same time)
- Historical node-pair removal (best solution obtained using edge)
- Historical request-pair removal (two requests served by same vehicle in good solution)

Repair Neighborhoods




Given some partial routes, insert q requests in *parallel*

- Basic greedy heuristic
- Regret heuristics (best-second-best)

Master local search framework

Simulated annealing


- Accept $x \rightarrow x'$ probability $e^{-\frac{f(x')-f(x)}{T}}$




- cooling scheme $T = T \cdot c$
- automatic calibration of T_0

Noising

- Simulated annealing ensures diversification at master level
- Need diversification in destroy and repair heuristics



Roulette wheel selection




Each insert-remove pair is measured wrt. three criteria

- new global best solution
- new solution, improved solution value
- new solution, worse solution value

Observed score $\bar{\pi}_{i,j}$

Smoothened score $\pi_{i,j}$ weighted sum of observed and historic score



- pickup and delivery problem with time windows (PDPTW)
- the VRP with backhauls (VRPB)
- mixed VRP with backhauls (MVRPB)
- multi-depot mixed VRP with backhauls (MDMVRPB)
- VRP with backhauls and time windows (VRPBTW)
- mixed VRP with backhauls and time windows (MVRPBTW)
- VRP with simultaneous deliveries and pickups (VRPSDP)
- **VRP with time windows (VRPTW)**
- **capacitated VRP (CVRP)**
- **multi-depot VRP (MDVRP)**
- **site dependent VRP (SDVRP)**
- **open VRP (OVRP)**


Rich Pickup and Delivery Problem with time windows

- Multiple depots
- Precedence constraints
- Site dependent
- Capacity of vehicles

- Performed on 3GHz Pentium 4 computer
- Almost same parameters as in previous papers
- Up to 60 requests are removed in each iteration
- Average of 10 runs (5 if very time consuming)
- Same time limit as competing algorithms (mostly)
- Details in Tech Report Pisinger and R pke [2005].

Compared to state-of-art algorithms when paper was submitted (2004)

VRP with Time Windows (large size)




minimize: (1) vehicles, (2) distance

Gehring and Homberger [1999], 300 instances, 200-1000 customers

Gehring and Homberger [1999], Gehring and Homberger [2001], Bent and Hentenryck [2004], Bouthillier and Crainic [2004], Br sly et al. [2003], Mester and Br sly [2004]

- ALNS best at minimizing number of vehicles
- Improved 122/300 large-scale instances

Multi depot VRP



minimize: distance

Cordeau et al. [1997] (Christofides, Eilon, Gillett, Johnson, Chao) 50–360 customers


Chao et al. [1993]

Renaud et al. [1996]

Cordeau et al. [1997]

- Improved 15/33

Site dependent VRP



minimize: distance


Nag et al. [1988], Cordeau and Laporte [2001]
27–1008 customers

Cordeau and Laporte [2001]

Chao et al. [1999]

- Improved 30/35

Capacitated VRP



minimize: distance

Christofides et al. [1979], 50-200 customers


Golden et al. [1998], up to 483 customers

Li et al. [2004] up to 1200 customers

Toth and Vigo [2003] Li et al. [2004], Cordeau et al. [1997, 2000], Ergun et al. [2003], Prins [2004], Tarantilis and Kiranoudis [2002], Mester and Bräysy [2004], Berger and Barkaoui [2003], Reimann et al. [2004]

- cannot compete with Mester and Bräysy [2004]
- On par with remaining
- Improved 1 (Golden), 3 (Li)

Open VRP



minimize: (1) vehicles, (2) distance
route ends when last request serviced

Christofides et al. [1979], Fisher [1994] 50–199 customers
Brandão [2004] and Fu et al. [2003]

- Improved 11/16

Conclusion

General ALNS framework

- Robust wrt. size and structure of instance
- Unified solution method
- Applied to 12 variants of VRP
- Overall framework same, parameters almost same
- Improved 183/486 for VRPTW, CVRP, MDVRP, SDVRP, OVRP

Future applications of ALNS

- Branch-and-cut (cuts compete)
- Branch-and-price (pricing algorithms compete)
- Manpower planning
- Timetable problems

- Mixture of good and less good heuristics lead to better solutions than using good heuristics solely
- Necessary to hierarchically controls the search, such that well-performing heuristics are given most influence, but such that all heuristics participate to the solution process
- Obtain robust and well-performing algorithm

References

Russel Bent and Pascal Van Hentenryck. A two-stage hybrid local search for the vehicle routing problem with time windows, 2004. To appear in Transportation Science.

J. Berger and M. Barkaoui. A new hybrid genetic algorithm for the capacitated vehicle routing problem. *Journal of the Operational Research Society*, 54:1254–1262, 2003.

Alexandre Le Bouthillier and Teodor Gabriel Crainic. A cooperative parallel meta-heuristic for the vehicle routing problem with time windows. *Computers and Operations Research*, 2004. to appear.

José Brandão. A tabu search algorithm for the open vehicle routing problem. *European Journal of Operational Research*, 157(3):552–564, 2004.

Olli Bräysy, Geir Hasle, and Wout Dullaert. A multi-start local search algorithm for the vehicle routing problem with time windows. *European Journal of Operational Research*, 2003. to appear.

I-Ming Chao, Bruce Golden, and Edward Wasil. A computational study of a new heuristic for the site-dependent vehicle routing problem. *INFOR*, 37(3):319–336, 1999.

I.M. Chao, B. L. Golden, and E.A. Wasil. A new heuristic for the multi-depot vehicle routing problem that improves upon best-known solutions. *Am. J. Math. Mgmt. Sci.*, 13:371–406, 1993.

Nicos Christofi des, Aristide Mingozzi, and Paolo Toth. The vehicle routing problem. In Nicos Christofi des, Aristide Mingozzi, Paolo Toth, and Claudio Sandi, editors, *Combinatorial Optimization*, chapter 11, pages 315 – 338. John Wiley & Sons, 1979.

Jean-François Cordeau, Michel Gendreau, and Gilbert Laporte. A tabu search heuristic for periodic and multi-depot vehicle routing problems. *Networks*, 30:105–119, 1997.

Jean-François Cordeau and Gilbert Laporte. A tabu search algorithm for the site dependent vehicle routing problem with time windows. *INFOR*, 39:292–298, 2001.

Jean-François Cordeau, Gilbert Laporte, and Anne Mercier. A unified tabu search heuristic for vehicle routing problems with time windows. *Journal of the Operational Research Society*, 52:928–936, 2000.

Ozlem Ergun, James B. Orlin, and Abran Steele-Feldman. Creating very large scale neighborhoods out of smaller ones by compounding moves: a study on the vehicle routing problem. Working Paper, Massachusetts Institute of Technology, 2003.

M. Fisher. Optimal solution of vehicle routing problems using minimum k -trees. *Operations Research*, 42(4):626–642, 1994.

Zhuo Fu, Richard W. Eglese, and Leon Li. A tabu search heuristic for the open vehicle routing problem. Technical Report 2003/042, Lancaster University Management School, Lancaster, United Kingdom, 2003.

Hermann Gehring and Jörg Homberger. A parallel hybrid evolutionary metaheuristic for the vehicle routing problem with time windows. In K. Miettinen, M. Mäkelä, and J. Toivanen, editors, *Proceedings of EUROGEN99 – Short Course on Evolutionary Algorithms in Engineering and Computer Science*, pages 57–64. University of Jyväskylä, 1999.

Hermann Gehring and Jörg Homberger. A parallel two-phase metaheuristic for routing problems with

Bruce L. Golden, Edward A. Wasil, James P. Kelly, and I-Ming Chao. Metaheuristics in vehicle routing. In T.G. Crainic and G. Laporte, editors, *Fleet Management and Logistics*, pages 33–56. Kluwer, Boston (MA), 1998.

Pierre Hansen and Nenad Mladenovic. An introduction to variable neighborhood search. In Stefan Voss et al., editor, *Metaheuristics, Advances and Trends in Local Search Paradigms for Optimization*, pages 433–458. Kluwer Academic Publishers, Dordrecht, 1999.

Feiyue Li, Bruce Golden, and Edward Wasil. Very large-scale vehicle routing: new test problems, algorithms, and results. *Computers and Operations Research*, 2004. To appear.

David Mester and Olli Bräysy. Active guided evolution strategies for large-scale vehicle routing problems with time windows. *Computers and Operations Research*, 2004. to appear.

Barindra Nag, Bruce L. Golden, and Arjang Assad. Vehicle routing with site dependencies. In B.L. Golden and A.A. Assad, editors, *Vehicle Routing: Methods and Studies*, pages 149–159. Elsevier Science Publishers B.V, 1988.

David Pisinger and Stefan Røpke. A general heuristic for vehicle routing problems. Technical Report 05/01, DIKU, University of Copenhagen, 2005.

Christian Prins. A simple and effective evolutionary algorithm for the vehicle routing problem. *Computers and Operations Research*, 31:1985–2002, 2004.

M. Reimann, K. Doerner, and R.F. Hartl. D-ants: Savings based ants divide and conquer the vrp. *Computers and Operations Research*, 31:563–591, 2004.

Jacques Renaud, Gilbert Laporte, and Fayez F. Boctor. A tabu search heuristic for the multi-depot vehicle routing problem. *Computers and Operations Research*, 23(3):229–235, 1996.

Paul Shaw. Using constraint programming and local search methods to solve vehicle routing problems. In *CP-98 (Fourth International Conference on Principles and Practice of Constraint Programming)*, volume 1520 of *Lecture Notes in Computer Science*, pages 417–431, 1998.

C.D. Tarantilis and C.T. Kiranoudis. Boneroute: an adaptive memory-based method for effective fleet management. *Annals of Operations Research*, 115:227–241, 2002.

Paulo Toth and Daniele Vigo. The granular tabu search and its application to the vehicle-routing problem. *INFORMS Journal on Computing*, 15(4):333–346, 2003.