

Supplementary Material

Complexity

Note that we could also transform the original problem into a “multiple choice branching” problem. Which is to find a subset $A' \in \mathcal{A}$ in a directed graph $G=(V, \mathcal{A})$ and a partition of \mathcal{A} into disjoint sets A_1, A_2, \dots, A_m with the sum of weights in subset A' larger than a given positive integer K such that A' contains no cycles and at most one arc from each partition. By reducing into a 3-SAT problem, the “multiple choice branching” problem turns out to be NP-Complete (Garey, Johnson and Stockmeyer 1976) (Garey and Johnson 1979). To be more specific, it remains NP-Complete even if G is strongly connected and all weights are equal as finding maximum weight branching was viewed as a 2-matroid intersection problem that could be solved in polynomial time (Garey, Johnson and Tarjan 1976). In other words, a maximum weight branching can be viewed as a maximum weight directed spanning tree for a strongly connected graph. Similarly, if the graph is symmetric, the problem become equivalent to the multiple choice spanning tree problem, another 2-matroid intersection problem that can be solved in polynomial time (Hassin and Levin 2012)(Henn 2007).

In spite of its $O(n^4)$ -seemingly structure depicted, the time complexity for our proposed BDPST algorithm ends up in $O(SEV/S)$ or $O(EV)$ since the worst case is to traverse each grid in all directions. Where E refers to the number of maximum directions one spanning tree could try (this variable is set to 2 in our Algorithm, equals to branching factor in the worst case), S refers to the total number of selected and recommended stations, and V indicates the number of grids labelled with road in the given area. Note that V is far greater than S and E . Meanwhile, the preprocessing time is $O(V^2)$ for grid-preprocessing with station-recommendation of constructing a look-up table for further indexing. Which indicates that runtime for our BDPST is not strongly related to the total number of selected and recommended stations (S) but mainly affected by the size of given area (V).

As we mentioned, existing route-planning algorithms are not applicable in our case. But for comparison, the time complexity to deal with our problem utilizing Brute-force searching turns out to be $O(E^V)$, A* algorithm to be $O(E^V)$, Dijkstra’s algorithm and Prim’s algorithm to be $O(EV \log V)$ or $O(EV + V \log V)$ depending on implementation, and bidirectional search to be $O(SE^{V/S})$. Since V is far greater than S and E in general (note that E refers to the branching factor instead of total number of edges in graph here), could turn out to find approximate solutions in affordable/reasonable time compared to all aforementioned route-planning algorithms..

Pseudocode

Algorithm BDPST

```

1  MV ← { /*must_visit_grids given by user*/ }
2  RM ← ∅
3  foreach g ∈ MV do
4    foreach g' ∈ area do
5      gd(g',g) ← G(g',g) × pf(g)
6      agd(g') ← agd(g') + gd(g',g) /*precomputed*/
7  foreach r from 0 to number_of_recommendation
8    foreach g ∈ area and g ∉ MV ∪ RM do
9      Let max be the maximum g of pf(g) - agd(g)
10   RM ← RM ∪ {max}
11   foreach g' ∈ area do
12     gd(g',g) ← G(g',g) × pf(g)
13     agd(g') ← agd(g') + gd(g',g) /*look-up table instead*/
14   foreach g ∈ area do
15     sid(g) ← -1
16     if g ∈ MV ∩ RM then
17       root[starter_id] ← g
18       set[starter_id,0].add(root[starter_id])
19       sid(g) ← starter_id
20       count[starter_id] ← 0
21       foreach g' ∈ area do
22         agd[starter_id,0](g') ← agd(g') - 2 × gd(g',g)
23   route ← ∅
24   foreach i from 0 to infinite do
25     foreach s ∈ MV ∩ RM do
26       foreach st ∈ set[s,i] do
27         if count(s) ≥ 2 then break
28         nst ← st /*deep copy*/
29         pt(nst,s) ← 0
30         foreach g ∈ nearby and reachable in road do
31           if sid(g) = s then
32             Renew parameters if current path is better
33           else
34             Let choice be the maximum g of
35               (agd[s,i](g) + distScore(unvisited(MV)))
36           if choice ≠ null
37             nst.visit(choice)
38             if sid(g) ≠ 1 and count(sid(g)) < 2 then
39               route.addseg(nst, obj(g))
40               count(s) ← count(s) + 1
41               count(sid(g)) ← count(sid(g)) + 1
42               if success to form a route then break
43             foreach g' ∈ area do
44               agd[s,i](g')
45                 ← agd[s,i](g') - 2 × gd(g', root[sid(g')])
46             if count(sid(g)) = 2 /*count(s) = 2*/ then
47               foreach st ∈ MV ∩ RM and g' ∈ area do
48                 agd[st,i](g') ← agd[st,i](g') -
49                   2 × gd(g', root[sid(g')])
50             else
51               set[s,i+1].add(nst)
52               sid(g) ← s
53               obj(g) ← nst
54               pt(st,s) ← pt(st,s) + 1
55               if pt(st,s) > 1 then
56                 set[s,i].delete(st)
57               set[s,i+1].add(set[s,i])
58               agd[s,i+1] ← agd[s,i]
59   if success to form a route then break

```