Run Configurations

Create, manage, and run configurations

type filter text

- Acceleo Application
- ▼ ATL Transformation
  - pisc2pipews
  - piServiceComposition2piPEWS
  - **piUseCase2piServiceProcess**
- Chain
- ▼ Eclipse Application
  - Eclipse Application
- Java Applet
- Java Application
- JET Transformation
- JUnit
- JUnit Plug-in Test
- MWE Workflow
- Operational QVT Interpreter
- OSGi Framework
- SCA Application
- Task Context Plug-in Test
- Task Context Test

Filter matched 19 of 19 items

Name: piUseCase2piServiceProcess

○ ATL Configuration   **○ Advanced**   **▤ Common**

ATL Module
                                                                        1
/Transformation-piUseCase2piServiceProcess/atl_file/piUseCase2piServiceProcess.atl   [Workspace...]

Metamodels
                                                                        2
PiUseCase: /Transformation-piUseCase2piServiceProcess/source/PiUseCases.ecore

☐ Is metametamodel   [Workspace...] [File system...] [EMF Registry...]
                                                                        3
PiServiceProcess: /Transformation-piUseCase2piServiceProcess/target/PiServiceProcess.ecore

☐ Is metametamodel   [Workspace...] [File system...] [EMF Registry...]

Source Models
                                                                        4
IN: /Transformation-piUseCase2piServiceProcess/example_test/music.piusecase

conforms to PiUseCase   [Workspace...] [File system...]

Target Models
                                                                        5
OUT: /Transformation-piUseCase2piServiceProcess/example_test/music.piserviceprocess

conforms to PiServiceProcess   [Workspace...] [File system...]

[Apply]   [Revert]

                                                                        6
[Close]   [Run]