

# Funcons-beta: Generating

The P<sub>Plan</sub>CompS Project

Funcons-beta/Computations/Normal/Generating/Generating.cbs\*

## Generating

[ *Type* **atoms**  
  *Entity* **used-atom-set**  
  *Funcon* **initialise-generating**  
  *Funcon* **fresh-atom**  
  *Funcon* **use-atom-not-in** ]

*Meta-variables*  $T <: \text{values}$

*Built-in Type* **atoms**

**atoms** is the type of values used as distinguishable tags. Notation for individual atoms is not provided.

*Entity*  $\langle \_, \text{used-atom-set}(\_ : \text{sets}(\text{atoms})) \rangle \longrightarrow \langle \_, \text{used-atom-set}(\_ : \text{sets}(\text{atoms})) \rangle$

*Built-in Funcon* **initialise-generating** $(\_ : \Rightarrow T) : \Rightarrow T$

The initial value of the **used-atom-set**(*SA*) entity is unspecified. It could contains atoms that are reserved for internal use.

*Funcon* **fresh-atom** :  $\Rightarrow \text{atoms}$

**fresh-atom** computes an atom distinct from all previously computed atoms.

---

\*Suggestions for improvement: [plancomps@gmail.com](mailto:plancomps@gmail.com).  
Issues: <https://github.com/plancomps/CBS-beta/issues>.

$$\text{Rule} \frac{\text{element-not-in}(\text{atoms}, SA) \rightsquigarrow A}{\langle \text{fresh-atom}, \text{used-atom-set}(SA) \rangle \longrightarrow \langle A, \text{used-atom-set}(\text{set-insert}(A, SA)) \rangle}$$

*Funcon*  $\text{use-atom-not-in}(\_ : \text{sets}(\text{atoms})) : \Rightarrow \text{atoms}$

$\text{use-atom-not-in}(SA)$  computes an atom not in the set  $SA$ , and inserts it in the  $\text{used-atom-set}(SA')$  entity, in case it was not previously used.

$$\text{Rule} \frac{\text{element-not-in}(\text{atoms}, SA) \rightsquigarrow A}{\langle \text{use-atom-not-in}(SA : \text{sets}(\text{atoms})), \text{used-atom-set}(SA') \rangle \longrightarrow \langle A, \text{used-atom-set}(\text{set-insert}(A, SA')) \rangle}$$