Languages-beta: OC-L-07-Expressions *

The PLanCompS Project

`OC-L-07-Expressions.cbs` | PLAIN | PRETTY

OUTLINE

Language "OCaml Light"

---

*Suggestions for improvement: `plancomps@gmail.com`.
Reports of issues: `https://github.com/plancomps/CBS-beta/issues`.

7 Expressions

Syntax

E : expr ::= value-path
| constant
| '(' expr ')'
| 'begin' expr 'end'
| '(' expr ':' typexpr ')'
| expr comma-expr^{+}
| expr '::' expr
| '[' expr semic-expr* ']'
| '[' expr semic-expr* ';' ']'
| '[|' expr semic-expr* '|]'
| '[|' expr semic-expr* ';' '|]'
| '{' field '=' expr semic-field-expr* '}'
| '{' field '=' expr semic-field-expr* ';' '}'
| '{' expr 'with' field '=' expr semic-field-expr* '}'
| '{' expr 'with' field '=' expr semic-field-expr* ';' '}'
| expr argument^{+}
| prefix-symbol expr
| '-' expr
| '-.' expr
| expr infix-op-1 expr
| expr infix-op-2 expr
| expr infix-op-3 expr
| expr infix-op-4 expr
| expr infix-op-5 expr
| expr infix-op-6 expr
| expr infix-op-7 expr
| expr infix-op-8 expr
| expr '.' field
| expr '.(' expr ')'
| expr '.(' expr ')' '<-' expr
| 'if' expr 'then' expr ('else' expr)?
| 'while' expr 'do' expr 'done'
| 'for' value-name '=' expr ('to' | 'downto') expr 'do' expr 'done'
| expr ';' expr
| 'match' expr 'with' pattern-matching
| 'function' pattern-matching
| 'fun' pattern^{+} '->' expr
| 'try' expr 'with' pattern-matching
| let-definition 'in' expr
| 'assert' expr

A : argument ::= expr

PM : pattern-matching ::= pattern '->' expr pattern-expr*
| '|' pattern '->' expr pattern-expr*

LD : let-definition ::= 'let' ('rec')? let-binding and-let-binding*

LB : let-binding ::= pattern '=' expr
| value-name pattern^{+} '=' expr
| value-name ':' poly-typexpr '=' expr

ALB : and-let-binding ::= 'and' let-binding

CE : comma-expr ::= ',' expr

SE : semic-expr ::= ';' expr

Rule ⟦ '(' E ')' ⟧ : expr = ⟦ E ⟧

Rule ⟦ 'begin' E 'end' ⟧ : expr = ⟦ E ⟧

Rule ⟦ '(' E ':' T ')' ⟧ : expr = ⟦ E ⟧

Rule ⟦ E_1 E_2 A A^* ⟧ : expr = ⟦ ('(' E_1 E_2 ')') A A^* ⟧

Rule ⟦ PS E ⟧ : expr = ⟦ ('(' PS ')') E ⟧

Rule ⟦ '-' E ⟧ : expr = ⟦ ('(' '~-' ')') E ⟧

Rule ⟦ '-.' E ⟧ : expr = ⟦ ('(' '~-.' ')') E ⟧

Rule ⟦ E_1 *IO-1* E_2 ⟧ : expr = ⟦ ('(' *IO-1* ')') E_1 E_2 ⟧

Rule ⟦ E_1 *IO-2* E_2 ⟧ : expr = ⟦ ('(' *IO-2* ')') E_1 E_2 ⟧

Rule ⟦ E_1 *IO-3* E_2 ⟧ : expr = ⟦ ('(' *IO-3* ')') E_1 E_2 ⟧

Rule ⟦ E_1 *IO-4* E_2 ⟧ : expr = ⟦ ('(' *IO-4* ')') E_1 E_2 ⟧

Rule ⟦ E_1 *IO-5* E_2 ⟧ : expr = ⟦ ('(' *IO-5* ')') E_1 E_2 ⟧

Rule ⟦ E_1 '&' E_2 ⟧ : expr = ⟦ E_1 '&&' E_2 ⟧

Rule ⟦ E_1 'or' E_2 ⟧ : expr = ⟦ E_1 '||' E_2 ⟧

Rule ⟦ E_1 *IO-8* E_2 ⟧ : expr = ⟦ ('(' *IO-8* ')') E_1 E_2 ⟧

Rule ⟦ E_1 '.(' E_2 ')' ⟧ : expr = ⟦ 'array_get' E_1 E_2 ⟧

Rule ⟦ E_1 '.(' E_2 ')' '<-' E_3 ⟧ : expr = ⟦ 'array_set' E_1 E_2 E_3 ⟧

Rule ⟦ 'if' E_1 'then' E_2 ⟧ : expr = ⟦ 'if' E_1 'then' E_2 'else' ('(' ')') ⟧

Rule ⟦ 'fun' P '->' E ⟧ : expr = ⟦ 'function' P '->' E ⟧

Rule ⟦ 'fun' P P^+ '->' E ⟧ : expr = ⟦ 'fun' P '->' ('fun' P^+ '->' E) ⟧

Rule ⟦ '[' E SE^* ';' ']' ⟧ : expr = ⟦ '[' E SE^* ']' ⟧

Rule ⟦ '[|' E SE^* ';' '|]' ⟧ : expr = ⟦ '[|' E SE^* '|]' ⟧

Rule ⟦ '{' F '=' E SFE^* ';' '}' ⟧ : expr = ⟦ '{' F '=' E SFE^* '}' ⟧

Rule ⟦ '{' E_1 'with' F '=' E_2 SFE^* ';' '}' ⟧ : expr =
⟦ '{' E_1 'with' F '=' E_2 SFE^* '}' ⟧

Rule ⟦ '|' P '->' E PE^* ⟧ : pattern-matching = ⟦ P '->' E PE^* ⟧

Rule ⟦ VN ':' PT '=' E ⟧ : let-binding = ⟦ VN '=' E ⟧

Rule ⟦ VN P^+ '=' E ⟧ : let-binding = ⟦ VN '=' ('fun' P^+ '->' E) ⟧

```
Semantics  evaluate⟦ _ : expr ⟧ : ⇒ implemented-values
Rule       evaluate⟦ VP ⟧ = bound(value-name⟦ VP ⟧)
Rule       evaluate⟦ CNST ⟧ = value⟦ CNST ⟧
Rule       evaluate⟦ '(' E ':' T ')' ⟧ = evaluate⟦ E ⟧
Rule       evaluate⟦ E1 ',' E2 CE* ⟧ =
             tuple(evaluate-comma-sequence⟦ E1 ',' E2 CE* ⟧)
Rule       evaluate⟦ E1 '::' E2 ⟧ = cons(evaluate⟦ E1 ⟧, evaluate⟦ E2 ⟧)
Rule       evaluate⟦ '[' E SE* ']' ⟧ = [evaluate-semic-sequence⟦ E SE* ⟧]
Rule       evaluate⟦ '[|' E SE* '|]' ⟧ =
             vector(
               left-to-right-map(
                 allocate-initialised-variable(implemented-values, given),
                 evaluate-semic-sequence⟦ E SE* ⟧))
Rule       evaluate⟦ '[|' '|]' ⟧ = vector( )
Rule       evaluate⟦ '{' F '=' E SFE* '}' ⟧ =
             record(collateral(evaluate-field-sequence⟦ F '=' E SFE* ⟧))
Rule       evaluate⟦ '{' E1 'with' F '=' E2 SFE* '}' ⟧ =
             record(
               map-override(
                 evaluate-field-sequence⟦ F '=' E2 SFE* ⟧,
                 checked record-map(evaluate⟦ E1 ⟧)))
Rule       evaluate⟦ CSTR E ⟧ =
             variant(constr-name⟦ CSTR ⟧, evaluate⟦ E ⟧)
Otherwise  evaluate⟦ E1 E2 ⟧ =
             apply(evaluate⟦ E1 ⟧, evaluate⟦ E2 ⟧)
Rule       evaluate⟦ E '.' F ⟧ =
             record-select(evaluate⟦ E ⟧, field-name⟦ F ⟧)
Rule       evaluate⟦ E1 '&&' E2 ⟧ =
             if-true-else(evaluate⟦ E1 ⟧, evaluate⟦ E2 ⟧, false)
Rule       evaluate⟦ E1 '||' E2 ⟧ =
             if-true-else(evaluate⟦ E1 ⟧, true, evaluate⟦ E2 ⟧)
Rule       evaluate⟦ 'if' E1 'then' E2 'else' E3 ⟧ =
             if-true-else(evaluate⟦ E1 ⟧, evaluate⟦ E2 ⟧, evaluate⟦ E3 ⟧)
Rule       evaluate⟦ 'while' E1 'do' E2 'done' ⟧ =
             while(evaluate⟦ E1 ⟧, effect(evaluate⟦ E2 ⟧))
Rule       evaluate⟦ 'for' VN '=' E1 'to' E2 'do' E3 'done' ⟧ =
             effect(
               left-to-right-map(
                 case-match(pattern-bind(value-name⟦ VN ⟧), evaluate⟦ E3 ⟧),
                 integer-sequence(evaluate⟦ E1 ⟧, evaluate⟦ E2 ⟧)))
Rule       evaluate⟦ 'for' VN '=' E1 'downto' E2 'do' E3 'done' ⟧ =
             effect(
               left-to-right-map(
                 case-match(pattern-bind(value-name⟦ VN ⟧), evaluate⟦ E3 ⟧),
                 reverse integer-sequence(evaluate⟦ E2 ⟧, evaluate⟦ E1 ⟧)))
Rule       evaluate⟦ E1 ';' E2 ⟧ =
             sequential(effect(evaluate⟦ E1 ⟧), evaluate⟦ E2 ⟧)
Rule       evaluate⟦ 'match' E 'with' PM ⟧ =
             give(
               evaluate⟦ E ⟧,
               else(match⟦ PM ⟧, throw(ocaml-light-match-failure)))
Rule       evaluate⟦ 'function' PM ⟧ =
             function closure(
```

Expression sequences and maps

Semantics evaluate-comma-sequence⟦ _ : (expr comma-expr*) ⟧ : (⇒ implemented-values)$^+$
Rule evaluate-comma-sequence⟦ E_1 ',' E_2 CE^* ⟧ =
evaluate⟦ E_1 ⟧, evaluate-comma-sequence⟦ E_2 CE^* ⟧
Rule evaluate-comma-sequence⟦ E ⟧ = evaluate⟦ E ⟧

Semantics evaluate-semic-sequence⟦ _ : (expr semic-expr*) ⟧ : (⇒ implemented-values)$^+$
Rule evaluate-semic-sequence⟦ E_1 ';' E_2 SE^* ⟧ =
evaluate⟦ E_1 ⟧, evaluate-semic-sequence⟦ E_2 SE^* ⟧
Rule evaluate-semic-sequence⟦ E ⟧ = evaluate⟦ E ⟧

Semantics evaluate-field-sequence⟦ _ : (field '=' expr semic-field-expr*) ⟧ : (⇒ envs)$^+$
Rule evaluate-field-sequence⟦ F_1 '=' E_1 ';' F_2 '=' E_2 SFE^* ⟧ =
{field-name⟦ F_1 ⟧ ↦ evaluate⟦ E_1 ⟧},
evaluate-field-sequence⟦ F_2 '=' E_2 SFE^* ⟧
Rule evaluate-field-sequence⟦ F '=' E ⟧ = {field-name⟦ F ⟧ ↦ evaluate⟦ E ⟧}

Matching

Semantics match⟦ _ : pattern-matching ⟧ : (implemented-values ⇒ implemented-values)$^+$
Rule match⟦ P_1 '->' E_1 '|' P_2 '->' E_2 PE^* ⟧ =
match⟦ P_1 '->' E_1 ⟧, match⟦ P_2 '->' E_2 PE^* ⟧
Rule match⟦ P '->' E ⟧ = case-match(evaluate-pattern⟦ P ⟧, evaluate⟦ E ⟧)

Value definitions

Semantics define-values⟦ _ : let-definition ⟧ : ⇒ environments
Rule define-values⟦ 'let' LB ALB^* ⟧ = define-values-nonrec⟦ LB ALB^* ⟧
Rule define-values⟦ 'let rec' LB ALB^* ⟧ =
recursive(
set(bound-ids-sequence⟦ LB ALB^* ⟧),
define-values-nonrec⟦ LB ALB^* ⟧)

Semantics define-values-nonrec⟦ _ : (let-binding and-let-binding*) ⟧ : ⇒ environments
Rule define-values-nonrec⟦ LB_1 'and' LB_2 ALB^* ⟧ =
collateral(define-values-nonrec⟦ LB_1 ⟧, define-values-nonrec⟦ LB_2 ALB^* ⟧)
Rule define-values-nonrec⟦ P '=' E ⟧ =
else(
match(evaluate⟦ E ⟧, evaluate-pattern⟦ P ⟧),
throw(ocaml-light-match-failure))

Semantics bound-ids-sequence⟦ _ : (let-binding and-let-binding*) ⟧ : ids$^+$
Rule bound-ids-sequence⟦ LB ⟧ = bound-id⟦ LB ⟧
Rule bound-ids-sequence⟦ LB_1 'and' LB_2 ALB^* ⟧ =
bound-id⟦ LB_1 ⟧, bound-ids-sequence⟦ LB_2 ALB^* ⟧

Semantics bound-id⟦ _ : let-binding ⟧ : ids
Rule bound-id⟦ VN '=' E ⟧ = value-name⟦ VN ⟧
Otherwise bound-id⟦ LB ⟧ = fail