Select a definition

D'Arome API v1

WebAppComp3011 | v1

1.0.0 OAS 3.1

/openapi/v1.json

Servers

https://localhost:7227/

UserCabinet

GET `/api/UserCabinet` Given an id, delete from the db

Parameters Try it out

No parameters

Responses

Code	Description	Links
200	OK Media type text/plain Controls `Accept` header. **Example Value** Schema	*No links*

```
[
  {
    "id": 0,
    "username": "string",
    "perfumeId": 0,
    "userId": 0,
    "comments": "string"
  }
]
```

POST `/api/UserCabinet` Add entry to user cabinet

Parameters Try it out

No parameters

Request body required application/json

Example Value Schema

```
{
  "id": 0,
  "username": "string",
  "perfumeId": 0,
  "userId": 0,
  "comments": "string"
}
```

Responses

Code	Description	Links
200	OK Media type text/plain Controls `Accept` header. **Example Value** Schema	*No links*

```
{
  "id": 0,
  "username": "string",
  "perfumeId": 0,
  "userId": 0,
  "comments": "string"
}
```

GET `/api/UserCabinet/{id}` Get a specific user cabinet entry by id

Parameters

Try it out

Name	Description
id * required `integer($int32)` *(path)*	id

Responses

Code	Description	Links
200	OK Media type text/plain Controls `Accept` header. **Example Value** Schema `{ "id": 0, "username": "string", "perfumeId": 0, "userId": 0, "comments": "string" }`	*No links*

PUT `/api/UserCabinet/{id}`
Given an id, update the corresponding user cabinet entry with the provided data

Parameters Try it out

Name	Description
id * required `integer | string($int32)` *(path)*	id

Request body required application/json

Example Value Schema

```
{
  "id": 0,
  "username": "string",
  "perfumeId": 0,
  "userId": 0,
  "comments": "string"
}
```

Responses

Code	Description	Links
200	OK	*No links*

DELETE `/api/UserCabinet/{id}` Given an id, delete cabinet entry from the db

Parameters

Cancel

Name	Description
id * required `integer | string($int32)` *(path)*	id

Execute

Responses

Code	Description	Links
200	OK	*No links*

GET `/api/UserCabinet/user/{userId}`
get all cabinet entries for a specifc user - giving a user cabine

Parameters

Try it out

Name	Description
userId * required `integer | string($int32)` *(path)*	userId

Responses

Code	Description	Links
200	OK Media type text/plain Controls `Accept` header. **Example Value** Schema	*No links*

```
[
  {
    "id": 0,
    "username": "string",
    "perfumeId": 0,
    "userId": 0,
    "comments": "string"
  }
]
```

GET `/api/UserCabinet/perfume/{perfumeId}`
which users have a specific perfume in their cabinet

Parameters Try it out

Name	Description
perfumeId * required `integer | string($int32)` *(path)*	perfumeId

Responses

Code	Description	Links
200	OK Media type text/plain Controls `Accept` header. **Example Value** Schema	*No links*

```
[
  {
    "id": 0,
    "username": "string",
    "perfumeId": 0,
    "userId": 0,
```

Code	Description	Links

```
    "comments": "string"
  }
]
```

UserPreference

GET `/api/UserPreference` Get all user preferences

Parameters Try it out

No parameters

Responses

Code	Description	Links
200	OK Media type text/plain Controls `Accept` header. **Example Value** Schema	*No links*

```
[
  {
    "id": 0,
    "userId": 0,
    "prefVal": "string",
    "prefType": "string"
  }
]
```

POST `/api/UserPreference` Add a new user preference

Parameters Try it out

No parameters

Request body required application/json

Example Value Schema

```
{
  "id": 0,
  "userId": 0,
  "prefVal": "string",
  "prefType": "string"
}
```

Responses

Code	Description	Links
200	OK Media type text/plain Controls `Accept` header. **Example Value** Schema	*No links*

```
{
  "id": 0,
  "userId": 0,
  "prefVal": "string",
  "prefType": "string"
}
```

GET `/api/UserPreference/{id}` Get a specific user preference by id

Parameters

Try it out

Name	Description
id * required `integer($int32)` *(path)*	id

Responses

Code	Description	Links
200	OK Media type text/plain	*No links*

Code	Description	Links
	Controls `Accept` header.	

Example Value Schema

```
{
  "id": 0,
  "userId": 0,
  "prefVal": "string",
  "prefType": "string"
}
```

PUT `/api/UserPreference/{id}` Update a user preference by id

Parameters Try it out

Name	Description
id * required `integer | string($int32)` *(path)*	id

Request body required application/json

Example Value Schema

```
{
  "id": 0,
  "userId": 0,
  "prefVal": "string",
  "prefType": "string"
}
```

Responses

Code	Description	Links
200	OK	*No links*

DELETE `/api/UserPreference/{id}` Delete a user preference by id

Parameters Try it out

Name	Description
id * required integer | string($int32) *(path)*	id

Responses

Code	Description	Links
200	OK	*No links*

GET `/api/UserPreference/user/{userId}` Get all preferences for a specific user

Parameters

Try it out

Name	Description
userId * required integer | string($int32) *(path)*	userId

Responses

Code	Description	Links
200	OK Media type text/plain Controls `Accept` header. **Example Value** Schema	*No links*

```
[
  {
    "id": 0,
    "userId": 0,
    "prefVal": "string",
    "prefType": "string"
```

Code	Description	Links

```
    }
  ]
```

UserProfile

GET `/api/UserProfile` Get all user profiles from db

Parameters Try it out

No parameters

Responses

Code	Description	Links
200	OK Media type text/plain Controls `Accept` header. **Example Value** Schema	*No links*

```
[
  {
    "id": 0,
    "username": "string",
    "password": "string",
    "name": "string",
    "firstLogin": true,
    "cabinet": [
      {
        "id": 0,
        "username": "string",
        "perfumeId": 0,
        "userId": 0,
        "comments": "string"
      }
    ]
  }
]
```

POST `/api/UserProfile` For creating new user profiles

Parameters Try it out

No parameters

Request body required

application/json

Example Value Schema


```
{
  "id": 0,
  "username": "string",
  "password": "string",
  "name": "string",
  "firstLogin": true,
  "cabinet": [
    {
      "id": 0,
      "username": "string",
      "perfumeId": 0,
      "userId": 0,
      "comments": "string"
    }
  ]
}
```


Responses

Code	Description	Links
200	OK Media type text/plain Controls `Accept` header. **Example Value** Schema	*No links*


```
{
  "id": 0,
  "username": "string",
  "password": "string",
  "name": "string",
  "firstLogin": true,
  "cabinet": [
    {
      "id": 0,
      "username": "string",
      "perfumeId": 0,
      "userId": 0,
      "comments": "string"
    }
  ]
}
```


GET `/api/UserProfile/{id}` Get user profile by id

Parameters Try it out

Name	Description
id * required integer($int32) *(path)*	id

Responses

Code	Description	Links
200	OK Media type text/plain Controls `Accept` header. **Example Value** Schema	*No links*

```
{
  "id": 0,
  "username": "string",
  "password": "string",
  "name": "string",
  "firstLogin": true,
  "cabinet": [
    {
      "id": 0,
      "username": "string",
      "perfumeId": 0,
      "userId": 0,
      "comments": "string"
    }
  ]
}
```

PUT `/api/UserProfile/{id}` Update user profile by id

Parameters

Try it out

Name	Description
id * required integer($int32) *(path)*	id

Request body required

application/json

Example Value Schema


```
{
  "id": 0,
  "username": "string",
  "password": "string",
  "name": "string",
  "firstLogin": true,
  "cabinet": [
    {
      "id": 0,
      "username": "string",
      "perfumeId": 0,
      "userId": 0,
      "comments": "string"
    }
  ]
}
```


Responses

Code	Description	Links
200	OK	*No links*

DELETE `/api/UserProfile/{id}` Delete user profile from db

Parameters Try it out

Name	Description
id * required `integer($int32)` *(path)*	id

Responses

Code	Description	Links
200	OK	*No links*

GET `/api/UserProfile/username/{username}` Get user profile by username

Parameters

Try it out

Name	Description
username * required `string` *(path)*	username

Responses

Code	Description	Links
200	OK Media type text/plain Controls `Accept` header. **Example Value** Schema	*No links*

```
{
  "id": 0,
  "username": "string",
  "password": "string",
  "name": "string",
  "firstLogin": true,
  "cabinet": [
    {
      "id": 0,
      "username": "string",
      "perfumeId": 0,
      "userId": 0,
      "comments": "string"
    }
  ]
}
```

Frag

GET `/api/Frag/{id}` Return Fragrance based on id

Parameters

Try it out

Name	Description
id * required integer($int32) (path)	id

Responses

Code	Description	Links
200	OK Media type text/plain Controls Accept header. Example Value Schema	No links

```
{
  "id": 0,
  "fragUrl": "string",
  "fragName": "string",
  "brand": "string",
  "country": "string",
  "gender": "string",
  "rating": 0.1,
  "year": "string",
  "notes": {
    "top": [
      "string"
    ],
    "middle": [
      "string"
    ],
    "base": [
      "string"
    ]
  },
  "accords": [
    "string"
  ],
  "perfumers": "string"
}
```

PUT /api/Frag/{id} Edit a fragrance based on id

Parameters

Try it out

Name	Description
id * required integer($int32) *(path)*	id

Request body required

application/json

Example Value Schema

```
{
  "id": 0,
  "fragUrl": "string",
  "fragName": "string",
  "brand": "string",
  "country": "string",
  "gender": "string",
  "rating": 0.1,
  "year": "string",
  "notes": {
    "top": [
      "string"
    ],
    "middle": [
      "string"
    ],
    "base": [
      "string"
    ]
  },
  "accords": [
    "string"
  ],
  "perfumers": "string"
}
```

Responses

Code	Description	Links
200	OK	*No links*

DELETE `/api/Frag/{id}` Given an id, delete from the db

Parameters Try it out

Name	Description
id * required integer($int32) (path)	id

Responses

Code	Description	Links
200	OK	*No links*

GET `/api/Frag` Return all Fragrances

Parameters Try it out

No parameters

Responses

Code	Description	Links
200	OK Media type text/plain Controls `Accept` header. **Example Value** Schema	*No links*


```
[
  {
    "id": 0,
    "fragUrl": "string",
    "fragName": "string",
    "brand": "string",
    "country": "string",
    "gender": "string",
    "rating": 0.1,
    "year": "string",
    "notes": {
      "top": [
        "string"
      ],
      "middle": [
```

Code	Description	Links


```
            "string"
          ],
          "base": [
            "string"
          ]
        },
        "accords": [
          "string"
        ],
        "perfumers": "string"
      }
    ]
```


POST `/api/Frag` Add a new fragrance to the db, return the id

Parameters Try it out

No parameters

Request body required applicatio son

Example Value Schema


```
{
  "id": 0,
  "fragUrl": "string",
  "fragName": "string",
  "brand": "string",
  "country": "string",
  "gender": "string",
  "rating": 0.1,
  "year": "string",
  "notes": {
    "top": [
      "string"
    ],
    "middle": [
      "string"
    ],
    "base": [
      "string"
    ]
  },
  "accords": [
    "string"
  ],
  "perfumers": "string"
}
```


Responses

Code	Description	Links
200	OK	*No links*

Media type

text/plain

Controls `Accept` header.

Example Value Schema


```
{
  "id": 0,
  "fragUrl": "string",
  "fragName": "string",
  "brand": "string",
  "country": "string",
  "gender": "string",
  "rating": 0.1,
  "year": "string",
  "notes": {
    "top": [
      "string"
    ],
    "middle": [
      "string"
    ],
    "base": [
      "string"
    ]
  },
  "accords": [
    "string"
  ],
  "perfumers": "string"
}
```


GET `/api/Frag/name/{name}` Return fragrances by name (case-insensitive, partial match)

Parameters Try it out

Name	Description
name * required `string` *(path)*	name

Responses

Code	Description	Links
200	OK	*No links*

Code	Description	Links

Media type

text/plain

Controls `Accept` header.

Example Value Schema


```
[
  {
    "id": 0,
    "fragUrl": "string",
    "fragName": "string",
    "brand": "string",
    "country": "string",
    "gender": "string",
    "rating": 0.1,
    "year": "string",
    "notes": {
      "top": [
        "string"
      ],
      "middle": [
        "string"
      ],
      "base": [
        "string"
      ]
    },
    "accords": [
      "string"
    ],
    "perfumers": "string"
  }
]
```


GET `/api/Frag/brand/{brandName}` Return fragrances by brand (case-insensitive, partial match)

Parameters Try it out

Name	Description
brandName * required `string` *(path)*	brandName

Responses

Code	Description	Links
200	OK	*No links*

Media type

Code	Description	Links

text/plain

Controls `Accept` header.

Example Value Schema


```
[
  {
    "id": 0,
    "fragUrl": "string",
    "fragName": "string",
    "brand": "string",
    "country": "string",
    "gender": "string",
    "rating": 0.1,
    "year": "string",
    "notes": {
      "top": [
        "string"
      ],
      "middle": [
        "string"
      ],
      "base": [
        "string"
      ]
    },
    "accords": [
      "string"
    ],
    "perfumers": "string"
  }
]
```


GET `/api/Frag/accord/{accord}` Return fragrances by accord (case-insensitive, partial match)

Parameters Try it out

Name	Description
accord * required `string` *(path)*	accord

Responses

Code	Description	Links
200	OK Media type text/plain	*No links*

Code	Description	Links
	Controls `Accept` header.	

Example Value Schema


```
[
  {
    "id": 0,
    "fragUrl": "string",
    "fragName": "string",
    "brand": "string",
    "country": "string",
    "gender": "string",
    "rating": 0.1,
    "year": "string",
    "notes": {
      "top": [
        "string"
      ],
      "middle": [
        "string"
      ],
      "base": [
        "string"
      ]
    },
    "accords": [
      "string"
    ],
    "perfumers": "string"
  }
]
```


GET `/api/Frag/note/{note}`

Return fragrances by their note, top middle or base (case-insensitive, partial match)

Parameters Try it out

Name	Description
note * required `string` *(path)*	note

Responses

Code	Description	Links
200	OK Media type **text/plain** Controls `Accept` header.	*No links*

Code	Description	Links

Example Value Schema


```
[
  {
    "id": 0,
    "fragUrl": "string",
    "fragName": "string",
    "brand": "string",
    "country": "string",
    "gender": "string",
    "rating": 0.1,
    "year": "string",
    "notes": {
      "top": [
        "string"
      ],
      "middle": [
        "string"
      ],
      "base": [
        "string"
      ]
    },
    "accords": [
      "string"
    ],
    "perfumers": "string"
  }
]
```


Schemas

Fragrance

Collapse all object

id integer | string int32 matches ^-?(?:0|[1-9]\d*)$

fragUrl string

fragName string

brand string

country string

gender string

rating number | string float matches ^-?(?:0|[1-9]\d*)(?:\.\d+)?(?:[eE][+-]?\d+)?$

year string

notes Expand all object

accords Expand all array<string>

perfumers string

Notes

Collapse all object

top Expand all array<string>

middle Expand all array<string>

base Expand all array<string>

UserCabinet Collapse all object

id integer | string int32 matches ^-?(?:0|[1-9]\d*)$

username string

perfumeId null | integer | string int32 matches ^-?(?:0|[1-9]\d*)$

userId null | integer | string int32 matches ^-?(?:0|[1-9]\d*)$

comments string

UserPreference Collapse all object

id integer | string int32 matches ^-?(?:0|[1-9]\d*)$

userId integer | string int32 matches ^-?(?:0|[1-9]\d*)$

prefVal string

prefType string

UserProfile Collapse all object

id integer | string int32 matches ^-?(?:0|[1-9]\d*)$

username string

password string

name string

firstLogin boolean

cabinet Expand all array<object>