
HYDRAULIC PARTICULARS HNSS MAIN CANAL FROM KM 159.550 TO 160.050


HNSS PROJECT PHASE I

REVEISED HYDRAULIC PARTICULARS PROPOSED OF HNSS MAIN CANAL FROM KM 155.00 TO 176.425

SL.No	Re	each in K	М		Hydraulic Particulars											LOSS (m)			BED LEVEL		Full Supply Level			
	FROM	то	Distance (IN Mts)	Required Discharge (Cumecs)	Bed Width (IN Mts)	F.S.D (IN Mits)		Side Slopes	COFF OF RUGOSITY"n'	A(m2)	P(m)	R=A/P IN Mts	R=2/3	VELOCITY M/Sec	Designed Discharge (Cumecs)	DUE TO BED FALL	DUE TO CM & CD STRUCTURES	TOTAL	AT START (M)	AT END (M)	AT START (M)	AT END (M)	SOIL STRATA AVAILABLE	
1	2	3	4	5	6	7	80	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
3	159.550	160.050	500	95.46	17.25	4.7	6500	1.0	0.03	103.165	30.544	3.378	2.251	0.931	96.047	0.77	0.000	0.77	438.400	438.323	443.100	443.023	HDR/F&F	



REACH STARTING



REACH ENDING