LL

Concrete external wall - Roof Cassete



Wooden roof cassetes:
13mm plywood
50mm air gap
350mm mineral wool
0.2mm DPM layer
1:40 slope

Roof finish:
DPC layer
2 layers of roofing felt,
1st is 3mm
2nd is 4mm Asphalt Felt torched-in

Concrete external walls:
420 sandwich element
70mm outer leaf
250mm insulation
100mm inner leaf

Suspended ceiling:

38X73mm ceiling battens
brackets that attach battens wooden hanger
Gypsum 12,5mm boards with 470mm of lenght

I100_F6_H5_N04

Connection roof cassete - Sandwich element (top):
Insulation is cut in half on elevation 5.111m
Nose drip at bottom of Element's outer leaf
30x130mm plywood board is placed on top of roof cassete in protection of insulation
Plywood shapped as triangle connected to plywood board
50mm air gap left around shield plywood
24mm soft insulation at bottom of hard insulation

Connection roof cassete - sandwich element (bottom):
Roof cassete connected to concrete inner leaf by Steel bracket and anchor screwed to bottom of vertical wooden cassete batten and inner leaf's concrete

VIA UNIVERSITY COLLEGE
SCHOOL OF TECHNOLOGY AND BUSINESSINDTAST BY

PROJECT: Multipurpose hall	DATE: 22/04/2022	I100_F6_H5_N04
SUBJECT: Concrete Element-Roof Casset-Suspended Ceiling	SCALE: As indicated	
DRAWN BY: Ana	CLASS:	



Wooden roof cassetes:
13mm plywood
50mm air gap
350mm mineral wool
0.2mm DPM layer
1:40 slope

Roof finish:
DPC layer
2 layers of roofing felt,
1st is 3mm
2nd is 4mm Asphalt Felt torched-in

Eave:
50mm opening on external facade to allow air flow
Flashing overlapping facade
DPC layer and roofing felt layers

Downpipe:
110ø downpipe inserted in 150ø PVC pipe surrounded with soft insulation
Downpipe is led through roof cassete and into external wall

Leaf catcher
Metal sheet layed on top of DPC, nailed to roof cassete and overlapping downpipe

Wooden External wall:

424mm pre fabricated wooden wall
19mm vertical wooden cladding
12mm air gap
12mm plywood
12mm gypsum board
140mm mineral wool
160mm mineral wool
0.5mm DPM
45mm mineral wool
12mm plywood
12mm gypsum board
Minimum U VALUE: 0,113W/m²K
Actual U value: 0,108W/m²K
Fire demand: REI60

Connection of roof cassete and external wooden wall:
Steel bracket screwed to external wall through a 90x350mm plywood board and further down where first batten on stud is
Steel bracket screwed to roof cassete through cassete's battens
0.2mm DPM from roof cassete overlaps steel bracket where it will be secured.

VIA UNIVERSITY COLLEGE
SCHOOL OF TECHNOLOGY AND BUSINESSINDTAST BY

PROJECT:Multipurpose hall	DATE: 22/04/2022	I100_F6_H5_N02
SUBJECT:Eave Detail Wooden Building	SCALE: As indicated	
DRAWN BY: Ana	CLASS:	

Glass hall foundation

Glass hall foundation:

500mmx250mm concrete reinforced
with 6 12ø reinforcement bars
2x 190mmx250mm light clinker block,
75mm insulation
10mm mortar on top of first light clinker block
Plaster on external side of light clinker block

Glass hallway:

Curtain walls
50x115mm mullions

Skylight:
Plasteco,
skylight double glazed cc/1
installed accoring to manefacturer
Ventilation in roof cassete stops before skylight
and is led out by a pipe
going around the skylight and entering the cassete again
13mm gypsum on sides connecting to gypsum ceiling
Uvalue: 0,56W/m²K

Doors:
Fire demand: EI 30



SectionRP3 - Callout 1
1 : 5

UNIVERSITY COLLEGE
SCHOOL OF TECHNOLOGY AND BUSINESS

INDTAST BY

PROJECT: Multipurpose hall	DATE: 06/14/22	I100_F6_H5_N1
SUBJECT: Glass Hall foundation	SCALE: As indicated	
DRAWN BY: Author	CLASS:	

Internal wall - roof connection
(Wooden building)
Detail is located between modular lines
17 and 18

Internal walls:

120mm pre fabricated wooden internal walls
13mm gypsum board
13mm gypsum board
70mm mineral wool
13mm gypsum board
13mm gypsum board
5mm above gypsym ceiling internal wall continues up as:
13mm gypsum board
70mm mineral wool
13mm gypsum board
Connected to roof cassetes by steel brackets bolted on both sides of gypsum boards of internal walls, into roof cassete battens

Wooden roof cassetes:
13mm plywood
50mm air gap
350mm mineral wool
0.2mm DPM layer
1:40 slope
Roof finish:
DPC layer
2 layers of roofing felt,
1st is 3mm DPC,
2nd is 4mm Asphalt Felt torched-in



UNIVERSITY COLLEGE
SCHOOL OF TECHNOLOGY AND BUSINESS

PROJECT: Multipurpose hall	DATE: 22/04(2022	I100_F6_H5_N08
SUBJECT: Ceiling-Internal Wall	SCALE: As indicated	
DRAWN BY: Ana	CLASS:	



Skylight:
Plasteco skylight double glazed cc/1 installed accoring to manefacturer

Ventilation in roof cassete stops before skylight and is led out by a pipe going around the skylight and entering the cassete again

13mm of gypsum on sides connecting to gympsum ceiling

VIA UNIVERSITY COLLEGE
SCHOOL OF TECHNOLOGY AND BUSINESSINDTAST BY

PROJECT:Multipurpose hall	DATE: 22/04/2022	I100_F6_H5_N05
SUBJECT:Skylight	SCALE: 1 : 5	
DRAWN BY: Ana	CLASS:	