External wall RC block 500 mm Min. U-value requirement: Actual U-value: Min. fire demand: R 60


Internal partition wall Pre-fabricated concrete panel (Ytong) 150/200 mm Min. fire demand: R 60

Internal wall (fire compartment separator)
Pre-fabricated concrete panel 150 mm
Min. fire demand: REI 60

Door

Min. fire demand: EI2 30-C

Ground supported slab Tiles 10 mm Screed 20 mm In-situ cast concrete 100 mm Hard insulation 300 mm Gravel 150 mm Soil Min. U-value requirement: 0.20 W/m2K Actual U-value: 0.107 W/m2K Min. fire demand:



Legends:

MECHANICAL EXTRACTION

RO RESCUE OPENING

R RADIATOR

METER FOR ELECTRICAL SUPPLY

DB MAIN DISTRIBUTION BOARD

External wall
Standard brick 108 mm
Mineral wool insulation 250 mm
Concrete panel (Ytong) 150 mm
Min. U-value requirement: 0.30 W/m2K
Actual U-value: 0.159 W/m2K
Min. fire demand: R 60

Internal partition wall Pre-fabricated concrete panel (Ytong) 150/200 mm Min. fire demand: REI 30

Heavy floor partition Concrete deck element (Expan) 220 mm Hard insulation 50 mm In-situ cast concrete Min. fire demand: REI 60


Legends:


MECHANICAL EXTRACTION


RO RESCUE OPENING


R RADIATOR

FLOOR HEATING











VENTILATION PLAN: 1st FLOOR



03/09/21 \$.

VENTILATION PLAN: BASEMENT



VENTILATION PLAN: GROUND FLOOR

