

The **freemath** Package, version 1.0

plante

November 22, 2025

Usage

The **freemath** package allows for the omission of backslashes from most math mode commands. Specifically, any consecutive string of at least two (Latin) letters appearing in math mode will automatically be replaced with the control sequence having the same name, if it is defined.

The package is loaded by `\usepackage{freemath}` and provides the `\freemathon` and `\freemathoff` commands which respectively activate and deactivate this behaviour. It is **disabled** by default upon loading.

Regular commands initiated by a backslash may of course still be used when freemath is active, and can furthermore be freely mixed with backslash-free commands.

To prevent undesirable command formation simply insert spaces in-between letters to break the word apart (eg. to write the product of three variables *e*, *x*, and *p* you can write `e x p`, `ex p`, or `e xp`).

Example with freemath:

```
lim_{n to infny} int_0mega n log left( 1 + frac{f}{n} right) d mu.
```

Example without freemath:

```
\lim_{n\rightarrow\infty} \int_\Omega n \log\left( 1 + \frac{f}{n} \right) d\mu.
```

$$\lim_{n \rightarrow \infty} \int_{\Omega} n \log \left(1 + \frac{f}{n} \right) d\mu.$$

Known Limitations

- Braces are required whenever such a string of letters appears as an argument to another macro. For instance, one must write `frac{\omega}{\phi}` instead of `frac omega phi`, even though `\frac{\omega}{\phi}` is acceptable in ordinary L^AT_EX.

- An exception to the rule above is super- and subscripts, where for instance `f_mu` renders as expected (f_μ). This compatibility is achieved by assigning the active category code (13) to `^` and `_`.
- Braces are required around the argument to `\sqrt` even when it consists of a single letter. Backslash commands must be used for `\left` and `\right` delimiters that are not single characters (eg. `\left \lVert`).
- Commands which typeset their own name may result in infinite loops. One class of such commands is the math operators (eg. `\lim`, `\exp`) and the package includes a fix in this case (by modifying `\operator@font`). The workaround in general is to patch these commands to insert `\freemathoff` locally.

License

This package is copyright © 2025 plante, and released under the L^AT_EX Project Public License (LPPL) 1.3c.

Repository

The upstream repository of this package may be found at

<https://github.com/plante3/freemath/tree/main>.