

COL1000: Introduction to Programming

Nuts & Bolts of Python — Nested Loops ..

Subodh Sharma | Lec 10 | Aug 22



Simple Loops: Best Practices (RECAP)

- (Correctness) Double check loop's condition (or the continuation condition)
 - Ensure that iteration variable is changing in a way that will eventually **falsify** the loop **continuation** condition

- (Error-prone) Avoid making side effects in Loop conditions

```
while (item := get_next()) is not None:  
    process(item)
```

Expr changes the value
of item

- (Interpretability) Avoid making too many exit conditions in the loop body
 - effectively use break for early termination
- (Optimisation) Avoid recomputing invariant expressions in the loop

```
nums = [1, 2, 3, 4, 5]
```

```
while i in range(len(numbers)):
```

```
    length = len(numbers)
```

✗ – Invariant expr computed every time

```
    print(...)
```



(Nested) Loops & Conditions: Practice Problems

- **(Simple)** Read n integers and print only those that are not divisible by 3.
- **(Simple)** Read n integers and find the first negative number.
- **(Fun)** Keep reading the integers until the user enter -1 (sentinel) or 20 numbers have been processed — whichever comes first. Print the sum of all non-zero positive numbers.
- **(Fun)** Search for a given substring in a user input string without using built-in functions. Print either “Found at position i ” or “Not found”.
- **(Challenge)** Find all primes up to n in an optimised way (better than $O(n\sqrt{n})$)
- **(Challenge)** Given a list $[a_0, a_1, \dots, a_{n-1}]$, and a target T , find indices i and j , such that $a_i + a_j = T, i \neq j$

For Loops: Syntax (RECAP)

- **iterable:** An object that can be iterated on
 - Eg: lists, tuples, pairs, strings, dictionaries, **range()**
 - **No explicit update of the target value**

```
for target in iterable:  
    # loop body
```

For Loops: Semantics (RECAP)

```
for target in iterable:
```

```
# loop body
```

- The loop calls the function **iter()** on the **iterable** object
- `iter_obj = iter(iterable)`
- Assigns the item to the **target**
- Runs the body
- Repeatedly call `next(iter_obj)` to get the next item

Equivalently

```
it = iter(iterable)
```

```
while True:
```

```
    x = next(it, None)
```

```
    if x is None:
```

```
        break
```

```
# loop body
```

Loop Invariants

- Predicates (or conditions) that hold true at the start of the loop
- AND, after the execution of the loop body — continue to remain true
- How are they connected to **Post-conditions**?
 - **Loop invariant + Loop termination condition \Rightarrow postcondition after the loop**

Loop Invariants

```
sum = 0
```

```
# Loop Invariant:  $\text{sum} = \sum_{j=0}^{i-1} j$ 
```

```
for i in range(1, n+1):
```

```
    sum += i
```

```
# Post condition:  $\text{sum} = \sum_{j=0}^{i-1} j \wedge i = n + 1$ 
```