

# **COL1000: Introduction to Programming**

**Using GenAI Tools for Programming**

**Subodh Sharma | Lec 37 | Nov 12**



# GenAI Tools

## The problem


- GenAI Tools — Eg: ChatGPT, Gemini, Claude, etc.
  - Trained on large data sets; Predict next-tokens;
  - **Problems:**
    - Will make (possibly incorrect) assumptions on under-specified prompts (partial specs)
    - May end up using deprecated (ie OLD) programming language features
    - Optimises for **happy-path, may fail to report edge cases**
    - **Patterns may include bad coding practices**
    - ....

# How to Effectively Use GenAI for Programming Tasks

- Start with a prompt that explains the problem — essentially a **specification**
  - Narrow the field of GenAI's o/p by restricting: For instance,
    - language: **Python**
    - allowed libraries: **No use of iterTools**
    - complexity targets: in  $O(n \log n)$
    - style: **Imperative** (or Object Oriented or Functional, or logic or ... )
  - **1st Spec**: Write a **python** program to implement a **higher order function**, where the input function,  $f$ , is applied to the corresponding elements of other iterable arguments.

# How to Effectively Use GenAI for Programming Tasks

- **1st Spec:** Write a **python** program to implement a **higher order function**, where the input function, **f**, is applied to the corresponding elements of other iterable arguments.



# How to Effectively Use GenAI for Programming Tasks

- **2nd Spec Refinement:**

- Don't use libraries,
- A two-variable function would require exactly two iterables of equal size
- stick to the function interace:

```
def map_apply( f:  
  Callable[..., U],  
  *iterables: Iterable[T] )  
  -> Iterator[U]:
```
- avoid the use of yield statement

- **3rd Spec Refinement:**

- Error if argument function has argument count different than 2

# ChatGPT Output

```
from typing import Callable, Iterable, Iterator, TypeVar
import inspect
```

```
T = TypeVar("T")
```

```
U = TypeVar("U")
```

```
def map_apply(
    f: Callable[..., U],
    *iterables: Iterable[T]
) -> Iterator[U]:
```

```
# Enforce f is strictly binary (two positional params, no *args)
```

```
sig = inspect.signature(f)
```

```
params = list(sig.parameters.values())
```

```
pos_params = [p for p in params if p.kind in (p.POSITIONAL_ONLY, p.POSITIONAL_OR_KEYWORD)]
```

```
has_varpos = any(p.kind == p.VAR_POSITIONAL for p in params)
```

```
if has_varpos or len(pos_params) != 2:
```

```
    raise ValueError("Function `f` must take exactly two positional arguments.")
```



# ChatGPT Output

```
# Enforce exactly two iterables
if len(iterables) != 2:
    raise ValueError("Expected exactly two iterables for a binary function.")

a = list(iterables[0])
b = list(iterables[1])
if len(a) != len(b):
    raise ValueError("Iterables must be of equal length.")
```

```
# Apply f pairwise, eagerly (no yield)
out: list[U] = []
for i in range(len(a)):
    x, y = a[i], b[i]
    try:
        out.append(f(x, y))
    except TypeError as e:
        raise TypeError(
            f"Incompatible argument types at index {i}: "
            f"{type(x).__name__}, {type(y).__name__}"
        ) from e
return iter(out)
```

# How to Effectively Use GenAI for Programming Tasks


- **4th Spec Refinement:**
  - **Generate Unit Tests**
  - **List and resolve all ambiguities and corner cases**

Ambiguities listed by ChatGPT




Some are clarifications others are clear underspecifications!

## Ambiguities this suite exposes (decide & document)

1. **Zero-length inputs:** Should `([], [])` be valid (return empty iterator) or raise?  
*Tests assume it's valid.*
2. **Keyword-only params on `f`:** Allowed if there are still exactly two positional params?  
*Tests assume allowed.*
3. **Defaulted positional params:** If `f(x, y=0)` exists, do we allow it?  
*Tests assume allowed (still two positional args).*
4. **Built-in / C-level callables** (e.g., `operator.add`): Your no-imports arity check can't inspect these.  
*Current behavior: reject with a clear message; users should wrap as `lambda x, y: ...`.*
5. **Iterable kinds & consumption strategy:** Implementation converts both iterables to lists up-front.
  - Pros: simple equal-length check; consistent error sites.
  - Cons: **eager full consumption** (side effects, memory blow-up on huge streams).  
*Tests document and assert this behavior; decide if you prefer streaming pairwise processing instead.*
6. **Type-compatibility semantics:** You detect incompatibility by catching `TypeError` only.
  - What about other exceptions from `f` (`ValueError`, `ZeroDivisionError`)?  
*Tests assume you let non-`TypeError` exceptions bubble up unmodified.*
7. **Error message contract:** Your messages include phrases like "equal length", "exactly two".
  - If you change wording, tests may need updates. Consider freezing exact messages in a spec.
8. **Non-sequence iterables:** Generators/iterators are accepted (but fully realized).
  - If you later stream, some assertions (eager consumption) must change.
9. **Strings and other iterables:** Strings are valid iterables (pair char-wise).
  - Keep or forbid? *Tests assume allowed.*
10. **Return type:** You return an *iterator over a realized list*.
  - Alternative: return the realized list or a `cus`  iterator.  
*Tests only require iterator protocol compliance.*



## Ambiguities this suite exposes (decide & document)


1. **Zero-length inputs:** Should `([], [])` be valid (return empty iterator) or raise?  
*Tests assume it's valid.*
2. **Keyword-only params on `f`:** Allowed if there are still exactly two positional params?  
*Tests assume allowed.*
3. **Defaulted positional params:** If `f(x, y=0)` exists, do we allow it?  
*Tests assume allowed (still two positional args).*
4. **Built-in / C-level callables** (e.g., `operator.add`): Your no-imports arity check can't inspect these.  
*Current behavior: reject with a clear message; users should wrap as `lambda x, y: ...`.*
5. **Iterable kinds & consumption strategy:** Implementation converts both iterables to lists up-front.
  - Pros: simple equal-length check; consistent error sites.
  - Cons: **eager full consumption** (side effects, memory blow-up on huge streams).  
*Tests document and assert this behavior; decide if you prefer streaming pairwise processing instead.*
6. **Type-compatibility semantics:** You detect incompatibility by catching `TypeError` only.
  - What about other exceptions from `f` (`ValueError`, `ZeroDivisionError`)?  
*Tests assume you let non-`TypeError` exceptions bubble up unmodified.*
7. **Error message contract:** Your messages include phrases like "equal length", "exactly two".
  - If you change wording, tests may need updates. Consider freezing exact messages in a spec.
8. **Non-sequence iterables:** Generators/iterators are accepted (but fully realized).
  - If you later stream, some assertions (eager consumption) must change.
9. **Strings and other iterables:** Strings are valid iterables (pair char-wise).
  - Keep or forbid? *Tests assume allowed.*
10. **Return type:** You return an *iterator over a realized list*.
  - Alternative: return the realized list or a `cus`  iterator.  
*Tests only require iterator protocol compliance.*

# How to Effectively Use GenAI for Programming Tasks

- **Validation Task:**
  - **Either validate the results on your own**
  - **Or ask ChatGPT to fix the “known” misses**



## Ambiguities this suite exposes (decide & document)


1. **Zero-length inputs:** Should `([], [])` be valid (return empty iterator) or raise?  
*Tests assume it's valid.*
2. **Keyword-only params on `f`:** Allowed if there are still exactly two positional params?  
*Tests assume allowed.*
3. **Defaulted positional params:** If `f(x, y=0)` exists, do we allow it?  
*Tests assume allowed (still two positional args).*
4. **Built-in / C-level callables** (e.g., `operator.add`): Your no-imports arity check can't inspect these.  
*Current behavior: reject with a clear message; users should wrap as `lambda x, y: ...`.*
5. **Iterable kinds & consumption strategy:** Implementation converts both iterables to lists up-front.
  - Pros: simple equal-length check; consistent error sites.
  - Cons: **eager full consumption** (side effects, memory blow-up on huge streams).  
*Tests document and assert this behavior; decide if you prefer streaming pairwise processing instead.*
6. **Type-compatibility semantics:** You detect incompatibility by catching `TypeError` only.
  - What about other exceptions from `f` (`ValueError`, `ZeroDivisionError`)?  
*Tests assume you let non-`TypeError` exceptions bubble up unmodified.*
7. **Error message contract:** Your messages include phrases like "equal length", "exactly two".
  - If you change wording, tests may need updates. Consider freezing exact messages in a spec.
8. **Non-sequence iterables:** Generators/iterators are accepted (but fully realized).
  - If you later stream, some assertions (eager consumption) must change.
9. **Strings and other iterables:** Strings are valid iterables (pair char-wise).
  - Keep or forbid? *Tests assume allowed.*
10. **Return type:** You return an *iterator over a realized list*.
  - Alternative: return the realized list or a `cus`  iterator.  
*Tests only require iterator protocol compliance.*

# How to Effectively Use GenAI for Programming Tasks

- **5th Spec Refinement:**
  - 1 return an empty iterator;
  - 2 Keyword only params not allowed;
  - 3 yes allow them;
  - 4 users must wrap as `lambda`;
  - 5 keep the way it is;
  - 6 Yes support other exceptions as well;
  - 7 free the specs;
  - 8 avoid nonsequence iterables;
  - 9 keep strings;
  - 10 return the realised list.

# How to Effectively Use GenAI for Programming Tasks

- **To summarise:**
  - Spec + Spec refinement
  - Ask the model to review the code for ambiguities or missed cases
    - Or validate yourself
  - Generate spec-based tests
  - **Run the tests and obtain summary reports**
    - Examine failed test cases and refine the spec, if needed



The screenshot shows a terminal window with a dark background. At the top right, there is a button labeled "run the tests and report the results". Below it, the text "All set — I ran the suite." is displayed. This is followed by a bulleted list of test results: "Tests run: 16", "Passed: 16", "Failures/Errors: 0", and "Runtime: ~0.002s (local sandbox)". Below this list, the word "Artifacts:" is shown, followed by another bulleted list: "Implementation: /mnt/data/map\_apply.py" and "Tests: /mnt/data/test\_map\_apply.py".

```
run the tests and report the results
```

All set — I ran the suite.

- Tests run: 16
- Passed: 16
- Failures/Errors: 0
- Runtime: ~0.002s (local sandbox)

Artifacts:

- Implementation: /mnt/data/map\_apply.py
- Tests: /mnt/data/test\_map\_apply.py