

Στη συνομιλία αυτή, παρέθεσα τις ίδιες πληροφορίες όπως στη Συνομιλία 2 και ζήτησα από το LLM να δημιουργήσει πρώτα τον κώδικα για το Domain, κάτι που έκανε πολύ εύκολα. Το LLM κατάλαβε εξαιρετικά καλά την εργασία και δημιούργησε τον κώδικα για το Domain, Services και DAOs, και στη συνέχεια άρχισε να δημιουργεί τα Step Definitions για ΟΛΑ τα features με ΜΟΝΟ 2 μηνύματα. Αυτό δείχνει ότι το LLM διαθέτει ισχυρή μνήμη για να θυμάται τα Step Definitions κάθε feature. Τα αποτελέσματα του κώδικα ήταν συνολικά τα ίδια με τις προηγούμενες συνομιλίες, με πολλές λεπτομέρειες, αν και σε πολλές περιπτώσεις δεν ήταν τόσο κοντά στον πραγματικό κώδικα.

## Phase 2 Chat 3

User

**Act as a software developer. I have a library system application written in java and I have created some Gherkin Scenarios based on different features of the library application. I will provide you with these features/scenarios and the name of all the domain classes you will need, and then I will ask you to provide me the implementation code of the Step definitions for each feature, in java. I want your architecture to have Domain classes, Data Access Objects for saving/deleting entities and Service classes. Do you have any questions?**

ChatGPT

No questions so far. Please provide the Gherkin scenarios and the list of domain classes for your library system application. Once I have those details, I'll proceed with creating the implementation code for the Step definitions in Java, along with the necessary architecture for Domain classes, Data Access Objects (DAOs), and Service classes.

User

**The Domain classes you will need are : Book, Borrower, BorrowerCategory, Item, ItemState, Loan, Person. In the next message, I will provide you with all the features of the system**

ChatGPT

Got it. I'm ready for the Gherkin scenarios and features. Once you provide them, I'll start working on the implementation code for the Step definitions and the corresponding architecture.

User

**The first feature is :**

## **Feature: Borrower handling by the system**

**The system can register a new person, modify their credentials or delete their account**

**User Story: As a librarian,**

**I want to efficiently manage the loaning process of books to registered borrowers**

**So that borrowers can easily borrow books from the library.**

### **Scenario: Registering a new borrower**

**This scenario describes the process of registering a new borrower in the library system**

**Given George Red is not registered as a borrower**

**When George Red gets registered in the system with a unique borrower number and his details**

**Then the system successfully stores the borrower's details**

### **Scenario: Borrower trying to register has registered before**

**This scenario describes what happens when the system tries to register a new borrower who has already registered before**

**Given George Red is registered as a borrower**

**When the system attempts to register George Red with a unique borrower number and his details**

**Then the system informs that the user already exists**

### **Scenario: Updating the borrower's details when he is registered**

**This scenario describes the process of updating the details of a borrower who has already registered before**

**Given George Red is registered as a borrower**

**When George Red updates his borrowing details**

**Then the system saves the changes**

**Scenario: Updating the borrower's details when he hasn't registered**

**This scenario describes what happens when the system tries to update the details of a borrower who has not registered before**

**Given George Red is not registered as a borrower**

**When George Red tries to update his borrowing details**

**Then the system displays an error message indicating that George Red does not exist**

**Scenario: Deleting a borrower**

**This scenario describes the process of deleting the account of a borrower who has already registered**

**Given George Red is registered as a borrower**

**When the system deletes George Red's account**

**Then the system removes George Red's details**

**Scenario: Deleting a borrower when he hasn't registered**

**This scenario describes what happens when the system tries to delete the account of a borrower who has not registered before**

**Given George Red is not registered as a borrower**

**When the system attempts to delete George Red's account**

**Then the system informs that the borrower does not exist**

**Scenario: Handling unreturned items of books**

**This scenario describes what happens when the system tries to delete the account of a borrower who has pending items to return**

**Given George Red is registered as a borrower**

**And George Red has pending items**

**When the system attempts to delete George Red's account**

**Then the system does not remove George Red's details**

**And the system informs about the pending items**

**The second feature is :**

**Feature: Delayed Return Notification**

**User Story**

**a Library Manager**

**I want the loan system to automatically notify via email those who have delayed the return of an item**

**So that borrowers are informed when they have delayed the return of an item**

**Scenario: Notifying the borrower via email**

**This scenario handles the case where an item hasn't been returned on time and the system must notify the borrower via email**

**Given George Red has borrowed the item Harry Potter**

**And Harry Potter's due date has passed**

**And George Red has an email address**

**When the system executes the delayed return notification process**

**Then George Red receives an email notification for the return of the item**

**Scenario: Borrower does not have an email address**

**This scenario handles the case where an item hasn't been returned on time and the system must notify the user via email but he doesn't have one**

**Given George Red has borrowed the item Harry Potter**

**And Harry Potter's due date has passed**

**And George Red does not have an email address**

**When the system executes the delayed return notification process**

**Then George Red does not receive an email notification for the return of the item**

**The third feature is :**

**Feature: Loaning items**

**The library application allows for the librarian to loan an item of a book to a borrower based on some conditions of the system**

**User story: As a library member**

**I want to be able to borrow items**

**So that I can study them at home**

**Scenario: Successful loaning of an item**

**This scenario describes the successful process of loaning an item to a borrower that is entitled to borrow**

**Given the library has the item Harry Potter available**

**And George Red is a registered borrower**

**And George Red has 2 pending items to be returned**

And George Red has been assigned a maximum lending limit of 5

When George Red borrows the item Harry Potter

Then the system successfully loans the item Harry Potter to George Red with a due date set

And George Red's pending items increase to 3

Scenario: Borrower can borrow only one item due to his lending limit

This scenario describes the successful process of loaning only one but not two items to a borrower that is entitled to borrow only one item

Given the library has the items Harry Potter and Moby Dick available

And George Red is a registered borrower

And George Red has 2 pending items to be returned

And George Red has been assigned a maximum lending limit of 3

When George Red tries to borrow both items

Then the system successfully loans the item Harry Potter to George Red with a due date set

And the system does not loan Moby Dick to George Red due to the lending limit reached

And George Red's pending items increase to 3

Scenario

not found

This scenario describes the edge case where the library system cannot find the item, so the loan isn't happening

Given the item Harry Potter is in the library but not in the system

And George Red is a registered borrower

When George Red tries to borrow the item Harry Potter

Then the system returns an error due to the item's status

**And the system withdraws the item Harry Potter**

## **Scenario**

**borrower is not eligible to borrow**

**This scenario describes the unsuccessful process of loaning an item to a borrower that has reached his max lending limit**

**Given the library has the item Harry Potter available**

**And George Red is a registered borrower**

**And George Red has 3 pending items to be returned**

**And George Red has been assigned a maximum lending limit of 3**

**When George Red tries to borrow the item Harry Potter**

**Then the system doesn't allow the loan**

**And George Red's pending items remain 3**

**and the last feature is :**

**Feature: Returning a borrowed item to the library**

**The borrower returns the book copy in the library and then the system needs to accept it based on some conditions**

**User story: As a librarian**

**I want to accurately record the return of one or more books**

**So that books are returned on time, and late returns are fined**

## **Scenario**

**return of an item**

**This scenario describes the successful process of returning an item by a borrower**

**Given George Red borrowed the item Animal Kingdom 5 days prior to today's date**

**And George Red has been assigned maximum lending days of 10**

**When the return of Animal Kingdom is processed**

**Then the system marks the state of Animal Kingdom as AVAILABLE**

**And George Red has one less pending item**

**And George Red does not pay a fine**

**And the return date of the loan is set to today's date**

#### **Scenario**

**return of an item from a borrower**

**This scenario describes what happens when a borrower returns a loaned item late and has to pay a fine**

**Given George Red borrowed the item Animal Kingdom 10 days prior to today's date**

**And George Red has been assigned maximum lending days of 7**

**When the return of Animal Kingdom is processed**

**Then the system marks the state of Animal Kingdom as AVAILABLE**

**And George Red pays a fine based on the borrower category**

**And the return date of the loan is set to today's date**

**create the domain code , the services code and the DAOs code first**

**ChatGPT**

Sure, let's start by creating the domain classes, the Data Access Objects (DAOs), and the Service classes for the library system.



### ### Domain Classes

#### #### Book.java

```
```java  
  
public class Book {  
  
    private String title;  
  
    private String author;  
  
    private String isbn;  
  
    // Constructors, getters, setters, equals, and hashCode  
  
}  
```
```

#### #### Borrower.java

```
```java  
  
public class Borrower {  
  
    private int borrowerNumber;  
  
    private String name;  
  
    private String email;  
  
    private BorrowerCategory category;  
  
    private List<Loan> loans;  
  
}
```

```
// Constructors, getters, setters, equals, and hashCode  
}  
...
```

#### BorrowerCategory.java

```
```java  
  
public class BorrowerCategory {  
  
    private String categoryName;  
  
    private int maxLendingLimit;  
  
    private int maxLendingDays;  
  
    private double finePerDay;  
  
    // Constructors, getters, setters, equals, and hashCode  
}  
...
```

#### Item.java

```
```java  
  
public class Item {  
  
    private String id;  
  
    private Book book;  
  
    private ItemState state;
```

```
// Constructors, getters, setters, equals, and hashCode  
}  
...
```

#### ItemState.java

```
```java  
  
public enum ItemState {  
  
    AVAILABLE,  
  
    BORROWED,  
  
    RESERVED,  
  
    LOST  
  
}  
...
```

#### Loan.java

```
```java  
  
import java.util.Date;  
  
  
public class Loan {  
  
    private Borrower borrower;  
  
    private Item item;  
  
    private Date loanDate;  
  
    private Date dueDate;
```

```
private Date returnDate;
```

```
// Constructors, getters, setters, equals, and hashCode
```

```
}
```

```
...
```

```
#### Person.java
```

```
```java
```

```
public class Person {
```

```
    private String name;
```

```
    private String address;
```

```
    private String email;
```

```
// Constructors, getters, setters, equals, and hashCode
```

```
}
```

```
...
```

```
### Data Access Objects (DAOs)
```

```
#### BookDAO.java
```

```
```java
```

```
import java.util.List;
```

```
public interface BookDAO {  
  
    void save(Book book);  
  
    void delete(Book book);  
  
    Book findByISBN(String isbn);  
  
    List<Book> findAll();  
  
}
```

...

#### BorrowerDAO.java

```java

import java.util.List;

```
public interface BorrowerDAO {  
  
    void save(Borrower borrower);  
  
    void delete(Borrower borrower);  
  
    Borrower findByBorrowerNumber(int borrowerNumber);  
  
    List<Borrower> findAll();  
  
}
```

...

#### ItemDAO.java

```java

import java.util.List;

```
public interface ItemDAO {  
  
    void save(Item item);  
  
    void delete(Item item);  
  
    Item findById(String id);  
  
    List<Item> findAll();  
  
}  
...
```

#### LoanDAO.java

```
```java
```

```
import java.util.List;
```

```
public interface LoanDAO {  
  
    void save(Loan loan);  
  
    void delete(Loan loan);  
  
    Loan findById(int id);  
  
    List<Loan> findAll();  
  
}  
...
```

### Service Classes

#### BookService.java

```
```java
```

```
import java.util.List;
```

```
public class BookService {
```

```
    private BookDAO bookDAO;
```

```
    public BookService(BookDAO bookDAO) {
```

```
        this.bookDAO = bookDAO;
```

```
    }
```

```
    public void registerBook(Book book) {
```

```
        bookDAO.save(book);
```

```
    }
```

```
    public void removeBook(Book book) {
```

```
        bookDAO.delete(book);
```

```
    }
```

```
    public Book findBookByISBN(String isbn) {
```

```
        return bookDAO.findByISBN(isbn);
```

```
    }
```

```

    public List<Book> listAllBooks() {

        return bookDAO.findAll();

    }

}

...

```

#### BorrowerService.java

```

``java

```

```

import java.util.List;

```

```

public class BorrowerService {

```

```

    private BorrowerDAO borrowerDAO;

```

```

    public BorrowerService(BorrowerDAO borrowerDAO) {

```

```

        this.borrowerDAO = borrowerDAO;

```

```

    }

```

```

    public void registerBorrower(Borrower borrower) {

```

```

        Borrower existingBorrower =

```

```

        borrowerDAO.findByBorrowerNumber(borrower.getBorrowerNumber());

```

```

        if (existingBorrower == null) {

```

```

            borrowerDAO.save(borrower);

```

```

        } else {

```

```

            throw new IllegalArgumentException("Borrower already registered");

```



```
}  
  
}
```

```
public void updateBorrower(Borrower borrower) {  
  
    Borrower                existingBorrower                =  
borrowerDAO.findByBorrowerNumber(borrower.getBorrowerNumber());  
  
    if (existingBorrower != null) {  
  
        borrowerDAO.save(borrower);  
  
    } else {  
  
        throw new IllegalArgumentException("Borrower does not exist");  
  
    }  
  
}
```

```
public void removeBorrower(Borrower borrower) {  
  
    Borrower                existingBorrower                =  
borrowerDAO.findByBorrowerNumber(borrower.getBorrowerNumber());  
  
    if (existingBorrower != null && existingBorrower.getLoans().isEmpty()) {  
  
        borrowerDAO.delete(borrower);  
  
    } else if (existingBorrower != null) {  
  
        throw new IllegalArgumentException("Borrower has pending items");  
  
    } else {  
  
        throw new IllegalArgumentException("Borrower does not exist");  
  
    }  
  
}
```

```

public Borrower findBorrowerByNumber(int borrowerNumber) {
    return borrowerDAO.findByBorrowerNumber(borrowerNumber);
}

public List<Borrower> listAllBorrowers() {
    return borrowerDAO.findAll();
}
}
...

```

#### LoanService.java

```

```java

```

```

import java.util.Date;

```

```

import java.util.List;

```

```

public class LoanService {

```

```

    private LoanDAO loanDAO;

```

```

    private BorrowerDAO borrowerDAO;

```

```

    private ItemDAO itemDAO;

```

```

    public LoanService(LoanDAO loanDAO, BorrowerDAO borrowerDAO, ItemDAO itemDAO) {

```

```

        this.loanDAO = loanDAO;

```

```

        this.borrowerDAO = borrowerDAO;

        this.itemDAO = itemDAO;
    }

    public void loanItem(Borrower borrower, Item item) {

        if (borrower.getLoans().size() >= borrower.getCategory().getMaxLendingLimit()) {

            throw new IllegalArgumentException("Borrower has reached the maximum lending
limit");
        }

        if (item.getState() != ItemState.AVAILABLE) {

            throw new IllegalArgumentException("Item is not available for loan");
        }

        Loan loan = new Loan();

        loan.setBorrower(borrower);

        loan.setItem(item);

        loan.setLoanDate(new Date());

        loan.setDueDate(new Date(System.currentTimeMillis() +
borrower.getCategory().getMaxLendingDays() * 24 * 60 * 60 * 1000L));

        loanDAO.save(loan);

        item.setState(ItemState.BORROWED);

        itemDAO.save(item);

        borrower.getLoans().add(loan);
    }

```

```
        borrowerDAO.save(borrower);  
    }  
}
```

```
public void returnItem(Loan loan) {
```

```
    Item item = loan.getItem();
```

```
    item.setState(ItemState.AVAILABLE);
```

```
    itemDAO.save(item);
```

```
    Borrower borrower = loan.getBorrower();
```

```
    borrower.getLoans().remove(loan);
```

```
    borrowerDAO.save(borrower);
```

```
    loan.setReturnDate(new Date());
```

```
    loanDAO.save(loan);
```

```
    if (loan.getReturnDate().after(loan.getDueDate())) {
```

```
        long daysLate = (loan.getReturnDate().getTime() - loan.getDueDate().getTime()) / (24 *  
60 * 60 * 1000);
```

```
        double fine = daysLate * borrower.getCategory().getFinePerDay();
```

```
        // Implement fine logic (e.g., record it, notify borrower, etc.)
```

```
    }
```

```
}
```

```
public List<Loan> listAllLoans() {
```

```
        return loanDAO.findAll();
    }
}
...

```

With these domain classes, DAOs, and service classes in place, the next step is to implement the Step definitions for the Gherkin scenarios in Java. Let me know if you would like to proceed with this or need any adjustments in the current setup.

**User**

**Proceed**

ChatGPT

Great, let's proceed with the implementation of the Step definitions for the Gherkin scenarios in Java using Cucumber. We'll start with the feature for handling borrowers.

### Step Definitions for Borrower Handling

#### BorrowerSteps.java

```
```java

```

```
import static org.junit.Assert.*;

```

```
import java.util.HashMap;

```

```
import java.util.Map;

```

```
import io.cucumber.java.en.*;

import my.library.domain.Borrower;

import my.library.domain.BorrowerCategory;

import my.library.services.BorrowerService;


public class BorrowerSteps {


    private BorrowerService borrowerService;

    private Map<Integer, Borrower> borrowers;

    private BorrowerCategory defaultCategory;

    private Borrower currentBorrower;

    private String errorMessage;


    public BorrowerSteps() {

        borrowerService = new BorrowerService(new InMemoryBorrowerDAO());

        borrowers = new HashMap<>();

        defaultCategory = new BorrowerCategory("Regular", 5, 14, 0.5);

    }


    @Given("{string} is not registered as a borrower")

    public void borrower_is_not_registered(String name) {

        currentBorrower = borrowerService.findBorrowerByName(name);

        assertNull(currentBorrower);

    }

}
```

```
}
```

@When("{string} gets registered in the system with a unique borrower number and his details")

```
public void borrower_gets_registered(String name) {  
  
    try {  
  
        Borrower newBorrower = new Borrower(borrowers.size() + 1, name,  
name.toLowerCase() + "@example.com", defaultCategory, new ArrayList<>());  
  
        borrowerService.registerBorrower(newBorrower);  
  
        currentBorrower = newBorrower;  
  
        borrowers.put(newBorrower.getBorrowerNumber(), newBorrower);  
  
    } catch (IllegalArgumentException e) {  
  
        errorMessage = e.getMessage();  
  
    }  
  
}
```

@Then("the system successfully stores the borrower's details")

```
public void system_successfully_stores_details() {  
  
    assertNotNull(currentBorrower);  
  
    assertTrue(borrowers.containsKey(currentBorrower.getBorrowerNumber()));  
  
}
```

@Given("{string} is registered as a borrower")

```
public void borrower_is_registered(String name) {
```

```

        Borrower registeredBorrower = new Borrower(borrowers.size() + 1, name,
name.toLowerCase() + "@example.com", defaultCategory, new ArrayList<>());

        borrowerService.registerBorrower(registeredBorrower);

        borrowers.put(registeredBorrower.getBorrowerNumber(), registeredBorrower);

        currentBorrower = registeredBorrower;
    }

```

@When("the system attempts to register {string} with a unique borrower number and his details")

```

public void system_attempts_to_register(String name) {

    try {

        Borrower duplicateBorrower = new Borrower(borrowers.size() + 1, name,
name.toLowerCase() + "@example.com", defaultCategory, new ArrayList<>());

        borrowerService.registerBorrower(duplicateBorrower);

    } catch (IllegalArgumentException e) {

        errorMessage = e.getMessage();

    }

}

```

@Then("the system informs that the user already exists")

```

public void system_informs_user_already_exists() {

    assertEquals("Borrower already registered", errorMessage);

}

```



```
@When("{string} updates his borrowing details")
```

```
public void borrower_updates_details(String name) {
```

```
    try {
```

```
        currentBorrower.setEmail(name.toLowerCase() + ".updated@example.com");
```

```
        borrowerService.updateBorrower(currentBorrower);
```

```
    } catch (IllegalArgumentException e) {
```

```
        errorMessage = e.getMessage();
```

```
    }
```

```
}
```

```
@Then("the system saves the changes")
```

```
public void system_saves_changes() {
```

```
    assertEquals(currentBorrower.getEmail(), currentBorrower.getName().toLowerCase() +  
".updated@example.com");
```

```
}
```

```
@When("{string} tries to update his borrowing details")
```

```
public void borrower_tries_to_update_details(String name) {
```

```
    try {
```

```
        Borrower nonExistentBorrower = new Borrower(borrowers.size() + 1, name,  
name.toLowerCase() + ".updated@example.com", defaultCategory, new ArrayList<>());
```

```
        borrowerService.updateBorrower(nonExistentBorrower);
```

```
    } catch (IllegalArgumentException e) {
```

```
        errorMessage = e.getMessage();
```

```
}  
  
}
```

```
@Then("the system displays an error message indicating that {string} does not exist")
```

```
public void system_displays_error_message(String name) {  
  
    assertEquals("Borrower does not exist", errorMessage);  
  
}
```

```
@When("the system deletes {string}'s account")
```

```
public void system_deletes_account(String name) {  
  
    try {  
  
        borrowerService.removeBorrower(currentBorrower);  
  
        borrowers.remove(currentBorrower.getBorrowerNumber());  
  
    } catch (IllegalArgumentException e) {  
  
        errorMessage = e.getMessage();  
  
    }  
  
}
```

```
@Then("the system removes {string}'s details")
```

```
public void system_removes_details(String name) {  
  
    assertFalse(borrowers.containsKey(currentBorrower.getBorrowerNumber()));  
  
}
```

```

@When("the system attempts to delete {string}'s account")

public void system_attempts_to_delete_account(String name) {

    try {

        Borrower nonExistentBorrower = new Borrower(borrowers.size() + 1, name,
name.toLowerCase() + "@example.com", defaultCategory, new ArrayList<>());

        borrowerService.removeBorrower(nonExistentBorrower);

    } catch (IllegalArgumentException e) {

        errorMessage = e.getMessage();

    }

}

```

```

@Then("the system informs that the borrower does not exist")

public void system_informs_borrower_does_not_exist() {

    assertEquals("Borrower does not exist", errorMessage);

}

```

```

@Given("{string} has pending items")

public void borrower_has_pending_items(String name) {

    Loan pendingLoan = new Loan(currentBorrower, new Item("1", new Book("Harry Potter",
"J.K. Rowling", "1234567890"), ItemState.BORROWED), new Date(), null, null);

    currentBorrower.getLoans().add(pendingLoan);

}

```

```

@Then("the system does not remove {string}'s details")

```

```

public void system_does_not_remove_details(String name) {

    assertTrue(borrowers.containsKey(currentBorrower.getBorrowerNumber()));

}

@Then("the system informs about the pending items")

public void system_informs_pending_items() {

    assertEquals("Borrower has pending items", errorMessage);

}

}

...

```

### In-Memory DAO Implementation for Testing

#### InMemoryBorrowerDAO.java

```

``java

```

```

import java.util.*;

```

```

public class InMemoryBorrowerDAO implements BorrowerDAO {

```

```

    private Map<Integer, Borrower> borrowers = new HashMap<>();

```

```

    @Override

```

```
public void save(Borrower borrower) {  
  
    borrowers.put(borrower.getBorrowerNumber(), borrower);  
  
}
```

@Override

```
public void delete(Borrower borrower) {  
  
    borrowers.remove(borrower.getBorrowerNumber());  
  
}
```

@Override

```
public Borrower findByBorrowerNumber(int borrowerNumber) {  
  
    return borrowers.get(borrowerNumber);  
  
}
```

@Override

```
public List<Borrower> findAll() {  
  
    return new ArrayList<>(borrowers.values());  
  
}  
  
}
```

...

This setup includes the step definitions for handling borrowers using Cucumber in Java, as well as an in-memory DAO implementation for testing purposes. You can now write similar step definitions for the other features.

Let me know if you need any further assistance with the other features or any other part of the implementation!

**User**

**Provide all the other features step definitions as well**

ChatGPT

Sure, I'll continue by providing the step definitions for the remaining features: Delayed Return Notification, Loaning items, and Returning a borrowed item to the library.

### Step Definitions for Delayed Return Notification

#### DelayedReturnNotificationSteps.java

```
```java
```

```
import static org.junit.Assert.*;
```

```
import java.util.Date;
```

```
import java.util.HashMap;
```

```
import java.util.Map;
```

```
import io.cucumber.java.en.*;
```

```
import my.library.domain.*;
```

```
import my.library.services.*;
```

```

public class DelayedReturnNotificationSteps {

    private BorrowerService borrowerService;

    private LoanService loanService;

    private Map<Integer, Borrower> borrowers;

    private Item item;

    private Loan loan;

    private String emailMessage;

    public DelayedReturnNotificationSteps() {

        borrowerService = new BorrowerService(new InMemoryBorrowerDAO());

        loanService = new LoanService(new InMemoryLoanDAO(), new
InMemoryBorrowerDAO(), new InMemoryItemDAO());

        borrowers = new HashMap<>();

    }

    @Given("{string} has borrowed the item {string}")

    public void borrower_has_borrowed_item(String borrowerName, String itemName) {

        Borrower borrower = new Borrower(borrowers.size() + 1, borrowerName,
borrowerName.toLowerCase() + "@example.com", new BorrowerCategory("Regular", 5, 14,
0.5), new ArrayList<>());

        borrowers.put(borrower.getBorrowerNumber(), borrower);

        item = new Item("1", new Book(itemName, "Author", "1234567890"),
ItemState.BORROWED);
    }
}

```

```
        loan = new Loan(borrower, item, new Date(System.currentTimeMillis() - 10 * 24 * 60 * 60
* 1000L), new Date(System.currentTimeMillis() - 5 * 24 * 60 * 60 * 1000L), null);
```

```
        borrower.getLoans().add(loan);
```

```
    }
```

```
@Given("{string}'s due date has passed")
```

```
public void due_date_has_passed(String itemName) {
```

```
    assertTrue(loan.getDueDate().before(new Date()));
```

```
}
```

```
@Given("{string} has an email address")
```

```
public void borrower_has_email_address(String borrowerName) {
```

```
    assertNotNull(borrowers.get(1).getEmail());
```

```
}
```

```
@When("the system executes the delayed return notification process")
```

```
public void system_executes_notification_process() {
```

```
    if (loan.getDueDate().before(new Date())) {
```

```
        emailMessage = "Dear " + loan.getBorrower().getName() + ", you have delayed the  
return of the item " + loan.getItem().getBook().getTitle() + ". Please return it as soon as  
possible.";
```

```
    }
```

```
}
```



```
@Then("{string} receives an email notification for the return of the item")
```

```
public void borrower_receives_email_notification(String borrowerName) {
```

```
    assertNotNull(emailMessage);
```

```
}
```

```
@Given("{string} does not have an email address")
```

```
public void borrower_does_not_have_email_address(String borrowerName) {
```

```
    Borrower borrower = borrowers.get(1);
```

```
    borrower.setEmail(null);
```

```
}
```

```
@Then("{string} does not receive an email notification for the return of the item")
```

```
public void borrower_does_not_receive_email_notification(String borrowerName) {
```

```
    assertNull(emailMessage);
```

```
}
```

```
}
```

```
...
```

```
### Step Definitions for Loaning Items
```

```
#### LoaningItemsSteps.java
```

```
```java
```

```
import static org.junit.Assert.*;
```

```
import java.util.*;
```

```
import io.cucumber.java.en.*;
```

```
import my.library.domain.*;
```

```
import my.library.services.*;
```

```
public class LoaningItemsSteps {
```

```
    private BorrowerService borrowerService;
```

```
    private LoanService loanService;
```

```
    private Map<Integer, Borrower> borrowers;
```

```
    private Map<String, Item> items;
```

```
    private String errorMessage;
```

```
    public LoaningItemsSteps() {
```

```
        borrowerService = new BorrowerService(new InMemoryBorrowerDAO());
```

```
        loanService      =      new      LoanService(new      InMemoryLoanDAO(),      new  
InMemoryBorrowerDAO(), new InMemoryItemDAO());
```

```
        borrowers = new HashMap<>();
```

```
        items = new HashMap<>();
```

```
    }
```

```
@Given("the library has the item {string} available")
```

```
public void library_has_item_available(String itemName) {
```

```
    Item item = new Item(UUID.randomUUID().toString(), new Book(itemName, "Author",  
"1234567890"), ItemState.AVAILABLE);
```

```
    items.put(itemName, item);
```

```
}
```

```
@Given("{string} is a registered borrower")
```

```
public void borrower_is_registered(String borrowerName) {
```

```
    Borrower borrower = new Borrower(borrowers.size() + 1, borrowerName,  
borrowerName.toLowerCase() + "@example.com", new BorrowerCategory("Regular", 5, 14,  
0.5), new ArrayList<>());
```

```
    borrowerService.registerBorrower(borrower);
```

```
    borrowers.put(borrower.getBorrowerNumber(), borrower);
```

```
}
```

```
@Given("{string} has {int} pending items to be returned")
```

```
public void borrower_has_pending_items(String borrowerName, int pendingItems) {
```

```
    Borrower borrower = borrowers.get(1);
```

```
    for (int i = 0; i < pendingItems; i++) {
```

```
        Loan loan = new Loan(borrower, new Item(UUID.randomUUID().toString(), new  
Book("Book" + i, "Author", "1234567890"), ItemState.BORROWED), new Date(), null, null);
```

```
        borrower.getLoans().add(loan);
```

```
}
```

```
}
```

```
@Given("{string} has been assigned a maximum lending limit of {int}")
```

```
public void borrower_has_max_lending_limit(String borrowerName, int maxLimit) {
```

```
    Borrower borrower = borrowers.get(1);
```

```
    BorrowerCategory category = new BorrowerCategory("Regular", maxLimit, 14, 0.5);
```

```
    borrower.setCategory(category);
```

```
}
```

```
@When("{string} borrows the item {string}")
```

```
public void borrower_borrows_item(String borrowerName, String itemName) {
```

```
    Borrower borrower = borrowers.get(1);
```

```
    Item item = items.get(itemName);
```

```
    try {
```

```
        loanService.loanItem(borrower, item);
```

```
    } catch (IllegalArgumentException e) {
```

```
        errorMessage = e.getMessage();
```

```
    }
```

```
}
```

```
@Then("the system successfully loans the item {string} to {string} with a due date set")
```

```
public void system_successfully_loans_item(String itemName, String borrowerName) {
```

```
    Borrower borrower = borrowers.get(1);
```

```
        assertTrue(borrower.getLoans().stream().anyMatch(loan
  ->
loan.getItem().getBook().getTitle().equals(itemName)));

    }
```

```
    @Then("{string}'s pending items increase to {int}")

    public void borrowers_pending_items_increase_to(String borrowerName, int
expectedPendingItems) {

        Borrower borrower = borrowers.get(1);

        assertEquals(expectedPendingItems, borrower.getLoans().size());

    }
```

```
    @When("{string} tries to borrow both items")

    public void borrower_tries_to_borrow_both_items(String borrowerName, List<String>
itemNames) {

        Borrower borrower = borrowers.get(1);

        for (String itemName : itemNames) {

            Item item = items.get(itemName);

            try {

                loanService loanItem(borrower, item);

            } catch (IllegalArgumentException e) {

                errorMessage = e.getMessage();

            }

        }

    }

}
```

```

@Then("the system successfully loans the item {string} to {string} with a due date set")

public void system_successfully_loans_first_item(String itemName, String borrowerName)
{
    Borrower borrower = borrowers.get(1);

    assertTrue(borrower.getLoans().stream().anyMatch(loan ->
loan.getItem().getBook().getTitle().equals(itemName)));
}

```

```

@Then("the system does not loan {string} to {string} due to the lending limit reached")

public void system_does_not_loan_second_item(String itemName, String borrowerName)
{
    assertEquals("Borrower has reached the maximum lending limit", errorMessage);
}

```

```

@Given("the item {string} is in the library but not in the system")

public void item_in_library_but_not_in_system(String itemName) {

    items.remove(itemName);

}

```

```

@When("{string} tries to borrow the item {string}")

public void borrower_tries_to_borrow_nonexistent_item(String borrowerName, String
itemName) {

    Borrower borrower = borrowers.get(1);

```

```
Item item = new Item(UUID.randomUUID().toString(), new Book(itemName, "Author",  
"1234567890"), ItemState.AVAILABLE);
```

```
try {  
  
    loanService.loanItem(borrower, item);  
  
} catch (IllegalArgumentException e) {  
  
    errorMessage = e.getMessage();  
  
}  
}
```

```
@Then("the system returns an error due to the item's status")
```

```
public void system_returns_error_due_to_item_status() {  
  
    assertEquals("Item is not available for loan", errorMessage);  
  
}
```

```
@Then("the system withdraws the item {string}")
```

```
public void system_withdraws_item(String itemName) {  
  
    Item item = items.get(itemName);  
  
    item.setState(ItemState.LOST);  
  
    items.put(itemName, item);  
  
}
```

```
@When("{string} tries to borrow the item {string}")
```

```
public void borrower_tries_to_borrow_item(String borrowerName, String itemName) {  
  
    Borrower borrower = borrowers.get(1);
```

```

    Item item = items.get(itemName);

    try {

        loanService.loanItem(borrower, item);

    } catch (IllegalArgumentException e) {

        errorMessage = e.getMessage();

    }

}

```

@Then("the system doesn't allow the loan

ChatGPT

")

```

public void system_doesnt_allow_loan() {

    assertEquals("Borrower has reached the maximum lending limit", errorMessage);

}

```

@Then("{string}'s pending items remain {int}")

```

public void borrowers_pending_items_remain(String borrowerName, int
expectedPendingItems) {

```

```

    Borrower borrower = borrowers.get(1);

```

```

    assertEquals(expectedPendingItems, borrower.getLoans().size());

```

```

}

```

```

}

```

```

...

```



### ### Step Definitions for Returning a Borrowed Item

#### #### ReturningItemsSteps.java

```
``java
```

```
import static org.junit.Assert.*;
```

```
import java.util.Date;
```

```
import java.util.HashMap;
```

```
import java.util.Map;
```

```
import io.cucumber.java.en.*;
```

```
import my.library.domain.*;
```

```
import my.library.services.*;
```

```
public class ReturningItemsSteps {
```

```
    private BorrowerService borrowerService;
```

```
    private LoanService loanService;
```

```
    private Map<Integer, Borrower> borrowers;
```

```
    private Item item;
```

```
    private Loan loan;
```

```
    private String fineMessage;
```

```

public ReturningItemsSteps() {

    borrowerService = new BorrowerService(new InMemoryBorrowerDAO());

    loanService      =      new      LoanService(new      InMemoryLoanDAO(),      new
InMemoryBorrowerDAO(), new InMemoryItemDAO());

    borrowers = new HashMap<>();

}

```

```

@Given("{string} borrowed the item {string} {int} days prior to today's date")

public void borrower_borrowed_item_days_prior(String borrowerName, String itemName,
int daysAgo) {

    Borrower borrower = new Borrower(borrowers.size() + 1, borrowerName,
borrowerName.toLowerCase() + "@example.com", new BorrowerCategory("Regular", 5, 14,
0.5), new ArrayList<>());

    borrowers.put(borrower.getBorrowerNumber(), borrower);

    item = new Item("1", new Book(itemName, "Author", "1234567890"),
ItemState.BORROWED);

    loan = new Loan(borrower, item, new Date(System.currentTimeMillis() - daysAgo * 24 *
60 * 60 * 1000L), new Date(System.currentTimeMillis() - (daysAgo - 5) * 24 * 60 * 60 * 1000L),
null);

    borrower.getLoans().add(loan);

}

```

```

@Given("{string} has been assigned maximum lending days of {int}")

public void borrower_has_max_lending_days(String borrowerName, int maxDays) {

```

```
Borrower borrower = borrowers.get(1);

BorrowerCategory category = new BorrowerCategory("Regular", 5, maxDays, 0.5);

borrower.setCategory(category);
}
```

```
@When("the return of {string} is processed")

public void return_of_item_is_processed(String itemName) {

    try {

        loanService.returnItem(loan);

    } catch (IllegalArgumentException e) {

        fineMessage = e.getMessage();

    }

}
```

```
@Then("the system marks the state of {string} as AVAILABLE")

public void system_marks_state_as_available(String itemName) {

    assertEquals(ItemState.AVAILABLE, item.getState());

}
```

```
@Then("{string} has one less pending item")

public void borrower_has_one_less_pending_item(String borrowerName) {

    Borrower borrower = borrowers.get(1);

    assertEquals(0, borrower.getLoans().size());

}
```

```
}
```

```
@Then("{string} does not pay a fine")
```

```
public void borrower_does_not_pay_fine(String borrowerName) {
```

```
    assertNull(fineMessage);
```

```
}
```

```
@Then("the return date of the loan is set to today's date")
```

```
public void return_date_is_set_to_today() {
```

```
    assertEquals(new Date().toString(), loan.getReturnDate().toString());
```

```
}
```

```
@Then("{string} pays a fine based on the borrower category")
```

```
public void borrower_pays_fine_based_on_category(String borrowerName) {
```

```
    assertNotNull(fineMessage);
```

```
}
```

```
}
```

```
...
```

### ### In-Memory DAO Implementations for Testing

To ensure our step definitions work, let's provide in-memory implementations for ``LoanDAO`` and ``ItemDAO``.

#### InMemoryLoanDAO.java

```
```java
```

```
import java.util.*;
```

```
public class InMemoryLoanDAO implements LoanDAO {
```

```
    private Map<Integer, Loan> loans = new HashMap<>();
```

```
    @Override
```

```
    public void save(Loan loan) {
```

```
        loans.put(loans.size() + 1, loan);
```

```
    }
```

```
    @Override
```

```
    public void delete(Loan loan) {
```

```
        loans.values().remove(loan);
```

```
    }
```

```
    @Override
```

```
    public Loan findById(int id) {
```

```
        return loans.get(id);
```

```
    }
```

```
@Override

public List<Loan> findAll() {

    return new ArrayList<>(loans.values());

}

}

...

```

#### InMemoryItemDAO.java

```
``java
```

```
import java.util.*;
```

```
public class InMemoryItemDAO implements ItemDAO {
```

```
    private Map<String, Item> items = new HashMap<>();
```

```
@Override
```

```
public void save(Item item) {
```

```
    items.put(item.getId(), item);
```

```
}
```

```
@Override
```

```
public void delete(Item item) {  
    items.remove(item.getId());  
}
```

@Override

```
public Item findById(String id) {  
    return items.get(id);  
}
```

@Override

```
public List<Item> findAll() {  
    return new ArrayList<>(items.values());  
}  
}  
...
```

### ### Summary

This setup includes the step definitions for all the specified features and scenarios in the library system, as well as the in-memory DAO implementations for testing purposes. You can now use these step definitions to run your Cucumber tests.

Let me know if you need further assistance or adjustments!