



PLATINUM **SOFTWARE**

## PlatSoft Grape Manual

Developer's guide to using the PlatSoft Grape Framework

# Table of Contents

1. Grape	Page 4
1.1. Architecture	Page 4
1.2. Getting started	Page 4
1.3. Structure of a Grape Application	Page 5
1.3.1. Directory layout	Page 5
1.4. Authentication and access control	Page 5
1.5. API Calls	Page 6
1.5.1. Anatomy of a Grape API call	Page 6
1.5.1.1. FS Request	
1.5.1.1.1. download_public_js_files	
1.5.1.2. DB API requests	
1.5.1.3. Other API calls	
1.5.2. Access control	Page 7
1.5.3. Consuming an API call	Page 7
1.6. How to send emails from Grape in PostgreSQL	Page 7
1.6.1. Setup	Page 7
1.6.2. Send an email	Page 8
1.6.3. Custom headers	Page 8
1.6.4. Email templates	Page 8
1.6.5. Example	Page 9
1.7. Grape settings	Page 9
1.7.1. Known Grape settings	Page 9
1.8. Grape config file	Page 10
1.9. Standardized Error Codes	Page 11
1.10. Grape SQL Functions	Page 11
1.10.1. API result functions	Page 11
1.10.2. Data importing functions	Page 12
1.10.3. JSON helpers	Page 12
1.10.3.1. json2xml(_data JSON, _root TEXT)	
1.10.3.2. json_diff (_old JSONB, _new JSONB)	
1.10.3.3. json_diff (_old JSON, _new JSON)	
1.10.3.4. json_object_diff (_old JSONB, _new JSONB)	
1.10.3.5. json_array_diff (_old JSONB, _new JSONB)	
1.10.3.6. json_to_composite_type_text(target_schema TEXT, target_type TEXT, data JSON)	
1.10.3.7. json_to_composite_type(target_schema TEXT, target_type TEXT, data JSON)	
1.10.3.8. cast_json_array_to_int_array (JSON)	
1.10.3.9. cast_json_array_to_text_array (JSON)	
1.10.4. List query	Page 13
1.10.4.1. list_query(JSON)	
1.10.4.2. list_query_whitelist_add(_schema text, _tables TEXT[], _roles TEXT[])	
1.10.4.3. list_query_whitelist_delete(_schema TEXT, _tablename TEXT)	
1.10.5. Reports	Page 13
1.10.5.1. save_report ()	
1.10.5.2. save_report ()	
1.10.5.3. save_report (JSON)	
1.10.5.4. execute_report (_report_id INTEGER, _parameters JSON)	
1.10.5.5. execute_report (JSON)	
1.10.6. User and session related functions	Page 14

1.10.6.1. toggle\_user (JSON)  
1.10.6.2. user\_save (JSON)  
1.10.6.3. user\_save\_password (JSON)  
1.10.6.4. username (\_user\_id INTEGER)  
1.10.6.5. user\_id\_from\_name (\_username TEXT)  
1.10.6.6. user\_id\_from\_fullnames(\_fullnames TEXT)  
1.10.6.7. username\_from\_fullnames(\_fullnames TEXT)  
1.10.6.8. hash\_user\_password (\_user\_id INTEGER)  
1.10.6.9. current\_user\_roles()  
1.10.6.10. hash\_user\_password (\_username TEXT)  
1.10.6.11. current\_user\_id()  
1.10.6.12. check\_session\_access (\_session\_id TEXT, \_check\_path TEXT, \_check\_method TEXT)  
1.10.6.13. set\_session\_user\_id (JSON)  
1.10.6.14. session\_insert (JSON)  
1.10.6.15. logout (JSON)  
1.10.7. Other utility functions

# 1. GRAPE

**Note!** This section deals mostly with the backend functionality of systems. For information on the user interface, see "Grape User Interface"

## 1.1 Architecture




Fig. 1: Grape Architecture

## 1.2 Getting started

The tool `grape_init` is a script which makes it easy to start a new Grape application. It is available from the Grape Tools repo ([npm install -g grape\\_tools](#)).

## 1.3 Structure of a Grape Application

### 1.3.1 Directory layout

The layout of a typical project is as follows:

- **api/** - API routes to be loaded and registered by Node on startup
- **db/** - Database-related files (mostly SQL)
  - **schema/** - The pgModeler dbm file, and exported SQL
  - **function/** - Files containing general stored procedures
  - **process/** - Files containing stored procedures related to background processes
  - **data/** - Files containing initial data for the system
  - **deployments/** - Containing subdirectories for specific deployments. See the section Deployments for more information regarding this
- **public/** - Public (HTML, Frontend JavaScript and CSS files). See Grape Frontend Development for more information regarding the contents of this directory
- **grape-ui/** - Public (HTML, Frontend JavaScript and CSS files) for GrapeUI components
- **scripts/** - Scripts
- **log/** - Log files
- **node\_modules/** - This directory is automatically generated by npm when installing modules
- **config.js** - Grape config file (should not be checked into the repo)
- **config.js.example** - Example Grape config file
- **default\_config.js** - Grape config file containing product-specific settings
- **email\_templates** - Email templates

## 1.4 Authentication and access control

Grape manages authentication, sessions, users, passwords and provide access control. Sessions are tracked using a session ID. Session IDs can be obtained by making a call to **POST /grape/login**, providing a valid username and password. On success, this call will return with the session ID, the user's ID, username, roles and employee GUID. In subsequent calls, the session ID is sent to the server using a custom header **X-SessionID** in the HTTP requests. Before an API call is executed, Grape will check the validity of the session ID, and do access control on the path against the user's roles.

Users and user-related information is stored in `grape.user`. Users can belong to one or more access roles, stored in `grape.access_path`. The link-table for these are `grape.user_role`.

Grape includes the following roles and access paths by default:

ROLE	DESCRIPTION	PATHS ALLOWED
guest	No or invalid login	<ul style="list-style-type: none"> <li>• /grape/login</li> </ul>
all	All logged in users	<ul style="list-style-type: none"> <li>• /lookup/*</li> <li>• /grape/list</li> <li>• /grape/api_list</li> </ul>
admin	Administrator	<ul style="list-style-type: none"> <li>• * (all paths allowed)</li> </ul>

## 1.5 API Calls

### 1.5.1 Anatomy of a Grape API call

Grape may receive different type of API calls:

1. Filesystem request: the browser requests a file from the filesystem (for example an HTML, CSS, JS or image file)
2. Database API request: the API call is implemented as a database function, accepting and returning a JSON object
3. File download request: API calls providing a different result than JSON (for example access-controlled files). This calls starts with '/download'

#### 1.5.1.1 FS Request

The first and most simple is a request for a file on the filesystem. A request that does not accept JSON, and does not start with **/download**, will fall under this category. This includes the initial call for **index.html**.

##### 1.5.1.1.1 download\_public\_js\_files

The **download\_public\_js\_files** API call is a special API call that will traverse all subdirectories in the public directories (defined by **public\_directories**), with the names defined by **compile\_js\_dirs**. The default values for **compile\_js\_dirs** is **pages**. This means all subdirectories named "pages" will be traversed for JS files, and served through this call.

#### 1.5.1.2 DB API requests

Database API calls are the most commonly used API calls. The logic for the function is typically implemented as a function in PostgreSQL. The function being called in the database accepts a JSON parameter, and returns a JSON object with the result.




Fig. 2: Anatomy of a DB API

In order to create a DB API call, two changes are needed:

1. The API call needs to be registered in a JS file in one of the project's API directories (defined by the config option **api\_directory**)

```

exports = module.exports = function(app) {
  // register the route
  app.get("/maths/sqrt/:value", api_maths_sqrt);
}
function api_maths_sqrt (req, res)
{
  // call the stored procedure for this API call
  res.locals.db.json_call("maths_sqrt", // the name of the PL/pgSQL function
    {value: req.params.value}, // Build the JSON object as input for this function
    null, // Optional callback (not used here)
    {response: res} // Send the response to res
  );
}
  
```

2. A database function accepting a JSON input parameter and returning a JSON type must be defined in the database. Ideally, the API access function (accepting and returning a JSON) does not implement the business logic, but calls another SQL function to do this.

```
CREATE OR REPLACE FUNCTION maths_sqrt (JSON) RETURNS JSON AS $$
DECLARE
    _value NUMERIC;
    _result NUMERIC;
BEGIN

    _value := ($1->>'value')::NUMERIC; -- Extract values from JSON

    _result := sqrt(_value);           -- Calculation

    RETURN grape.api_success('result', _result); -- Build and return JSON object
END; $$ LANGUAGE plpgsql;
```

**Note!** API calls should always be properly documented! See the section "Documenting code" for more information on this

### 1.5.1.3 Other API calls

## 1.5.2 Access control

Access control is applied to all API calls. Before the API call is executed, the session is validated. If it cannot be validated, the default role **guest** is used. All users belongs to one or more roles, and always to the role named **all**. API calls are registered in the database (table `access_path`) by **path**, **method** and the **role** allowed. The **path** is a regular expression, matching the incoming URL of the request.

**Note!** The SQL function `grape.add_access_path (_path TEXT, _roles TEXT[], _methods TEXT[])` can be used to add a new access path.

## 1.5.3 Consuming an API call

In order to use an API call, you will need to know the following:

1. The URL of the call. This will look like a typical path, for example `/login`
2. The call method. This will usually be **GET** or **POST**

## 1.6 How to send emails from Grape in PostgreSQL

### 1.6.1 Setup

The following needs to be set up in order to send emails from within SQL functions:

1. **smtp** settings in config

```
smtp: {
  host: 'mail.platsoft.net',
  from: 'Merlot <merlot-live@platsoft.net>',
```

```
secureConnection: true,  
port: 465,  
auth: {  
  user: 'username',  
  pass: 'password'  
}  
}
```

2. `email_template_directory` in config containing templates, typically `__dirname + '/email_templates'`

## 1.6.2 Send an email

Call `grape.send_email(to TEXT, template TEXT, data JSON, headers JSON)` to send an email. The values of the parameters should be as follows:

- **to** Email address of receiver
- **template** Template name (see **Email templates** below)
- **data** Template data
- **headers** Optional - this is an array of additional headers to include in the email. For example: `{'X-Key1': 'value', 'X-Key2': 'value'}`

## 1.6.3 Custom headers

Commonly used custom headers:

- **From:** Change the From field
- **Reply-To:** Reply To field

## 1.6.4 Email templates

Email templates live in the `email_template_directory` defined in the app's config. Each template has 4 files (each starting with the specified `templatename`):

- `templatename.subject` - To generate the subject
- `templatename.text` - To generate the plain-text body of the email
- `templatename.html` - To generate the HTML body of the email
- `templatename.attachments` - To generate a list of attachments to include in the email

Underscore's template engine is used. The data sent to `grape.send_email(to, template, data)` is accessible inside the template files. For example, if an email is called with the following data:

```
{ "firstname": "Piet" }
```

The field `firstname` is accessible inside of the templates using `<%= firstname %>`



## 1.6.5 Example

A typical welcome email will have the following templates (assuming the template name is **welcome**):

**welcome.subject:**

```
Hi <%= firstname %>! Welcome to <%= product_name %>
```

**welcome.text:**

```
Hi <%= firstname %>!
Welcome to <%= product_name %>.

Your login details are as follows:
Username: <%= username %>
Password: <%= password %>

Goodbye
```

The HTML file is optional, and follows the same pattern.

This template must be called with a JSON object containing at least fields **firstname**, **product\_name**, **username** and **password**. The send this email, call the `grape.send_email` function:

```
SELECT grape.send_email('piet@platsoft.net', 'welcome',
'{"firstname": "Piet",
"product_name": "Some System",
"username": "Piet",
"password": "Piet123"}'::JSON);
```

## 1.7 Grape settings

Grape stores internal settings in the table `grape.setting`. The following functions can be used to read and manipulate these settings:

1. **grape.set\_value** (*name TEXT, value TEXT*) - sets the value of setting **name** to **value**
2. **grape.get\_value** (*name TEXT, default\_value TEXT*) - returns the value of the setting **name**, or if it does not exist returns **default\_value**
3. **grape.setting** (*name TEXT, default\_value TEXT*) - alias for **grape.get\_value** (*name TEXT, default\_value TEXT*)

### 1.7.1 Known Grape settings

NAME	DESCRIPTION	DEFAULT VALUE
hash_passwords	Indicate whether passwords in <code>grape.user</code> is hashed	false
allow_default_paths	If a path is not found and this setting is true, access will be granted	false
grape_version	Current Grape version	
product_name	Name of the current system	
product_uuid	Unique identifier for the product/system	
product_version	Product version	

NAME	DESCRIPTION	DEFAULT VALUE
data_upload_schema	Default schema for data import tables	grape
disable_passwords	If true, authentication will not check whether the password is correct	false
system_url	URL to access system's frontend	

## 1.8 Grape config file

The following options are recognized in the config passed to Grape:

NAME	DESCRIPTION	DEFAULT VALUE
dburi	DB connection settings	
guest_dburi	DB connection settings for guest users	
api_directory	Directory (or array of directories) containing API files	
db_definition	Array containing directories with DB definitions. Subdirectories schema, function, view and data will be traversed when recreating	
sql_dirs	Array containing directories with DB definitions. All subdirectories will be recursively read	
pg_temp_directory	Path to a directory to which both PostgreSQL and the running node process has write access	
port	Port on which the UI will be available	
http_port	If this is set, and HTTPS is enabled (use_https), then a normal HTTP server will listen on this port	
public_directory	Directory containing public files	
public_directories	List of directories containing public files	
debug		true
maxsockets	Controls the maximum number of sockets supported	500
bordeaux_config_file	Path to Bordeaux config file	__dirname + '/bordeaux_config.json'
document_store	Path to document store	
use_https	Enable or disable HTTPS. sslkey and sslcert need to be set up correctly	false
session_management	Enable or disable session management	true
smtp	SMTP settings for GrapeMailer	

NAME	DESCRIPTION	DEFAULT VALUE
server_timeout	The number of milliseconds of inactivity before a socket is presumed to have timed out	50000
sslkey	Path to private SSL key file	__dirname + '/cert/private.pem'
sslcert	Path to private SSL public certificate	__dirname + '/cert/public_nopass.pem'
hr_system	URL to get access to the Bordeaux system running on Savanna HR system	https://192.168.50.86:3999/
email_template_directory	Path to email templates (See GrapeMailer for more information)	__dirname + '/email_templates'
compile_js_dirs	List of directory names that will be recursed when all JS is being compiled	['pages']

## 1.9 Standardized Error Codes

CODE	DESCRIPTION
-1	Unknown Error
-2	Permission Denied
-3	Invalid Input
-5	Requested data not found
-99	Database Error

## 1.10 Grape SQL Functions

### 1.10.1 API result functions

This functions deal with the creation of standardized API results (in JSON format) to be sent back to the API call. They can be found in [api\\_result\\_json.sql](#)

NAME	PARAMETERS	DESCRIPTION
api_result_error	<b>message</b> TEXT <b>code</b> INTEGER <b>info</b> JSON	Returns a standardized JSON error object with stats as "ERROR" and the other fields populated. Example: <pre>{"status": "ERROR", "message": "Message", "code": -2, "error": {}}</pre>
api_error	<b>message</b> TEXT <b>code</b> INTEGER <b>info</b> JSON	Overload for api_result_error
api_error		With no arguments, an "Unknown error" message will be generated
api_error_invalid_input		Similar to calling <code>api_result_error("Invalid input", -2)</code>
api_success	<b>keys</b> TEXT[] <b>values</b> TEXT[] <b>types</b> TEXT[]	This function will construct a JSON object containing at least one field, "status" with the value "OK". The 3 input parameters should be arrays containing additional keys, values and the associated types (n/i/number/integer, j/json or nothing for text).

NAME	PARAMETERS	DESCRIPTION
api_success	<i>keys</i> TEXT[] <i>values</i> TEXT[]	
api_success	<i>key</i> TEXT <i>value</i> INTEGER	
api_success	<i>key1</i> TEXT <i>value1</i> INTEGER <i>key2</i> TEXT <i>value2</i> INTEGER	Create an API result success JSON object with two integer fields added.
api_success	<i>key</i> TEXT <i>value</i> JSON	Create an API result success JSON object with a JSON field merged into the result.
api_success		Returns a API result object with a status field set to "OK".

## 1.10.2 Data importing functions

NAME	PARAMETERS	DESCRIPTION
data_import_insert		
data_upload_done		
data_import_row_insert		

## 1.10.3 JSON helpers

### 1.10.3.1 json2xml(\_data JSON, \_root TEXT)

**Filename:** json2xml.sql

### 1.10.3.2 json\_diff (\_old JSONB, \_new JSONB)

**Filename:** json\_diff.sql

### 1.10.3.3 json\_diff (\_old JSON, \_new JSON)

**Filename:** json\_diff.sql

### 1.10.3.4 json\_object\_diff (\_old JSONB, \_new JSONB)

**Filename:** json\_diff.sql

### 1.10.3.5 json\_array\_diff (\_old JSONB, \_new JSONB)

**Filename:** json\_diff.sql

### 1.10.3.6 json\_to\_composite\_type\_text(target\_schema TEXT, target\_type TEXT, data JSON)

### 1.10.3.7 json\_to\_composite\_type(target\_schema TEXT, target\_type TEXT, data JSON)

This function will populate a custom type from a JSON object. What sets it apart from the functions available in PostgreSQL, is the fact that it supports complicated multi-level nested objects. **Filename:** json\_to\_composite\_type\_text.sql

### 1.10.3.8 cast\_json\_array\_to\_int\_array (JSON)

Provides an implicit cast from JSON to INT[] (cast\_json\_array\_to\_int\_array.sql).

```
# select cast_json_array_to_int_array('[1,2,3']::JSON);
cast_json_array_to_int_array
-----
{1,2,3}
```

### 1.10.3.9 cast\_json\_array\_to\_text\_array (JSON)

Provides an implicit cast from JSON to TEXT[] ([cast\\_json\\_array\\_to\\_text\\_array.sql](#)).

## 1.10.4 List query

Grape's list\_query call provides an easy way to retrieve rows from a table. Before the contents of a table can be retrieved this way it needs to be added to a whitelist. This functions can be found in [list\\_query.sql](#)

### 1.10.4.1 list\_query(JSON)

This function returns row from a database table. The following input fields are recognized:

- tablename
- schema (optional) TEXT
- sortfield (optional) TEXT
- sortorder (optional) TEXT DESC
- limit (optional) INTEGER default 50
- offset (optional) INTEGER default 0
- filter (optional) array of fields:
- field TEXT
- operand TEXT of '=', '#x003E;', '#x003C;', '#x003E;=', '#x003C;=', 'LIKE', 'ILIKE', 'IS\_NULL', 'IS\_NOT\_NULL', 'IN'
- value text

### 1.10.4.2 list\_query\_whitelist\_add(\_schema text, \_tables TEXT[], \_roles TEXT[])

Adds tables to the whitelist for use in grape list\_query. Users must be in \_roles to be able to access the data in the table

### 1.10.4.3 list\_query\_whitelist\_delete(\_schema TEXT, \_tablename TEXT)

Removes a table from the whitelist.

## 1.10.5 Reports

This functions can be found in [reports.sql](#).

### 1.10.5.1 save\_report ( )

### 1.10.5.2 save\_report ( )

### 1.10.5.3 save\_report (JSON)

### 1.10.5.4 execute\_report (\_report\_id INTEGER, \_parameters JSON)

### 1.10.5.5 execute\_report (JSON)

## 1.10.6 User and session related functions

### 1.10.6.1 toggle\_user (JSON)

**Filename:** user.sql

### 1.10.6.2 user\_save (JSON)

Save user field. Also used to add a new user to the system. **API Call:** POST /grape/user/save

**Filename:** user.sql

### 1.10.6.3 user\_save\_password (JSON)

**Filename:** user.sql

### 1.10.6.4 username (\_user\_id INTEGER)

Returns a TEXT field containing the username matching the user ID provided

**Filename:** user.sql

### 1.10.6.5 user\_id\_from\_name (\_username TEXT)

Returns the user ID (or NULL if not found) for the user matching the username provided.

**Filename:** user.sql

### 1.10.6.6 user\_id\_from\_fullnames(\_fullnames TEXT)

Returns an integer containing the user ID matching the full names provided

**Filename:** user.sql

### 1.10.6.7 username\_from\_fullnames(\_fullnames TEXT)

Returns the username for the user matching the fullnames provided

**Filename:** user.sql

### 1.10.6.8 hash\_user\_password (\_user\_id INTEGER)

Hashes a password for user and updates the user table afterwards.

- If the hash length is the same as the password length and the password starts with a '\$' sign, it is assumed that the password is already hashed and the update is ignored (-1 is returned)
- If grape.setting passwords\_hashed isn't true, nothing is done (return -2)
- On success 0 is returned

### 1.10.6.9 current\_user\_roles()

Returns a list of all roles the current user belongs to **Filename:** user.sql

**Filename:** user.sql

### 1.10.6.10 hash\_user\_password (\_username TEXT)

Overload function for `hash_user_password (_user_id INTEGER)`, taking a username instead of a user ID as input.

**Filename:** user.sql

### 1.10.6.11 current\_user\_id()

Returns the integer value of the current session's "grape.user\_id" setting. This is typically set with grape before any API call is called.

**Filename:** current\_user\_id.sql

### 1.10.6.12 check\_session\_access (\_session\_id TEXT, \_check\_path TEXT, \_check\_method TEXT)

This function performs access control on an API call (based on the path and session ID). It is automatically called by the express app before any API call is performed:

1. Check that the path has access control on it. If it cannot be found, the grape setting `default_access_allowed` is checked, and if true, access will be granted. If not, it will be denied and code 9 will be returned
2. If the path has a role 'guest' granted access to it, everyone will be allowed (even if the session is invalid)
3. If the session is invalid, access will be denied and code 1 returned
4. If the path has a role 'all', only, and all, valid sessions will be granted access
5. If the user has access granted to the access path's role, access is granted
6. If all the above fails, access is denied with code 2

**Filename:** session\_access\_path.sql

### 1.10.6.13 set\_session\_user\_id (JSON)

Sets the current database session's `grape.user_id` config variable for use in stored procedures to identify the current user.

**Filename:** session\_access\_path.sql

**Returns:** JSON

### 1.10.6.14 session\_insert (JSON)

This function inserts a new session for a valid username and password provided.

**Filename:** session.sql

### 1.10.6.15 logout (JSON)

**Filename:** session.sql

## 1.10.7 Other utility functions

NAME	PARAMETERS	DESCRIPTION
month_diff	<code>_d1</code> DATE <code>_d2</code> DATE	Returns an integer containing the number of months between the two dates provided. If the first parameter is after the second (higher date), the return value will be negative.
set_value	<code>_name</code> TEXT <code>_value</code> TEXT	Sets the value (insert if new, replace if exist) in the key-value pair table <code>grape.setting</code> returning <code>_value</code> .
get_value	<code>_name</code> TEXT <code>_default_value</code> TEXT	Gets the value for setting <code>_name</code> , and if not found it will return <code>_default_value</code> . Defined in <a href="#">setting.sql</a>
generate_uuid		Generates a unique UUID (for example b1086d35-e973-4356-3adc-2eeb6f4963e2). Defined in <a href="#">uuid.sql</a>
array_lowercase	TEXT[]	
clean_telephone_number	<code>_tel</code> TEXT	

NAME	PARAMETERS	DESCRIPTION
random_string	<i>length</i> INTEGER	Generates a random string of <i>length</i> length. Defined in <a href="#">random_string.sql</a>