

# molecule **destroy** && molecule **converge**

```
PLAY [Converge] *****
```

```
TASK [Include web] *****
```

```
Thursday 18 August 2022 16:34:56 +0000 (0:00:00.052) 0:00:00.052 *****
```

```
TASK [web : Converge state - present] *****
```

```
Thursday 18 August 2022 16:34:56 +0000 (0:00:00.038) 0:00:00.090 *****
```

```
included: /home/ansible/.ansible/roles/web/tasks/present.yml for ubi8
```

```
TASK [web : Manage web server] *****
```

```
Thursday 18 August 2022 16:34:57 +0000 (0:00:00.037) 0:00:00.127 *****
```

```
[WARNING]: The "podman" connection plugin has an improperly configured remote target value, forcing "inventory_hostname" templated value instead of the string
```

```
changed: [ubi8]
```

```
TASK [web : Verify state - present] *****
```

```
Thursday 18 August 2022 16:35:03 +0000 (0:00:06.323) 0:00:06.450 *****
```

```
RUNNING HANDLER [web : Control web server] *****
```

```
Thursday 18 August 2022 16:35:03 +0000 (0:00:00.043) 0:00:06.493 *****
```

```
[WARNING]: The "podman" connection plugin has an improperly configured remote target value, forcing "inventory_hostname" templated value instead of the string
```

```
changed: [ubi8]
```

```
PLAY RECAP *****
```

```
ubi8 : ok=3 changed=2 unreachable=0 failed=0 s
```

```
kipped=0 rescued=0 ignored=0
```

# Going Further

## Modelling Desired State

### 4. Model desired states 'absent' and 'present' for the web server

- handler/main.yml - start or stop the web server
- Install and start, or stop and delete

`tasks/present.yml`

`tasks/absent.yml`

`tasks/main.yml`

- defaults/main.yml:  
`desired_state: present`  
`package: httpd`
- vars/main.yml:  
`service: "{{ package }}"`