

Starting a service

```
$ vim tasks/present.yml
```

```
---  
# tasks file for web  
- name: Manage web server  
  ansible.builtin.package:  
    name: "{{ webserver }}"  
    state: present  
  notify: Control web server
```

```
$ vim handlers/main.yml
```

```
---  
- name: Control web server  
  ansible.builtin.systemd:  
    name: "{{ webserver }}"  
    state: started  
    enabled: true
```

molecule converge

```
PLAY [Converge] *****  
TASK [Include web] *****  
Thursday 18 August 2022  16:32:57 +0000 (0:00:00.053)          0:00:00.053 *****  
  
TASK [web : Converge state - present] *****  
Thursday 18 August 2022  16:32:57 +0000 (0:00:00.036)          0:00:00.090 *****  
included: /home/ansible/.ansible/roles/web/tasks/present.yml for ubi8  
  
TASK [web : Manage web server] *****  
Thursday 18 August 2022  16:32:57 +0000 (0:00:00.032)          0:00:00.122 *****  
[WARNING]: The "podman" connection plugin has an improperly configured remote  
target value, forcing "inventory_hostname" templated value instead of the  
string  
ok: [ubi8]  
  
TASK [web : Verify state - present] *****  
Thursday 18 August 2022  16:33:01 +0000 (0:00:03.665)          0:00:03.787 *****  
  
PLAY RECAP *****  
ubi8                        : ok=2    changed=0    unreachable=0    failed=0    s  
kipped=0    rescued=0    ignored=0
```