A map of changing contracts.

Follow inputs through each function. See what comes back — and what else might happen.

5 functions changed · 3 files touched · 2 callers to review

Find file, function or type · Entire codebase · Unchanged branches collapsed

+ Added − Removed ~ Changed ? Unknown

storefront / src — 5 changed functions

CONTRACT MAP

CODE TREE	INPUTS	FUNCTION	OUTPUTS	POSSIBLE EFFECTS
api create-user.ts 1 changed	= input: CreateUserInput	~ RETURN FIELD createUser L10 · async	− User.isActive: boolean + User.isActive: ActivityState Promise<User> · nested field	= Writes users ? Indirect calls
auth access.ts 3 changed	− user.isActive: boolean + user.isActive: ActivityState	~ INPUT FIELD canAccess L12 · 2 callers	= boolean ~ Return logic changed	= No direct effects detected Property read + comparison
	+ user: User	+ NEW FUNCTION isSuspended L16 · exported	+ boolean	No direct effects detected
	+ user: User	+ NEW FUNCTION assertActive L20 · exported	+ void	+ Throws AccessError
services activity.ts 1 changed	= userId: string − active: boolean + state: ActivityState	~ INPUT + OUTPUT setActivity L8 · async	− Promise<void> + Promise<User>	= Writes users + Emits activity.changed ? Listener effects

› components › hooks › types › utils › tests Expand all branches ↗

canAccess / follow this change

2 callers to review · signatures unchanged

Open source diff ↗

User.isActive
types/user.ts · boolean → ActivityState

→ canAccess(user) → boolean
access.ts · now checks ActivityState.Active

→ AccountMenu · requireAccess
Review behavior for inactive and suspended users

Effects: direct-body analysis only. ? marks unresolved calls or listeners; no detected effects is not a guarantee.

ILLUSTRATIVE SNAPSHOT