Republic of the Philippines
PHILIPPINE HEALTH INSURANCE CORPORATION
Citystate Centre, 709 Shaw Boulevard, Pasig City
(02) 8662-2588 www.philhealth.gov.ph
PhilHealthOfficial teamphilhealth

PhilHealth YAKAP
PARA MALAYO SA SAKIT

PRIMARY CARE API (PCAPI)

Implementation Guide

YAKAP 2.0 – API Services

Document Control	
Document Title	Primary Care API – YAKAP 2.0 Implementation Guide
Document Code	PCAPI-IG-2.0
Version	Rev.20261026
Proponent Office	PMT-ISM, Information Technology Management Department (ITMD), PhilHealth
Distribution	Service Providers and EMR Developers

APPROVAL SHEET

This document and its attachments have been approved as the Official Implementation Guide for the PhilHealth YAKAP 2.0 Primary Care API (PCAPI).

Following approval of this document, the documents will be distributed to Health Facilities and HIS and EMR Service Providers for compliance to the said project.

Prepared by:

(Sgd.) ZIA NICOLE LLANTO
Head, System Analysis and Design Section
Team Lead for YAKAP Project, AOST
PMT-ISM, ITMD

(Sgd.) PAUL LOUIS CARDANO
YAKAP API Developer, AOST
PMT-ISM, ITMD

Reviewed by:

(Sgd.) MANUEL S. MANLANGIT
Head, Development Section, PMT-ISM, ITMD

Noted by:

(Sgd.) SENECA L. BELCHEZ
Acting Head, PMT-ISM, ITMD

Approved by:

(Sgd.) ALLAN M. DE VILLA
Acting Senior Manager, ITMD

(Sgd.) DR. JESSON V. BUTCON
Acting Senior Vice President, IMS

Document Control

Revision History

Version	Date	Description	Author
Rev.20261026	10/26/2026	Initial release.	Zia Nicole Llanto

Table of Contents

Document Control 3
Revision History 3
Table of Contents 4
1. Introduction 6
1.1 Purpose 6
1.2 Intended Audience 6
1.3 Scope 6
1.4 Reference Documents and Conventions 6
2. API Architecture Overview 8
2.1 Service Coverage 8
2.2 The YAKAP Beneficiary Journey 8
2.3 Environments 9
2.4 Developer Quick Start 9
3. General Integration Guidelines 11
3.1 Integration Model 11
3.2 API Authentication (Bearer Token/JWT) 11
3.3 Standard Response Envelope 13
3.4 HTTP Status Codes and Error Handling 15
3.5 Consent and Data Privacy 16
3.6 Security and Production Readiness Checklist 16
3.7 Date and Time Formats 17
3.8 Payload Encryption 18
3.9 Transaction Identifiers 19
3.10 Patient Verification Modes 21
4. Service Specifications 22
4.1 Service 01 – PhilHealth Check Utility (PCU) 22
4.2 Service 02 – Primary Care Validator 31
4.3 Service 03 – YAKAP Empanelment 36
4.4 Service 04 – YAKAP Selection 40
4.5 Service 05 – Selection Masterlist Download 44
4.5.1 Individual Lookup 44
4.5.2 Batch Download 48
4.6 Service 06 – YAKAP Data Upload 52
Processing model 52
4.6.1 Health Screening and Assessment (FPE) Upload 53

4.6.2 Consultation Upload 69
4.6.3 Diagnostic Request Upload 100
4.6.4 Diagnostic Results Upload 104
4.6.5 Drugs and Medicines Upload 124
4.6.6 Referral Request Upload 129
4.6.7 Upload Status 135
4.7 Service 07 – YAKAP Patient Verification Code 138
4.8 Service 08 – YAKAP Availment Slip 141
Annexes 144
Annex A – Data Dictionary and Library Reference 144
Annex B – PCU Result and Status Code Reference 144
Annex C – Guidelines for Data Encryption Using the Cipher Key 145
Encrypted Data Envelope 145
Encryption Procedure 145
Decryption Procedure 146
Test Vector 146

1. Introduction

1.1 Purpose

PhilHealth's YAKAP 2.0 program connects every Filipino member to a primary care provider for regular checkups, consultations, and basic medicines. The Primary Care API (PCAPI) lets a health facility's Electronic Medical Record (EMR) or Hospital Information System (HIS) exchange YAKAP transactions with PhilHealth electronically: identity verification, provider selection, the Mutual Care Agreement, and clinical encounter data.

This Implementation Guide is the technical reference for that integration. For every PCAPI service it states how to authenticate, what to send, what comes back, which rules apply, and how errors are reported, so an EMR team can build, test and troubleshoot its integration without routine clarification from PhilHealth.

1.2 Intended Audience

- **IT Solution Developers**
- **EMR Service Providers**
- **In-House Developers of Health Facilities (HFs)**

1.3 Scope

This guide covers the eight PCAPI – YAKAP 2.0 services and the token endpoint that precedes them:

#	Service	Function
01	PhilHealth Check Utility (PCU)	Liveness check and PhilSys and PhilHealth membership verification, called through PCAPI.
02	Primary Care Validator	One query returning the beneficiary's standing across PCU, Selection, Empanelment, FPE and Consultation.
03	YAKAP Empanelment	Records the Mutual Care Agreement between the beneficiary and the YAKAP Clinic.
04	YAKAP Selection	Records the beneficiary's selection or reselection of a YAKAP Clinic.
05	Selection Masterlist Download	Individual lookup by PIN and batch download by assignment date.
06	YAKAP Data Upload	Six asynchronous upload endpoints, one per clinical form, and an Upload Status endpoint.
07	YAKAP Patient Verification Code	Validates the verification code (one-time PIN) PhilHealth issues to a patient.
08	YAKAP Availment Slip	Returns the beneficiary's YAKAP Availment Slip as a PDF file.

1.4 Reference Documents and Conventions

Document	Version	Role
Primary Care API – YAKAP 2.0 Data Dictionary	rev20261026 (10/26/2026)	Authoritative field definitions: names, JSON types, sizes, required status, JSON paths and validation rules for every request and response (Annexes A to G).
Primary Care API – YAKAP 2.0 Library Reference	rev20261026 (10/26/2026)	Authoritative coded values. Send only codes with LIBRARY STATUS 1.

Conventions used in this guide:

- **Required** columns use Yes, No or Conditional. Conditional fields state the rule that makes them required.
- Request samples are shown **before encryption** and response data **after decryption** (Section 3.8). Error responses are shown exactly as returned.
- Field names are lower snake_case. Codes are text: keep leading zeros (for example "01").
- Where this guide and the Data Dictionary differ on a field, the Data Dictionary prevails.

2. API Architecture Overview

2.1 Service Coverage

All eight services are called from the EMR backend through PCAPI with a bearer token. Only the PCU LIVENESS capture page runs in the member's browser. Each service is independently callable; together they cover one beneficiary journey.

No.	Service	Endpoints	Section
–	Token	POST /api/v1/auth/token	3.2
01	PhilHealth Check Utility (PCU)	POST /api/v1/pcu/start POST /api/v1/pcu/verify	4.1
02	Primary Care Validator	POST /api/v1/philhealth-yakap-validator	4.2
03	YAKAP Empanelment	POST /api/v1/yakap-empanelment	4.3
04	YAKAP Selection	POST /api/v1/yakap-selection	4.4
05	Selection Masterlist Download	POST /api/v1/yakap-selection-masterlist/individual POST /api/v1/yakap-selection-masterlist/batch	4.5
06	YAKAP Data Upload	POST /api/v1/yakap-data-upload/{fpe | consultation | diagnostic-request | diagnostic-results | medicine | referral} GET /api/v1/yakap-data-upload/status/{upload_transaction_no}	4.6
07	YAKAP Patient Verification Code	POST /api/v1/yakap-patient-verification-code	4.7
08	YAKAP Availment Slip	POST /api/v1/yakap-availment-slip	4.8

2.2 The YAKAP Beneficiary Journey

A typical journey uses the services in this order:

1. Identity verification – PCU (4.1): the EMR backend starts a check, the member completes a browser LIVENESS capture, and the EMR backend verifies it through PCAPI and stores the returned trans_no.

2. Clinic selection and FPE – YAKAP Selection (4.4) and FPE Upload (4.6.1): the verified beneficiary selects or reselects the YAKAP Clinic, and the EMR uploads the First Patient Encounter (FPE) and confirms through Upload Status that it is accepted.

3. Empanelment – YAKAP Empanelment (4.3): the verified beneficiary with an active Selection and FPE signs the Mutual Care Agreement.

4. Clinical encounters – YAKAP Data Upload (4.6): the EMR uploads the Consultation, Diagnostic Request and Results, Medicine and Referral records, then reads each outcome from Upload Status.

5. Status checks – Primary Care Validator (4.2): at any point the EMR reads the beneficiary's standing in one call.

6. Clinic records – Masterlist (4.5) and Availment Slip (4.8): the YAKAP Clinic downloads its assigned beneficiaries and prints availment slips.

> **Note:** The order above is typical, not enforced, except where a service states a precondition (for example, Empanelment requires an active Selection and an accepted FPE at the facility).

2.3 Environments

Environment	Purpose	Base URL
PCAPI Staging and Integration	Developer integration testing for all eight services	https://{pcapi-host}/primary-care – announced by PhilHealth advisory
PCAPI Production	Live transactions after certification	Issued at certification onboarding
LIVENESS (browser only)	LIVENESS SDK and capture page used by PCU (Section 4.1)	Returned by POST /api/v1/pcu/start (sdk_url and launch_url); loaded by the member's browser only and not configured in the EMR

Hosts are issued through an official PhilHealth advisory to certified Service Providers and in the certification onboarding notice. This guide does not list them so that a host change does not require a new revision; the next revision records them for reference.

2.4 Developer Quick Start

The steps below take an EMR from credentials to a processed upload. Each step points to the section with the full rules.

Step	What to do	Section
1. Prepare	Obtain the software certificate ID and secret key (one per Service Provider) and one cipher key per accreditation number (facility). Store all secrets on the backend only.	3.2, 3.6, 4.1
2. Get a token	POST software_cert_id, accre_no (9 characters) and secret_key to /api/v1/auth/token. Use data.access_token as "Authorization: Bearer <token>" for one hour.	3.2
3. Build the request	Build the plain JSON body as specified for the endpoint, including consent: true and, where required, the patient verification fields. Send every string field of each group you send; use "" when a string has no value; leave out number fields with no value; never send null.	3.3, 3.5, 3.10
4. Encrypt	Compute the SHA-256 hash of the plain JSON, derive the AES-256 key from the facility cipher key, encrypt with AES-256-CBC and null-byte padding, and send the encrypted envelope as the request body.	3.8, Annex C
5. Call the API	POST to {base-url}/api/v1/... with Content-Type: application/json and the bearer token.	4
6. Decrypt	On success, decrypt the data member and check its hash. Error responses are never encrypted.	3.8, Annex C
7. Check uploads	An upload returns HTTP 202 and an upload_transaction_no. Poll GET /api/v1/yakap-data-upload/status/{upload_transaction_no} until processing_status is accepted or rejected.	4.6, 4.6.7
8. Handle errors	Read errors[].issue (always a code) and act on the HTTP status: fix and resend on 400, re-authenticate on 401, resolve the cause on 403 and 422, do not resend on 409, contact support with the request_id on 500.	3.4

Minimal call sequence for a consultation

```
POST /api/v1/auth/token                          -> 200, data.access_token
POST /api/v1/pcu/start                           -> 201, launch_token and sdk_url (browser runs
LIVENESS)
POST /api/v1/pcu/verify                          -> 200, data.trans_no (store it)
POST /api/v1/philhealth-yakap-validator          -> 200, current standing
POST /api/v1/yakap-data-upload/consultation      -> 202, data.upload_transaction_no
GET  /api/v1/yakap-data-upload/status/{number}   -> 200, processing_status = accepted
```

3. General Integration Guidelines

3.1 Integration Model

PCAPI is the single entry point for every backend call. PCAPI forwards PCU calls to the PCU service on your behalf. Only the PCU LIVENESS capture runs in the member's browser against the LIVENESS host.

Caller	Services	Authentication
EMR backend → PCAPI	Token endpoint and Services 01 to 08	Bearer token (JWT), Section 3.2; token endpoint is public
Member browser → LIVENESS	Service 01 capture step only	One-time launch token obtained through PCAPI, Section 4.1

Endpoints are versioned in the path (/api/v1/). Paths in Section 4 are relative to the environment base URL, which includes /primary-care: POST /api/v1/auth/token is called as {base-url}/api/v1/auth/token. This guide is versioned independently of the API with date-based revisions (for example rev20261026).

3.2 API Authentication (Bearer Token/JWT)

Every service requires a bearer token. Each Service Provider holds one software certificate ID and secret key, linked to the accreditation numbers (accre_no) of the facilities it serves. The backend exchanges them, with the accre_no of the facility it is acting for, for a token valid for one hour, and presents it on every call.

`POST` `/api/v1/auth/token`

Item	Value
Authentication	None (public endpoint)
Encryption	None: request and response are plain JSON (the only exception to Section 3.8)
Success	HTTP 200

Request

```
{
  "software_cert_id": "SC-123456",
  "accre_no": "H12345678",
  "secret_key": "<secret key>"
}
```

Parameter	Type	Required	Description
software_cert_id	string	Yes	Software certificate ID issued to the Service Provider (one per Service Provider).
accre_no	string (9)	Yes	Accreditation number of the health facility the EMR is acting for. Must be linked to the software certificate and active. Exactly 9 characters.
secret_key	string	Yes	Secret key issued with the software certificate.

Response

```
{
  "status": "success",
  "code": 200,
  "message": "Authentication successful",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
    "access_token": "eyJhbGci...",
    "token_type": "Bearer",
    "expires_in": 3600
  }
}
```

Field	Type	Returned	Description
data.access_token	string	Always	Bearer token to present on every other API call.
data.token_type	string	Always	Always Bearer.
data.expires_in	number	Always	Seconds until the token expires (3600).

Present the token on every other call as a standard header:

```
Authorization: Bearer <access_token>
```

What PhilHealth checks before issuing a token

- The software certificate exists, is active and is certified.
- accre_no is exactly 9 characters, is linked to the software certificate, and the link and facility are active.
- secret_key matches the stored credential.

Token contents (for reference; you do not need to decode the token)

```
{
  "sub": "SC-123456",          // software_cert_id
  "accre_no": "H12345678",
  "version": "2.0",
```

```
  "jti": "uuid-unique-per-token",
  "iat": 1789430400,
  "exp": 1789434000            // one hour after issuance
}
```

Certification, expiry and revocation

- Access is granted per software certificate, not per endpoint: a certified certificate can call every endpoint in this guide.
- The facility in the token (accre_no) is the facility for every request: services take accre_no from the token and select the cipher key by it.
- Tokens expire after 3600 seconds. Request a new one; do not cache tokens beyond expiry.
- PhilHealth may revoke a token early (secret rotated or compromised, certificate or facility link deactivated, certification withdrawn). A revoked token returns 401; re-authenticate.

Errors

HTTP	Issue	When
400	validation_error	software_cert_id, accre_no or secret_key missing or malformed, or accre_no not 9 characters.
401	invalid_credentials	The software certificate does not exist, or secret_key does not match.
403	software_not_certified	The software certificate is inactive or not certified, or its certification was withdrawn.
403	facility_not_linked	accre_no is not linked to the software certificate, or the link or facility is inactive.
500	internal_error	Contact PhilHealth support with the request_id. Do not retry automatically.

Sample error response

```
{
  "status": "error",
  "code": 401,
  "message": "Authentication failed",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "errors": [
    {
      "field": "secret_key",
      "issue": "invalid_credentials"
    }
  ]
}
```

3.3 Standard Response Envelope

Every endpoint returns the same envelope. status, code, message, timestamp and request_id are always readable; data is present on success and errors on failure.

```
{
  "status": "success" | "error",
  "code": 200,
  "message": "human-readable summary",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "<uuid>",
  "data": { ... },                                  // success only; encrypted (Section 3.8)
  "errors": [ { "field": "<JSON path>", "issue": "<issue code>" } ]   // error only
}
```

Field	Type	Returned	Description
status	string	Always	"success" or "error".
code	number	Always	HTTP status code repeated in the body.
message	string	Always	Human-readable summary.
timestamp	string (YYYY-MM-DDTHH:MM:SS)	Always	Time of the response, Philippine Standard Time.
request_id	string	Always	UUID of the request; log it for support.
data	object	Conditional	Service payload on success; encrypted on every endpoint except the token endpoint (Section 3.8).
errors[].field	string	Conditional	Request field the error refers to (JSON path).
errors[].issue	string	Conditional	Issue code from the error table of the endpoint (for example validation_error, beneficiary_not_found). Always a code; the readable text is in message.

- Log and keep the request_id of every response; quote it to PhilHealth support.
- message is informational and may be reworded; program against code, errors[].issue and the data fields.
- All field names, in the envelope and every payload, are lower snake_case.

Values, empty strings, null and omitted fields

Null, an empty string and an omitted field are not equivalent. Requests follow these rules (Data Dictionary, Validation Rules):

Field status	String field	Number or boolean field
Required (Yes)	Present with a valid, non-empty value.	Present with a valid value.
Optional (No), no value	Present as an empty string "". Leaving it out is rejected.	Left out.
Conditional, rule applies	As Required.	As Required.
Conditional, rule does not apply	Present as "".	Left out.
Field or group whose rule says "leave out" or "must be absent"	Omitted entirely (for example the guardian group when patient_type = MM).	Omitted entirely.
null	Never accepted in a request.	Never accepted in a request.

These rules apply to every field of each data group you send. A group that does not apply (for example gynehist for a male patient) is left out as a whole. PCU request fields follow the rules in Section 4.1. In responses, each service states how a missing value is returned: the Primary Care Validator omits fields that have no value; YAKAP Empanelment and the Selection Masterlist return an empty string.

3.4 HTTP Status Codes and Error Handling

Code	Meaning	Usage and client action
200	OK	Request processed. For PCU, also a failed verification: read data.status and data.result_code. For an upload, an identical resend.
201	Created	Record created: LIVENESS authorization, Empanelment, Selection.
202	Accepted	Upload queued; read the outcome from Upload Status (4.6.7).
400	Bad Request	Validation, decryption or hash failure. Fix the request and resend.
401	Unauthorized	Token missing, invalid, expired or revoked. Request a new token.
403	Forbidden	Not permitted: missing consent (consent_required), uncertified software or unlinked facility on the token endpoint or an invalid LIVENESS launch or authorization on PCU. Resolve the cause; do not retry blindly.
404	Not Found	No matching beneficiary, record, assignment, upload or slip.
409	Conflict	Duplicate: the record or transaction already exists. Do not resend.
422	Unprocessable Entity	Business rule failure (for example deceased beneficiary, verification not accepted, beneficiary assigned elsewhere).
429	Too Many Requests	Rate limit (PCU only). Back off; do not replay a verification.
500	Internal Server Error	Server fault; no stack trace is exposed. Contact support with the request_id.
502, 503, 504	Upstream or availability errors	PCU only (Section 4.1). Follow the PCU retry rules.

Error envelope

Errors are returned in plain JSON (never encrypted) with one errors[] entry per problem. **field** is the JSON path of the request field concerned and **issue** is always an issue code from the endpoint's error table; the readable explanation is in message.

Sample error response

```
{
  "status": "error",
  "code": 400,
  "message": "Invalid request payload",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "errors": [
    {
      "field": "patient_pin",
```

```
      "issue": "validation_error"
    }
  ]
}
```

Errors common to every encrypted endpoint

HTTP	Issue	When
400	validation_error	A field fails a required, conditional, type, size, format or library-code check. Every failing field is listed.
400	decryption_failed / hash_mismatch	The encrypted request cannot be read (Section 3.8).
401	unauthorized	Bearer token missing, invalid, or expired (Section 3.2). Request a new token.
403	consent_required	consent is missing or not true (Section 3.5).
500	internal_error	Contact PhilHealth support with the request_id. Do not retry automatically.

Each service section lists its own errors in addition to these. Apply timeouts and controlled retry with backoff only to 5xx responses and network failures; never retry 4xx responses unchanged.

3.5 Consent and Data Privacy

- Obtain and keep the patient's explicit consent before calling any service that processes personal or health information, and attest it in the request: every service except the token endpoint and PCU carries **consent** (boolean, must be true). PCU has no consent field; obtain and record consent before starting a check (Section 4.1). For uploads, consent sits at the top level of the request body.
- A missing or false consent value returns 403 consent_required; the request is not processed.
- Do not log software certificates, secret keys, cipher keys, access tokens, LIVENESS launch tokens, complete identity payloads or ID images. Mask identifying fields in logs: partially mask a PIN (for example 1234-*****-12) and a birth date; fully mask secrets.
- ID pictures sent as valid_id_image (patient_verification_mode = VALID_ID) are personal data: transmit them only inside the encrypted request and keep any local copy encrypted at rest with restricted access.
- Handle all beneficiary data under the Data Privacy Act of 2012 (RA 10173) and PhilHealth data governance policies.

3.6 Security and Production Readiness Checklist

Applies to every integration, in addition to the PCU checklist in Section 4.1.

- Call PCAPI only from a protected backend; never expose certificates, secret keys, cipher keys or tokens to a browser or mobile client.

- Use HTTPS with certificate and hostname verification for PCAPI, the LIVENESS host and your EMR.
- Store secrets in a secrets manager or protected server configuration, never in source control.
- Use the cipher key of the facility named in the token; keep one key per accreditation number.
- Request a new token at expiry (one hour); never extend or reuse an expired token.
- Load the LIVENESS SDK only from the sdk_url returned by POST /api/v1/pcu/start.
- Send consent: true only after consent is recorded; keep the consent record.
- Apply timeouts, controlled retry with backoff for 5xx and network errors, and correlation by request_id and transaction numbers.
- Generate record numbers in the 23-character format (Section 3.9) and never reuse a number for different content.
- Poll Upload Status for every upload until it is accepted or rejected; correct and resubmit rejected records.
- Rotate test credentials before production onboarding.
- Test failure paths: expired token, missing consent, validation errors, duplicate submissions, rejected uploads and decryption errors.

3.7 Date and Time Formats

Formats are fixed and validated. MM/DD/YYYY is used in every request, including the PCU start request; PCAPI converts the PCU birth date to the format PCU expects. Month-only dates use MM/YYYY, years YYYY, times HH:MM (24-hour), and timestamps YYYY-MM-DDTHH:MM:SS (Philippine Standard Time).

Service	Dates in the request	Dates in the response
Envelope (all)	–	timestamp: YYYY-MM-DDTHH:MM:SS
4.1 PCU	birth_date: MM/DD/YYYY (start)	YYYY-MM-DD (konsulta.date_assigned, returned by PCU unchanged); expires_at: YYYY-MM-DDTHH:MM:SS
4.2 Primary Care Validator	patient_dob: MM/DD/YYYY; eff_year: YYYY	MM/DD/YYYY in the status objects; eff_year: YYYY
4.3 YAKAP Empanelment	No dates	eff_year: YYYY
4.4 YAKAP Selection	selection_date: MM/DD/YYYY	selection.date: MM/DD/YYYY
4.5 Selection Masterlist Download	start_date, end_date: MM/DD/YYYY; eff_year: YYYY	patient_dob, member_dob, assignment_date: MM/DD/YYYY
4.6 YAKAP Data Upload	MM/DD/YYYY; MM/YYYY; YYYY; HH:MM	received_at, processed_at: YYYY-MM-DDTHH:MM:SS
4.7 YAKAP Patient Verification Code	transaction_date: MM/DD/YYYY	transaction_date: MM/DD/YYYY

Service	Dates in the request	Dates in the response
4.8 YAKAP Availment Slip	eff_year: YYYY	No dates (PDF file)

3.8 Payload Encryption

Every endpoint in Section 4 exchanges its payload encrypted with the facility cipher key, using AES-256-CBC and the encrypted data envelope in Annex C. PhilHealth issues one cipher key per accreditation number; use the key of the facility in the bearer token (accre_no). The same key works in both directions. The token endpoint is the only exception.

Requests

The whole request body is the encrypted envelope, sent with Content-Type: application/json. GET endpoints have no body; their path parameters are sent as usual.

```
{
  "docMimeType": "application/json",
  "hash": "<lowercase hex SHA-256 of the plain JSON>",
  "key1": "",
  "key2": "",
  "iv": "<base-64 IV>",
  "doc": "<base-64 encrypted JSON>"
}
```

Responses

The envelope fields stay readable; only data is encrypted and carries the encrypted envelope in place of the plain object. Decrypt it with Annex C to obtain the data shown in each service section. The YAKAP Availment Slip decrypts to a PDF file (docMimeType = application/pdf).

```
{
  "status": "success",
  "code": 200,
  "message": "string",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
    "docMimeType": "application/json",
    "hash": "<lowercase hex SHA-256 of the plain JSON>",
    "key1": "",
    "key2": "",
    "iv": "<base-64 IV>",
    "doc": "<base-64 encrypted JSON>"
  }
}
```

Field	Type	Returned	Description
docMimeType	string	Always	MIME type of the plain data: application/json, or application/pdf for the Availment Slip.
hash	string	Always	Lowercase hex SHA-256 of the plain data (64 characters).
key1	string	Always	Reserved; empty string.
key2	string	Always	Reserved; empty string.
iv	string	Always	Base-64 initialization vector (16 random bytes).
doc	string	Always	Base-64 AES-256-CBC encrypted data.

Errors

Error responses are never encrypted. Two errors concern encryption:

HTTP	Issue	When
400	decryption_failed	The body is not a valid encrypted envelope or cannot be decrypted with the facility cipher key. Check the fields, key derivation, IV and padding (Annex C).
400	hash_mismatch	The decrypted request does not match its hash. Recompute the hash over the plain JSON before encrypting.

Sample error response

```
{
  "status": "error",
  "code": 400,
  "message": "Request could not be decrypted",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "errors": [
    {
      "field": "doc",
      "issue": "decryption_failed"
    }
  ]
}
```

3.9 Transaction Identifiers

Record numbers are 23 characters: a one-letter prefix, the 9-character accre_no of the facility in the token, the date as YYYY + MM + DD, and a 5-digit series that restarts every day. Example: SH123456782026102500001 is consultation 00001 of facility H12345678 on 10/25/2026. The EMR generates T, E, P, S, D, L, M and R numbers; PhilHealth generates K and U numbers.

Identifier	Prefix	Size	Identifies	Role
case_no	T	23 BYTE (all annexes)	Patient case number	Record association: links every record of one patient. Generated by the EMR.
enlist_transaction_no	E	23 BYTE	Enlistment record	Primary transaction of the enlistment record. Generated by the EMR.
profile_transaction_no	P	23 BYTE	FPE (Health Screening) record	Primary transaction of the FPE record. Generated by the EMR.
soap_transaction_no	S	23 BYTE (all annexes)	Consultation (SOAP) record	Primary transaction in Annex B; parent reference in C, D, E and F. Generated by the EMR.
request_transaction_no	D	23 BYTE	Diagnostic request	Primary transaction in Annex C; parent reference in Annex D. Generated by the EMR.
result_transaction_no	L	23 BYTE	Diagnostic result entry	Primary transaction of one result entry and resend key of the Diagnostic Results upload. Generated by the EMR.
request_transaction_no + diagnostic_code	-	-	Link between a result entry and its requested test	Linkage key: each diagnostic_code appears at most once per request; the result entry repeats the pair.
meds_transaction_no	M	23 BYTE	Medication prescription	Primary transaction of the prescription. Linked to the consultation by soap_transaction_no. Generated by the EMR.
referral_transaction_no	R	23 BYTE	Referral request	Primary transaction of the referral; unique per referral. One consultation may have one or more referrals. Generated by the EMR.
selection.transaction_no	K	23 BYTE	Selection or reselection record	Identifies a successful selection or reselection; not sent in a request.
upload_transaction_no	U	23 BYTE	Submission to a YAKAP Data Upload endpoint	Identifies one submission and its processing outcome; not a record key; not sent in an upload request body; used as the Upload Status path parameter.
yes_reference_no	MCA	10 BYTE	Mutual Care Agreement (empanelment) record	Reference number of the recorded agreement; not part of the 23-character family.
patient_pin	-	12 BYTE	Patient (member or dependent)	Patient identifier (member PIN if MM, dependent PIN if DD).
pcu_transaction_code (PCU trans_no); one_time_pin	-	20 BYTE	Patient verification	Verification evidence for the encounter, not a record key.

- A record number identifies one record; resending it with identical content is safe (Section 4.6), with different content is rejected (409).
- The accre_no segment must equal the accre_no in the bearer token.
- trans_no returned by PCU is at most 20 characters; it is sent as pcu_transaction_code in Empanelment, Selection and the uploads. In the samples, PCU-LOG-TRANS-NO stands for that value.

3.10 Patient Verification Modes

Empanelment, Selection, the FPE upload and the Consultation upload record how the patient was verified (patient_verification_mode, Library Reference – Patient Verification Mode). The mode decides which evidence fields are required. String evidence fields that do not apply are sent as "" (Section 3.3).

Mode	Required evidence	Checks applied	Obtained from
PCU	pcu_transaction_code (PCU trans_no, at most 20 characters)	Empanelment and Selection: verification on the same day, PIN on the PCU record equals patient_pin, result code 105 or 109.	Service 01 (Section 4.1)
OTP	one_time_pin (YAKAP Patient Verification Code, at most 20 characters)	Valid for the patient, the facility in the token and the transaction date; validation does not use up the code.	Issued by PhilHealth to the patient; validated by Service 07 (Section 4.7)
VALID_ID	valid_id_type (Library Reference – Valid ID Type) and valid_id_image (base-64 JPEG, at most 2 MB before encoding)	Only listed ID types are accepted. The image is required on the first VALID_ID request for the patient, facility and date and may be "" on later requests that day.	ID presented by the patient at the facility

Valid ID images: PhilHealth decrypts the request and stores the image on premises (file server and database) for review. Send JPEG only, resized to at most 2 MB before base-64 encoding. An ID not in Library Reference – Valid ID Type is not accepted; facilities request additions from PhilHealth.

4. Service Specifications

This section documents each of the eight PCAPI – YAKAP 2.0 services.

4.1 Service 01 – PhilHealth Check Utility (PCU)

PCU verifies a member's identity in three steps: your backend starts a check through PCAPI, the member completes a LIVENESS face capture in their browser, and your backend then asks PCAPI to verify. PCAPI builds both PCU requests for you – you send only the patient's details at the start and, after the capture, the authorization ID.

Field	Value
Function	Liveness check and PhilHealth membership verification at the point of service.
Authentication	Bearer JWT (Section 3.2), as for every other service.
Integration model	Two backend calls to PCAPI – POST /api/v1/pcu/start and POST /api/v1/pcu/verify – with the LIVENESS face capture in the member's browser in between. PCAPI prepares and sends the PCU requests on your behalf.

Integration flow

1. Start – when staff start the PhilHealth check, your backend sends the patient's details to POST /api/v1/pcu/start. PCAPI prepares the verification and returns a one-time LIVENESS authorization.

2. Capture – your page loads the LIVENESS SDK from the address returned in step 1 and redirects the tab to the PhilHealth capture page; the member completes the face capture and the tab returns to your page.

3. Verify – your page checks the return, then your backend sends the authorization ID to POST /api/v1/pcu/verify. PCAPI calls PCU with the details from step 1.

4. Result – read the PCU result (status, result_code, trans_no) and store trans_no with the patient's record.

Obtain and record the member's consent before starting a check (Section 3.5). The PCU endpoints have no consent field.

> **Important:**
> Both PCAPI calls are made from your backend. The browser receives only a short-lived, one-time LIVENESS launch token; it never receives your PCAPI credentials or bearer token.
>
> **One attempt per reference:**
> Check the return status, state, authorization ID, path and expiry before calling verify. A completed capture is not proof of identity. PCU performs the verification; every retry after a submitted verification requires a new check, starting from Step 1.

Step 1 – Start the check (backend)

When staff start the check, your backend sends the patient's details to PCAPI. PCAPI prepares the PCU verification and returns a one-time LIVENESS authorization for the browser.

`POST` `/api/v1/pcu/start`

Send your bearer token in the Authorization header (Section 3.2). Send the patient's details as shown in your EMR – usually from the beneficiary search – so that PSA can match them with the face capture. Do not send a transaction ID, purpose, origin or consent field: PCAPI sets these.

Request body (application/json), shown before encryption (Section 3.8):

```
{
  "pin": "123456789012",
  "first_name": "JUAN",
  "middle_name": "SANTOS",
  "last_name": "DELA CRUZ",
  "suffix": "",
  "birth_date": "01/31/1990"
}
```

Parameter	Type	Required	Description
pin	string (12)	No	PIN of the patient, when known. Not sent to PCU; PCAPI uses it to set pin_matched in the verify response (Step 3).
first_name	string	Yes	Member's first name.
middle_name	string	No	Use an empty string, or leave it out, when the member has no middle name. PCAPI sends an empty string to PCU.
last_name	string	Yes	Member's last name.
suffix	string	No	Name suffix such as Jr., Sr. or III.
birth_date	string (MM/DD/YYYY)	Yes	Member's date of birth. PCAPI converts it to YYYY-MM-DD for PCU.

What PCAPI does: it calls LIVENESS authorize with a new transaction ID – the request_id of this call, so quote that request_id to PhilHealth support for any issue with this check – and keeps your patient's details with the authorization until it expires, ready for Step 3. Each call starts a new attempt.

A successful start returns HTTP 201. The data object is encrypted (Section 3.8); it is shown here before encryption. Pass launch_token only to the SDK; never log it, store it, or place it in a URL.

```
{
  "status": "success",
  "code": 201,
  "message": "PhilHealth check started",
  "timestamp": "2026-10-25T10:15:30",
```

```
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
    "authorization_id": "string",
    "launch_token": "string",
    "launch_url": "string",
    "sdk_url": "string",
    "expires_at": "string"
  }
}
```


Field	Type	Description
data.authorization_id	string	ID of this attempt. Keep it: pass it to the SDK (Step 2), and send it to verify as liveness_authorization_id (Step 3).
data.launch_token	string	One-time token for the SDK. Never log it, store it, or place it in a URL.
data.launch_url	string	Address of the PhilHealth capture page, for the SDK.
data.sdk_url	string	Address of the LIVENESS SDK script. Load it in your page from this value (Step 2) – do not hard-code a LIVENESS address in your EMR.
data.expires_at	string	When the authorization expires. The capture and the verify call must both happen before then.

Step 2 – Run LIVENESS in the browser

Load the LIVENESS SDK from data.sdk_url returned in Step 1, then redirect the tab to the capture page with the authorization from Step 1. Because the address comes from PCAPI, your EMR does not configure any LIVENESS address. After the capture, the same tab returns to your page; no popup is needed.

`GET` {sdk_url} – returned by Step 1

Browser example:

This example uses sample form IDs and two endpoints of your own backend – /index.php/welcome/start_pcu and /index.php/welcome/verify_pcu – which call PCAPI (Steps 1 and 3) and return only the data object to the browser, never your bearer token. Adapt the IDs and paths to your EMR.

```
<script>
// Loads the LIVENESS SDK from the address returned by Step 1 (data.sdk_url).
function loadSdk(url) {
  return new Promise((resolve, reject) => {
    if (window.eKYC) { resolve(); return; }
    const script = document.createElement('script');
    script.src = url;
    script.onload = () => resolve();
    script.onerror = () => reject(new Error('The LIVENESS SDK could not be loaded.'));
    document.head.appendChild(script);
  });
```

```
}

async function startPhilHealthCheck() {
  const bytes = crypto.getRandomValues(new Uint8Array(32));
  const state = Array.from(bytes, b => b.toString(16).padStart(2, '0')).join('');
  const returnUrl = location.origin + location.pathname;
  try {
    // Step 1: your backend calls POST /api/v1/pcu/start with the patient's details
    // and returns only the data object. Include the CSRF field rendered by your backend.
    const form = new URLSearchParams();
    ['pin', 'first_name', 'middle_name', 'last_name', 'suffix', 'birth_date'].forEach(id => {
      form.append(id, document.getElementById(id).value);
    });
    form.append(document.getElementById('pcu_csrf').name,
                document.getElementById('pcu_csrf').value);
    const authorization = await fetch('/index.php/welcome/start_pcu', {
      method: 'POST',
      headers: {'X-Requested-With': 'XMLHttpRequest'},
      body: form,
      credentials: 'same-origin'
    }).then(async response => {
      const data = await response.json();
      if (!response.ok) { throw new Error(data.message); }
      return data;
    });

    // Step 2: load the SDK from the returned address.
    await loadSdk(authorization.sdk_url);
    const client = window.eKYC();
    if (typeof client.redirect !== 'function') {
      throw new Error('The configured SDK does not support redirect mode. Contact PhilHealth
support.');
    }

    // Keep the attempt in a temporary tab-scoped draft. Never store the launch token.
    sessionStorage.setItem('pcu.liveness.redirect.v1', JSON.stringify({
      authorizationId: authorization.authorization_id, state, returnUrl,
      expiresAt: Math.min(Date.parse(authorization.expires_at), Date.now() + 300000)
    }));

    // Go to the capture page. The redirect promise signals navigation,
    // not capture completion.
    await client.redirect({
      authorizationId: authorization.authorization_id,
      launchToken: authorization.launch_token,
      launchUrl: authorization.launch_url,
      returnUrl, returnState: state
    });
  } catch (error) {
    sessionStorage.removeItem('pcu.liveness.redirect.v1');
    // Show the error and let staff start a new check. Never reuse the token.
  }
}

// Step 3: on return, check the fragment against the saved attempt, then verify.
async function onLivenessReturn() {
```

```
  const params = new URLSearchParams(location.hash.slice(1));
  const saved = JSON.parse(sessionStorage.getItem('pcu.liveness.redirect.v1') || 'null');
  history.replaceState(null, '', location.pathname);   // remove the fragment
  sessionStorage.removeItem('pcu.liveness.redirect.v1');
  if (!saved
      || params.get('pcu_liveness_status') !== 'COMPLETED'
      || params.get('pcu_liveness_authorization_id') !== saved.authorizationId
      || params.get('pcu_liveness_state') !== saved.state
      || location.origin + location.pathname !== saved.returnUrl
      || Date.now() > saved.expiresAt) {
    return; // show "check not completed" and let staff start a new check
  }
  // Your backend calls POST /api/v1/pcu/verify with
  // { "liveness_authorization_id": saved.authorizationId } and returns the PCU result.
  const result = await fetch('/index.php/welcome/verify_pcu', {
    method: 'POST',
    headers: {'Content-Type': 'application/json', 'X-Requested-With': 'XMLHttpRequest'},
    body: JSON.stringify({ liveness_authorization_id: saved.authorizationId }),
    credentials: 'same-origin'   // also send your CSRF token
  }).then(response => response.json());
  // Show result.status and result.message; store result.trans_no with the patient.
}

if (location.hash.includes('pcu_liveness_status=')) { onLivenessReturn(); }
</script>
```

Same-tab return

After recording the capture, LIVENESS returns to your EMR URL with the following fragment fields. This is a browser callback, not a PCU API response. The placeholders below are illustrative; do not submit them as real values.

```
#pcu_liveness_status=COMPLETED&pcu_liveness_authorization_id=<completed-authorization-
id>&pcu_liveness_state=<matching-return-state>
```

The return carries the status, the authorization ID and your random state in the URL fragment. Check them against the tab's saved attempt and its expiry, then remove them from the address bar. Cancel, failure, expiry, or browser Back means the attempt is over: start a new check from Step 1. The SDK redirect promise signals navigation, not a successful capture. Use a 64-character lowercase hexadecimal state generated from 32 random bytes. Your return URL must be the EMR page that started the check, with no credentials, query, or fragment. Do not integrate directly with the vendor URL.

Step 3 – Verify (backend)

After the capture, your backend asks PCAPI to verify. You send only the authorization ID; PCAPI adds the patient's details kept from Step 1.

Where liveness_authorization_id comes from

Where	Field	What to do
Step 1 response	data.authorization_id	Keep it with the attempt – in your backend session or the tab's temporary draft.
Browser return (Step 2)	pcu_liveness_authorization_id, in the URL fragment	Must equal the value kept from Step 1, with pcu_liveness_status = COMPLETED and your state.
Step 3 request	liveness_authorization_id	Send that same value.

It is one value under three names. Call verify only when every check passes: if the status is not COMPLETED, the IDs differ, the state does not match or the attempt has expired, start a new check from Step 1.

`POST` `/api/v1/pcu/verify`

Required headers:

```
Accept: application/json
Content-Type: application/json
Authorization: Bearer <access_token>
```

Never place your bearer token, secret key or software certificate in frontend JavaScript, mobile application source, URLs, or public repositories.

Request body (application/json), shown before encryption (Section 3.8):

```
{
  "liveness_authorization_id": "<authorization_id from Step 1>"
}
```

Request parameters

Parameter	Type	Required	Description
liveness_authorization_id	string	Yes	The authorization_id returned by Step 1, after a completed capture (see the table above).

PCAPI finds the attempt started in Step 1 and builds the PCU verification request from the details kept with it and your authorization ID:

What PCAPI sends to PCU

PCU parameter	Type	Required	Value set by PCAPI
consent	boolean	Yes	true. The provider's attestation that explicit consent was obtained; PCAPI sets it because you obtain and record consent before Step 1 (Section 3.5).

PCU parameter	Type	Required	Value set by PCAPI
first_name	string	Yes	Member's first name, from Step 1.
middle_name	string	No	Member's middle name from Step 1, or an empty string when the member has none.
last_name	string	Yes	Member's last name, from Step 1.
suffix	string	No	Name suffix such as Jr., Sr. or III, from Step 1.
birth_date	string	Yes	Date of birth from Step 1, converted from MM/DD/YYYY to YYYY-MM-DD.
sex	string	Yes	Value sent to PSA. PCAPI sends X, the value the current PCU client uses.
liveness_authorization_id	string	Yes	Your liveness_authorization_id: a completed, unexpired, unused authorization belonging to the authenticated provider.

You do not send any of these fields to PCU yourself. The attempt must have been started by your software certificate and must not have expired. An authorization permits only one verification, even if an upstream call fails; start a new check before retrying. PCAPI never retries a verification on its own: if your call times out, treat the authorization as used and start a new check.

Expected response

Valid PCU business outcomes use HTTP 200. The PCU result is returned unchanged in the data object of the standard envelope (Section 3.3), with PCU's own request_id kept as data.request_id, plus pin_matched when you sent a pin in Step 1: Y when it equals member.pin, N when it differs – confirm the patient's identity before continuing. Always evaluate data.status and data.result_code – a valid business outcome such as norecord is still HTTP 200.


```
{
  "status": "success",
  "code": 200,
  "message": "PCU verification completed",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
    "request_id": "1f820a13-18f3-4ef5-b257-672132d30d30",
    "status": "success",
    "message": "PhilHealth Number found",
    "result_code": "105",
    "trans_no": "PCU-LOG-TRANS-NO",
    "verified": "Y",
    "pin_matched": "Y",
    "member": {
      "pin": "MEMBER-PIN",
      "type": "M",
      "sex": "M"
    },
    "konsulta": {
      "searched": true,
      "available": true,
      "assigned": "YES",
```

```
      "hci_name": "KONSULTA FACILITY",
      "date_assigned": "2026-01-01",
      "message": ""
    }
  }
}
```


Where trans_no is used

The trans_no returned by PCU is the PCU transaction number referred to elsewhere in this guide, under the field names below. The field names differ by service, but they all carry this same value. Store trans_no with the patient's record as soon as it is returned: a retry requires a fresh LIVENESS check, so a lost trans_no means verifying the patient again.

Where	Field name	Notes
PCU response (Section 4.1)	data.trans_no	Returned on every verification.
Primary Care Validator response (Section 4.2)	pcu.transaction_no	The PCU verification on record for the beneficiary.
YAKAP Empanelment and YAKAP Selection requests (Sections 4.3 and 4.4)	pcu_transaction_code	Must come from a PCU verification performed on the same day as the request, with result code 105 or 109.
FPE, Consultation and Referral Request uploads (Sections 4.6.1, 4.6.2 and 4.6.6)	pcu_transaction_code	Required when patient_verification_mode = PCU (for the Referral Request, when the consultation was verified with PCU).

Business statuses

Status	Typical code	Meaning
success	105	PhilHealth number found. KONSULTA is searched.
success	109	Member tagged deceased in membership records and updated to active because of the member's liveness check. Counts as verified.
duplicate	106	The profile requires further verification.
deceased	107	Deceased-related membership outcome. KONSULTA is searched.
norecord	108	No PhilHealth number was found.
invalid	101 or 102	PSA could not validate the submitted identity or liveness data.
psaerror	100	PSA processing error.
PSA API 104	104	LIVENESS or PSA credential or session-related error.
error	Varies	Unmapped PCU business response. Inspect message.

See Annex B for the consolidated PCU result and status code reference.

KONSULTA (YAKAP) field interpretation

- searched is true only when the PSA outcome allows a beneficiary lookup.

- available confirms that at least one valid KONSULTA response was received.
- assigned is YES, NO, or null.
- When assignment is NO, hci_name is returned as NOT YET ASSIGNED.

Error responses

HTTP	Status	Action
400	invalid_request	Send a valid JSON object.
400	validation_error	A required field is missing or invalid – for example birth_date not MM/DD/YYYY, or liveness_authorization_id missing. Every failing field is listed in errors.
400	decryption_failed / hash_mismatch	The encrypted request cannot be read (Section 3.8).
401	unauthorized	Bearer token missing, invalid, or expired (Section 3.2). Request a new token and retry.
403	invalid_launch	The launch was not accepted. Start a new check from Step 1.
403	invalid_liveness_authorization	The authorization ID is unknown, the capture is not completed, the attempt has expired or was already verified, or it was started by another software certificate. Start a new check from Step 1.
429	rate_limit_exceeded	Respect the assigned limits and retry with controlled backoff; do not automatically replay verification.
500	configuration_error	A PhilHealth-side configuration problem, including PCU credential errors. Contact PhilHealth support with the request_id.
502	upstream_unavailable	Retry later using controlled backoff and a new check; never reuse a submitted authorization.
502	upstream_error	PSA returned a non-success HTTP response. Start a new check later.
502	invalid_upstream_response	Contact PhilHealth support with the request_id.
503	service_unavailable	Contact PhilHealth support.
504	gateway_timeout	PCU did not respond in time. Treat the authorization as used and start a new check; do not resend the same liveness_authorization_id.

Error response example. PCU errors are returned in the standard error envelope (Section 3.4), with the PCU error status as the issue:

```
{
  "status": "error",
  "code": 403,
  "message": "The LIVENESS authorization cannot be used for verification.",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "errors": [
    {
      "field": "liveness_authorization_id",
      "issue": "invalid_liveness_authorization"
    }
  ]
}
```

Keep and log request_id and data.trans_no for support correlation; trans_no is also needed by later services (see Where trans_no is used). Do not log your bearer token, LIVENESS launch token, or unnecessary identity data.

EMR integration checklist

- Obtain and record the member's consent before starting a check (Section 3.5).
- Call PCAPI only from a protected backend service.
- Use HTTPS for your EMR, PCAPI and the LIVENESS host; keep certificate and hostname verification enabled.
- Store your PCAPI credentials in a secret manager or protected server configuration.
- Never log credentials, bearer tokens, or complete identity or liveness payloads.
- Check the return status, state, authorization ID, path and expiry before calling verify, then clear the fragment and temporary draft.
- Interpret PCU's business status and result code; capture completion and HTTP 200 alone do not prove identity verification succeeded.
- Apply request timeouts and log the request_id of each call. A retry requires a new check from Step 1.
- Rotate test and staging credentials before production onboarding.

Relationship to the Primary Care Validator

A PCU verification result is not automatically visible elsewhere in PCAPI. Its outcome is separately surfaced, read-only, as the PCU status object inside the Primary Care Validator response (Section 4.2) once the underlying verification has been recorded.

4.2 Service 02 – Primary Care Validator

Purpose

Returns the beneficiary's current standing across PCU verification, Selection, FPE, Empanelment and Consultation in one call, so the EMR can confirm status before it transacts. It is read-only.

Item	Value
Endpoint	POST /api/v1/philhealth-yakap-validator
Authentication	Bearer token (Section 3.2); the facility is the accre_no in the token
Encryption	Request body and response data encrypted (Section 3.8, Annex C); errors in plain JSON
Success	HTTP 200

Business rules and preconditions

- Look up by patient_pin, or by first_name + last_name + patient_dob when the PIN is not known (middle_name helps disambiguate).
- eff_year defaults to the current year.
- Identity fields (patient_lname, patient_fname, patient_mname, patient_extname, patient_dob) are returned only when selection.status = ASSIGNED at the facility in the token; otherwise they are omitted and message is returned. Detect this from the presence of the fields, not from the text of message.
- Fields with no value are omitted, not returned as null or "". Do not model them as required properties.
- The latest consultation is decided by consultation_date; when two share the same date, the later consultation_time wins. consultation.date and consultation.transaction_no describe the same record.

Request (before encryption)

```
{
  "patient_pin": "123456789012",
  "eff_year": "2026",
  "first_name": "",
  "last_name": "",
  "middle_name": "",
  "patient_dob": "",
  "consent": true
}
```

Lookup by name and birth date sends patient_pin as "" and the name fields and patient_dob with values.

Parameter	Type	Required	Description
patient_pin	string (12)	Conditional	PhilHealth Identification Number — exactly 12 digits, no separators or spaces. Required if first_name, last_name, and patient_dob are not supplied.
eff_year	string (YYYY)	No	Effectivity year to check against. Defaults to the current year if left blank.
first_name	string (30)	Conditional	Beneficiary first name. Required if patient_pin is not supplied (name-based lookup, with last_name and patient_dob).
last_name	string (30)	Conditional	Beneficiary last name. Required if patient_pin is not supplied (name-based lookup, with first_name and patient_dob).
middle_name	string (30)	No	Beneficiary middle name, used to disambiguate a name-based lookup.
patient_dob	string (MM/DD/YYYY)	Conditional	Beneficiary birth date, format MM/DD/YYYY. Required if patient_pin is not supplied (name-based lookup, with first_name and last_name).

Parameter	Type	Required	Description
consent	boolean	Yes	Must be true: the provider's attestation that the patient's explicit consent was obtained before this request (Implementation Guide 3.5). A missing or false value returns 403 consent_required.

Response (after decryption)


```
{
  "status": "success",
  "code": 200,
  "message": "Validation completed successfully",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
    "patient_pin": "123456789012",
    "accre_no": "H12345678",
    "eff_year": "2026",
    "patient_lname": "DELA CRUZ",
    "patient_fname": "MARIA",
    "patient_mname": "SANTOS",
    "patient_extname": "",
    "patient_dob": "07/04/2009",
    "pcu": {
      "status": "VERIFIED",
      "latest_date": "03/01/2026",
      "transaction_no": "PCU-LOG-TRANS-NO"
    },
    "selection": {
      "status": "ASSIGNED",
      "transaction_no": "KH123456782026030200001",
      "date": "03/02/2026"
    },
    "fpe": {
      "status": "Y",
      "date": "03/05/2026",
      "transaction_no": "PH123456782026030500001",
      "upload_transaction_no": "UH123456782026030500001"
    },
    "empanelment": {
      "status": "Y",
      "date": "03/06/2026",
      "transaction_no": "MCA3C06287"
    },
    "consultation": {
      "status": "Y",
      "date": "10/23/2026",
      "transaction_no": "SH123456782026102300001",
      "upload_transaction_no": "UH123456782026102300001"
    }
  }
}
```

Field	Type	Returned	Description
data.patient_pin	string (12)	Always	PIN of the beneficiary.
data.accre_no	string (9)	Always	Accreditation number of the facility linked to the bearer token.
data.eff_year	string (YYYY)	Always	Effectivity year checked.
data.message	string	Conditional	Returned only when the identity fields are withheld (the beneficiary is not assigned to your facility). Informational; do not match on its text.
data.patient_lname	string (30)	Conditional	Last name of the beneficiary. Returned only when the beneficiary is assigned to your facility.
data.patient_fname	string (30)	Conditional	First name of the beneficiary. Returned only when the beneficiary is assigned to your facility.
data.patient_mname	string (30)	Conditional	Middle name of the beneficiary. Returned only when the beneficiary is assigned to your facility.
data.patient_extname	string (30)	Conditional	Name extension of the beneficiary, for example JR or III. Returned only when the beneficiary is assigned to your facility.
data.patient_dob	string (MM/DD/YYYY)	Conditional	Birth date of the beneficiary. Returned only when the beneficiary is assigned to your facility.
data.pcu.status	string	Always	PCU verification status. VERIFIED: a PCU verification with result code 105 or 109 is on record. FAILED: PCU attempts with a result code exist, but none returned 105 or 109. UNVERIFIED: no attempt with a result code exists. HTTP-level failures without a result code are not attempts. Valid values: Library Reference – PCU Verification Status.
data.pcu.latest_date	string (MM/DD/YYYY)	Conditional	Date of the latest PCU attempt that returned a result code. HTTP-level failures are not counted. Omitted when pcu.status = UNVERIFIED.
data.pcu.transaction_no	string (20)	Conditional	PCU trans_no of the same attempt as latest_date (Section 4.1). Omitted when pcu.status = UNVERIFIED.
data.selection.status	string	Always	Selection status: ASSIGNED, TRANSFERRED, CANCELLED, or NOT_ASSIGNED when the patient has no Selection record. Valid values: Library Reference – Enlistment Status (VALIDATOR VALUE column).
data.selection.transaction_no	string (23)	Conditional	Transaction number of the Selection record that selection.status describes, generated by PhilHealth. Omitted when selection.status = NOT_ASSIGNED. Format: K + accre_no + YYYY + MM + DD + 5-digit daily series (23 characters).
data.selection.date	string (MM/DD/YYYY)	Conditional	Date of the Selection record that selection.status describes; for TRANSFERRED, the transfer date. Omitted when selection.status = NOT_ASSIGNED.
data.fpe.status	string	Always	"Y" when an accepted FPE exists at your facility for eff_year; "N" otherwise.
data.fpe.date	string (MM/DD/YYYY)	Conditional	FPE date. Omitted when fpe.status = "N".
data.fpe.transaction_no	string (23)	Conditional	profile_transaction_no of the FPE. Omitted when fpe.status = "N".

Field	Type	Returned	Description
data.fpe.upload_transaction_no	string (23)	Conditional	Upload number of the FPE submission. Omitted when fpe.status = "N".
data.empanelment.status	string	Always	"Y" when the Mutual Care Agreement is recorded for eff_year; "N" otherwise.
data.empanelment.date	string (MM/DD/YYYY)	Conditional	Date of the empanelment. Omitted when empanelment.status = "N".
data.empanelment.transaction_no	string (10)	Conditional	yes_reference_no of the empanelment (Section 4.3). Omitted when empanelment.status = "N".
data.consultation.status	string	Always	"Y" when at least one accepted consultation exists for eff_year; "N" otherwise.
data.consultation.date	string (MM/DD/YYYY)	Conditional	Date of the beneficiary's latest consultation (its consultation_date). The latest consultation is decided by consultation_date, not upload time; when two consultations share the same consultation_date, the one with the later consultation_time is the latest. Refers to the same consultation record as consultation.transaction_no. Omitted when consultation.status = "N".
data.consultation.transaction_no	string (23)	Conditional	soap_transaction_no of the same latest consultation as consultation.date. Omitted when consultation.status = "N".
data.consultation.upload_transaction_no	string (23)	Conditional	Upload number of that same consultation. Omitted when consultation.status = "N".

Status values

Object	Value	Meaning
pcu.status	VERIFIED	A PCU verification with result code 105 or 109 is on record.
pcu.status	FAILED	PCU attempts with a result code exist, but none returned 105 or 109. HTTP-level failures are not attempts.
pcu.status	UNVERIFIED	No PCU attempt with a result code is on record. latest_date and transaction_no are omitted.
selection.status	ASSIGNED	Currently assigned to a YAKAP Clinic.
selection.status	TRANSFERRED	A transfer of YAKAP Clinic assignment is recorded; selection.date is the transfer date.
selection.status	CANCELLED	The selection or assignment is cancelled.
selection.status	NOT_ASSIGNED	No Selection record; selection.transaction_no and selection.date are omitted.
fpe, empanelment, consultation .status	"Y" or "N"	"N" means that stage has not occurred for eff_year; it is not an error. Dates and numbers are omitted when "N".

Valid values: Library Reference – PCU Verification Status and Enlistment Status (API VALUE column).

Validation rules

- patient_pin is 12 digits when not empty; when it is empty, first_name, last_name and patient_dob (MM/DD/YYYY) are all required.
- eff_year is a four-digit year, or "" for the current year.
- consent must be true.

Errors

HTTP	Issue	When
400	validation_error	Neither patient_pin nor the name and birth-date combination supplied, or a field malformed.
400	decryption_failed / hash_mismatch	The encrypted request cannot be read (Section 3.8).
401	unauthorized	Bearer token missing, invalid, or expired (Section 3.2). Request a new token.
403	consent_required	consent is missing or not true (Section 3.5).
404	beneficiary_not_found	No beneficiary matches the PIN, or the name and birth date.
422	beneficiary_deceased	The beneficiary is recorded as deceased. Do not retry.
422	multiple_matches	The name and birth date match more than one beneficiary. Send patient_pin or middle_name.
500	internal_error	Contact PhilHealth support with the request_id. Do not retry automatically.

Sample error response

```
{
  "status": "error",
  "code": 404,
  "message": "Beneficiary not found",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "errors": [
    {
      "field": "patient_pin",
      "issue": "beneficiary_not_found"
    }
  ]
}
```

4.3 Service 03 – YAKAP Empanelment

Purpose

Records the Mutual Care Agreement (MCA) between a verified beneficiary and the YAKAP Clinic in the token.

Item	Value
Endpoint	POST /api/v1/yakap-empanelment
Authentication	Bearer token (Section 3.2); the facility is the accre_no in the token
Encryption	Request body and response data encrypted (Section 3.8, Annex C); errors in plain JSON
Success	HTTP 201 Created

Business rules and preconditions

- The patient must be verified: patient_verification_mode is required, with the evidence for that mode (Section 3.10).
- PCU: the verification was done on the same day as this request, its PIN equals patient_pin, and its result code is 105 or 109.
- OTP: the code is valid for the patient, the facility in the token and today. VALID_ID: a listed ID type and, on the first VALID_ID request of the day, the ID image.
- For every mode, the beneficiary must hold an active Selection at this facility (Section 4.4) and an accepted FPE at this facility (Section 4.6.1).
- One agreement per member, facility and year. A second submission returns 409 empanelment_already_exists.
- eff_year is the current calendar year, assigned by the service. accre_no and the submitting system come from the token.
- with_yes and with_fpe are always true on success.

Request (before encryption)

```
{
  "patient_pin": "123456789012",
  "consent": true,
  "patient_verification_mode": "PCU",
  "pcu_transaction_code": "PCU-LOG-TRANS-NO",
  "one_time_pin": "",
  "valid_id_type": "",
  "valid_id_image": "",
  "created_by": "emr.user01"
}
```

Parameter	Type	Required	Description
patient_pin	string (12)	Yes	PhilHealth Identification Number — exactly 12 digits, no separators.
consent	boolean	Yes	Must be true: the provider's attestation that the patient's explicit consent was obtained before this request (Implementation Guide 3.5). A missing or false value returns 403 consent_required.

Parameter	Type	Required	Description
patient_verification_mode	string (10)	Yes	Method used to verify the patient before the agreement is recorded: PCU, OTP or VALID_ID. Verification is required, as in Selection. For every mode, the beneficiary must also hold an active Selection at this facility (422 no_active_selection) and an accepted FPE at this facility (422 no_accepted_fpe). Valid values: Library Reference – Patient Verification Mode.
pcu_transaction_code	string (20)	Conditional	Required if patient_verification_mode = PCU. The trans_no returned by PCU (Section 4.1). The PCU verification must be on the same day as this request, the PIN recorded on it must match patient_pin, and its result code must be 105 or 109.
one_time_pin	string (20)	Conditional	Required if patient_verification_mode = OTP. The YAKAP Patient Verification Code issued by PhilHealth for this patient, the facility in the bearer token and the date of this request; validated as in Service 07.
valid_id_type	string (2)	Conditional	Required if patient_verification_mode = VALID_ID. Type of valid government-issued ID presented. Only codes in the library are accepted. Valid values: Library Reference – Valid ID Type.
valid_id_image	string (base-64 JPEG, at most 2 MB before encoding)	Conditional	Required on the first request with patient_verification_mode = VALID_ID for the same patient, facility and date; may be sent as an empty string on later requests that day. Base-64 encoded JPEG of the ID, at most 2 MB before encoding. Format: Base-64 (JPEG).
created_by	string (150)	Yes	Username of the person recording the agreement. Stored against the record.

Response (after decryption)


```
{
  "status": "success",
  "code": 201,
  "message": "Empanelment submitted successfully",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
    "yes_reference_no": "MCA3C06287",
    "patient_pin": "123456789012",
    "accre_no": "H12345678",
    "eff_year": "2026",
    "with_yes": true,
    "with_fpe": true,
    "fpe_transaction_no": "PH123456782026102300001",
    "pcu_transaction_code": "PCU-LOG-TRANS-NO"
  }
}
```

Field	Type	Returned	Description
data.yes_reference_no	string (10)	Always	Reference number of the recorded agreement, generated by the service. Ten characters, prefixed MCA. Retain it alongside the envelope's request_id for support correlation.
data.patient_pin	string (12)	Always	Echoes the submitted PhilHealth Identification Number.
data.accre_no	string (9)	Always	Facility accreditation number taken from the bearer token.
data.eff_year	string (YYYY)	Always	Effectivity year assigned by the service — the current calendar year.
data.with_yes	boolean	Always	Set by the service: true when the checks for patient_verification_mode (PCU, OTP or VALID_ID) passed. Because verification is required, a successful empanelment always returns true.
data.with_fpe	boolean	Always	Set by the service: always true on success, because an accepted FPE at this facility is required (otherwise 422 no_accepted_fpe).
data.fpe_transaction_no	string (23)	Always	The transaction number of the accepted FPE of the beneficiary at this facility.
data.pcu_transaction_code	string (20)	Always	Echoes pcu_transaction_code. An empty string when it was not sent.

The 201 is the confirmation that the agreement was recorded; read the empanelment status and date back through the Primary Care Validator. pcu_transaction_code is returned as an empty string when it was not sent.

Status values

None: HTTP 201 confirms that the agreement was recorded; with_yes and with_fpe are always true on success. The empanelment status is read through the Primary Care Validator (empanelment.status).

Validation rules

- patient_pin: 12 digits. created_by: at most 150 characters. consent: true.
- patient_verification_mode: PCU, OTP or VALID_ID; the evidence fields of the other modes are sent as "".
- valid_id_image: valid base-64 of a JPEG of at most 2 MB.

Errors

HTTP	Issue	When
400	validation_error	A field missing or malformed, including missing evidence for the verification mode or an invalid ID image.
400	decryption_failed / hash_mismatch	The encrypted request cannot be read (Section 3.8).
401	unauthorized	Bearer token missing, invalid, or expired (Section 3.2). Request a new token.

HTTP	Issue	When
403	consent_required	consent is missing or not true (Section 3.5).
404	beneficiary_not_found	patient_pin matches no member or dependent.
404	facility_not_found	The accre_no in the token matches no YAKAP Clinic.
404	pcu_transaction_not_found	pcu_transaction_code matches no PCU record.
409	empanelment_already_exists	An agreement already exists for this member, facility and year. Confirm it through Section 4.2.
422	beneficiary_deceased	The beneficiary is recorded as deceased.
422	pcu_not_verified	The PCU record has no verified date. Re-run PCU.
422	pcu_pin_mismatch	patient_pin differs from the PIN on the PCU record.
422	pcu_result_not_accepted	The PCU result code is not 105 or 109.
422	pcu_not_same_day	The PCU verification was not done today.
422	code_invalid	one_time_pin is not valid for the patient, facility and date (OTP).
422	no_active_selection	No active Selection at this facility.
422	no_accepted_fpe	No accepted FPE for the beneficiary at this facility. Upload the FPE (4.6.1) and wait until Upload Status shows accepted.
500	internal_error	Contact PhilHealth support with the request_id. Do not retry automatically.

Sample error response

```
{
  "status": "error",
  "code": 409,
  "message": "Empanelment already exists",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "errors": [
    {
      "field": "patient_pin",
      "issue": "empanelment_already_exists"
    }
  ]
}
```

4.4 Service 04 – YAKAP Selection

Purpose

Records a verified beneficiary's selection, or reselection, of the YAKAP Clinic in the token. It does not transfer a beneficiary between clinics.

Item	Value
Endpoint	POST /api/v1/yakap-selection
Authentication	Bearer token (Section 3.2); the facility is the accre_no in the token
Encryption	Request body and response data encrypted (Section 3.8, Annex C); errors in plain JSON
Success	HTTP 201 Created

Business rules and preconditions

- The patient must be verified with the same rules as Empanelment (Section 3.10): PCU same-day with result code 105 or 109, a valid OTP, or a listed valid ID.
- selection_date is not later than the date of the request.
- The outcome depends on the beneficiary's existing assignment status (table below); the resulting status is always ASSIGNED.

Existing status	Outcome	Resulting status
NOT_ASSIGNED (no Selection record)	New selection recorded.	ASSIGNED
CANCELLED	Reselection recorded.	ASSIGNED
ASSIGNED at this facility	Rejected: 409 selection_already_exists.	–
ASSIGNED at another YAKAP Clinic	Rejected: 422 selected_other_facility.	–
TRANSFERRED	Rejected with the message "The beneficiary is not assigned in this facility." (422 selected_other_facility).	–

Request (before encryption)

```
{
  "patient_pin": "123456789012",
  "selection_date": "10/25/2026",
  "consent": true,
  "patient_verification_mode": "OTP",
  "pcu_transaction_code": "",
  "one_time_pin": "<code issued to the patient>",
  "valid_id_type": "",
  "valid_id_image": ""
}
```

Parameter	Type	Required	Description
patient_pin	string (12)	Yes	PIN of the beneficiary, 12 digits.
selection_date	string (MM/DD/YYYY)	Yes	Date the beneficiary chose this YAKAP Clinic. Not later than the date of the request.

Parameter	Type	Required	Description
consent	boolean	Yes	Must be true: the provider's attestation that the patient's explicit consent was obtained before this request (Implementation Guide 3.5). A missing or false value returns 403 consent_required.
patient_verification_mode	string (10)	Yes	Method used to verify the patient before the selection is recorded: PCU, OTP or VALID_ID. A selection requires a verified patient. Valid values: Library Reference – Patient Verification Mode.
pcu_transaction_code	string (20)	Conditional	Required if patient_verification_mode = PCU. The trans_no returned by PCU (Section 4.1). The PCU verification must be on the same day as this request, the PIN recorded on it must match patient_pin, and its result code must be 105 or 109.
one_time_pin	string (20)	Conditional	Required if patient_verification_mode = OTP. The YAKAP Patient Verification Code issued by PhilHealth for this patient, the facility in the bearer token and the date of this request; validated as in Service 07.
valid_id_type	string (2)	Conditional	Required if patient_verification_mode = VALID_ID. Type of valid government-issued ID presented. Only codes in the library are accepted. Valid values: Library Reference – Valid ID Type.
valid_id_image	string (base-64 JPEG, at most 2 MB before encoding)	Conditional	Required on the first request with patient_verification_mode = VALID_ID for the same patient, facility and date; may be sent as an empty string on later requests that day. Base-64 encoded JPEG of the ID, at most 2 MB before encoding. Format: Base-64 (JPEG).

Response (after decryption)

```
{
  "status": "success",
  "code": 201,
  "message": "Selection recorded",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
    "patient_pin": "123456789012",
    "accre_no": "H12345678",
    "selection": {
      "status": "ASSIGNED",
      "transaction_no": "KH123456782026102500001",
      "date": "10/25/2026"
    }
  }
}
```

Field	Type	Returned	Description
data.patient_pin	string (12)	Always	Echoes the request.
data.accre_no	string (9)	Always	Accreditation number of the facility linked to the bearer token.

Field	Type	Returned	Description
data.selection.status	string	Always	Resulting YAKAP Clinic assignment status after this transaction. Always ASSIGNED on a successful selection or reselection; TRANSFERRED is never returned by this service. Valid values: Library Reference – Enlistment Status (VALIDATOR VALUE column), the same values as selection.status in the Primary Care Validator (Section 4.2).
data.selection.transaction_no	string (23)	Always	Transaction number of the successful selection or reselection, generated by PhilHealth. Format: K + accre_no + YYYY + MM + DD + 5-digit daily series (23 characters).
data.selection.date	string (MM/DD/YYYY)	Always	Effective date of the successful clinic selection.

Status values

selection.status is always ASSIGNED on success (Library Reference – Enlistment Status, API VALUE column). selection.transaction_no is a K number generated by PhilHealth (Section 3.9).

Validation rules

- patient_pin: 12 digits. selection_date: MM/DD/YYYY, not in the future. consent: true.
- Verification fields as in Section 3.10; fields of other modes sent as "".

Errors

HTTP	Issue	When
400	validation_error	A field missing or malformed, selection_date in the future, or verification evidence missing or invalid.
400	decryption_failed / hash_mismatch	The encrypted request cannot be read (Section 3.8).
401	unauthorized	Bearer token missing, invalid, or expired (Section 3.2). Request a new token.
403	consent_required	consent is missing or not true (Section 3.5).
404	beneficiary_not_found	patient_pin matches no member or dependent.
404	pcu_transaction_not_found	pcu_transaction_code matches no PCU record.
409	selection_already_exists	The beneficiary is already ASSIGNED to this facility.
422	beneficiary_deceased	The beneficiary is recorded as deceased.
422	pcu_not_verified / pcu_pin_mismatch / pcu_result_not_accepted / pcu_not_same_day	PCU evidence fails the check named by the code.
422	code_invalid	one_time_pin is not valid for the patient, facility and date (OTP).
422	selected_other_facility	The beneficiary is ASSIGNED to another YAKAP Clinic, or is TRANSFERRED ("The beneficiary is not assigned in this facility.").
500	internal_error	Contact PhilHealth support with the request_id. Do not retry automatically.

Sample error response

```
{
  "status": "error",
  "code": 422,
  "message": "The beneficiary is not assigned in this facility.",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "errors": [
    {
      "field": "patient_pin",
      "issue": "selected_other_facility"
    }
  ]
}
```

4.5 Service 05 – Selection Masterlist Download

Purpose

Lets a YAKAP Clinic download the beneficiaries assigned to it, one by PIN or in batch by assignment date. Both endpoints return the same layout.

Business rules

- The facility is the accre_no in the token; it is not sent.
- Dates use MM/DD/YYYY, the same format as the matching FPE fields, so values can be copied into the FPE upload unchanged.
- A field with no value is returned as an empty string. assignment_status returns the database code (1 Active, 2 Cancelled, 3 Transferred; Library Reference – Enlistment Status).
- transmittal_no identifies the download; quote it when raising an issue about the list.

4.5.1 Individual Lookup

Item	Value
Endpoint	POST /api/v1/yakap-selection-masterlist/individual
Authentication	Bearer token (Section 3.2); the facility is the accre_no in the token
Encryption	Request body and response data encrypted (Section 3.8, Annex C); errors in plain JSON
Success	HTTP 200

Request (before encryption)

```
{
  "patient_pin": "123456789012",
  "eff_year": "2026",
  "consent": true
```

```
}
```

Parameter	Type	Required	Description
patient_pin	string (12)	Yes	PIN of the beneficiary, 12 digits.
eff_year	string (YYYY)	No	Effective year. Defaults to the current year when sent as an empty string.
consent	boolean	Yes	Must be true: the provider's attestation that the patient's explicit consent was obtained before this request (Implementation Guide 3.5). A missing or false value returns 403 consent_required.

Response (after decryption)

```
{
  "status": "success",
  "code": 200,
  "message": "Masterlist retrieved",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
    "accre_no": "H12345678",
    "transmittal_no": "<transmittal number>",
    "eff_year": "2026",
    "total_records": 1,
    "assignments": [
      {
        "patient_pin": "123456789012",
        "patient_lname": "DELA CRUZ",
        "patient_fname": "MARIA",
        "patient_mname": "SANTOS",
        "patient_extname": "",
        "patient_dob": "07/04/2009",
        "patient_sex": "F",
        "patient_type": "DD",
        "member_pin": "123456789013",
        "member_lname": "DELA CRUZ",
        "member_fname": "JUAN",
        "member_mname": "SANTOS",
        "member_extname": "",
        "member_dob": "05/15/1980",
        "member_sex": "M",
        "patient_mobile_no": "09171234567",
        "patient_landline_no": "",
        "member_category": "<category code>",
        "member_category_desc": "<category description>",
        "package_type": "K",
        "assignment_date": "10/20/2026",
        "assignment_status": "1",
        "eff_year": "2026"
      }
    ]
  }
```

```
}
```

Field	Type	Returned	Description
data.accre_no	string (9)	Always	Accreditation number of the facility linked to the bearer token.
data.transmittal_no	string	Always	Reference number of this download, generated by the service. Quote it when raising an issue about the list.
data.eff_year	string (YYYY)	Always	4.5.1 only. The year of the assignments returned.
data.total_records	number	Always	Number of entries in assignments.
data.assignments	array	Always	One entry per assigned beneficiary; the fields are listed below. Empty when nothing matches.
data.assignments[].patient_pin	string (12)	Always	PhilHealth Identification Number (PIN) of the assigned beneficiary.
data.assignments[].patient_lname	string (30)	Always	Last name of the beneficiary.
data.assignments[].patient_fname	string (30)	Always	First name of the beneficiary.
data.assignments[].patient_mname	string (30)	Always	Middle name of the beneficiary.
data.assignments[].patient_extname	string (30)	Always	Name extension (for example JR, III).
data.assignments[].patient_dob	string (MM/DD/YYYY)	Always	Birth date of the beneficiary.
data.assignments[].patient_sex	string (1)	Always	Sex of the beneficiary. Library Reference – Sex (M, F). Valid values: Library Reference – Sex.
data.assignments[].patient_type	string (2)	Always	MM – the beneficiary is the member; DD – a dependent. Library Reference – Patient Type. Valid values: Library Reference – Patient Type.
data.assignments[].member_pin	string (12)	Always	PIN of the principal member. Same as patient_pin when patient_type = MM.
data.assignments[].member_lname	string (30)	Always	Last name of the principal member.
data.assignments[].member_fname	string (30)	Always	First name of the principal member.
data.assignments[].member_mname	string (30)	Always	Middle name of the principal member.
data.assignments[].member_extname	string (30)	Always	Name extension of the principal member.
data.assignments[].member_dob	string (MM/DD/YYYY)	Always	Birth date of the principal member.
data.assignments[].member_sex	string (1)	Always	Sex of the principal member. Library Reference – Sex. Valid values: Library Reference – Sex.

Field	Type	Returned	Description
data.assignments[].patient_mobile_no	string (15)	Always	Mobile number on record.
data.assignments[].patient_landline_no	string (15)	Always	Landline number on record.
data.assignments[].member_category	string	Always	Membership category code of the member, as recorded by PhilHealth.
data.assignments[].member_category_desc	string	Always	Description of member_category.
data.assignments[].package_type	string (1)	Always	Benefit package of the assignment, as recorded by PhilHealth (for example K).
data.assignments[].assignment_date	string (MM/DD/YYYY)	Always	Date the beneficiary was assigned to the facility. 4.5.2 selects on this date.
data.assignments[].assignment_status	string (1)	Always	1 Active, 2 Cancelled, 3 Transferred. Library Reference – Enlistment Status. Valid values: Library Reference – Enlistment Status.
data.assignments[].eff_year	string (YYYY)	Always	Year the assignment applies to.

Status values

assignment_status	Meaning
1	Active (API value ASSIGNED in the Validator)
2	Cancelled (CANCELLED)
3	Transferred (TRANSFERRED)

Validation rules

- patient_pin: 12 digits. eff_year: four-digit year, or "" for the current year. consent: true.

Errors

HTTP	Issue	When
400	validation_error	patient_pin not 12 digits or eff_year not a four-digit year.
400	decryption_failed / hash_mismatch	The encrypted request cannot be read (Section 3.8).
401	unauthorized	Bearer token missing, invalid, or expired (Section 3.2). Request a new token.
403	consent_required	consent is missing or not true (Section 3.5).
404	assignment_not_found	The beneficiary has no assignment to your facility for eff_year.
500	internal_error	Contact PhilHealth support with the request_id. Do not retry automatically.

Sample error response

```
{
  "status": "error",
  "code": 404,
  "message": "Assignment not found",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "errors": [
    {
      "field": "patient_pin",
      "issue": "assignment_not_found"
    }
  ]
}
```

4.5.2 Batch Download

Item	Value
Endpoint	POST /api/v1/yakap-selection-masterlist/batch
Authentication	Bearer token (Section 3.2); the facility is the accre_no in the token
Encryption	Request body and response data encrypted (Section 3.8, Annex C); errors in plain JSON
Success	HTTP 200 (total_records = 0 and an empty assignments array when nothing matches)

Business rules

- Returns every assignment whose assignment_date falls in the range, counting both dates.
- The range is 1 to 7 days: end_date is not before start_date and not more than 6 days after it. Use the same date twice for one day.

Request (before encryption)

```
{
  "start_date": "10/17/2026",
  "end_date": "10/23/2026",
  "consent": true
}
```

Parameter	Type	Required	Description
start_date	string (MM/DD/YYYY)	Yes	First assignment date to include.
end_date	string (MM/DD/YYYY)	Yes	Last assignment date to include. Must not be before start_date, and the range may cover at most 7 days counting both dates (for example 10/17/2026 to 10/23/2026). Use the same date in both for a single day.

Parameter	Type	Required	Description
consent	boolean	Yes	Must be true: the provider's attestation that the patient's explicit consent was obtained before this request (Implementation Guide 3.5). A missing or false value returns 403 consent_required.

Response (after decryption)


```
{
  "status": "success",
  "code": 200,
  "message": "Masterlist retrieved",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
    "accre_no": "H12345678",
    "transmittal_no": "<transmittal number>",
    "start_date": "10/17/2026",
    "end_date": "10/23/2026",
    "total_records": 2,
    "assignments": [
      {
        "patient_pin": "123456789012",
        "patient_lname": "DELA CRUZ",
        "patient_fname": "MARIA",
        "patient_mname": "SANTOS",
        "patient_extname": "",
        "patient_dob": "07/04/2009",
        "patient_sex": "F",
        "patient_type": "DD",
        "member_pin": "123456789013",
        "member_lname": "DELA CRUZ",
        "member_fname": "JUAN",
        "member_mname": "SANTOS",
        "member_extname": "",
        "member_dob": "05/15/1980",
        "member_sex": "M",
        "patient_mobile_no": "09171234567",
        "patient_landline_no": "",
        "member_category": "<category code>",
        "member_category_desc": "<category description>",
        "package_type": "K",
        "assignment_date": "10/20/2026",
        "assignment_status": "1",
        "eff_year": "2026"
      },
      {
        "patient_pin": "123456789014",
        "patient_lname": "REYES",
        "patient_fname": "JOSE",
        "patient_mname": "LIM",
        "patient_extname": "JR",
        "patient_dob": "11/02/1975",
        "patient_sex": "M",
        "patient_type": "MM",
        "member_pin": "123456789014",
```

```
        "member_lname": "REYES",
        "member_fname": "JOSE",
        "member_mname": "LIM",
        "member_extname": "JR",
        "member_dob": "11/02/1975",
        "member_sex": "M",
        "patient_mobile_no": "09181234567",
        "patient_landline_no": "0281234567",
        "member_category": "<category code>",
        "member_category_desc": "<category description>",
        "package_type": "K",
        "assignment_date": "10/22/2026",
        "assignment_status": "1",
        "eff_year": "2026"
      }
    ]
  }
}
```


Field	Type	Returned	Description
data.accre_no	string (9)	Always	Accreditation number of the facility linked to the bearer token.
data.transmittal_no	string	Always	Reference number of this download, generated by the service. Quote it when raising an issue about the list.
data.start_date	string (MM/DD/YYYY)	Always	4.5.2 only. The date range requested.
data.end_date	string (MM/DD/YYYY)	Always	4.5.2 only. The date range requested.
data.total_records	number	Always	Number of entries in assignments.
data.assignments	array	Always	One entry per assigned beneficiary; the fields are listed below. Empty when nothing matches.
data.assignments[].patient_pin	string (12)	Always	PhilHealth Identification Number (PIN) of the assigned beneficiary.
data.assignments[].patient_lname	string (30)	Always	Last name of the beneficiary.
data.assignments[].patient_fname	string (30)	Always	First name of the beneficiary.
data.assignments[].patient_mname	string (30)	Always	Middle name of the beneficiary.
data.assignments[].patient_extname	string (30)	Always	Name extension (for example JR, III).
data.assignments[].patient_dob	string (MM/DD/YYYY)	Always	Birth date of the beneficiary.
data.assignments[].patient_sex	string (1)	Always	Sex of the beneficiary. Library Reference – Sex (M, F). Valid values: Library Reference – Sex.
data.assignments[].patient_type	string (2)	Always	MM – the beneficiary is the member; DD – a dependent. Library Reference – Patient Type. Valid values: Library Reference – Patient Type.

Field	Type	Returned	Description
data.assignments[].member_pin	string (12)	Always	PIN of the principal member. Same as patient_pin when patient_type = MM.
data.assignments[].member_lname	string (30)	Always	Last name of the principal member.
data.assignments[].member_fname	string (30)	Always	First name of the principal member.
data.assignments[].member_mname	string (30)	Always	Middle name of the principal member.
data.assignments[].member_extname	string (30)	Always	Name extension of the principal member.
data.assignments[].member_dob	string (MM/DD/YYYY)	Always	Birth date of the principal member.
data.assignments[].member_sex	string (1)	Always	Sex of the principal member. Library Reference – Sex. Valid values: Library Reference – Sex.
data.assignments[].patient_mobile_no	string (15)	Always	Mobile number on record.
data.assignments[].patient_landline_no	string (15)	Always	Landline number on record.
data.assignments[].member_category	string	Always	Membership category code of the member, as recorded by PhilHealth.
data.assignments[].member_category_desc	string	Always	Description of member_category.
data.assignments[].package_type	string (1)	Always	Benefit package of the assignment, as recorded by PhilHealth (for example K).
data.assignments[].assignment_date	string (MM/DD/YYYY)	Always	Date the beneficiary was assigned to the facility. 4.5.2 selects on this date.
data.assignments[].assignment_status	string (1)	Always	1 Active, 2 Cancelled, 3 Transferred. Library Reference – Enlistment Status. Valid values: Library Reference – Enlistment Status.
data.assignments[].eff_year	string (YYYY)	Always	Year the assignment applies to.

Status values

assignment_status as in 4.5.1.

Validation rules

- start_date and end_date: MM/DD/YYYY; end_date not before start_date; at most 7 days counting both dates. consent: true.

Errors

HTTP	Issue	When
400	validation_error	start_date or end_date missing or not MM/DD/YYYY, end_date before start_date, or a range longer than 7 days.

HTTP	Issue	When
400	decryption_failed / hash_mismatch	The encrypted request cannot be read (Section 3.8).
401	unauthorized	Bearer token missing, invalid, or expired (Section 3.2). Request a new token.
403	consent_required	consent is missing or not true (Section 3.5).
500	internal_error	Contact PhilHealth support with the request_id. Do not retry automatically.

Sample error response

```
{
  "status": "error",
  "code": 400,
  "message": "Date range exceeds 7 days",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "errors": [
    {
      "field": "end_date",
      "issue": "validation_error"
    }
  ]
}
```

4.6 Service 06 – YAKAP Data Upload

Six upload endpoints accept the clinical forms of a beneficiary's visit, one endpoint per form, and an Upload Status endpoint reports each outcome. Field definitions follow the Data Dictionary rev20261026, Annexes A to F; codes follow the Library Reference rev20261026.

Section	Form	Endpoint	Data Dictionary
4.6.1	Health Screening and Assessment (FPE)	POST /api/v1/yakap-data-upload/fpe	Annex A (143 fields, Rev. 7)
4.6.2	Consultation	POST /api/v1/yakap-data-upload/consultation	Annex B (270 fields, Rev. 7)
4.6.3	Diagnostic Request	POST /api/v1/yakap-data-upload/diagnostic-request	Annex C (7 fields, Rev. 7)
4.6.4	Diagnostic Results	POST /api/v1/yakap-data-upload/diagnostic-results	Annex D (137 fields, Rev. 8)
4.6.5	Drugs and Medicines	POST /api/v1/yakap-data-upload/medicine	Annex E (31 fields, Rev. 6)
4.6.6	Referral Request	POST /api/v1/yakap-data-upload/referral	Annex F (32 fields, Rev. 7)
4.6.7	Upload Status	GET /api/v1/yakap-data-upload/status/{upload_transaction_no}	Data Dictionary Annex G

Processing model

Stage	What happens
1. On receipt	The request is decrypted and checked against its section: structure, consent, required and conditional fields, types, sizes, formats and library codes. A failing submission is rejected at once with HTTP 400. A passing one is queued and answered with HTTP 202 and an upload_transaction_no (U number, Section 3.9).
2. After queueing	The submission is checked against the records already held (for example that case_no matches an accepted FPE) and recorded. The outcome, accepted or rejected with errors, is read from Upload Status (4.6.7).
Order	Submissions for the same case_no are processed in the order received. A submission whose parent (for example the consultation of a Diagnostic Request) is still queued waits for it; if the parent is rejected, the dependent submission is rejected too.
Duplicates and retries	Resending a record number with identical content returns HTTP 200 with the original upload_transaction_no and its current processing_status, so a retry after a timeout never creates a second record. The same record number with different content returns 409 transaction_already_exists while the original is queued or accepted. A rejected record may be corrected and resubmitted with the same number.
Final result	Only processing_status = accepted means the record is held by PhilHealth; it then appears in the Primary Care Validator (FPE and consultation) and can be referenced by later submissions.

Upload response (all six endpoints)

Field	Type	Returned	Description
data.upload_transaction_no	string (23)	Always	Number of this submission, generated by PhilHealth (U + accre_no + YYYY + MM + DD + 5-digit daily series). Use it with Upload Status.
data.form	string	Always	fpe, consultation, diagnostic_request, diagnostic_results, medicine or referral.
data.processing_status	string	Always	queued on first receipt; on an identical resend, the current status (Upload Status values).
data.<record numbers>	string, or array of strings	Always	Echo of the submission's record numbers (per form below).

Errors common to the six upload endpoints

HTTP	Issue	When
400	validation_error	A field fails the checks of its section. Every failing field is listed.
400	decryption_failed / hash_mismatch	The encrypted request cannot be read (Section 3.8).
401	unauthorized	Bearer token missing, invalid, or expired (Section 3.2). Request a new token.
403	consent_required	consent is missing or not true (Section 3.5).
409	transaction_already_exists	The record number is queued or accepted with different content. Use a new number for a new record.
500	internal_error	Contact PhilHealth support with the request_id. Do not retry automatically.

4.6.1 Health Screening and Assessment (FPE) Upload

Purpose

Submits the First Patient Encounter (FPE): the patient's enlistment and profile, medical, family, social and OB-GYN history, and physical examination. Fields follow Data Dictionary Annex A (Rev. 7, 10/25/2026).

Item	Value
Endpoint	POST /api/v1/yakap-data-upload/fpe
Authentication	Bearer token (Section 3.2); the facility is the accre_no in the token
Encryption	Request body and response data encrypted (Section 3.8, Annex C); errors in plain JSON
Success	HTTP 202 Accepted (200 on an identical resend)

Business rules and preconditions

- Record numbers: case_no (T), enlist_transaction_no (E) and profile_transaction_no (P) follow Section 3.9. case_no identifies the patient record and is reused by every later submission for the patient. enlistment.accre_no equals the accre_no in the token and in every record number.
- Patient verification: patient_verification_mode PCU requires pcu_transaction_code; OTP requires one_time_pin; VALID_ID requires valid_id_type and, on the first VALID_ID request for the patient, facility and fpe_date, valid_id_image (Section 3.10).
- Dependent patients: The guardian group is required when patient_type = DD and left out when patient_type = MM.
- Checked after queueing and reported through Upload Status: case_no and profile_transaction_no are not already used by another patient record.

Request (before encryption)


```
{
  "consent": true,
  "enlistment": {
    "case_no": "TH123456782026102300001",
    "enlist_transaction_no": "EH123456782026102300001",
    "accre_no": "H12345678",
    "assignment_status": "1",
    "patient_type": "MM",
    "patient_pin": "123456789012",
    "patient_fname": "MARIA",
    "patient_mname": "SANTOS",
    "patient_lname": "DELA CRUZ",
    "patient_extname": "",
    "patient_sex": "F",
    "patient_dob": "07/04/1990",
    "patient_mobile_no": "09171234567",
    "patient_alt_mobile_no": "09181234567",
    "patient_landline_no": "0281234567",
    "assignment_date": "10/23/2026",
    "created_by": "emr.user01",
```

```
    "gender": "W",
    "permanent_address_province_code": "0402100000",
    "permanent_address_municipality_code": "0402103000",
    "permanent_address_barangay_code": "0402103012",
    "permanent_address_other_details": "Blk 5 Lot 12, Mabini St., Purok 3",
    "religion": "1",
    "civil_status": "S",
    "current_address_province_code": "0402100000",
    "current_address_municipality_code": "0402103000",
    "current_address_barangay_code": "0402103012",
    "current_address_other_details": "Blk 5 Lot 12, Mabini St., Purok 3",
    "occupation": "Teacher",
    "email_address": "maria.delacruz@example.com",
    "pwd_id_no": ""
  },
  "profile": {
    "method_of_service_delivery": "F",
    "patient_verification_mode": "PCU",
    "pcu_transaction_code": "PCU-LOG-TRANS-NO",
    "one_time_pin": "",
    "valid_id_type": "",
    "valid_id_image": "",
    "mca_flag": "Y",
    "co_payment_flag": "Y",
    "co_payment_date_payment": "10/23/2026",
    "co_payment": 300,
    "co_payment_balance": 600,
    "fpe_classification_type": "1",
    "profile_transaction_no": "PH123456782026102300001",
    "fpe_date": "10/23/2026",
    "fpe_time": "09:30",
    "patient_age": "36 YR(S), 3 MO(S), 19 DAY(S)"
  },
  "medhist": [
    {
      "mdisease_code": "001",
      "mhspecific": {
        "is_on_dialysis": "Y",
        "dialysis_type": "Hemodialysis",
        "dialysis_year_started": "2024",
        "specific_desc": "Diagnosed 2019, maintained on medication"
      }
    }
  ],
  "hosphist": [
    {
      "previous_hospitalization": "Dengue fever, admitted 4 days",
      "date_previous_hospitalization": "10/23/2026"
    }
  ],
  "accidenthist": [
    {
      "previous_accident_injury": "Fractured left wrist (fall)",
      "date_previous_accident_injury": "10/23/2026"
    }
  ],
  "surghist": [
```

```
    {
      "surg_desc": "Appendectomy",
      "surg_date": "10/23/2026"
    }
  ],
  "allergy": {
    "food_allergy": "Y - Shrimp",
    "medication_allergy": "N",
    "allergy_others": "Dust mites"
  },
  "currentmed": {
    "current_medications": "Y",
    "current_medication_pndf": "Amlodipine",
    "current_medication_non_pndf": ""
  },
  "immunizationhist": [
    {
      "immunization_code": "02"
    }
  ],
  "famhist": [
    {
      "mdisease_code": "001"
    }
  ],
  "fhspecific": [
    {
      "mdisease_code": "001",
      "specific_desc": "Diagnosed 2019, maintained on medication"
    }
  ],
  "sochist": {
    "is_smoker": "Y",
    "no_cigpk": 2.5,
    "is_adrinker": "Y",
    "no_glasses": 2,
    "ill_drug_user": "Y",
    "secondhand_smoke_exposure": "P",
    "cigarette_sticks_per_day": 10,
    "smoking_years": 5,
    "vape_current_user": "Y",
    "vape_former_user": "Y",
    "alcohol_drinker_subtype": "O",
    "alcohol_types": "1,2",
    "alcohol_intake_years": 3,
    "alcohol_frequency_per_week": 1,
    "substance_abuse_family_member": "",
    "dietary_intake_type": "W",
    "breastfeeding_status": "N",
    "physical_activity_status": "Y",
    "fluoride_toothpaste_use": "Y",
    "dental_checkup_status": "U",
    "dental_checkup_year": "2025",
    "neighborhood_communicable_disease": "None",
    "mental_health_event_code": "02",
    "other_mental_health_event": ""
  },
```

```
  "gynehist": {
    "menarche_flag": "Y",
    "menarche_period": 12,
    "last_mens_period_flag": "Y",
    "last_mens_period": "10/23/2026",
    "contraceptive_use_status": "02",
    "contraceptive_method_desired": "01,02",
    "birth_ctrl_method": "01",
    "is_menopause": "Y",
    "gynecological_disease_flag": "Y",
    "gynecological_disease": "",
    "gyn_sexually_transmitted_flag": "Y",
    "gyn_sexually_transmitted_disease": ""
  },
  "preghist": {
    "is_currently_pregnant": "Y",
    "prenatal_checkup_count": "A",
    "age_of_gestation": "",
    "expected_date_of_delivery": "",
    "is_applicable": "Y",
    "preg_cnt": 2,
    "delivery_cnt": 2,
    "full_term_cnt": 2,
    "premature_cnt": 0,
    "abortion_cnt": 0,
    "liv_children_cnt": 2
  },
  "pegensurvey": {
    "gen_survey_id": "1",
    "gen_survey_rem": ""
  },
  "pepert": {
    "systolic": 120,
    "diastolic": 80,
    "heart_rate": 78,
    "respiratory_rate": 18,
    "temperature": 36.6,
    "height": 160,
    "weight": 60.5,
    "bmi": 23.63,
    "mid_upper_arm_circ": 27
  },
  "facilitator": {
    "facilitator_type": "P",
    "facilitator_name": "JUAN P. REYES, RN"
  }
}
```

The sample is a member (patient_type = MM), so the guardian group is left out; for a dependent, add it. Codes are real Library Reference codes. Number fields that do not apply (for example length for an adult) are left out.

Payload structure

Data group	Structure	Content and applicability	Fields
enlistment	Object	Patient enlistment and demographic details. Always required.	31
guardian	Object	Parent or guardian. Required when patient_type = DD (dependent); left out when patient_type = MM (member).	7
profile	Object	FPE profile: service delivery, patient verification (PCU, OTP or VALID_ID evidence), co-payment, date and time. Always required.	16
medhist	Array	Past medical history – one entry per disease. Required (mdisease_code is required). Each entry may carry a nested mhspecific object.	1
mhspecific	Object, nested in each medhist entry	Details of the disease in that medhist entry: dialysis and specific description. Optional.	4
hosphist	Array	Previous hospitalizations – one entry per hospitalization. Optional.	2
accidenthist	Array	Previous accidents or injuries – one entry per event. Optional.	2
surghist	Array	Surgical history – one entry per operation. Optional.	2
allergy	Object	Food, medication and other allergies. Required.	3
currentmed	Object	Current medications. Required.	3
immunizationhist	Array	Immunization history – one entry per immunization. Required (immunization_code is required).	1
famhist	Array	Family medical history – one entry per disease. Required (mdisease_code is required).	1
fhspecific	Array	Specific description of a family-history disease – one entry per disease. Optional.	2
sochist	Object	Personal and social history: smoking, vaping, alcohol, drugs, diet, activity, dental and mental health. Required.	26
gynehist	Object	Menstrual and gynecological history. Female patients only (patient_sex = F).	13
preghist	Object	Pregnancy and obstetric history. Female patients only (patient_sex = F).	11
pegensurvey	Object	Physical examination – general survey. Required.	2
pepert	Object	Vital signs and body measurements. Required.	14
facilitator	Object	FPE facilitator. Required.	2

Request fields

Parameter	Type	Required	Description
enlistment · Object			
case_no	string (23)	Yes	Patient case number that links all records of the patient. Format: T+ACCRE_NO+YYYY+MM+DD+5 digits daily series number = T+XXXXXXXXX+YYYY+MM+DD+99999.

Parameter	Type	Required	Description
enlist_transaction_no	string (23)	Yes	Transaction number of the enlistment record. Format: E+ACCRE_NO+YYYY+MM+DD+5 digits daily series number = E+XXXXXXXXX+YYYY+MM+DD+99999.
accre_no	string (9)	Yes	PhilHealth accreditation number of the primary care facility (9 characters). Rule: Exactly 9 characters. Must equal the accre_no in the bearer token and the accre_no segment of every record number (case_no, enlist_transaction_no, profile_transaction_no).
assignment_status	string (1)	Yes	Enlistment status; flags a transfer from a previous primary care provider. Valid values: Library Reference – Enlistment Status.
patient_type	string (2)	Yes	Patient type: member or dependent. Valid values: Library Reference – Patient Type.
patient_pin	string (12)	Yes	PhilHealth Identification Number (PIN) of the patient. Rule: Use the member PIN if patient_type = MM; the dependent PIN if patient_type = DD.
patient_fname	string (30)	Yes	First name of the patient. Rule: Use the member name if patient_type = MM; the dependent name if patient_type = DD.
patient_mname	string (30)	No	Middle name of the patient. Rule: Use the member name if patient_type = MM; the dependent name if patient_type = DD.
patient_lname	string (30)	Yes	Last name of the patient. Rule: Use the member name if patient_type = MM; the dependent name if patient_type = DD.
patient_extname	string (30)	No	Name extension of the patient (for example Jr. or III). Rule: Use the member name if patient_type = MM; the dependent name if patient_type = DD.
patient_sex	string (1)	Yes	Sex of the patient. Valid values: Library Reference – Sex.
patient_dob	string (MM/DD/YYYY)	Yes	Date of birth of the patient. Format: MM/DD/YYYY.
patient_mobile_no	string (15)	Yes	Mobile number of the patient.
patient_alt_mobile_no	string (15)	No	Alternate mobile number of the patient.
patient_landline_no	string (15)	No	Landline number of the patient.
assignment_date	string (MM/DD/YYYY)	Yes	Date the patient was registered to the primary care provider. Format: MM/DD/YYYY.
created_by	string (150)	Yes	User who created the record.
gender	string (30)	No	Gender of the patient, distinct from sex. Valid values: Library Reference – Gender.
permanent_address_province_code	string (10)	Yes	PSGC province code of the patient's permanent address. Standard: PSGC.

Parameter	Type	Required	Description
permanent_address_municipality_code	string (10)	Yes	PSGC city or municipality code of the patient's permanent address. Standard: PSGC.
permanent_address_barangay_code	string (10)	Yes	PSGC barangay code of the patient's permanent address. Standard: PSGC.
permanent_address_other_details	string (500)	No	House, lot or unit number, street, subdivision, sitio or purok of the permanent address.
religion	string (50)	Yes	Religion of the patient. Valid values: Library Reference – Religion.
civil_status	string (20)	Yes	Civil status of the patient. Valid values: Library Reference – Civil Status.
current_address_province_code	string (10)	Yes	PSGC province code of the patient's current address. Standard: PSGC.
current_address_municipality_code	string (10)	Yes	PSGC city or municipality code of the patient's current address. Standard: PSGC.
current_address_barangay_code	string (10)	Yes	PSGC barangay code of the patient's current address. Standard: PSGC.
current_address_other_details	string (500)	No	House, lot or unit number, street, subdivision, sitio or purok of the current address.
occupation	string (100)	No	Occupation of the patient, if any.
email_address	string (100)	Yes	Email address of the patient, or of the parent or guardian for a minor.
pwd_id_no	string (20)	No	PWD ID number of the patient, if any.
guardian · Object			
guardian_name	string (150)	Conditional	Full name of the parent or guardian (surname, first name, middle name, suffix). Rule: Required if patient_type = DD (dependent). Leave out when patient_type = MM (member).
guardian_age	number	Conditional	Age of the parent or guardian, in years. Rule: Required if patient_type = DD (dependent). Leave out when patient_type = MM (member).
guardian_sex	string (1)	Conditional	Sex of the parent or guardian. Valid values: Library Reference – Sex. Rule: Required if patient_type = DD (dependent). Leave out when patient_type = MM (member).
guardian_birthday	string (MM/DD/YYYY)	Conditional	Date of birth of the parent or guardian. Format: MM/DD/YYYY. Rule: Required if patient_type = DD (dependent). Leave out when patient_type = MM (member).
guardian_contact_no	string (15)	Conditional	Contact number of the parent or guardian. Rule: Required if patient_type = DD (dependent). Leave out when patient_type = MM (member).

Parameter	Type	Required	Description
guardian_relationship	string (100)	Conditional	Relationship of the parent or guardian to the patient. Valid values: Library Reference – Guardian Relationship. Rule: Required if patient_type = DD (dependent). Leave out when patient_type = MM (member).
guardian_pin	string (12)	No	PhilHealth Identification Number (PIN) of the parent or guardian.
profile · Object			
method_of_service_delivery	string (1)	Yes	Method of service delivery for the FPE. Valid values: Library Reference – Service Delivery Method.
patient_verification_mode	string (10)	Yes	Method used to verify the identity of the patient for this encounter: PCU (PCU transaction code), OTP (YAKAP Patient Verification Code) or VALID_ID (valid government-issued ID). Decides which of pcu_transaction_code, one_time_pin, or valid_id_type and valid_id_image is required. Valid values: Library Reference – Patient Verification Mode.
pcu_transaction_code	string (20)	Conditional	PhilHealth Check Utility (PCU) transaction code: the trans_no returned by PCU (Implementation Guide 4.1), at most 20 characters. Rule: Required if patient_verification_mode = PCU
one_time_pin	string (20)	Conditional	YAKAP Patient Verification Code (one-time PIN) issued by PhilHealth to the patient and validated through Service 07; used when no PCU transaction code is available. Rule: Required if patient_verification_mode = OTP
valid_id_type	string (2)	Conditional	Type of valid government-issued ID presented to verify the patient when patient_verification_mode = VALID_ID. Valid values: Library Reference – Valid ID Type. Rule: Required if patient_verification_mode = VALID_ID. Only codes in the library are accepted.
valid_id_image	string (base-64 JPEG, at most 2 MB before encoding)	Conditional	Picture of the valid ID presented, as a base-64 encoded JPEG image. PhilHealth decrypts the request and stores the image on premises (file server and database) for review. Format: Base-64 (JPEG). Rule: Required on the first request with patient_verification_mode = VALID_ID for the same patient, facility and encounter date (fpe_date); may be sent as an empty string on later requests for that date. JPEG only; at most 2 MB before base-64 encoding.
mca_flag	string (1)	Yes	Indicates whether the Mutual Care Agreement on the YAKAP Empanelment Slip was signed. Valid values: "Y" - Yes; "N" - No.
co_payment_flag	string (1)	Yes	Indicates whether the patient has a co-payment. Valid values: "Y" - With co-payment (max. PHP 900 per year for private facilities); "N" - No co-payment (government health institutions).
co_payment_date_payment	string (MM/DD/YYYY)	Conditional	Date the co-payment was paid. Format: MM/DD/YYYY. Rule: Required if co_payment_flag = Y
co_payment	number	Conditional	Co-payment amount paid, in PHP. Default: 0.00. Rule: Required if co_payment_flag = Y

Parameter	Type	Required	Description
co_payment_balance	number	Conditional	Remaining co-payment balance, in PHP. Default: 0.00. Rule: Required if co_payment_flag = Y
fpe_classification_type	string (1)	Yes	Classification of the First Patient Encounter (new or repeat). Valid values: Library Reference – FPE Classification.
profile_transaction_no	string (23)	Yes	Transaction number of the FPE or health screening record for the effectivity year. Format: P+ACCRE_NO+YYYY+MM+DD+5 digits daily series number = P+XXXXXXXXX+YYYY+MM+DD+99999.
fpe_date	string (MM/DD/YYYY)	Yes	Date of the FPE or health screening. Its year is the effectivity year of the FPE. Format: MM/DD/YYYY.
fpe_time	string (5)	Yes	Time of the FPE (24-hour). Format: HH:MM.
patient_age	string (30)	Yes	Age of the patient on the FPE date, computed from the date of birth. Format: Y YR(S), M MO(S), D DAY(S) Example: 1 YR(S), 0 MO(S), 25 DAY(S). Rule: Required in the request. The backend computes the age from patient_dob and fpe_date and rejects a submitted value that does not match.
medhist · Array			
mdisease_code	string (3)	Yes	Past medical history: disease code. Valid values: Library Reference – Medical Disease.
mhspecific · Object, nested in medhist[]			
is_on_dialysis	string (1)	No	Indicates whether a patient with a kidney disorder is on dialysis. Valid values: "Y" - Yes; "N" - No.
dialysis_type	string (50)	Conditional	Type of dialysis. Rule: Required if is_on_dialysis = Y.
dialysis_year_started	string (4)	No	Year dialysis started.
hosphist · Array			
previous_hospitalization	string (2000)	No	Description of a previous hospitalization.
date_previous_hospitalization	string (MM/DD/YYYY)	No	Date of a previous hospitalization. Format: MM/DD/YYYY.
accidenthist · Array			
previous_accident_injury	string (2000)	No	Description of a previous accident or injury.
date_previous_accident_injury	string (MM/DD/YYYY)	No	Date of a previous accident or injury. Format: MM/DD/YYYY.
mhspecific · Object, nested in medhist[]			

Parameter	Type	Required	Description
specific_desc	string (2000)	No	Specific description for the selected disease code (for example the cancer type).
surghist · Array			
surg_desc	string (500)	No	Description of a previous surgery.
surg_date	string (MM/DD/YYYY)	No	Date of a previous surgery. Format: MM/DD/YYYY.
allergy · Object			
food_allergy	string (500)	Yes	Food allergy of the patient, if any. Valid values: "Y" - Yes (specify); "N" - No. Rule: Send "N", or "Y - " followed by the allergy (for example "Y - Shrimp"), within 500 bytes.
medication_allergy	string (500)	Yes	Medication allergy of the patient, if any. Valid values: "Y" - Yes (specify); "N" - No. Rule: Send "N", or "Y - " followed by the allergy (for example "Y - Shrimp"), within 500 bytes.
allergy_others	string (500)	No	Other allergies of the patient.
currentmed · Object			
current_medications	string (2000)	Yes	Indicates whether the patient takes current medications. Valid values: "N" - None; "Y" - Yes (specify).
current_medication_pndf	string (2000)	No	Current medications listed in the PNDF (molecule names).
current_medication_non_pndf	string (500)	No	Current medications not listed in the PNDF.
immunizationhist · Array			
immunization_code	string (3)	Yes	Immunization history of the patient. Valid values: Library Reference – Immunization History.
famhist · Array			
mdisease_code	string (3)	Yes	Family medical history: disease code. Valid values: Library Reference – Medical Disease.
fhspecific · Array			
mdisease_code	string (3)	No	Family medical history: disease code with a specific description. Valid values: Library Reference – Medical Disease. For cancer, send the cancer type (Breast, Liver, Lung, Colorectal, Others) as free text in specific_desc.
specific_desc	string (2000)	No	Specific description for the selected family history disease code (for example the cancer type).
sochist · Object			
is_smoker	string (1)	Yes	Smoking status of the patient. Valid values: Library Reference – Smoking Status.
no_cigpk	number	Conditional	Smoking history in pack-years. Rule: Required if is_smoker = Y.

Parameter	Type	Required	Description
is_adrinker	string (1)	Yes	Alcohol use status of the patient. Valid values: Library Reference – Alcohol Use Status.
no_glasses	number	Conditional	Number of alcoholic drinks (glasses) per day. Rule: Required if is_adrinker = Y.
ill_drug_user	string (1)	Yes	Indicates whether the patient uses illicit drugs. Valid values: "Y" - Yes; "N" - No.
secondhand_smoke_exposure	string (1)	No	Type of secondhand smoke exposure. Valid values: Library Reference – Secondhand Smoke Exposure.
cigarette_sticks_per_day	number	No	Number of cigarette sticks smoked per day.
smoking_years	number	No	Number of years the patient has smoked.
vape_current_user	string (1)	No	Indicates whether the patient currently vapes. Valid values: "Y" - Yes; "N" - No.
vape_current_years	number	Conditional	Number of years of vape use (current user). Rule: Required if vape_current_user = Y.
vape_former_user	string (1)	No	Indicates whether the patient formerly vaped. Valid values: "Y" - Yes; "N" - No.
vape_former_years	number	Conditional	Number of years of vape use (former user). Rule: Required if vape_former_user = Y.
alcohol_drinker_subtype	string (1)	No	Sub-classification of the alcohol drinker. Valid values: Library Reference – Alcohol Drinker Type.
alcohol_types	string (100)	No	Types of alcohol consumed. Valid values: Library Reference – Alcohol Type; multiple selection allowed (codes separated by a comma).
alcohol_intake_years	number	No	Number of years of alcohol intake.
alcohol_frequency_per_week	number	No	Number of days per week the patient drinks alcohol.
substance_abuse_family_member	string (500)	No	Substance used by a family member or housemate, for a patient who does not use drugs.
dietary_intake_type	string (1)	Yes	Dietary intake pattern of the patient. Valid values: Library Reference – Dietary Intake.
breastfeeding_status	string (1)	No	Breastfeeding status of a patient aged 0 to 1 year. Valid values: Library Reference – Breastfeeding Status.
physical_activity_status	string (1)	Yes	Indicates whether the patient meets the recommended physical activity. Valid values: "Y" - Yes; "N" - No.
fluoride_toothpaste_use	string (1)	Yes	Indicates whether the patient uses fluoride toothpaste. Valid values: "Y" - Yes; "N" - No.
dental_checkup_status	string (1)	Yes	Dental check-up status of the patient. Valid values: Library Reference – Dental Check-up Status.
dental_checkup_year	string (4)	Conditional	Year of the last dental check-up. Format: YYYY. Rule: Required if dental_checkup_status = Y.

Parameter	Type	Required	Description
neighborhood_communicable_disease	string (500)	No	Communicable diseases prevalent in the patient's neighborhood, if any.
mental_health_event_code	string (2)	Yes	Mental health or traumatic life event. Valid values: Library Reference – Mental Health Event.
other_mental_health_event	string (500)	Conditional	Other mental health or traumatic life event (code 99, Others). Rule: Required if mental_health_event_code = 99 (Others).
gynehist · Object			
menarche_flag	string (1)	Yes	Indicates whether the patient has had her first menstrual period. Valid values: "Y" - Yes; "N" - No. Rule: Applicable only if patient_sex = F.
menarche_period	number	Conditional	Age at first menstrual period (menarche), in years. Rule: Required if menarche_flag = Y
last_mens_period_flag	string (1)	No	Indicates whether the last menstrual period applies. Valid values: "Y" - Yes; "N" - Not applicable. Rule: Applicable only if patient_sex = F.
last_mens_period	string (MM/DD/YYYY)	Conditional	Date of the last menstrual period. Format: MM/DD/YYYY. Rule: Required if last_mens_period_flag = Y
contraceptive_use_status	string (2)	No	Contraceptive use status of the patient. Valid values: Library Reference – Contraceptive Use Status. Rule: Applicable only if patient_sex = F.
contraceptive_method_desired	string (500)	Conditional	Contraceptive methods the patient wants to start. Valid values: Library Reference – Contraceptive Method; multiple selection allowed (codes separated by a comma). Rule: Required if contraceptive_use_status = 03
birth_ctrl_method	string (21)	No	Contraceptive method in use. Valid values: Library Reference – Contraceptive Method.
is_menopause	string (1)	No	Indicates whether the patient has reached menopause. Valid values: "Y" - Yes; "N" - No.
menopause_age	number	Conditional	Age at menopause, in years. Rule: Required if is_menopause = Y
gynecological_disease_flag	string (1)	Yes	Indicates whether the patient has a gynecological disease. Valid values: "Y" - Yes; "N" - No.
gynecological_disease	string (500)	Conditional	Gynecological disease of the patient. Rule: Required if gynecological_disease_flag = Y.
gyn_sexually_transmitted_flag	string (1)	Yes	Indicates whether the patient has a sexually transmitted disease. Valid values: "Y" - Yes; "N" - No.
gyn_sexually_transmitted_disease	string (500)	Conditional	Current sexually transmitted disease of the patient. Rule: Required if gyn_sexually_transmitted_flag = Y.
preghist · Object			

Parameter	Type	Required	Description
is_currently_pregnant	string (1)	Yes	Indicates whether the patient is currently pregnant. Valid values: "Y" - Yes; "N" - No.
prenatal_checkup_count	string (1)	No	Number of prenatal check-ups in the current pregnancy. Valid values: Library Reference – Prenatal Check-up Count.
age_of_gestation	string (20)	No	Age of gestation of the current pregnancy. Rule: System-computed from last_mens_period when is_currently_pregnant = Y.
expected_date_of_delivery	string (MM/DD/YYYY)	No	Expected date of delivery of the current pregnancy. Format: MM/DD/YYYY. Rule: System-computed from last_mens_period when is_currently_pregnant = Y.
is_applicable	string (1)	Yes	Indicates whether the patient has ever been pregnant. Valid values: "Y" - Yes; "N" - No.
preg_cnt	number	No	OB score: number of pregnancies (gravidity).
delivery_cnt	number	No	OB score: number of deliveries (parity).
full_term_cnt	number	No	OB score: number of full-term deliveries.
premature_cnt	number	No	OB score: number of preterm deliveries.
abortion_cnt	number	No	OB score: number of abortions.
liv_children_cnt	number	No	OB score: number of living children.
pegensurvey · Object			
gen_survey_id	string (1)	Yes	General survey findings. Valid values: Library Reference – General Survey.
gen_survey_rem	string (2000)	Conditional	Remarks on the general survey (code 7, Others). Rule: Required if gen_survey_id = 7
pepert · Object			
systolic	number	Conditional	Systolic blood pressure, in mmHg. Rule: Required if the patient is 4 years old and above on fpe_date.
diastolic	number	Conditional	Diastolic blood pressure, in mmHg. Rule: Required if the patient is 4 years old and above on fpe_date.
heart_rate	number	Yes	Heart rate, in beats per minute.
respiratory_rate	number	Yes	Respiratory rate, in breaths per minute.
temperature	number	Yes	Body temperature, in degrees Celsius.
height	number	Conditional	Height of the patient, in cm. Rule: Required if the patient is 2 years old and above on fpe_date.
weight	number	Yes	Weight of the patient, in kg.

Parameter	Type	Required	Description
bmi	number	Yes	Body mass index: weight (kg) divided by height (m) squared. Rule: Required in the request. The backend computes weight (kg) divided by height (m) squared, using length for patients aged 0 to 24 months, and rejects a submitted value that differs after rounding to 2 decimal places.
waist	number	No	Waist circumference, in cm. Rule: For patients aged 3 to 18 years.
mid_upper_arm_circ	number	Conditional	Mid-upper arm circumference, in cm. Rule: Required for patients aged 6 months to 5 years.
length	number	Conditional	Length of the patient, in cm. Rule: Required if the patient is 0 to 24 months old on fpe_date.
head_circ	number	No	Head circumference, in cm. Rule: For patients aged 0 to 24 months.
skinfold_thickness	number	No	Skinfold thickness, in cm. Rule: For patients aged 6 months to 5 years.
hip	number	No	Hip circumference, in cm. Rule: For patients aged 3 to 18 years.
facilitator · Object			
facilitator_type	string (1)	Yes	Type of FPE facilitator. Valid values: Library Reference – Facilitator Type.
facilitator_name	string (150)	Yes	Name of the FPE facilitator.

Response (after decryption)

```
{
  "status": "success",
  "code": 202,
  "message": "Submission accepted for processing",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
    "upload_transaction_no": "UH123456782026102500001",
    "form": "fpe",
    "processing_status": "queued",
    "case_no": "TH12345678202610230001",
    "profile_transaction_no": "PH12345678202610230001"
  }
}
```

Field	Type	Returned	Description
data.upload_transaction_no	string (23)	Always	Number of this submission, generated by the service. Use it to check the outcome (Section 4.6.7). Format: U + accre_no + YYYY + MM + DD + 5-digit daily series number (23 characters).

Field	Type	Returned	Description
data.form	string	Always	The form submitted: fpe.
data.processing_status	string	Always	queued – the submission passed the checks made on receipt and is waiting to be processed.
data.case_no	string	Always	Echoes case_no – the patient record.
data.profile_transaction_no	string	Always	Echoes profile_transaction_no – the FPE record.

Status values

processing_status = queued in the upload response; the final status (accepted or rejected) is read from Upload Status (4.6.7). Resending the FPE record (profile_transaction_no) with identical content returns HTTP 200 with the original upload_transaction_no.

Validation rules

Rule	Validation
Encryption and consent	The body is the encrypted envelope (Section 3.8). consent: true is sent at the top level of the body, beside the data groups.
Field names and nesting	Send each field inside its data group, using the names and JSON paths in the field table. A data group that does not apply is left out as a whole.
Values	Yes fields carry a valid value. Within each group sent, every string field is present: "" when it has no value. Number fields with no value are left out. null is never accepted (Section 3.3).
Types and sizes	Send each value with the JSON type shown. String sizes are maximums in bytes (UTF-8; ñ counts as two bytes). Numbers carry no unit; the unit is in the field description, except Diagnostic Results values that the form reports in two units, which have one field per unit (4.6.4). Codes and record numbers are strings, so leading zeros are kept.
Dates and times	MM/DD/YYYY, MM/YYYY, YYYY and HH:MM (24-hour), as stated per field (Section 3.7).
Coded values	Codes must be active codes (LIBRARY STATUS 1) of the named Library Reference worksheet. Yes or No fields use "Y" and "N". Where several codes are allowed, separate them with a comma and no spaces, within the field size.
Record numbers	case_no (T), enlist_transaction_no (E) and profile_transaction_no (P) follow Section 3.9. case_no identifies the patient record and is reused by every later submission for the patient. enlistment.accre_no equals the accre_no in the token and in every record number.
Patient verification	patient_verification_mode PCU requires pcu_transaction_code; OTP requires one_time_pin; VALID_ID requires valid_id_type and, on the first VALID_ID request for the patient, facility and fpe_date, valid_id_image (Section 3.10).
Dependent patients	The guardian group is required when patient_type = DD and left out when patient_type = MM.
Female patients	gynehist and preghist are sent only when patient_sex = F.
Age-dependent measures	systolic and diastolic from 4 years old; height from 2 years old; length from 0 to 24 months, on fpe_date.
Allergies	food_allergy and medication_allergy take "N", or "Y - " followed by the allergy (for example "Y - Shrimp").
Computed values	patient_age and bmi are required; the backend recomputes them (age from patient_dob and fpe_date; bmi = weight kg ÷ height or length m², rounded to 2 decimals) and rejects a mismatch.

Rule	Validation
Effectivity	The year of fpe_date is the effectivity year of the FPE.

Errors

The errors common to the six upload endpoints apply (Section 4.6). Problems found after queueing are reported through Upload Status.

Sample error response

```
{
  "status": "error",
  "code": 400,
  "message": "Invalid request payload",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "errors": [
    {
      "field": "profile.profile_transaction_no",
      "issue": "validation_error"
    }
  ]
}
```

4.6.2 Consultation Upload

Purpose

Submits a consultation (SOAP) with any Specific Forms accomplished during it (OB-Gyn, Pediatric, Adolescent, Full HEADSSS and BP Monitoring). Fields follow Data Dictionary Annex B (Rev. 7, 10/25/2026).

Item	Value
Endpoint	POST /api/v1/yakap-data-upload/consultation
Authentication	Bearer token (Section 3.2); the facility is the accre_no in the token
Encryption	Request body and response data encrypted (Section 3.8, Annex C); errors in plain JSON
Success	HTTP 202 Accepted (200 on an identical resend)

Business rules and preconditions

- Record numbers: case_no is that of the patient's FPE record (4.6.1). soap_transaction_no (S) follows Section 3.9 and is unique per consultation.
- Patient verification: As in 4.6.1, using consultation_date for the VALID_ID image rule.
- Dependent patients: The guardian group is required when patient_type = DD and left out when patient_type = MM.

- Checked after queueing and reported through Upload Status: case_no matches an accepted FPE record; soap_transaction_no is not used by another consultation.

Request (before encryption)


```
{
  "consent": true,
  "soap": {
    "case_no": "TH123456782026102300001",
    "soap_transaction_no": "SH123456782026102300001",
    "patient_type": "MM",
    "patient_pin": "123456789012",
    "created_by": "emr.user01",
    "patient_age": "36 YR(S), 3 MO(S), 19 DAY(S)",
    "consultation_setting": "Y",
    "method_of_service_delivery": "F",
    "patient_verification_mode": "PCU",
    "pcu_transaction_code": "PCU-LOG-TRANS-NO",
    "one_time_pin": "",
    "valid_id_type": "",
    "valid_id_image": "",
    "co_payment_flag": "Y",
    "co_payment_date_payment": "10/23/2026",
    "co_payment": 300,
    "co_payment_balance": 600,
    "consultation_date": "10/23/2026",
    "consultation_time": "10:15"
  },
  "subjective": {
    "consult_reason": "01",
    "consult_reason_details": "Cough and colds for 3 days",
    "illness_history": "Cough and colds for 3 days, no fever."
  },
  "medhist": [
    {
      "mdisease_code": "001",
      "mhspecific": {
        "is_on_dialysis": "Y",
        "dialysis_type": "Hemodialysis",
        "dialysis_year_started": "2024",
        "specific_desc": "Diagnosed 2019, maintained on medication"
      }
    }
  ],
  "hosphist": [
    {
      "previous_hospitalization": "Dengue fever, admitted 4 days",
      "date_previous_hospitalization": "10/23/2026"
    }
  ],
  "surghist": [
    {
      "surg_desc": "Appendectomy",
      "surg_date": "10/23/2026"
    }
  ],
  "accidenthist": [
```

```
    {
      "previous_accident_injury": "Fractured left wrist (fall)",
      "date_previous_accident_injury": "10/23/2026"
    }
  ],
  "allergy": {
    "food_allergy": "Y - Shrimp",
    "medication_allergy": "N",
    "allergy_others": "Dust mites"
  },
  "currentmed": {
    "current_medications": "Y",
    "current_medication_pndf": "Amlodipine",
    "current_medication_non_pndf": ""
  },
  "immunizationhist": [
    {
      "immunization_code": "02"
    }
  ],
  "famhist": [
    {
      "mdisease_code": "001"
    }
  ],
  "fhspecific": [
    {
      "mdisease_code": "001",
      "specific_desc": "Diagnosed 2019, maintained on medication"
    }
  ],
  "sochist": {
    "is_smoker": "Y",
    "secondhand_smoke_exposure": "P",
    "cigarette_sticks_per_day": 10,
    "smoking_years": 5,
    "no_cigpk": 2.5,
    "vape_current_user": "Y",
    "vape_former_user": "Y",
    "is_adrinker": "Y",
    "alcohol_drinker_subtype": "O",
    "alcohol_types": "1,2",
    "alcohol_intake_years": 3,
    "no_glasses": 2,
    "alcohol_frequency_per_week": 1,
    "ill_drug_user": "Y",
    "substance_former_user_spec": "",
    "substance_current_user_spec": "",
    "substance_abuse_family_member": "",
    "dietary_intake_type": "W",
    "breastfeeding_status": "N",
    "physical_activity_status": "Y",
    "fluoride_toothpaste_use": "Y",
    "dental_checkup_status": "U",
    "dental_checkup_year": "2025",
    "neighborhood_communicable_disease": "None",
    "mental_health_event_code": "02",
```

```
    "other_mental_health_event": ""
  },
  "sexhist": {
    "sexual_hist_consent_status": "01",
    "have_you_ever_had_sex": "Y",
    "age_at_first_sexual_contact": 19,
    "sexually_active": "Y",
    "male_partner_sexual_activity": "Y",
    "male_partner_recent_anal_neovag": "09/2026",
    "male_partner_recent_condomless": "09/2026",
    "female_partner_sexual_activity": "Y",
    "female_partner_recent_anal_neovag": "09/2026",
    "female_partner_recent_condomless": "09/2026",
    "sexual_risk_behaviors": "01,02",
    "sexual_risk_recent_risk_date": "09/2026",
    "sexual_risk_other_concerns_spec": "",
    "sti_hist": "Y",
    "sti_spec": ""
  },
  "ros": {
    "general_ros_id": "01,02",
    "skin_ros_id": "01,02",
    "heent_ros_id": "01,02",
    "cardiorespiratory_ros_id": "01,02",
    "gastrointestinal_ros_id": "01,02",
    "genitourinary_ros_id": "01,02",
    "musculoskeletal_ros_id": "01,02",
    "neuro_ros_id": "01,02",
    "psych_neurodev_ros_id": "01,02",
    "ros_other_spec": ""
  },
  "pegensurvey": {
    "gen_survey_id": "1",
    "gen_survey_rem": ""
  },
  "pepert": {
    "systolic": 120,
    "diastolic": 80,
    "heart_rate": 78,
    "respiratory_rate": 18,
    "temperature": 36.6,
    "weight": 60.5,
    "height": 160,
    "bmi": 23.63,
    "waist_circ": 78,
    "mid_upper_arm_circ": 27,
    "sam_form": "Y",
    "vision_chart_type": "01",
    "vision_right_eye": "20/20",
    "vision_left_eye": "20/20",
    "vision_both_eyes": "20/20",
    "vision_right_eye_corrected": "",
    "vision_left_eye_corrected": "",
    "vision_both_eyes_corrected": ""
  },
  "pemisc": {
    "heent": "11,12",
```

```
    "chest_breast_lungs": "3,4",
    "cbe": "3,4",
    "heart": "3,4",
    "abdomen": "7,8",
    "skin_extremities": "1,2",
    "genitourinary": "1,2",
    "digital_rectal_exam": "1",
    "neuro_exam": "6,7"
  },
  "physiciansignoff": {
    "physician_name": "MARIA L. SANTOS, MD",
    "physician_designation": "Attending Physician",
    "physician_license_no": "0123456",
    "physician_accre_no": "1234-5678901-2"
  },
  "diagnosis": {
    "primary_diagnosis": "Acute upper respiratory infection",
    "primary_diagnosis_icd_code": "J06.9",
    "other_diagnosis": "Essential hypertension",
    "other_diagnosis_icd_code": "I10",
    "specific_diagnosis": "01,02"
  },
  "management": {
    "counseling_health_education": "5,6",
    "routine_vaccine_name": "",
    "routine_vaccine_date": "10/23/2026",
    "adults_routine_screening": "1,2",
    "pediatric_routine_screening": "1,2",
    "prenatal_screening_services": "1,2",
    "cancer_screening_flag": "Y",
    "cancer_screening_selected": "1,2",
    "diagnostic_services_flag": "N",
    "medication_prescription_flag": "Y",
    "referral_flag": "Y",
    "other_medical_advice_spec": "Increase fluid intake",
    "follow_up_flag": "Y",
    "follow_up_on": "11/06/2026",
    "follow_up_reason": "Blood pressure check",
    "follow_up_vaccine_name": "",
    "follow_up_next_vaccine_date": "10/23/2026"
  },
  "sf_obgyne_menshist": {
    "menarche_flag": "Y",
    "menarche_period": 12,
    "last_mens_period_flag": "Y",
    "last_mens_period": "10/23/2026",
    "is_menopause": "Y",
    "contraceptive_use_status": "02",
    "contraceptive_method_desired": "01,02",
    "birth_ctrl_method": "01",
    "gynecological_disease_flag": "Y",
    "gynecological_disease": ""
  },
  "sf_obgyne_preghist": {
    "is_applicable": "Y",
    "is_currently_pregnant": "Y",
    "prenatal_checkup_count": "A",
```

```
    "preg_cnt": 2,
    "delivery_cnt": 2,
    "full_term_cnt": 2,
    "premature_cnt": 0,
    "abortion_cnt": 0,
    "liv_children_cnt": 2,
    "age_of_gestation": "",
    "expected_date_of_delivery": ""
  },
  "sf_obgyne_pe": {
    "fundic_height": 24.5,
    "fetal_heart_tone": 140,
    "estimated_fetal_weight": 650,
    "leopold_l1": "Fundus: breech",
    "leopold_l2": "Fetal back on the left",
    "leopold_l3": "Cephalic presentation",
    "leopold_l4": "Not engaged",
    "perineal_inspection": "",
    "speculum_exam": "",
    "internal_exam": "",
    "bimanual_exam": "",
    "rectovaginal_exam": ""
  },
  "sf_pedia_immunization": {
    "routine_immunization_status": "01"
  },
  "sf_pedia_vaccine": [
    {
      "vaccine_code": "01",
      "vaccine_other_spec": "",
      "vaccination_status": "01"
    }
  ],
  "sf_pedia_devmilestone": [
    {
      "milestone_visit_age": "01",
      "milestone_at_par_flag": "Y",
      "gross_motor_danger_signs": "GM01,GM02",
      "fine_motor_danger_signs": "GM01,GM02",
      "language_danger_signs": "GM01,GM02",
      "cognitive_danger_signs": "GM01,GM02",
      "psychosocial_danger_signs": "GM01,GM02"
    }
  ],
  "sf_adol_immunization": {
    "routine_immunization_status": "01"
  },
  "sf_adol_vaccine": [
    {
      "vaccine_code": "01",
      "vaccine_other_spec": "",
      "vaccination_status": "01"
    }
  ],
  "sf_adol_smr": {
    "smr_assessment_status": "Y",
    "smr_pubic_hair_stage": 3,
```

```
    "smr_breast_stage": 3,
    "smr_genital_stage": 3,
    "smr_assessment_result": "01"
  },
  "sf_adol_rapidheadsss": {
    "rh_assent_consent_status": "Y",
    "rh_education_employment_status": "01",
    "rh_relationship_status": "01",
    "rh_living_arrangement": "01",
    "rh_living_arrangement_other_spec": "",
    "rh_q01_home_violence": "Y",
    "rh_q02_runaway_thoughts": "Y",
    "rh_q03_bullying": "Y",
    "rh_q04_suicidal_ideation": "Y",
    "rh_q05_smoking": "Y",
    "rh_q06_alcohol": "Y",
    "rh_q07_drug_exposure": "Y",
    "rh_q08_romantic_relationship": "Y",
    "rh_q09_sexual_intercourse": "Y",
    "rh_q10_forced_sex": "Y",
    "rh_q11_pregnancy": "Y",
    "rh_q12_counseling_request": "Y",
    "rh_full_headsss_flag": "Y"
  },
  "sf_headsss": {
    "headsss_assent_consent_status": "Y",
    "headsss_home_questions": "HM01,HM02",
    "headsss_home_answer": "Lives with both parents; feels safe at home",
    "headsss_home_red_flags": "HM01,HM02",
    "headsss_education_questions": "HM01,HM02",
    "headsss_education_answer": "Grade 10 student",
    "headsss_education_red_flags": "HM01,HM02",
    "headsss_eating_questions": "HM01,HM02",
    "headsss_eating_answer": "Eats three meals a day",
    "headsss_eating_red_flags": "HM01,HM02",
    "headsss_activities_questions": "HM01,HM02",
    "headsss_activities_answer": "Plays basketball after school",
    "headsss_activities_red_flags": "HM01,HM02",
    "headsss_drugs_questions": "HM01,HM02",
    "headsss_drugs_answer": "Denies use",
    "headsss_drugs_red_flags": "HM01,HM02",
    "headsss_sexuality_questions": "HM01,HM02",
    "headsss_sexuality_answer": "Not sexually active",
    "headsss_sexuality_red_flags": "HM01,HM02",
    "headsss_suicide_depression_questions": "HM01,HM02",
    "headsss_suicide_depression_answer": "Denies",
    "headsss_suicide_depression_red_flags": "HM01,HM02",
    "headsss_urgent_referral_flag": "Y",
    "headsss_safety_questions": "HM01,HM02",
    "headsss_safety_answer": "Uses a helmet when cycling",
    "headsss_safety_red_flags": "HM01,HM02"
  },
  "sf_bpmon": {
    "bpmon_start_date": "10/23/2026",
    "bpmon_end_date": "10/23/2026"
  },
  "sf_bpmon_day": [
```

```
    {
      "bpmon_day_no": 1,
      "bpmon_location": "01",
      "bpmon_after_medication": "Y",
      "bpmon_am_systolic": 130,
      "bpmon_am_diastolic": 85,
      "bpmon_pm_systolic": 128,
      "bpmon_pm_diastolic": 82
    }
  ]
}
```

The sample is an adult member: the guardian group and length are left out; Specific Form groups are included only to show their structure.

Payload structure

Data group	Structure	Content and applicability	Fields
soap	Object	Consultation header: patient, verification, co-payment, date and time. Always required; includes patient verification (PCU, OTP or VALID_ID evidence).	19
guardian	Object	Parent or guardian. Required when patient_type = DD (dependent); left out when patient_type = MM (member).	7
subjective	Object	Reason for consultation and history of present illness. Required.	3
medhist	Array	Past medical history – one entry per disease. Required (mdisease_code is required). Each entry may carry a nested mhspecific object.	1
mhspecific	Object, nested in each medhist entry	Details of the disease in that medhist entry: dialysis and specific description. Optional.	4
hosphist	Array	Previous hospitalizations – one entry per hospitalization. Optional.	2
surghist	Array	Surgical history – one entry per operation. Optional.	2
accidenthist	Array	Previous accidents or injuries – one entry per event. Optional.	2
allergy	Object	Food, medication and other allergies. Required.	3
currentmed	Object	Current medications. Required.	3
immunizationhist	Array	Immunization history – one entry per immunization. Required (immunization_code is required).	1
famhist	Array	Family medical history – one entry per disease. Required (mdisease_code is required).	1
fhspecific	Array	Specific description of a family-history disease – one entry per disease. Optional.	2
sochist	Object	Personal and social history. Required.	28
sexhist	Object	Sexual history, risk behaviors and sexually transmitted infections. Required.	15
ros	Object	Review of systems. Required.	10

Data group	Structure	Content and applicability	Fields
pegensurvey	Object	Physical examination – general survey. Required.	2
pepert	Object	Vital signs, anthropometric measurements and visual acuity. Required.	23
pemisc	Object	Physical examination findings by body system. Required.	9
physiciansignoff	Object	Physician who conducted the consultation. Required.	4
diagnosis	Object	Assessment and diagnosis. Required.	5
management	Object	Plan and management. Required.	17
sf_obgyne_menshist	Object	OB-Gyn Specific Form – gynecological history. Sent when the OB-Gyn Specific Form is accomplished. Female patients only.	11
sf_obgyne_preghist	Object	OB-Gyn Specific Form – obstetric history. Sent when the OB-Gyn Specific Form is accomplished. Female patients only.	11
sf_obgyne_pe	Object	OB-Gyn Specific Form – physical and other examinations. Optional within the OB-Gyn Specific Form.	12
sf_pedia_immunization	Object	Pediatric Specific Form – routine immunization status. Sent when the Pediatric Specific Form is accomplished.	1
sf_pedia_vaccine	Array	Pediatric Specific Form – one entry per vaccine. Sent with the Pediatric Specific Form; at least one entry.	3
sf_pedia_devmilestone	Array	Pediatric Specific Form – one entry per visit-age row. Sent with the Pediatric Specific Form for patients 0 to 5 years old; at least one entry.	7
sf_adol_immunization	Object	Adolescent Specific Form – routine immunization status. Sent when the Adolescent Specific Form is accomplished.	1
sf_adol_vaccine	Array	Adolescent Specific Form – one entry per vaccine. Sent with the Adolescent Specific Form; at least one entry.	3
sf_adol_smr	Object	Adolescent Specific Form – Tanner staging (sexual maturity rating). Optional within the Adolescent Specific Form.	5
sf_adol_rapidheadsss	Object	Adolescent Specific Form – Rapid HEADSSS assessment. Sent with the Adolescent Specific Form (patients 10 to 19 years old).	18
sf_headsss	Object	Full HEADSSS assessment. Sent when rh_full_headsss_flag = Y and the Full HEADSSS questionnaire is accomplished.	26
sf_bpmon	Object	BP Monitoring Form – monitoring period. Sent when the BP Monitoring Form is accomplished.	2
sf_bpmon_day	Array	BP Monitoring Form – one entry per day. Sent with sf_bpmon; 1 to 7 entries.	7

Request fields

Parameter	Type	Required	Description
soap · Object			
case_no	string (23)	Yes	Patient case number that links the consultation to the patient and FPE records. Format: T+ACCRE_NO+YYYY+MM+DD+99999.

Parameter	Type	Required	Description
soap_transaction_no	string (23)	Yes	Transaction number of the consultation record. Format: S+ACCRE_NO+YYYY+MM+DD+99999.
patient_type	string (2)	Yes	Patient type: member or dependent. Valid values: Library Reference – Patient Type.
patient_pin	string (12)	Yes	PhilHealth Identification Number (PIN) of the patient.
created_by	string (150)	Yes	User who created the record.
patient_age	string (30)	Yes	Age of the patient on the consultation date. Format: Y YR(S), M MO(S), D DAY(S) (e.g., 1 YR(S), 0 MO(S), 25 DAY(S)). Rule: Required in the request. The backend computes the age from the patient's date of birth on the PhilHealth record and consultation_date and rejects a submitted value that does not match.
consultation_setting	string (1)	No	Consultation setting: walk-in or with appointment. Valid values: "Y" - Walk-in patient; "N" - With appointment.
method_of_service_delivery	string (1)	Yes	Method of service delivery for the consultation. Valid values: Library Reference – Service Delivery Method.
patient_verification_mode	string (10)	Yes	Method used to verify the identity of the patient for this encounter: PCU (PCU transaction code), OTP (YAKAP Patient Verification Code) or VALID_ID (valid government-issued ID). Decides which of pcu_transaction_code, one_time_pin, or valid_id_type and valid_id_image is required. Valid values: Library Reference – Patient Verification Mode.
pcu_transaction_code	string (20)	Conditional	PhilHealth Check Utility (PCU) transaction code: the trans_no returned by PCU (Implementation Guide 4.1), at most 20 characters. Rule: Required if patient_verification_mode = PCU.
one_time_pin	string (20)	Conditional	YAKAP Patient Verification Code (one-time PIN) issued by PhilHealth to the patient and validated through Service 07; used when no PCU transaction code is available. Rule: Required if patient_verification_mode = OTP
valid_id_type	string (2)	Conditional	Type of valid government-issued ID presented to verify the patient when patient_verification_mode = VALID_ID. Valid values: Library Reference – Valid ID Type. Rule: Required if patient_verification_mode = VALID_ID. Only codes in the library are accepted.
valid_id_image	string (base-64 JPEG, at most 2 MB before encoding)	Conditional	Picture of the valid ID presented, as a base-64 encoded JPEG image. PhilHealth decrypts the request and stores the image on premises (file server and database) for review. Format: Base-64 (JPEG). Rule: Required on the first request with patient_verification_mode = VALID_ID for the same patient, facility and consultation_date; may be sent as an empty string on later requests for that date. JPEG only; at most 2 MB before base-64 encoding.
co_payment_flag	string (1)	Yes	Indicates whether the patient has a co-payment. Valid values: "Y" - With co-payment (max. PHP 900 per year for private facilities); "N" - No co-payment (government health institutions).

Parameter	Type	Required	Description
co_payment_date_payment	string (MM/DD/YYYY)	No	Date the co-payment was paid. Format: MM/DD/YYYY.
co_payment	number	No	Co-payment amount paid, in PHP.
co_payment_balance	number	No	Remaining co-payment balance, in PHP.
consultation_date	string (MM/DD/YYYY)	Yes	Date of the consultation. Format: MM/DD/YYYY.
consultation_time	string (5)	Yes	Time of the consultation (24-hour). Format: HH:MM.
guardian · Object			
guardian_name	string (150)	Conditional	Full name of the parent or guardian (surname, first name, middle name, suffix). Rule: Required if patient_type = DD (dependent). Leave out when patient_type = MM (member).
guardian_age	number	Conditional	Age of the parent or guardian, in years. Rule: Required if patient_type = DD (dependent). Leave out when patient_type = MM (member).
guardian_sex	string (1)	Conditional	Sex of the parent or guardian. Valid values: Library Reference – Sex. Rule: Required if patient_type = DD (dependent). Leave out when patient_type = MM (member).
guardian_birthday	string (MM/DD/YYYY)	Conditional	Date of birth of the parent or guardian. Format: MM/DD/YYYY. Rule: Required if patient_type = DD (dependent). Leave out when patient_type = MM (member).
guardian_contact_no	string (15)	Conditional	Contact number of the parent or guardian. Rule: Required if patient_type = DD (dependent). Leave out when patient_type = MM (member).
guardian_relationship	string (100)	Conditional	Relationship of the parent or guardian to the patient. Valid values: Library Reference – Guardian Relationship. Rule: Required if patient_type = DD (dependent). Leave out when patient_type = MM (member).
guardian_pin	string (12)	No	PhilHealth Identification Number (PIN) of the parent or guardian.
subjective · Object			
consult_reason	string (2)	Yes	Reason for consultation. Valid values: Library Reference – Consultation Reason.
consult_reason_details	string (250)	Conditional	Details of the consultation reason. Rule: Required if consult_reason = 04 (For Consultation).
illness_history	string (250)	Yes	History of present illness.
medhist · Array			
mdisease_code	string (3)	Yes	Past medical history: disease code. Valid values: Library Reference – Medical Disease.
mhspecific · Object, nested in medhist[]			

Parameter	Type	Required	Description
is_on_dialysis	string (1)	No	Indicates whether a patient with a kidney disorder is on dialysis. Valid values: "Y" - Yes; "N" - No.
dialysis_type	string (50)	Conditional	Type of dialysis. Rule: Required if is_on_dialysis = Y.
dialysis_year_started	string (4)	No	Year dialysis started.
hosphist · Array			
previous_hospitalization	string (2000)	No	Description of a previous hospitalization.
date_previous_hospitalization	string (MM/DD/YYYY)	No	Date of a previous hospitalization. Format: MM/DD/YYYY.
surghist · Array			
surg_desc	string (500)	No	Description of a previous surgery.
surg_date	string (MM/DD/YYYY)	No	Date of a previous surgery. Format: MM/DD/YYYY.
accidenthist · Array			
previous_accident_injury	string (2000)	No	Description of a previous accident or injury.
date_previous_accident_injury	string (MM/DD/YYYY)	No	Date of a previous accident or injury. Format: MM/DD/YYYY.
mhspecific · Object, nested in medhist[]			
specific_desc	string (2000)	No	Specific description for the selected disease code (for example the cancer type).
allergy · Object			
food_allergy	string (500)	Yes	Food allergy of the patient, if any. Valid values: "Y" - Yes (specify); "N" - No. Rule: Send "N", or "Y - " followed by the allergy (for example "Y - Shrimp"), within 500 bytes.
medication_allergy	string (500)	Yes	Medication allergy of the patient, if any. Valid values: "Y" - Yes (specify); "N" - No. Rule: Send "N", or "Y - " followed by the allergy (for example "Y - Shrimp"), within 500 bytes.
allergy_others	string (500)	No	Other allergies of the patient.
currentmed · Object			
current_medications	string (2000)	Yes	Indicates whether the patient takes current medications. Valid values: "N" - None; "Y" - Yes (specify).
current_medication_pndf	string (2000)	No	Current medications listed in the PNDF (molecule names). Valid values: Molecules of Medications only.
current_medication_non_pndf	string (500)	No	Current medications not listed in the PNDF.
immunizationhist · Array			

Parameter	Type	Required	Description
immunization_code	string (3)	Yes	Immunization history of the patient. Valid values: Library Reference – Immunization History.
famhist · Array			
mdisease_code	string (3)	Yes	Family medical history: disease code. Valid values: Library Reference – Medical Disease.
fhspecific · Array			
mdisease_code	string (3)	No	Family medical history: disease code with a specific description. Valid values: Library Reference – Medical Disease. For cancer, send the cancer type (Breast, Liver, Lung, Colorectal, Others) as free text in specific_desc.
specific_desc	string (2000)	No	Specific description for the selected family history disease code (for example the cancer type).
sochist · Object			
is_smoker	string (1)	Yes	Smoking status of the patient. Valid values: Library Reference – Smoking Status.
secondhand_smoke_exposure	string (1)	No	Type of secondhand smoke exposure. Valid values: Library Reference – Secondhand Smoke Exposure.
cigarette_sticks_per_day	number	Conditional	Number of cigarette sticks smoked per day. Rule: Required if is_smoker = Y or X.
smoking_years	number	Conditional	Number of years the patient has smoked. Rule: Required if is_smoker = Y or X.
no_cigpk	number	Conditional	Smoking history in pack-years. Rule: Required if is_smoker = Y or X. May be system-computed: (cigarette_sticks_per_day ÷ 20) × smoking_years.
vape_current_user	string (1)	No	Indicates whether the patient currently vapes. Valid values: "Y" - Yes; "N" - No.
vape_current_years	number	Conditional	Number of years of vape use (current user). Rule: Required if vape_current_user = Y.
vape_former_user	string (1)	No	Indicates whether the patient formerly vaped. Valid values: "Y" - Yes; "N" - No.
vape_former_years	number	Conditional	Number of years of vape use (former user). Rule: Required if vape_former_user = Y.
is_adrinker	string (1)	Yes	Alcohol use status of the patient. Valid values: Library Reference – Alcohol Use Status.
alcohol_drinker_subtype	string (1)	Conditional	Sub-classification of the alcohol drinker. Valid values: Library Reference – Alcohol Drinker Type. Rule: Required if is_adrinker = Y.
alcohol_types	string (100)	Conditional	Types of alcohol consumed. Valid values: Library Reference – Alcohol Type; multiple selection allowed (codes separated by a comma). Rule: Required if is_adrinker = Y.

Parameter	Type	Required	Description
alcohol_intake_years	number	No	Number of years of alcohol intake.
no_glasses	number	No	Number of alcoholic drinks (glasses or bottles) per day.
alcohol_frequency_per_week	number	No	Number of days per week the patient drinks alcohol.
ill_drug_user	string (1)	Yes	Indicates whether the patient uses illicit drugs. Valid values: "Y" - Yes; "N" - No.
substance_former_user_spec	string (250)	Conditional	Substance used by a former user (stopped more than 1 year ago). Rule: Required if history of recreational drug intake is selected.
substance_current_user_spec	string (250)	Conditional	Substance used by a current user. Rule: Required if ill_drug_user = Y.
substance_abuse_family_member	string (500)	No	Substance used by a family member or housemate, for a patient who does not use drugs.
dietary_intake_type	string (1)	Yes	Dietary intake pattern of the patient. Valid values: Library Reference – Dietary Intake.
breastfeeding_status	string (1)	Conditional	Breastfeeding status of a patient aged 0 to 1 year. Valid values: Library Reference – Breastfeeding Status. Rule: Required if the patient is 0 to 1 year old.
physical_activity_status	string (1)	Yes	Indicates whether the patient meets the recommended physical activity. Valid values: "Y" - Yes; "N" - No.
fluoride_toothpaste_use	string (1)	Yes	Indicates whether the patient uses fluoride toothpaste. Valid values: "Y" - Yes; "N" - No.
dental_checkup_status	string (1)	Yes	Dental check-up status of the patient. Valid values: Library Reference – Dental Check-up Status.
dental_checkup_year	string (4)	Conditional	Year of the last dental check-up. Format: YYYY. Rule: Required if dental_checkup_status = Y.
neighborhood_communicable_disease	string (500)	No	Communicable diseases prevalent in the patient's neighborhood. Rule: Send None if there are none.
mental_health_event_code	string (2)	Yes	Mental health or traumatic life events. Valid values: Library Reference – Mental Health Event.
other_mental_health_event	string (500)	Conditional	Other mental health or traumatic life event (code 99, Others). Rule: Required if mental_health_event_code = 99 (Others).
sexhist · Object			
sexual_hist_consent_status	string (2)	Yes	Assent and consent status before the sexual history interview. Valid values: Library Reference – Sexual History Consent. Rule: Interview the patient alone and assure confidentiality.

Parameter	Type	Required	Description
have_you_ever_had_sex	string (1)	Yes	Indicates whether the patient has ever had sex. Valid values: "Y" - Yes; "N" - No.
age_at_first_sexual_contact	number	No	Age of the patient at first sexual contact, in years.
sexually_active	string (1)	Yes	Indicates whether the patient is sexually active. Valid values: "Y" - Yes; "N" - No.
male_partner_sexual_activity	string (1)	No	Indicates any oral, anal or vaginal sex with a male partner. Valid values: "Y" - Yes; "N" - No. Rule: Male partner: assigned male at birth, including transgender and non-binary partners.
male_partner_recent_anal_neovag	string (MM/YYYY)	No	Date of the most recent anal or neovaginal sex with a male partner. Format: MM/YYYY. Rule: Month precision only; send day as 01. Male partner: assigned male at birth, including transgender and non-binary partners.
male_partner_recent_condomless	string (MM/YYYY)	No	Date of the most recent condomless anal or neovaginal sex with a male partner. Format: MM/YYYY. Rule: Month precision only; send day as 01. Male partner: assigned male at birth, including transgender and non-binary partners.
female_partner_sexual_activity	string (1)	No	Indicates any oral, anal or vaginal sex with a female partner. Valid values: "Y" - Yes; "N" - No. Rule: Female partner: assigned female at birth, including transgender and non-binary partners.
female_partner_recent_anal_neovag	string (MM/YYYY)	No	Date of the most recent anal or neovaginal sex with a female partner. Format: MM/YYYY. Rule: Month precision only; send day as 01. Female partner: assigned female at birth, including transgender and non-binary partners.
female_partner_recent_condomless	string (MM/YYYY)	No	Date of the most recent condomless anal or neovaginal sex with a female partner. Format: MM/YYYY. Rule: Month precision only; send day as 01. Female partner: assigned female at birth, including transgender and non-binary partners.
sexual_risk_behaviors	string (1000)	No	Sexual risk behaviors of the patient. Valid values: Library Reference – Sexual Risk Behavior; multiple selection allowed (codes separated by a comma). Rule: Check all that apply.
sexual_risk_recent_risk_date	string (MM/YYYY)	No	Date of the most recent risk, per selected risk category. Format: MM/YYYY. Rule: Month precision only; send day as 01.
sexual_risk_other_concerns_spec	string (250)	No	Other sexual risk concerns.
sti_hist	string (1)	No	Indicates any history of sexually transmitted infections. Valid values: "Y" - Yes (specify in sti_spec); "N" - No.

Parameter	Type	Required	Description
sti_spec	string (250)	Conditional	Sexually transmitted infections in the patient's history. Rule: Required if sti_hist = Y.
ros · Object			
general_ros_id	string (1000)	Yes	Review of systems: general signs and symptoms. Valid values: Library Reference – Signs and Symptoms; multiple selection allowed (codes separated by a comma). Rule: Check all that apply; select at least one per category.
skin_ros_id	string (1000)	Yes	Review of systems: skin signs and symptoms. Valid values: Library Reference – Signs and Symptoms; multiple selection allowed (codes separated by a comma). Rule: Check all that apply; select at least one per category.
heent_ros_id	string (1000)	Yes	Review of systems: HEENT signs and symptoms. Valid values: Library Reference – Signs and Symptoms; multiple selection allowed (codes separated by a comma). Rule: Check all that apply; select at least one per category.
cardiorespiratory_ros_id	string (1000)	Yes	Review of systems: cardiorespiratory signs and symptoms. Valid values: Library Reference – Signs and Symptoms; multiple selection allowed (codes separated by a comma). Rule: Check all that apply; select at least one per category.
gastrointestinal_ros_id	string (1000)	Yes	Review of systems: gastrointestinal signs and symptoms. Valid values: Library Reference – Signs and Symptoms; multiple selection allowed (codes separated by a comma). Rule: Check all that apply; select at least one per category.
genitourinary_ros_id	string (1000)	Yes	Review of systems: genitourinary signs and symptoms. Valid values: Library Reference – Signs and Symptoms; multiple selection allowed (codes separated by a comma). Rule: Check all that apply; select at least one per category.
musculoskeletal_ros_id	string (1000)	Yes	Review of systems: musculoskeletal signs and symptoms. Valid values: Library Reference – Signs and Symptoms; multiple selection allowed (codes separated by a comma). Rule: Check all that apply; select at least one per category.
neuro_ros_id	string (1000)	Yes	Review of systems: neurological signs and symptoms. Valid values: Library Reference – Signs and Symptoms; multiple selection allowed (codes separated by a comma). Rule: Check all that apply; select at least one per category.
psych_neurodev_ros_id	string (1000)	Yes	Review of systems: psychiatric and neurodevelopmental signs and symptoms. Valid values: Library Reference – Signs and Symptoms; multiple selection allowed (codes separated by a comma). Rule: Check all that apply; select at least one per category.
ros_other_spec	string (250)	Conditional	Other review of systems findings. Rule: Required if code X (Others) is selected in any review of systems field (general_ros_id to psych_neurodev_ros_id).
pegensurvey · Object			
gen_survey_id	string (1)	Yes	General survey findings. Valid values: Library Reference – General Survey.
gen_survey_rem	string (2000)	Conditional	Remarks on the general survey (Others). Rule: Required if gen_survey_id = 7 (Others).

Parameter	Type	Required	Description
pepert · Object			
systolic	number	Conditional	Systolic blood pressure, in mmHg. Format: Unit: mmHg.. Rule: Required if the patient is 4 years old and above on consultation_date.
diastolic	number	Conditional	Diastolic blood pressure, in mmHg. Format: Unit: mmHg.. Rule: Required if the patient is 4 years old and above on consultation_date.
heart_rate	number	Yes	Heart rate, in beats per minute. Format: Unit: per min..
respiratory_rate	number	Yes	Respiratory rate, in breaths per minute. Format: Unit: per min..
temperature	number	Yes	Body temperature, in degrees Celsius. Format: Unit: °C..
weight	number	Yes	Weight of the adult patient, in kg. Format: Unit: kg..
height	number	Conditional	Height of the patient, in cm. Format: Unit: cm.. Rule: Required if the patient is 2 years old and above on consultation_date.
bmi	number	Yes	Body mass index: weight (kg) divided by height (m) squared; system-computed. Format: Unit: kg/m².. Rule: Required in the request. The backend computes weight (kg) divided by height (m) squared, using length for patients aged 0 to 24 months, and rejects a submitted value that differs after rounding to 2 decimal places.
waist_circ	number	No	Waist circumference of the adult patient, in cm. Format: Unit: cm..
mid_upper_arm_circ	number	No	Mid-upper arm circumference of the adult patient, in cm. Format: Unit: cm..
length	number	Conditional	Length of the patient, in cm. Format: Unit: cm.. Rule: Required if the patient is 0 to 24 months old on consultation_date.
head_circ	number	No	Head circumference of a patient aged 0 to 2 years, in cm. Format: Unit: cm..
skinfold_thickness	number	No	Skinfold thickness of a patient aged 6 months to 5 years, in mm. Format: Unit: mm..
waist	number	No	Waist circumference of a patient aged 3 to 18 years, in cm. Format: Unit: cm..
hip	number	No	Hip circumference of a patient aged 3 to 18 years, in cm. Format: Unit: cm..

Parameter	Type	Required	Description
sam_form	string (1)	No	Indicates whether to open the Severe Acute Malnutrition (SAM) form. Valid values: "Y" - Yes; "N" - No.
vision_chart_type	string (2)	No	Visual acuity chart used. Valid values: Library Reference – Visual Acuity Chart.
vision_right_eye	string (100)	Yes	Visual acuity of the right eye (OD).
vision_left_eye	string (100)	Yes	Visual acuity of the left eye (OS).
vision_both_eyes	string (100)	Yes	Visual acuity of both eyes (OU).
vision_right_eye_corrected	string (100)	No	Visual acuity of the right eye with corrective lenses.
vision_left_eye_corrected	string (100)	No	Visual acuity of the left eye with corrective lenses.
vision_both_eyes_corrected	string (100)	No	Visual acuity of both eyes with corrective lenses.
pemisc · Object			
heent	string (1000)	Yes	Physical examination findings: HEENT. Valid values: Library Reference – PE HEENT; multiple selection allowed (codes separated by a comma). Rule: Perform if indicated by age, sex or symptoms.
chest_breast_lungs	string (1000)	Yes	Physical examination findings: chest, breast and lungs. Valid values: Library Reference – PE Chest Breast Lungs; multiple selection allowed (codes separated by a comma). Chest codes: 3 to 8, 99.
cbe	string (1000)	No	Clinical breast examination findings. Valid values: Library Reference – PE Chest Breast Lungs; multiple selection allowed (codes separated by a comma). CBE codes: 6, 11 to 15, 99. Rule: Consider for patients with symptoms or concerns; obtain assent and consent.
heart	string (1000)	Yes	Physical examination findings: heart. Valid values: Library Reference – PE Heart; multiple selection allowed (codes separated by a comma).
abdomen	string (1000)	Yes	Physical examination findings: abdomen. Valid values: Library Reference – PE Abdomen; multiple selection allowed (codes separated by a comma).
skin_extremities	string (1000)	Yes	Physical examination findings: skin and extremities. Valid values: Library Reference – PE Skin Extremities; multiple selection allowed (codes separated by a comma).
genitourinary	string (1000)	No	Physical examination findings: genitourinary. Valid values: Library Reference – PE Genitourinary; multiple selection allowed (codes separated by a comma). Rule: Consider for patients with symptoms; obtain assent and consent; refer to women and child protection programs if abuse is suspected.
digital_rectal_exam	string (1000)	No	Digital rectal examination findings. Valid values: Library Reference – PE Digital Rectal Exam; multiple selection allowed (codes separated by a comma). Rule: Consider for patients with symptoms; obtain assent and consent.

Parameter	Type	Required	Description
neuro_exam	string (1000)	No	Physical examination findings: neurological. Valid values: Library Reference – PE Neurological; multiple selection allowed (codes separated by a comma).
physiciansignoff · Object			
physician_name	string (150)	Yes	Printed name of the physician who conducted the consultation.
physician_designation	string (150)	Yes	Designation of the physician.
physician_license_no	string (100)	Yes	Professional license number of the physician.
physician_accre_no	string (100)	Yes	PhilHealth accreditation number of the physician.
diagnosis · Object			
primary_diagnosis	string (100)	Yes	Primary diagnosis (narrative).
primary_diagnosis_icd_code	string (10)	Yes	ICD-10 code of the primary diagnosis. Standard: ICD-10. Valid values: External library: ICD-10 (Konsulta ICD-10 Library; not in the Library Reference Document).
other_diagnosis	string (1000)	No	Other diagnoses (narrative). Valid values: No options provided in the form. Rule: Multiple entries allowed.
other_diagnosis_icd_code	string (1000)	No	ICD-10 codes of the other diagnoses. Standard: ICD-10. Valid values: External library: ICD-10 (Konsulta ICD-10 Library; not in the Library Reference Document); multiple entries allowed.
specific_diagnosis	string (1000)	No	Specific diagnoses that open a follow-up form or program. Valid values: Library Reference – Specific Diagnosis; multiple selection allowed (codes separated by a semicolon). Rule: Select all that apply.
management · Object			
counseling_health_education	string (1000)	Yes	Counseling and health education given. Valid values: Library Reference – Counseling Health Education; multiple selection allowed (codes separated by a semicolon). Rule: Select at least one.
routine_vaccine_name	string (150)	Conditional	Name of the routine vaccine given. Rule: Required if counseling_health_education includes 16 (Routine Vaccination Counselling/Education).
routine_vaccine_date	string (MM/DD/YYYY)	No	Date the routine vaccine was given. Format: MM/DD/YYYY.
adults_routine_screening	string (1000)	Yes	Routine screening plan for adults. Valid values: Library Reference – Diagnostic Examination; multiple selection allowed (codes separated by a comma). Rule: Select at least one.

Parameter	Type	Required	Description
pediatric_routine_screening	string (1000)	Yes	Routine screening plan for pediatric patients. Valid values: Library Reference – Diagnostic Examination; multiple selection allowed (codes separated by a comma). Rule: Select at least one.
prenatal_screening_services	string (1000)	Yes	Prenatal screening services. Valid values: Library Reference – Diagnostic Examination; multiple selection allowed (codes separated by a comma). Rule: Select at least one.
cancer_screening_flag	string (1)	Yes	Indicates whether cancer screening tests are planned. Valid values: "Y" - Yes; "N" - No.
cancer_screening_selected	string (1000)	Conditional	Cancer screening tests selected. Valid values: Library Reference – Diagnostic Examination; multiple selection allowed (codes separated by a comma). Rule: Required if cancer_screening_flag = Y; select at least one.
diagnostic_services_flag	string (1)	Yes	Indicates whether diagnostic services are requested, and with or without results. Valid values: Library Reference – Diagnostic Services Option. Rule: Yes: proceed to the Diagnostic Request Form. Yes, with Diagnostic Results: proceed to the Diagnostic Results Form.
medication_prescription_flag	string (1)	Yes	Indicates whether medicines are prescribed. Valid values: "Y" - Yes; "N" - No. Rule: If Y, proceed to the Medication Prescription Form (Annex E).
referral_flag	string (1)	Yes	Indicates whether the patient is referred. Valid values: "Y" - Yes; "N" - No. Rule: If Y, proceed to the Referral Request Form (Annex F).
other_medical_advice_spec	string (250)	No	Other medical advice.
follow_up_flag	string (1)	Yes	Indicates whether a follow-up is scheduled. Valid values: "Y" - Yes; "N" - No. Rule: Available only after all other Plan and Management selections are made.
follow_up_on	string (100)	Conditional	Date of the follow-up. Rule: Required if follow_up_flag = Y.
follow_up_reason	string (250)	Conditional	Reason for the follow-up. Rule: Required if follow_up_flag = Y.
follow_up_vaccine_name	string (150)	No	Vaccine scheduled for the follow-up.
follow_up_next_vaccine_date	string (MM/DD/YYYY)	No	Date of the next scheduled vaccination. Format: MM/DD/YYYY.
sf_obgyne_menshist · Object			
menarche_flag	string (1)	Yes	Indicates whether the patient has had her first menstrual period. Valid values: "Y" - Yes; "N" - No. Rule: Applicable only if patient_sex = F.

Parameter	Type	Required	Description
menarche_period	number	Conditional	Age at first menstrual period (menarche), in years. Rule: Required if menarche_flag = Y. Applicable only if patient_sex = F.
last_mens_period_flag	string (1)	Yes	Indicates whether the last menstrual period applies. Valid values: "Y" - Yes; "N" - Not applicable. Rule: Applicable only if patient_sex = F.
last_mens_period	string (MM/DD/YYYY)	Conditional	Date of the last menstrual period. Format: MM/DD/YYYY. Rule: Required if last_mens_period_flag = Y. Applicable only if patient_sex = F.
is_menopause	string (1)	Yes	Indicates whether the patient has reached menopause. Valid values: "Y" - Yes; "N" - No. Rule: Applicable only if patient_sex = F.
menopause_age	number	Conditional	Age at menopause, in years. Rule: Required if is_menopause = Y. Applicable only if patient_sex = F.
contraceptive_use_status	string (2)	No	Contraceptive use status of the patient. Valid values: Library Reference – Contraceptive Use Status. Rule: Applicable only if patient_sex = F. Select one.
contraceptive_method_desired	string (500)	Conditional	Contraceptive methods the patient wants to start. Valid values: Library Reference – Contraceptive Method; multiple selection allowed (codes separated by a comma). Rule: Required if contraceptive_use_status = 03 (Without contraceptive use and wants to start).
birth_ctrl_method	string (21)	No	Contraceptive method in use. Valid values: Library Reference – Contraceptive Method.
gynecological_disease_flag	string (1)	Yes	Indicates whether the patient has a gynecological disease. Valid values: "Y" - Yes; "N" - None. Rule: Applicable only if patient_sex = F.
gynecological_disease	string (500)	Conditional	Gynecological disease of the patient. Rule: Required if gynecological_disease_flag = Y.
sf_obgyne_preghist · Object			
is_applicable	string (1)	Yes	Indicates whether the patient has ever been pregnant. Valid values: "Y" - Yes; "N" - No. Rule: Applicable only if patient_sex = F.
is_currently_pregnant	string (1)	Yes	Indicates whether the patient is currently pregnant. Valid values: "Y" - Yes; "N" - No. Rule: Applicable only if patient_sex = F.
prenatal_checkup_count	string (1)	Conditional	Number of prenatal check-ups in the current pregnancy. Valid values: Library Reference – Prenatal Check-up Count. Rule: Required if is_currently_pregnant = Y.
preg_cnt	number	Conditional	OB score: number of pregnancies (gravidity). Rule: Required if is_applicable = Y.
delivery_cnt	number	Conditional	OB score: number of deliveries (parity). Rule: Required if is_applicable = Y.

Parameter	Type	Required	Description
full_term_cnt	number	Conditional	OB score: number of full-term deliveries. Rule: Required if is_applicable = Y.
premature_cnt	number	Conditional	OB score: number of preterm deliveries. Rule: Required if is_applicable = Y.
abortion_cnt	number	Conditional	OB score: number of abortions. Rule: Required if is_applicable = Y.
liv_children_cnt	number	Conditional	OB score: number of living children. Rule: Required if is_applicable = Y.
age_of_gestation	string (20)	No	Age of gestation of the current pregnancy. Rule: System-computed from last_mens_period when is_currently_pregnant = Y.
expected_date_of_delivery	string (MM/DD/YYYY)	No	Expected date of delivery of the current pregnancy. Format: MM/DD/YYYY. Rule: System-computed from last_mens_period when is_currently_pregnant = Y.
sf_obgyne_pe · Object			
fundic_height	number (5,1)	No	Fundic height, in cm. Format: Unit: cm.. Rule: Applicable if is_currently_pregnant = Y.
fetal_heart_tone	number (3)	No	Fetal heart tone, in beats per minute. Format: Unit: bpm.. Rule: Applicable if is_currently_pregnant = Y.
estimated_fetal_weight	number (5)	No	Estimated fetal weight, in grams. Format: Unit: grams.. Rule: Applicable if is_currently_pregnant = Y.
leopold_l1	string (250)	No	Leopold's maneuver L1 findings. Rule: Applicable if is_currently_pregnant = Y.
leopold_l2	string (250)	No	Leopold's maneuver L2 findings. Rule: Applicable if is_currently_pregnant = Y.
leopold_l3	string (250)	No	Leopold's maneuver L3 findings. Rule: Applicable if is_currently_pregnant = Y.
leopold_l4	string (250)	No	Leopold's maneuver L4 findings. Rule: Applicable if is_currently_pregnant = Y.
perineal_inspection	string (500)	No	Perineal inspection findings. Rule: A value means the examination was done.
speculum_exam	string (500)	No	Speculum examination findings. Rule: A value means the examination was done.
internal_exam	string (500)	No	Internal examination findings. Rule: A value means the examination was done.
bimanual_exam	string (500)	No	Bimanual examination findings. Rule: A value means the examination was done.
rectovaginal_exam	string (500)	No	Rectovaginal examination findings. Rule: A value means the examination was done.
sf_pedia_immunization · Object			

Parameter	Type	Required	Description
routine_immunization_status	string (2)	Yes	Overall routine childhood immunization status (DOH-EPI). Valid values: Library Reference – Routine Immunization Status. Rule: Select one. Same parameter name is used in the Adolescent Specific Form; the data group (JSON path) tells them apart.
sf_pedia_vaccine · Array			
vaccine_code	string (10)	Yes	Vaccine given or recorded; one record per vaccine. Valid values: Library Reference – Vaccine. Rule: Repeating group (1..n). Select at least one. Same parameter name is used in the Adolescent Specific Form; the data group (JSON path) tells them apart.
vaccine_other_spec	string (250)	Conditional	Name of a vaccine not in the list. Rule: Required if vaccine_code = 99 (Others). Same parameter name is used in the Adolescent Specific Form; the data group (JSON path) tells them apart.
vaccination_status	string (2)	Yes	Vaccination status of the vaccine. Valid values: Library Reference – Vaccination Status. Rule: Repeating group (1..n). One value per vaccine record. Same parameter name is used in the Adolescent Specific Form; the data group (JSON path) tells them apart.
sf_pedia_devmilestone · Array			
milestone_visit_age	string (2)	Yes	Visit age row assessed for developmental milestones. Valid values: Library Reference – Milestone Visit Age. Rule: Repeating group (1..n). Applicable for ages 0 to 5 years. Select at least one. Fill earlier age rows as well (for example, a 15-month-old includes the 4 to 12 month rows).
milestone_at_par_flag	string (1)	Conditional	Indicates whether milestones are at par with age for the visit age row. Valid values: "Y" - Yes; "N" - No. Rule: Required if no danger sign is selected for the visit age row.
gross_motor_danger_signs	string (1000)	Conditional	Gross motor danger signs observed. Valid values: Library Reference – Developmental Danger Sign; multiple selection allowed (codes separated by a comma). Rule: Required if milestone_at_par_flag = N. Consider referral to a pediatric specialist if any danger sign is present. Check all that apply; only values for the selected milestone_visit_age are valid. Only codes with prefix GM are valid in this field.
fine_motor_danger_signs	string (1000)	Conditional	Fine motor danger signs observed. Valid values: Library Reference – Developmental Danger Sign; multiple selection allowed (codes separated by a comma). Rule: Required if milestone_at_par_flag = N. Consider referral to a pediatric specialist if any danger sign is present. Check all that apply; only values for the selected milestone_visit_age are valid. Only codes with prefix FM are valid in this field.

Parameter	Type	Required	Description
language_danger_signs	string (1000)	Conditional	Language danger signs observed. Valid values: Library Reference – Developmental Danger Sign; multiple selection allowed (codes separated by a comma). Rule: Required if milestone_at_par_flag = N. Consider referral to a pediatric specialist if any danger sign is present. Check all that apply; only values for the selected milestone_visit_age are valid. Only codes with prefix LG are valid in this field.
cognitive_danger_signs	string (1000)	Conditional	Cognitive danger signs observed. Valid values: Library Reference – Developmental Danger Sign; multiple selection allowed (codes separated by a comma). Rule: Required if milestone_at_par_flag = N. Consider referral to a pediatric specialist if any danger sign is present. Check all that apply; only values for the selected milestone_visit_age are valid. Only codes with prefix CG are valid in this field.
psychosocial_danger_signs	string (1000)	Conditional	Psychosocial danger signs observed. Valid values: Library Reference – Developmental Danger Sign; multiple selection allowed (codes separated by a comma). Rule: Required if milestone_at_par_flag = N. Consider referral to a pediatric specialist if any danger sign is present. Check all that apply; only values for the selected milestone_visit_age are valid. Only codes with prefix PS are valid in this field.
sf_adol_immunization · Object			
routine_immunization_status	string (2)	Yes	Overall routine childhood immunization status (DOH-EPI). Valid values: Library Reference – Routine Immunization Status. Rule: Select one. Same parameter name is used in the Pediatric Specific Form; the data group (JSON path) tells them apart.
sf_adol_vaccine · Array			
vaccine_code	string (10)	Yes	Vaccine given or recorded; one record per vaccine. Valid values: Library Reference – Vaccine. Rule: Repeating group (1..n). Select at least one. Same parameter name is used in the Pediatric Specific Form; the data group (JSON path) tells them apart.
vaccine_other_spec	string (250)	Conditional	Name of a vaccine not in the list. Rule: Required if vaccine_code = 99 (Others). Same parameter name is used in the Pediatric Specific Form; the data group (JSON path) tells them apart.
vaccination_status	string (2)	Yes	Vaccination status of the vaccine. Valid values: Library Reference – Vaccination Status. Rule: Repeating group (1..n). One value per vaccine record. Same parameter name is used in the Pediatric Specific Form; the data group (JSON path) tells them apart.
sf_adol_smr · Object			
smr_assessment_status	string (1)	No	Indicates whether the Sexual Maturity Rating was assessed. Valid values: "Y" - Assessed (with consent or assent); "N" - Not assessed. Rule: Assessment requires patient assent and consent.

Parameter	Type	Required	Description
smr_pubic_hair_stage	number (1)	Conditional	Tanner stage of pubic hair. Valid values: 1; 2; 3; 4; 5. Rule: Required if smr_assessment_status = Y (Assessed).
smr_breast_stage	number (1)	Conditional	Tanner stage of breast development (female). Valid values: 1; 2; 3; 4; 5. Rule: Required if smr_assessment_status = Y (Assessed) and patient_sex = F.
smr_genital_stage	number (1)	Conditional	Tanner stage of external genitalia (male). Valid values: 1; 2; 3; 4; 5. Rule: Required if smr_assessment_status = Y (Assessed) and patient_sex = M.
smr_assessment_result	string (2)	Conditional	Interpretation of pubertal development. Valid values: Library Reference – SMR Assessment Result. Rule: Required if smr_assessment_status = Y (Assessed).
sf_adol_rapidheadsss · Object			
rh_assent_consent_status	string (1)	Yes	Indicates that assent and consent were obtained before the Rapid HEADSSS interview. Valid values: "Y" - With assent and consent; "N" - Did not consent. Rule: For adolescent patients only (10 to 19 years old). API control field; the form gives this as an instruction, not a checkbox.
rh_education_employment_status	string (2)	Conditional	Rapid HEADSSS: school or work status (Katayuan). Valid values: Library Reference – HEADSSS Education Employment. Rule: Required if rh_assent_consent_status = Y (With assent and consent). Select one.
rh_relationship_status	string (2)	Conditional	Rapid HEADSSS: relationship status (Katayuan). Valid values: Library Reference – HEADSSS Relationship Status. Rule: Required if rh_assent_consent_status = Y (With assent and consent). Select one.
rh_living_arrangement	string (2)	Conditional	Rapid HEADSSS: living arrangement (Katayuan). Valid values: Library Reference – HEADSSS Living Arrangement. Rule: Required if rh_assent_consent_status = Y (With assent and consent). Select one.
rh_living_arrangement_other_spec	string (250)	Conditional	Other household members besides the parents. Rule: Required if rh_living_arrangement = 02 (Iba pang kasamahan sa bahay bukod sa magulang).
rh_q01_home_violence	string (1)	Conditional	Rapid HEADSSS Q1: experiences harm or threats at home. Valid values: "Y" - Yes (Oo); "N" - No (Hindi). Rule: Required if rh_assent_consent_status = Y (With assent and consent). Answer is confidential.
rh_q02_runaway_thoughts	string (1)	Conditional	Rapid HEADSSS Q2: has thought of running away from home. Valid values: "Y" - Yes (Oo); "N" - No (Hindi). Rule: Required if rh_assent_consent_status = Y (With assent and consent). Answer is confidential.

Parameter	Type	Required	Description
rh_q03_bullying	string (1)	Conditional	Rapid HEADSSS Q3: has experienced physical or cyber bullying at school or work. Valid values: "Y" - Yes (Oo); "N" - No (Hindi). Rule: Required if rh_assent_consent_status = Y (With assent and consent). Answer is confidential.
rh_q04_suicidal_ideation	string (1)	Conditional	Rapid HEADSSS Q4: has seriously thought of ending own life. Valid values: "Y" - Yes (Oo); "N" - No (Hindi). Rule: Required if rh_assent_consent_status = Y (With assent and consent). Answer is confidential.
rh_q05_smoking	string (1)	Conditional	Rapid HEADSSS Q5: smokes. Valid values: "Y" - Yes (Oo); "N" - No (Hindi). Rule: Required if rh_assent_consent_status = Y (With assent and consent). Answer is confidential.
rh_q06_alcohol	string (1)	Conditional	Rapid HEADSSS Q6: drinks alcohol. Valid values: "Y" - Yes (Oo); "N" - No (Hindi). Rule: Required if rh_assent_consent_status = Y (With assent and consent). Answer is confidential.
rh_q07_drug_exposure	string (1)	Conditional	Rapid HEADSSS Q7: has seen prohibited drugs. Valid values: "Y" - Yes (Oo); "N" - No (Hindi). Rule: Required if rh_assent_consent_status = Y (With assent and consent). Answer is confidential.
rh_q08_romantic_relationship	string (1)	Conditional	Rapid HEADSSS Q8: has had a romantic relationship. Valid values: "Y" - Yes (Oo); "N" - No (Hindi). Rule: Required if rh_assent_consent_status = Y (With assent and consent). Answer is confidential.
rh_q09_sexual_intercourse	string (1)	Conditional	Rapid HEADSSS Q9: has had sexual intercourse. Valid values: "Y" - Yes (Oo); "N" - No (Hindi). Rule: Required if rh_assent_consent_status = Y (With assent and consent). Answer is confidential.
rh_q10_forced_sex	string (1)	Conditional	Rapid HEADSSS Q10: has been forced to have sex. Valid values: "Y" - Yes (Oo); "N" - No (Hindi). Rule: Required if rh_assent_consent_status = Y (With assent and consent). Answer is confidential.
rh_q11_pregnancy	string (1)	Conditional	Rapid HEADSSS Q11: has been pregnant or gotten someone pregnant. Valid values: "Y" - Yes (Oo); "N" - No (Hindi). Rule: Required if rh_assent_consent_status = Y (With assent and consent). Answer is confidential.
rh_q12_counseling_request	string (1)	Conditional	Rapid HEADSSS Q12: wants counseling or consultation. Valid values: "Y" - Yes (Oo); "N" - No (Hindi). Rule: Required if rh_assent_consent_status = Y (With assent and consent). Answer is confidential.
rh_full_headsss_flag	string (1)	Conditional	Indicates whether to proceed to the Full HEADSSS questionnaire. Valid values: "Y" - Yes (proceed to the Full HEADSSS questionnaire); "N" - No. Rule: System sets to Y if any of rh_q01 to rh_q12 = Y (Oo).
sf_headsss · Object			

Parameter	Type	Required	Description
headsss_assent_consent_status	string (1)	Yes	Indicates that assent and consent were obtained before the Full HEADSSS interview. Valid values: "Y" - With assent and consent; "N" - Did not consent. Rule: For adolescent patients. Interview is done without the parent or guardian. API control field; the form gives this as an instruction, not a checkbox.
headsss_home_questions	string (500)	Conditional	Full HEADSSS Home: guide questions asked. Valid values: Library Reference – HEADSSS Guide Question; multiple selection allowed (codes separated by a comma). Rule: Required if headsss_assent_consent_status = Y (With assent and consent). Check all that apply.
headsss_home_answer	string (1000)	Conditional	Full HEADSSS Home: patient's answers, written by the provider. Rule: Required if headsss_assent_consent_status = Y (With assent and consent).
headsss_home_red_flags	string (1000)	Conditional	Full HEADSSS Home: red flags present. Valid values: Library Reference – HEADSSS Red Flag; multiple selection allowed (codes separated by a comma). Rule: Required if headsss_assent_consent_status = Y (With assent and consent). Select at least one. Check all that apply; None cannot be combined with other values.
headsss_education_questions	string (500)	Conditional	Full HEADSSS Education and Employment: guide questions asked. Valid values: Library Reference – HEADSSS Guide Question; multiple selection allowed (codes separated by a comma). Rule: Required if headsss_assent_consent_status = Y (With assent and consent). Check all that apply.
headsss_education_answer	string (1000)	Conditional	Full HEADSSS Education and Employment: patient's answers, written by the provider. Rule: Required if headsss_assent_consent_status = Y (With assent and consent).
headsss_education_red_flags	string (1000)	Conditional	Full HEADSSS Education and Employment: red flags present. Valid values: Library Reference – HEADSSS Red Flag; multiple selection allowed (codes separated by a comma). Rule: Required if headsss_assent_consent_status = Y (With assent and consent). Select at least one. Check all that apply; None cannot be combined with other values.
headsss_eating_questions	string (500)	Conditional	Full HEADSSS Eating: guide questions asked. Valid values: Library Reference – HEADSSS Guide Question; multiple selection allowed (codes separated by a comma). Rule: Required if headsss_assent_consent_status = Y (With assent and consent). Check all that apply.
headsss_eating_answer	string (1000)	Conditional	Full HEADSSS Eating: patient's answers, written by the provider. Rule: Required if headsss_assent_consent_status = Y (With assent and consent).

Parameter	Type	Required	Description
headsss_eating_red_flags	string (1000)	Conditional	Full HEADSSS Eating: red flags present. Valid values: Library Reference – HEADSSS Red Flag; multiple selection allowed (codes separated by a comma). Rule: Required if headsss_assent_consent_status = Y (With assent and consent). Select at least one. Check all that apply; None cannot be combined with other values.
headsss_activities_questions	string (500)	Conditional	Full HEADSSS Activities: guide questions asked. Valid values: Library Reference – HEADSSS Guide Question; multiple selection allowed (codes separated by a comma). Rule: Required if headsss_assent_consent_status = Y (With assent and consent). Check all that apply.
headsss_activities_answer	string (1000)	Conditional	Full HEADSSS Activities: patient's answers, written by the provider. Rule: Required if headsss_assent_consent_status = Y (With assent and consent).
headsss_activities_red_flags	string (1000)	Conditional	Full HEADSSS Activities: red flags present. Valid values: Library Reference – HEADSSS Red Flag; multiple selection allowed (codes separated by a comma). Rule: Required if headsss_assent_consent_status = Y (With assent and consent). Select at least one. Check all that apply; None cannot be combined with other values.
headsss_drugs_questions	string (500)	Conditional	Full HEADSSS Drugs, Smoking and Alcohol: guide questions asked. Valid values: Library Reference – HEADSSS Guide Question; multiple selection allowed (codes separated by a comma). Rule: Required if headsss_assent_consent_status = Y (With assent and consent). Check all that apply.
headsss_drugs_answer	string (1000)	Conditional	Full HEADSSS Drugs, Smoking and Alcohol: patient's answers, written by the provider. Rule: Required if headsss_assent_consent_status = Y (With assent and consent).
headsss_drugs_red_flags	string (1000)	Conditional	Full HEADSSS Drugs, Smoking and Alcohol: red flags present. Valid values: Library Reference – HEADSSS Red Flag; multiple selection allowed (codes separated by a comma). Rule: Required if headsss_assent_consent_status = Y (With assent and consent). Select at least one. Check all that apply; None cannot be combined with other values.
headsss_sexuality_questions	string (500)	Conditional	Full HEADSSS Sexuality: guide questions asked. Valid values: Library Reference – HEADSSS Guide Question; multiple selection allowed (codes separated by a comma). Rule: Required if headsss_assent_consent_status = Y (With assent and consent). Check all that apply.
headsss_sexuality_answer	string (1000)	Conditional	Full HEADSSS Sexuality: patient's answers, written by the provider. Rule: Required if headsss_assent_consent_status = Y (With assent and consent).

Parameter	Type	Required	Description
headsss_sexuality_red_flags	string (1000)	Conditional	Full HEADSSS Sexuality: red flags present. Valid values: Library Reference – HEADSSS Red Flag; multiple selection allowed (codes separated by a comma). Rule: Required if headsss_assent_consent_status = Y (With assent and consent). Select at least one. Check all that apply; None cannot be combined with other values.
headsss_suicide_depression_questions	string (500)	Conditional	Full HEADSSS Suicide and Depression: guide questions asked. Valid values: Library Reference – HEADSSS Guide Question; multiple selection allowed (codes separated by a comma). Rule: Required if headsss_assent_consent_status = Y (With assent and consent). Check all that apply.
headsss_suicide_depression_answer	string (1000)	Conditional	Full HEADSSS Suicide and Depression: patient's answers, written by the provider. Rule: Required if headsss_assent_consent_status = Y (With assent and consent).
headsss_suicide_depression_red_flags	string (1000)	Conditional	Full HEADSSS Suicide and Depression: red flags present. Valid values: Library Reference – HEADSSS Red Flag; multiple selection allowed (codes separated by a comma). Rule: Required if headsss_assent_consent_status = Y (With assent and consent). Select at least one. Check all that apply; None cannot be combined with other values.
headsss_urgent_referral_flag	string (1)	Conditional	Indicates an urgent referral for thoughts of self-harm or ending one's life. Valid values: "Y" - Yes; "N" - No. Rule: Required if 'Have you ever thought of hurting yourself or ending your life?' answer is Yes. If Y, proceed to the Urgent Referral Form.
headsss_safety_questions	string (500)	Conditional	Full HEADSSS Safety: guide questions asked. Valid values: Library Reference – HEADSSS Guide Question; multiple selection allowed (codes separated by a comma). Rule: Required if headsss_assent_consent_status = Y (With assent and consent). Check all that apply.
headsss_safety_answer	string (1000)	Conditional	Full HEADSSS Safety: patient's answers, written by the provider. Rule: Required if headsss_assent_consent_status = Y (With assent and consent).
headsss_safety_red_flags	string (1000)	Conditional	Full HEADSSS Safety: red flags present. Valid values: Library Reference – HEADSSS Red Flag; multiple selection allowed (codes separated by a comma). Rule: Required if headsss_assent_consent_status = Y (With assent and consent). Select at least one. Check all that apply; None cannot be combined with other values.
sf_bpmon · Object			
bpmon_start_date	string (MM/DD/YYYY)	Yes	Start date of the one-week BP monitoring. Format: MM/DD/YYYY.
bpmon_end_date	string (MM/DD/YYYY)	Yes	End date of the one-week BP monitoring. Format: MM/DD/YYYY. Rule: Must be on or after bpmon_start_date; maximum 7 days.
sf_bpmon_day · Array			

Parameter	Type	Required	Description
bpmon_day_no	number (1)	Yes	BP monitoring day number (1 to 7). Valid values: 1; 2; 3; 4; 5; 6; 7. Rule: Repeating group (1..7). Unique per record.
bpmon_location	string (2)	Yes	Where the BP was measured (clinic or home). Valid values: Library Reference – BP Measurement Location.
bpmon_after_medication	string (1)	Yes	Indicates whether the BP was measured after medication. Valid values: "Y" - Yes; "N" - No.
bpmon_am_systolic	number (3)	Conditional	Morning systolic blood pressure, in mmHg. Format: Unit: mmHg.. Rule: At least one of the AM or PM readings is required per day.
bpmon_am_diastolic	number (3)	Conditional	Morning diastolic blood pressure, in mmHg. Format: Unit: mmHg.. Rule: At least one of the AM or PM readings is required per day.
bpmon_pm_systolic	number (3)	Conditional	Evening systolic blood pressure, in mmHg. Format: Unit: mmHg.. Rule: At least one of the AM or PM readings is required per day.
bpmon_pm_diastolic	number (3)	Conditional	Evening diastolic blood pressure, in mmHg. Format: Unit: mmHg.. Rule: At least one of the AM or PM readings is required per day.

Response (after decryption)


```
{
  "status": "success",
  "code": 202,
  "message": "Submission accepted for processing",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
    "upload_transaction_no": "UH123456782026102500002",
    "form": "consultation",
    "processing_status": "queued",
    "case_no": "TH123456782026102300001",
    "soap_transaction_no": "SH123456782026102300001"
  }
}
```


Field	Type	Returned	Description
data.upload_transaction_no	string (23)	Always	Number of this submission, generated by the service. Use it to check the outcome (Section 4.6.7). Format: U + accre_no + YYYY + MM + DD + 5-digit daily series number (23 characters).
data.form	string	Always	The form submitted: consultation.

Field	Type	Returned	Description
data.processing_status	string	Always	queued – the submission passed the checks made on receipt and is waiting to be processed.
data.case_no	string	Always	Echoes case_no – the patient record.
data.soap_transaction_no	string	Always	Echoes soap_transaction_no – the consultation.

Status values

processing_status = queued in the upload response; the final status (accepted or rejected) is read from Upload Status (4.6.7). Resending the consultation (soap_transaction_no) with identical content returns HTTP 200 with the original upload_transaction_no.

Validation rules

Rule	Validation
Encryption and consent	The body is the encrypted envelope (Section 3.8). consent: true is sent at the top level of the body, beside the data groups.
Field names and nesting	Send each field inside its data group, using the names and JSON paths in the field table. A data group that does not apply is left out as a whole.
Values	Yes fields carry a valid value. Within each group sent, every string field is present: "" when it has no value. Number fields with no value are left out. null is never accepted (Section 3.3).
Types and sizes	Send each value with the JSON type shown. String sizes are maximums in bytes (UTF-8; ñ counts as two bytes). Numbers carry no unit; the unit is in the field description, except Diagnostic Results values that the form reports in two units, which have one field per unit (4.6.4). Codes and record numbers are strings, so leading zeros are kept.
Dates and times	MM/DD/YYYY, MM/YYYY, YYYY and HH:MM (24-hour), as stated per field (Section 3.7).
Coded values	Codes must be active codes (LIBRARY STATUS 1) of the named Library Reference worksheet. Yes or No fields use "Y" and "N". Where several codes are allowed, separate them with a comma and no spaces, within the field size.
Record numbers	case_no is that of the patient's FPE record (4.6.1). soap_transaction_no (S) follows Section 3.9 and is unique per consultation.
Patient verification	As in 4.6.1, using consultation_date for the VALID_ID image rule.
Dependent patients	The guardian group is required when patient_type = DD and left out when patient_type = MM.
Age-dependent measures	systolic and diastolic from 4 years old; height from 2 years old; length from 0 to 24 months, on consultation_date.
Sexual history	sti_hist and sti_spec appear in two Annex B sections; send them once, in sexhist.
Review of systems	Each ROS field needs at least one Signs and Symptoms code (00 = None); when X (Others) is used, send ros_other_spec.
Specific Forms	sf_ groups are sent only for the forms accomplished; their Yes fields are required only when the group is sent. sf_obgyne_ groups are for female patients only. rh_full_headsss_flag is Y when any rh_q01 to rh_q12 answer is Y.
Plan and management	diagnostic_services_flag, medication_prescription_flag and referral_flag announce the Diagnostic Request and Results (4.6.3, 4.6.4), Medicine (4.6.5) and Referral (4.6.6) uploads that follow.
Allergies and computed values	As in 4.6.1 (age from the PhilHealth date of birth and consultation_date).

Errors

The errors common to the six upload endpoints apply (Section 4.6). Problems found after queueing are reported through Upload Status.

Sample error response

```
{
  "status": "error",
  "code": 400,
  "message": "Invalid request payload",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "errors": [
    {
      "field": "soap.soap_transaction_no",
      "issue": "validation_error"
    }
  ]
}
```

4.6.3 Diagnostic Request Upload

Purpose

Submits the laboratory and imaging tests requested during a consultation, one diagrequest entry per test. Fields follow Data Dictionary Annex C (Rev. 7, 10/25/2026).

Item	Value
Endpoint	POST /api/v1/yakap-data-upload/diagnostic-request
Authentication	Bearer token (Section 3.2); the facility is the accre_no in the token
Encryption	Request body and response data encrypted (Section 3.8, Annex C); errors in plain JSON
Success	HTTP 202 Accepted (200 on an identical resend)

Business rules and preconditions

- Record numbers: request_transaction_no (D) follows Section 3.9 and is unique per request. case_no and soap_transaction_no are those of the consultation. The three numbers carry the same values in every diagrequest entry.
- Requested tests: diagnostic_code takes one Diagnostic Examination code; each code at most once per request. Code 99 (Others) requires not_listed_specify.
- Recommendation and consent: doctor_recommendation and client_consent take a Recommendation Consent code, one value per test.
- Checked after queueing and reported through Upload Status: case_no and soap_transaction_no match an accepted consultation; request_transaction_no is not already used.

Request (before encryption)

```
{
  "consent": true,
  "diagrequest": [
    {
      "case_no": "TH123456782026102300001",
      "soap_transaction_no": "SH123456782026102300001",
      "request_transaction_no": "DH123456782026102300001",
      "diagnostic_code": "1",
      "doctor_recommendation": "Y",
      "client_consent": "Y",
      "not_listed_specify": ""
    },
    {
      "case_no": "TH123456782026102300001",
      "soap_transaction_no": "SH123456782026102300001",
      "request_transaction_no": "DH123456782026102300001",
      "diagnostic_code": "7",
      "doctor_recommendation": "Y",
      "client_consent": "Y",
      "not_listed_specify": ""
    },
    {
      "case_no": "TH123456782026102300001",
      "soap_transaction_no": "SH123456782026102300001",
      "request_transaction_no": "DH123456782026102300001",
      "diagnostic_code": "4",
      "doctor_recommendation": "Y",
      "client_consent": "Y",
      "not_listed_specify": ""
    }
  ]
}
```

Payload structure

Data group	Structure	Content and applicability	Fields
diagrequest	Array	One entry per requested test: the record numbers, the test code, the doctor's recommendation and the client's consent. At least one entry.	7

Request fields

Parameter	Type	Required	Description
diagrequest · Array			
case_no	string (23)	Yes	Patient case number that links the request to the patient, FPE and consultation records. Format: T+ACCRE_NO+YYYY+MM+DD+99999. Rule: Repeated with the same value in every DIAGREQUEST row of one submission (one row per requested test).

Parameter	Type	Required	Description
soap_transaction_no	string (23)	Yes	Transaction number of the consultation that ordered the request. Format: S+ACCRE_NO+YYYY+MM+DD+99999. Rule: Repeated with the same value in every DIAGREQUEST row of one submission (one row per requested test).
request_transaction_no	string (23)	Yes	Transaction number of the diagnostic request. Format: D+ACCRE_NO+YYYY+MM+DD+99999. Rule: Repeated with the same value in every DIAGREQUEST row of one submission (one row per requested test).
diagnostic_code	string (2)	Yes	Requested laboratory or imaging test; one row per test. Valid values: Library Reference – Diagnostic Examination. Rule: One DIAGREQUEST row per requested test. Key: request_transaction_no + diagnostic_code (unique within a request). Pairs with the Annex D DIAGRESULT_ITEM row of the same code. Laboratory or imaging comes from the library REQUEST CATEGORY. DIAGNOSTIC.pDiagnosticId (consultation-level).
doctor_recommendation	string (1)	Yes	Doctor's recommendation for the requested test. Valid values: Library Reference – Recommendation Consent. Rule: One value per DIAGREQUEST row. DIAGNOSTIC.pIsPhysicianRecommendation (consultation-level).
client_consent	string (1)	Yes	Client consent for the requested test. Valid values: Library Reference – Recommendation Consent. Rule: One value per DIAGREQUEST row. ENLISTMENT.pWithConsent (general consent).
not_listed_specify	string (250)	Conditional	Name of a test not on the listed services. Rule: Required when diagnostic_code = 99 (Others); blank otherwise.

Response (after decryption)


```
{
  "status": "success",
  "code": 202,
  "message": "Submission accepted for processing",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
    "upload_transaction_no": "UH123456782026102500003",
    "form": "diagnostic_request",
    "processing_status": "queued",
    "case_no": "TH12345678202610230000 1",
    "soap_transaction_no": "SH123456782026102300001",
    "request_transaction_no": "DH12345678202610230000 1"
  }
}
```

Field	Type	Returned	Description
data.upload_transaction_no	string (23)	Always	Number of this submission, generated by the service. Use it to check the outcome (Section 4.6.7). Format: U + accre_no + YYYY + MM + DD + 5-digit daily series number (23 characters).
data.form	string	Always	The form submitted: diagnostic_request.
data.processing_status	string	Always	queued – the submission passed the checks made on receipt and is waiting to be processed.
data.case_no	string	Always	Echoes case_no – the patient record.
data.soap_transaction_no	string	Always	Echoes soap_transaction_no – the consultation.
data.request_transaction_no	string	Always	Echoes request_transaction_no – the Diagnostic Request.

Status values

processing_status = queued in the upload response; the final status (accepted or rejected) is read from Upload Status (4.6.7). Resending the Diagnostic Request (request_transaction_no) with identical content returns HTTP 200 with the original upload_transaction_no.

Validation rules

Rule	Validation
Encryption and consent	The body is the encrypted envelope (Section 3.8). consent: true is sent at the top level of the body, beside the data groups.
Field names and nesting	Send each field inside its data group, using the names and JSON paths in the field table. A data group that does not apply is left out as a whole.
Values	Yes fields carry a valid value. Within each group sent, every string field is present: "" when it has no value. Number fields with no value are left out. null is never accepted (Section 3.3).
Types and sizes	Send each value with the JSON type shown. String sizes are maximums in bytes (UTF-8; ñ counts as two bytes). Numbers carry no unit; the unit is in the field description, except Diagnostic Results values that the form reports in two units, which have one field per unit (4.6.4). Codes and record numbers are strings, so leading zeros are kept.
Dates and times	MM/DD/YYYY, MM/YYYY, YYYY and HH:MM (24-hour), as stated per field (Section 3.7).
Coded values	Codes must be active codes (LIBRARY STATUS 1) of the named Library Reference worksheet. Yes or No fields use "Y" and "N". Where several codes are allowed, separate them with a comma and no spaces, within the field size.
Record numbers	request_transaction_no (D) follows Section 3.9 and is unique per request. case_no and soap_transaction_no are those of the consultation. The three numbers carry the same values in every diagrequest entry.
Requested tests	diagnostic_code takes one Diagnostic Examination code; each code at most once per request. Code 99 (Others) requires not_listed_specify.
Recommendation and consent	doctor_recommendation and client_consent take a Recommendation Consent code, one value per test.

Errors

The errors common to the six upload endpoints apply (Section 4.6). Problems found after queueing are reported through Upload Status.

Sample error response

```
{
  "status": "error",
  "code": 400,
  "message": "Invalid request payload",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "errors": [
    {
      "field": "diagrequest[0].diagnostic_code",
      "issue": "validation_error"
    }
  ]
}
```

4.6.4 Diagnostic Results Upload

Purpose

Submits the results of the tests in a Diagnostic Request, one diagresult_item entry per test. Fields follow Data Dictionary Annex D (Rev. 8, 10/26/2026).

Item	Value
Endpoint	POST /api/v1/yakap-data-upload/diagnostic-results
Authentication	Bearer token (Section 3.2); the facility is the accre_no in the token
Encryption	Request body and response data encrypted (Section 3.8, Annex C); errors in plain JSON
Success	HTTP 202 Accepted (200 on an identical resend)

Business rules and preconditions

- Record numbers: case_no, soap_transaction_no and request_transaction_no are those of the Diagnostic Request (4.6.3). Each diagresult_item carries its own result_transaction_no (L, Section 3.9), generated by the EMR and unique per result.
- Result entries: One diagresult_item per requested test. diagnostic_code must be a code sent in that request; request_transaction_no + diagnostic_code links the result to the requested test. test_status is required for every entry.
- Result groups: When test_status = 01 (Done), nest the test's result group (table below) and send test_exam_date and test_lab_loc. Code 28 has no result group: send status and test_remarks only. Code 99 uses otherdiagexam.
- Checked after queueing and reported through Upload Status: request_transaction_no matches an accepted Diagnostic Request for the same case_no and soap_transaction_no,

every diagnostic_code was requested in it, and each result_transaction_no is new or a resend of the same result.

Request (before encryption)


```
{
  "consent": true,
  "diagnosticresult": {
    "case_no": "TH123456782026102300001",
    "soap_transaction_no": "SH123456782026102300001",
    "request_transaction_no": "DH123456782026102300001"
  },
  "diagresult_item": [
    {
      "result_transaction_no": "LH1234567820261024000001",
      "diagnostic_code": "1",
      "test_status": "01",
      "test_lab_loc": "01",
      "test_exam_date": "10/22/2026",
      "test_remarks": "",
      "cbc": {
        "cbc_hemoglobin_g_dl": 13.5,
        "cbc_hematocrit": 40.2,
        "cbc_mch_pg": 29.1,
        "cbc_mchc_g_dl": 33.4,
        "cbc_mcv_fl": 88,
        "cbc_platelet_count": 250,
        "cbc_wbc_x10_9_l": 7.2,
        "cbc_rbc_x10_12_l": 4.6,
        "cbc_diff_granulocytes": 60,
        "cbc_diff_neutrophils_band": 2,
        "cbc_diff_neutrophils_seg": 58,
        "cbc_diff_lymphocytes": 30,
        "cbc_diff_monocytes": 6,
        "cbc_diff_eosinophils": 3,
        "cbc_diff_basophils": 1
      }
    },
    {
      "result_transaction_no": "LH1234567820261024000002",
      "diagnostic_code": "7",
      "test_status": "01",
      "test_lab_loc": "01",
      "test_exam_date": "10/22/2026",
      "test_remarks": "",
      "fbs": {
        "fbs_results_mg_dl": 95,
        "fbs_interp": "Normal"
      }
    },
    {
      "result_transaction_no": "LH1234567820261024000003",
      "diagnostic_code": "4",
      "test_status": "01",
      "test_lab_loc": "01",
      "test_exam_date": "10/22/2026",
      "test_remarks": "",
```

```
      "chestxray": {
        "chest_xray_impression": "No active lung lesions"
      }
    }
  ],
  "physiciansignoff": {
    "physician_name": "MARIA L. SANTOS, MD",
    "physician_designation": "Attending Physician",
    "physician_license_no": "0123456",
    "physician_accre_no": "1234-5678901-2"
  }
}
```

The sample shows some result groups; send the group named for each test (table below).

Payload structure

Data group	Structure	Content and applicability	Fields
diagnosticresult	Object	Results header: links the results to the patient record, the consultation and the Diagnostic Request. Always required.	3
diagresult_item	Array	One entry per requested test: result_transaction_no, diagnostic_code, status, location, date and remarks, with the test's result group nested when done.	6
cbc	Object, nested in a diagresult_item entry (code 1)	CBC with platelet count only. Sent when the test was done; results reported in two units have one field per unit.	20
pregtest	Object, nested in a diagresult_item entry (code 30)	Urine HCG Pregnancy Test. Sent when the test was done.	1
urinalysis	Object, nested in a diagresult_item entry (code 2)	Urinalysis. Sent when the test was done.	18
uacr	Object, nested in a diagresult_item entry (code 42)	Urinary Albumin and Urinary Creatinine. Sent when the test was done.	4
hbsag	Object, nested in a diagresult_item entry (code 25)	Hepatitis B Surface Antigen (HBsAg) Test. Sent when the test was done.	1
hivrdt	Object, nested in a diagresult_item entry (code 24)	HIV Rapid Diagnostic Test. Sent when the test was done.	1
rpr	Object, nested in a diagresult_item entry (code 43)	Rapid Plasma Reagin (RPR). Sent when the test was done.	1
vdrl	Object, nested in a diagresult_item entry (code 44)	VDRL (Venereal Disease Research Laboratory). Sent when the test was done.	1
malariasmear	Object, nested in a diagresult_item entry (code 45)	Blood Smear Microscopy for Malaria. Sent when the test was done.	1

Data group	Structure	Content and applicability	Fields
filariasissmear	Object, nested in a diagresult_item entry (code 46)	Blood Smear Microscopy for Filariasis. Sent when the test was done.	2
fbs	Object, nested in a diagresult_item entry (code 7)	Fasting Blood Sugar (FBS). Sent when the test was done; results reported in two units have one field per unit.	3
hba1c	Object, nested in a diagresult_item entry (code 18)	HbA1C. Sent when the test was done.	2
ogtt	Object, nested in a diagresult_item entry (code 14)	Oral Glucose Tolerance Test (OGTT). Sent when the test was done; results reported in two units have one field per unit.	7
fecalysis	Object, nested in a diagresult_item entry (code 3)	Fecalysis. Sent when the test was done.	8
fecalysiskk	Object, nested in a diagresult_item entry (code 47)	Fecalysis using Kato-Katz Technique. Sent when the test was done.	3
fobt	Object, nested in a diagresult_item entry (code 15)	Fecal Occult Blood Test (FOBT). Sent when the test was done.	1
lipidprofile	Object, nested in a diagresult_item entry (code 6)	Lipid Profile. Sent when the test was done; results reported in two units have one field per unit.	10
afp	Object, nested in a diagresult_item entry (code 39)	Alpha Fetoprotein (AFP). Sent when the test was done.	1
alt	Object, nested in a diagresult_item entry (code 48)	Alanine Aminotransferase (ALT)/SGPT. Sent when the test was done.	1
ast	Object, nested in a diagresult_item entry (code 49)	Aspartate Aminotransferase (AST)/SGOT. Sent when the test was done.	1
creatinine	Object, nested in a diagresult_item entry (code 8)	Serum Creatinine. Sent when the test was done; results reported in two units have one field per unit.	2
papsmear	Object, nested in a diagresult_item entry (code 13)	Pap Smear Cytology (Cervical). Sent when the test was done.	1
via	Object, nested in a diagresult_item entry (code 31)	Visual Inspection with Acetic Acid (VIA). Sent when the test was done.	3
sputum	Object, nested in a diagresult_item entry (code 5)	Sputum Smear Microscopy. Sent when the test was done.	2
alp	Object, nested in a diagresult_item entry (code 53)	Alkaline Phosphatase (ALP). Sent when the test was done; results reported in two units have one field per unit.	2

Data group	Structure	Content and applicability	Fields
serumalbumin	Object, nested in a diagresult_item entry (code 54)	Serum Albumin. Sent when the test was done; results reported in two units have one field per unit.	2
electrolytes	Object, nested in a diagresult_item entry (code 55)	Serum Electrolytes (Sodium, Potassium, Chloride, Calcium, Phosphorus). Sent when the test was done; results reported in two units have one field per unit.	10
chestxray	Object, nested in a diagresult_item entry (code 4)	Chest X-Ray. Sent when the test was done.	1
chestct	Object, nested in a diagresult_item entry (code 50)	Low Dose Chest CT Scan. Sent when the test was done.	1
ecg	Object, nested in a diagresult_item entry (code 9)	12-Lead ECG. Sent when the test was done.	7
colonoscopy	Object, nested in a diagresult_item entry (code 35)	Colonoscopy. Sent when the test was done.	2
spirometry	Object, nested in a diagresult_item entry (code 52)	Spirometry. Sent when the test was done.	2
otherdiagexam	Object, nested in a diagresult_item entry (code 99)	Others. Sent when the test was done.	2
physiciansignoff	Object	Physician who signed off the results. Always required.	4

Test codes and result groups

Code	Test	Result group
1	CBC with platelet count only	cbc
2	Urinalysis	urinalysis
3	Fecalysis	fecalysis
4	Chest X-Ray	chestxray
5	Sputum Smear Microscopy	sputum
6	Lipid Profile	lipidprofile
7	Fasting Blood Sugar (FBS)	fbs
8	Serum Creatinine	creatinine
9	12-Lead ECG	ecg
13	Pap Smear Cytology (Cervical)	papsmear
14	Oral Glucose Tolerance Test (OGTT)	ogtt
15	Fecal Occult Blood Test (FOBT)	fobt
18	HbA1C	hba1c

Code	Test	Result group
24	HIV Rapid Diagnostic Test	hivrdt
25	Hepatitis B Surface Antigen (HBsAg) Test	hbsag
28	Rapid Blood Test using Filariasis Test Strip	-
30	Urine HCG Pregnancy Test	pregtest
31	Visual Inspection with Acetic Acid (VIA)	via
35	Colonoscopy	colonoscopy
39	Alpha Fetoprotein (AFP)	afp
42	Urinary Albumin and Urinary Creatinine	uacr
43	Rapid Plasma Reagin (RPR)	rpr
44	VDRL (Venereal Disease Research Laboratory)	vdrl
45	Blood Smear Microscopy for Malaria	malariasmear
46	Blood Smear Microscopy for Filariasis	filariasissmear
47	Fecalysis using Kato-Katz Technique	fecalysiskk
48	Alanine Aminotransferase (ALT)/SGPT	alt
49	Aspartate Aminotransferase (AST)/SGOT	ast
50	Low Dose Chest CT Scan	chestct
52	Spirometry	spirometry
53	Alkaline Phosphatase (ALP)	alp
54	Serum Albumin	serumalbumin
55	Serum Electrolytes (Sodium, Potassium, Chloride, Calcium, Phosphorus)	electrolytes
99	Others	otherdiagexam

Request fields

Parameter	Type	Required	Description
diagnosticresult · Object			
case_no	string (23)	Yes	Patient case number that links the results to the patient, FPE and consultation records. Format: T+ACCRE_NO+YYYY+MM+DD+99999.
soap_transaction_no	string (23)	Yes	Transaction number of the consultation that ordered the tests. Format: S+ACCRE_NO+YYYY+MM+DD+99999.
request_transaction_no	string (23)	Yes	Transaction number of the diagnostic request; links each result to its request. Format: D+ACCRE_NO+YYYY+MM+DD+99999.
diagresult_item · Array			

Parameter	Type	Required	Description
result_transaction_no	string (23)	Yes	Transaction number of this result entry, generated by the EMR. Identifies the result; request_transaction_no + diagnostic_code still link it to the requested test. Format: L+ACCRE_NO+YYYY+MM+DD+99999. Rule: One per diagresult_item entry; unique per result. Resend key of the Diagnostic Results upload: the same number with identical content returns the original upload_transaction_no; different content returns 409 transaction_already_exists.
diagnostic_code	string (2)	Yes	Test this result answers; one row per requested test. Valid values: Library Reference – Diagnostic Examination. Rule: Repeating group. Key: request_transaction_no + diagnostic_code; must match the diagnostic_code of an Annex C DIAGREQUEST row of the same request_transaction_no. Test values follow in the test data group named in the REFERENCE column and in the library ANNEX D DATA GROUP.
test_status	string (2)	Yes	Status of the requested test. Valid values: Library Reference – Diagnostic Test Status. Rule: Required for every requested test.
test_lab_loc	string (2)	Conditional	Where the test was done. Valid values: Library Reference – Diagnostic Test Location. Rule: Required if test_status = 01 (Done).
test_exam_date	string (MM/DD/YYYY)	Conditional	Date the test was done. Format: MM/DD/YYYY. Rule: Required if test_status = 01 (Done).
test_remarks	string (250)	No	Remarks on the test result.
cbc · Object, nested in diagresult_item[]			
cbc_hemoglobin_g_dl	number	No	CBC: hemoglobin, in g/dL. Format: Unit: g/dL.. Rule: Value in g/dL. Send the field for the unit the laboratory reported; send at most one of cbc_hemoglobin_g_dl and cbc_hemoglobin_g_l. Up to 2 decimal places.
cbc_hemoglobin_g_l	number	No	CBC: hemoglobin, in g/L. Format: Unit: g/L.. Rule: Value in g/L. Send the field for the unit the laboratory reported; send at most one of cbc_hemoglobin_g_dl and cbc_hemoglobin_g_l. Up to 2 decimal places.
cbc_hematocrit	number	No	CBC: hematocrit, in %. Format: Unit: %.. Rule: Up to 2 decimal places.
cbc_mch_pg	number	No	CBC: mean corpuscular hemoglobin (MCH), in pg. Format: Unit: pg.. Rule: The form reports MCH in pg only. Up to 2 decimal places.
cbc_mchc_g_dl	number	No	CBC: mean corpuscular hemoglobin concentration (MCHC), in g/dL. Format: Unit: g/dL.. Rule: Value in g/dL. Send the field for the unit the laboratory reported; send at most one of cbc_mchc_g_dl and cbc_mchc_g_l. Up to 2 decimal places.

Parameter	Type	Required	Description
cbc_mchc_g_l	number	No	CBC: mean corpuscular hemoglobin concentration (MCHC), in g/L. Format: Unit: g/L.. Rule: Value in g/L. Send the field for the unit the laboratory reported; send at most one of cbc_mchc_g_dl and cbc_mchc_g_l. Up to 2 decimal places.
cbc_mcv_fl	number	No	CBC: mean corpuscular volume (MCV), in fL. Format: Unit: fL.. Rule: Value in fL. Send the field for the unit the laboratory reported; send at most one of cbc_mcv_fl and cbc_mcv_um3. Up to 2 decimal places.
cbc_mcv_um3	number	No	CBC: mean corpuscular volume (MCV), in µm³. Format: Unit: µm³.. Rule: Value in µm³. Send the field for the unit the laboratory reported; send at most one of cbc_mcv_fl and cbc_mcv_um3. Up to 2 decimal places.
cbc_platelet_count	number	No	CBC: platelet count. Format: Unit: x10⁹/L.. Rule: Up to 2 decimal places.
cbc_wbc_x10_9_l	number	No	CBC: white blood cell (WBC) count, in x10⁹/L. Format: Unit: x10⁹/L.. Rule: Value in x10⁹/L. Send the field for the unit the laboratory reported; send at most one of cbc_wbc_x10_9_l and cbc_wbc_cells_ul. Up to 2 decimal places.
cbc_wbc_cells_ul	number	No	CBC: white blood cell (WBC) count, in cells/µL. Format: Unit: cells/µL.. Rule: Value in cells/µL. Send the field for the unit the laboratory reported; send at most one of cbc_wbc_x10_9_l and cbc_wbc_cells_ul. Up to 2 decimal places.
cbc_rbc_x10_12_l	number	No	CBC: red blood cell (RBC) count, in x10¹²/L. Format: Unit: x10¹²/L.. Rule: Value in x10¹²/L. Send the field for the unit the laboratory reported; send at most one of cbc_rbc_x10_12_l and cbc_rbc_x10_6_ul. x10¹²/L and x10⁶/µL are numerically equal for this analyte. Up to 2 decimal places.
cbc_rbc_x10_6_ul	number	No	CBC: red blood cell (RBC) count, in x10⁶/µL. Format: Unit: x10⁶/µL.. Rule: Value in x10⁶/µL. Send the field for the unit the laboratory reported; send at most one of cbc_rbc_x10_12_l and cbc_rbc_x10_6_ul. x10¹²/L and x10⁶/µL are numerically equal for this analyte. Up to 2 decimal places.
cbc_diff_granulocytes	number	No	CBC differential: granulocytes, in %. Format: Unit: %.. Rule: No granulocytes param; differential is myelocyte/neutrophils/lymph/mono/eos/baso. Up to 2 decimal places. Value from 0 to 100.
cbc_diff_neutrophils_band	number	No	CBC differential: band neutrophils, in %. Format: Unit: %.. Rule: Up to 2 decimal places. Value from 0 to 100.
cbc_diff_neutrophils_seg	number	No	CBC differential: segmented neutrophils, in %. Format: Unit: %.. Rule: Up to 2 decimal places. Value from 0 to 100.

Parameter	Type	Required	Description
cbc_diff_lymphocytes	number	No	CBC differential: lymphocytes, in %. Format: Unit: %.. Rule: Up to 2 decimal places. Value from 0 to 100.
cbc_diff_monocytes	number	No	CBC differential: monocytes, in %. Format: Unit: %.. Rule: Up to 2 decimal places. Value from 0 to 100.
cbc_diff_eosinophils	number	No	CBC differential: eosinophils, in %. Format: Unit: %.. Rule: Up to 2 decimal places. Value from 0 to 100.
cbc_diff_basophils	number	No	CBC differential: basophils, in %. Format: Unit: %.. Rule: Up to 2 decimal places. Value from 0 to 100.
pregtest · Object, nested in diagresult_item[]			
urine_hcg_results	string (2)	No	Urine HCG pregnancy test result. Valid values: Library Reference – Qualitative Test Result. Rule: Choose one.
urinalysis · Object, nested in diagresult_item[]			
urinalysis_color	string (100)	No	Urinalysis: color. Rule: Letters only.
urinalysis_appearance	string (100)	No	Urinalysis: appearance. Rule: Letters only.
urinalysis_specific_gravity	number	No	Urinalysis: specific gravity. Rule: Up to 3 decimal places.
urinalysis_ph	number	No	Urinalysis: pH. Rule: Up to 1 decimal place.
urinalysis_protein_albumin	string (100)	No	Urinalysis: protein (albumin). Rule: This parameter carries protein and albumin as one result. Letters, numbers, + and – only.
urinalysis_glucose	string (100)	No	Urinalysis: glucose. Rule: Letters, numbers, + and – only.
urinalysis_bilirubin	string (100)	No	Urinalysis, chemical: bilirubin. Rule: Letters, numbers, + and – only.
urinalysis_blood	string (100)	No	Urinalysis, chemical: blood. Rule: cf. URINALYSIS.pRbCells (RBC count, differs from dipstick blood). Letters, numbers, + and – only.
urinalysis_leukocytes	string (100)	No	Urinalysis, chemical: leukocytes. Rule: cf. URINALYSIS.pWbCells (microscopic WBC count, differs from dipstick leukocyte esterase). Letters, numbers, + and – only.
urinalysis_nitrite	string (100)	No	Urinalysis, chemical: nitrite. Rule: Letters, numbers, + and – only.
urinalysis_urobilinogen	string (100)	No	Urinalysis, chemical: urobilinogen. Rule: Letters, numbers, + and – only.
urinalysis_ketones	string (100)	No	Urinalysis, chemical: ketones. Rule: Letters, numbers, + and – only.

Parameter	Type	Required	Description
urinalysis_epithelial_cells	string (100)	No	Urinalysis, microscopic: epithelial cells. Rule: cf. URINALYSIS.pSquamousCell / pTubularCell / pBladderCell. Numbers, letters or hyphen only (for example 0-2).
urinalysis_mucus_threads	string (100)	No	Urinalysis, microscopic: mucus threads. Rule: Numbers, letters or hyphen only (for example 0-2).
urinalysis_bacteria	string (100)	No	Urinalysis, microscopic: bacteria. Rule: Numbers, letters or hyphen only (for example 0-2).
urinalysis_pus_cells	string (100)	No	Urinalysis, microscopic: pus cells. Rule: Numbers, letters or hyphen only (for example 0-2).
urinalysis_red_blood_cells	string (100)	No	Urinalysis, microscopic: red blood cells, per high-power field. Format: Unit: /hpf.. Rule: Numbers, letters or hyphen only (for example 0-2).
urinalysis_white_blood_cells	string (100)	No	Urinalysis, microscopic: white blood cells, per high-power field. Format: Unit: /hpf.. Rule: Numbers, letters or hyphen only (for example 0-2).
uacr · Object, nested in diagresult_item[]			
uacr_albumin	number	No	Urinary albumin, in mg/dL. Format: Unit: mg/dL.. Rule: Up to 2 decimal places.
uacr_creatinine	number	No	Urinary creatinine, in mmol/L. Format: Unit: mmol/L.. Rule: The form prints "mmol/"; mmol/L is the standard (SI) unit for urine creatinine concentration. Up to 2 decimal places.
uacr_ratio	number	No	Urinary albumin-creatinine ratio, in mg/g. Format: Unit: mg/g.. Rule: Computed by the EMR: uacr_albumin (mg/dL) ÷ (uacr_creatinine (mmol/L) × 11.312) × 1000, giving mg albumin per g creatinine; up to 2 decimal places.
uacr_interp	string (100)	No	Interpretation of the urinary albumin-creatinine ratio. Rule: Derived from uacr_ratio: below 30 Normal; 30 to 300 Micro; above 300 Macro.
hbsag · Object, nested in diagresult_item[]			
hbsag_test_results	string (2)	No	HBsAg test result. Valid values: Library Reference – Qualitative Test Result. Rule: Choose one.
hivrdt · Object, nested in diagresult_item[]			
hiv_rdt_results	string (2)	No	HIV rapid diagnostic test result. Valid values: Library Reference – Qualitative Test Result. Rule: Choose one.
rpr · Object, nested in diagresult_item[]			
rpr_results	string (2)	No	RPR test result. Valid values: Library Reference – Qualitative Test Result. Rule: Choose one.

Parameter	Type	Required	Description
vdrl · Object, nested in diagresult_item[]			
vdrl_results	string (2)	No	VDRL test result. Valid values: Library Reference – Qualitative Test Result. Rule: Choose one.
malariasmear · Object, nested in diagresult_item[]			
malaria_smear_results	string (2)	No	Blood smear microscopy for malaria: result. Valid values: Library Reference – Malaria Smear Result. Rule: Choose one.
filariasissmear · Object, nested in diagresult_item[]			
filariasis_smear_results	string (2)	No	Blood smear microscopy for filariasis: result. Valid values: Library Reference – Microscopy Finding. Rule: Choose one.
filariasis_smear_findings_spec	string (250)	Conditional	Findings of blood smear microscopy for filariasis. Rule: Required if filariasis_smear_results = 02 (With Findings). Letters, whole numbers and special characters.
fbs · Object, nested in diagresult_item[]			
fbs_results_mg_dl	number	No	Fasting blood sugar result, in mg/dL. Format: Unit: mg/dL.. Rule: Value in mg/dL. Send the field for the unit the laboratory reported; send at most one of fbs_results_mg_dl and fbs_results_mmol_l. Up to 2 decimal places.
fbs_results_mmol_l	number	No	Fasting blood sugar result, in mmol/L. Format: Unit: mmol/L.. Rule: Value in mmol/L. Send the field for the unit the laboratory reported; send at most one of fbs_results_mg_dl and fbs_results_mmol_l. Up to 2 decimal places.
fbs_interp	string (100)	No	Interpretation of the fasting blood sugar result. Rule: Based on standard FBS thresholds.
hba1c · Object, nested in diagresult_item[]			
hba1c_results	number	No	HbA1c result, in %. Format: Unit: %.. Rule: Up to 2 decimal places.
hba1c_interp	string (100)	No	Interpretation of the HbA1c result. Rule: Based on standard HbA1c ranges.
ogtt · Object, nested in diagresult_item[]			
ogtt_fasting_mg_dl	number	No	OGTT: fasting blood glucose, in mg/dL. Format: Unit: mg/dL.. Rule: Value in mg/dL. Send the field for the unit the laboratory reported; send at most one of ogtt_fasting_mg_dl and ogtt_fasting_mmol_l. Up to 2 decimal places.

Parameter	Type	Required	Description
ogtt_fasting_mmol_l	number	No	OGTT: fasting blood glucose, in mmol/L. Format: Unit: mmol/L.. Rule: Value in mmol/L. Send the field for the unit the laboratory reported; send at most one of ogtt_fasting_mg_dl and ogtt_fasting_mmol_l. Up to 2 decimal places.
ogtt_1_hour_mg_dl	number	No	OGTT: blood glucose at 1 hour, in mg/dL. Format: Unit: mg/dL.. Rule: Value in mg/dL. Send the field for the unit the laboratory reported; send at most one of ogtt_1_hour_mg_dl and ogtt_1_hour_mmol_l. Up to 2 decimal places.
ogtt_1_hour_mmol_l	number	No	OGTT: blood glucose at 1 hour, in mmol/L. Format: Unit: mmol/L.. Rule: Value in mmol/L. Send the field for the unit the laboratory reported; send at most one of ogtt_1_hour_mg_dl and ogtt_1_hour_mmol_l. Up to 2 decimal places.
ogtt_2_hours_mg_dl	number	No	OGTT: blood glucose at 2 hours, in mg/dL. Format: Unit: mg/dL.. Rule: Value in mg/dL. Send the field for the unit the laboratory reported; send at most one of ogtt_2_hours_mg_dl and ogtt_2_hours_mmol_l. Up to 2 decimal places.
ogtt_2_hours_mmol_l	number	No	OGTT: blood glucose at 2 hours, in mmol/L. Format: Unit: mmol/L.. Rule: Value in mmol/L. Send the field for the unit the laboratory reported; send at most one of ogtt_2_hours_mg_dl and ogtt_2_hours_mmol_l. Up to 2 decimal places.
ogtt_interp	string (100)	No	Interpretation of the OGTT result. Rule: Based on pregnancy status and the OGTT thresholds.
fecalysis · Object, nested in diagresult_item[]			
fecalysis_color	string (100)	No	Fecalysis: color. Rule: Letters only.
fecalysis_consistency	string (100)	No	Fecalysis: consistency. Rule: Letters only.
fecalysis_rbc	number	No	Fecalysis: red blood cells, per high-power field. Format: Unit: /hpf.. Rule: Whole number only.
fecalysis_pus_cells	number	No	Fecalysis: pus cells, per high-power field. Format: Unit: /hpf.. Rule: Whole number only.
fecalysis_ova_parasite	string (100)	No	Fecalysis: ova or parasites seen. Rule: This parameter carries ova and parasites as one result. Letters only.
fecalysis_fat_globules	number	No	Fecalysis: fat globules, per low-power field. Format: Unit: /lpf.. Rule: Whole number only.

Parameter	Type	Required	Description
fecalysis_bacteria	number	No	Fecalysis: bacteria, per high-power field. Format: Unit: /hpf.. Rule: No bacteria param in FECALYSIS group. Whole number only.
fecalysis_other	string (100)	No	Fecalysis: other findings.
fecalysiskk · Object, nested in diagresult_item[]			
fecalysis_kato_katz_results	string (2)	No	Kato-Katz fecalysis result (parasite species found). Valid values: Library Reference – Kato-Katz Result. Rule: When the result is 01 (Normal test result or no parasites seen), leave out fecalysis_kato_katz_epg_value and send fecalysis_kato_katz_intensity as "".
fecalysis_kato_katz_epg_value	number	No	Kato-Katz eggs per gram (EPG) value. Format: Unit: EPG.. Rule: One EPG value; the species is identified through the Kato-Katz Result library (fecalysis_kato_katz_results). Whole number only.
fecalysis_kato_katz_intensity	string (2)	No	Kato-Katz intensity of infection. Valid values: Library Reference – Kato-Katz Intensity. Rule: Choose one.
fobt · Object, nested in diagresult_item[]			
gfobt_results	string (2)	No	Guaiac fecal occult blood test (gFOBT) result. Valid values: Library Reference – Qualitative Test Result. Rule: Choose one.
lipidprofile · Object, nested in diagresult_item[]			
lipid_total_chol_mg_dl	number	No	Lipid profile: total cholesterol, in mg/dL. Format: Unit: mg/dL.. Rule: Value in mg/dL. Send the field for the unit the laboratory reported; send at most one of lipid_total_chol_mg_dl and lipid_total_chol_mmol_l. Up to 2 decimal places.
lipid_total_chol_mmol_l	number	No	Lipid profile: total cholesterol, in mmol/L. Format: Unit: mmol/L.. Rule: Value in mmol/L. Send the field for the unit the laboratory reported; send at most one of lipid_total_chol_mg_dl and lipid_total_chol_mmol_l. Up to 2 decimal places.
lipid_trig_mg_dl	number	No	Lipid profile: triglycerides, in mg/dL. Format: Unit: mg/dL.. Rule: Value in mg/dL. Send the field for the unit the laboratory reported; send at most one of lipid_trig_mg_dl and lipid_trig_mmol_l. Up to 2 decimal places.
lipid_trig_mmol_l	number	No	Lipid profile: triglycerides, in mmol/L. Format: Unit: mmol/L.. Rule: Value in mmol/L. Send the field for the unit the laboratory reported; send at most one of lipid_trig_mg_dl and lipid_trig_mmol_l. Up to 2 decimal places.

Parameter	Type	Required	Description
lipid_hdl_mg_dl	number	No	Lipid profile: HDL cholesterol, in mg/dL. Format: Unit: mg/dL.. Rule: Value in mg/dL. Send the field for the unit the laboratory reported; send at most one of lipid_hdl_mg_dl and lipid_hdl_mmol_l. Up to 2 decimal places.
lipid_hdl_mmol_l	number	No	Lipid profile: HDL cholesterol, in mmol/L. Format: Unit: mmol/L.. Rule: Value in mmol/L. Send the field for the unit the laboratory reported; send at most one of lipid_hdl_mg_dl and lipid_hdl_mmol_l. Up to 2 decimal places.
lipid_ldl_mg_dl	number	No	Lipid profile: LDL cholesterol, in mg/dL. Format: Unit: mg/dL.. Rule: Value in mg/dL. Send the field for the unit the laboratory reported; send at most one of lipid_ldl_mg_dl and lipid_ldl_mmol_l. Up to 2 decimal places.
lipid_ldl_mmol_l	number	No	Lipid profile: LDL cholesterol, in mmol/L. Format: Unit: mmol/L.. Rule: Value in mmol/L. Send the field for the unit the laboratory reported; send at most one of lipid_ldl_mg_dl and lipid_ldl_mmol_l. Up to 2 decimal places.
lipid_vldl_mg_dl	number	No	Lipid profile: VLDL cholesterol, in mg/dL. Format: Unit: mg/dL.. Rule: Value in mg/dL. Send the field for the unit the laboratory reported; send at most one of lipid_vldl_mg_dl and lipid_vldl_mmol_l. Up to 2 decimal places.
lipid_vldl_mmol_l	number	No	Lipid profile: VLDL cholesterol, in mmol/L. Format: Unit: mmol/L.. Rule: Value in mmol/L. Send the field for the unit the laboratory reported; send at most one of lipid_vldl_mg_dl and lipid_vldl_mmol_l. Up to 2 decimal places.
afp · Object, nested in diagresult_item[]			
afp_results	number	No	Alpha fetoprotein (AFP) result, in ng/mL. Format: Unit: ng/mL.. Rule: Up to 2 decimal places.
alt · Object, nested in diagresult_item[]			
alt_sgpt_results	number	No	ALT (SGPT) result, in U/L. Format: Unit: U/L.. Rule: Up to 2 decimal places.
ast · Object, nested in diagresult_item[]			
ast_sgot_results	number	No	AST (SGOT) result, in U/L. Format: Unit: U/L.. Rule: Up to 2 decimal places.
creatinine · Object, nested in diagresult_item[]			
serum_creatinine_results_mg_dl	number	No	Serum creatinine result, in mg/dL. Format: Unit: mg/dL.. Rule: Value in mg/dL. Send the field for the unit the laboratory reported; send at most one of serum_creatinine_results_mg_dl and serum_creatinine_results_umol_l. Up to 2 decimal places.

Parameter	Type	Required	Description
serum_creatinine_results_umol_l	number	No	Serum creatinine result, in µmol/L. Format: Unit: µmol/L.. Rule: Value in µmol/L. Send the field for the unit the laboratory reported; send at most one of serum_creatinine_results_mg_dl and serum_creatinine_results_umol_l. Up to 2 decimal places.
papsmear · Object, nested in diagresult_item[]			
pap_smear_findings	string (250)	No	Pap smear cytology findings. Rule: Single findings field on the form. Letters, whole numbers and special characters.
via · Object, nested in diagresult_item[]			
via_test_results_findings	string (250)	No	VIA test result and findings. Rule: Letters, numbers (up to 2 decimal places) and special characters.
via_impression	string (2)	No	VIA impression. Valid values: Library Reference – Qualitative Test Result. Codes 01 and 02 only. Rule: Choose one.
via_recommendation	string (250)	No	Recommendation after VIA. Rule: Letters and whole numbers only.
sputum · Object, nested in diagresult_item[]			
sputum_smear_results	string (2)	No	Sputum smear microscopy result. Valid values: Library Reference – Microscopy Finding. Rule: Choose one.
sputum_smear_findings_spec	string (250)	Conditional	Findings of sputum smear microscopy. Rule: Required if sputum_smear_results = 02 (With Findings). Letters, whole numbers and special characters.
alp · Object, nested in diagresult_item[]			
alp_results_u_l	number	No	Alkaline phosphatase (ALP) result, in U/L. Format: Unit: U/L.. Rule: Value in U/L. Send the field for the unit the laboratory reported; send at most one of alp_results_u_l and alp_results_iu_l. U/L and IU/L are numerically equal for this analyte. Up to 2 decimal places.
alp_results_iu_l	number	No	Alkaline phosphatase (ALP) result, in IU/L. Format: Unit: IU/L.. Rule: Value in IU/L. Send the field for the unit the laboratory reported; send at most one of alp_results_u_l and alp_results_iu_l. U/L and IU/L are numerically equal for this analyte. Up to 2 decimal places.
serumalbumin · Object, nested in diagresult_item[]			
serum_albumin_results_g_dl	number	No	Serum albumin result, in g/dL. Format: Unit: g/dL.. Rule: Value in g/dL. Send the field for the unit the laboratory reported; send at most one of serum_albumin_results_g_dl and serum_albumin_results_g_l. Up to 2 decimal places.

Parameter	Type	Required	Description
serum_albumin_results_g_l	number	No	Serum albumin result, in g/L. Format: Unit: g/L.. Rule: Value in g/L. Send the field for the unit the laboratory reported; send at most one of serum_albumin_results_g_dl and serum_albumin_results_g_l. Up to 2 decimal places.
electrolytes · Object, nested in diagresult_item[]			
serum_electrolytes_sodium_meq_l	number	No	Serum electrolytes: sodium (Na+), in mEq/L. Format: Unit: mEq/L.. Rule: Value in mEq/L. Send the field for the unit the laboratory reported; send at most one of serum_electrolytes_sodium_meq_l and serum_electrolytes_sodium_mmol_l. mEq/L and mmol/L are numerically equal for this analyte. Up to 2 decimal places.
serum_electrolytes_sodium_mmol_l	number	No	Serum electrolytes: sodium (Na+), in mmol/L. Format: Unit: mmol/L.. Rule: Value in mmol/L. Send the field for the unit the laboratory reported; send at most one of serum_electrolytes_sodium_meq_l and serum_electrolytes_sodium_mmol_l. mEq/L and mmol/L are numerically equal for this analyte. Up to 2 decimal places.
serum_electrolytes_potassium_meq_l	number	No	Serum electrolytes: potassium (K+), in mEq/L. Format: Unit: mEq/L.. Rule: Value in mEq/L. Send the field for the unit the laboratory reported; send at most one of serum_electrolytes_potassium_meq_l and serum_electrolytes_potassium_mmol_l. mEq/L and mmol/L are numerically equal for this analyte. Up to 2 decimal places.
serum_electrolytes_potassium_mmol_l	number	No	Serum electrolytes: potassium (K+), in mmol/L. Format: Unit: mmol/L.. Rule: Value in mmol/L. Send the field for the unit the laboratory reported; send at most one of serum_electrolytes_potassium_meq_l and serum_electrolytes_potassium_mmol_l. mEq/L and mmol/L are numerically equal for this analyte. Up to 2 decimal places.
serum_electrolytes_chloride_meq_l	number	No	Serum electrolytes: chloride (Cl-), in mEq/L. Format: Unit: mEq/L.. Rule: Value in mEq/L. Send the field for the unit the laboratory reported; send at most one of serum_electrolytes_chloride_meq_l and serum_electrolytes_chloride_mmol_l. mEq/L and mmol/L are numerically equal for this analyte. Up to 2 decimal places.
serum_electrolytes_chloride_mmol_l	number	No	Serum electrolytes: chloride (Cl-), in mmol/L. Format: Unit: mmol/L.. Rule: Value in mmol/L. Send the field for the unit the laboratory reported; send at most one of serum_electrolytes_chloride_meq_l and serum_electrolytes_chloride_mmol_l. mEq/L and mmol/L are numerically equal for this analyte. Up to 2 decimal places.

Parameter	Type	Required	Description
serum_electrolytes_calcium_mg_dl	number	No	Serum electrolytes: calcium (Ca2+), in mg/dL. Format: Unit: mg/dL.. Rule: Value in mg/dL. Send the field for the unit the laboratory reported; send at most one of serum_electrolytes_calcium_mg_dl and serum_electrolytes_calcium_mmol_l. Up to 2 decimal places.
serum_electrolytes_calcium_mmol_l	number	No	Serum electrolytes: calcium (Ca2+), in mmol/L. Format: Unit: mmol/L.. Rule: Value in mmol/L. Send the field for the unit the laboratory reported; send at most one of serum_electrolytes_calcium_mg_dl and serum_electrolytes_calcium_mmol_l. Up to 2 decimal places.
serum_electrolytes_phosphorus_mg_dl	number	No	Serum electrolytes: phosphorus (PO4), in mg/dL. Format: Unit: mg/dL.. Rule: Value in mg/dL. Send the field for the unit the laboratory reported; send at most one of serum_electrolytes_phosphorus_mg_dl and serum_electrolytes_phosphorus_mmol_l. Up to 2 decimal places.
serum_electrolytes_phosphorus_mmol_l	number	No	Serum electrolytes: phosphorus (PO4), in mmol/L. Format: Unit: mmol/L.. Rule: Value in mmol/L. Send the field for the unit the laboratory reported; send at most one of serum_electrolytes_phosphorus_mg_dl and serum_electrolytes_phosphorus_mmol_l. Up to 2 decimal places.
chestxray · Object, nested in diagresult_item[]			
chest_xray_impression	string (250)	No	Chest X-ray impression. Rule: Free-text impression. Letters, numbers (up to 2 decimal places) and special characters.
chestct · Object, nested in diagresult_item[]			
ldct_impression	string (250)	No	Low-dose chest CT impression. Rule: Letters, numbers (up to 2 decimal places) and special characters.
ecg · Object, nested in diagresult_item[]			
ecg_atrial_r_min	number	No	12-lead ECG: atrial rate, per minute. Format: Unit: R/min.. Rule: Up to 2 decimal places.
ecg_ventricular_r_min	number	No	12-lead ECG: ventricular rate, per minute. Format: Unit: R/min.. Rule: Up to 2 decimal places.
ecg_pr_interval_sec	number	No	12-lead ECG: PR interval, in seconds. Format: Unit: sec.. Rule: Up to 2 decimal places.
ecg_qrs_interval_sec	number	No	12-lead ECG: QRS interval, in seconds. Format: Unit: sec.. Rule: Up to 2 decimal places.

Parameter	Type	Required	Description
ecg_qtc_sec	number	No	12-lead ECG: corrected QT interval (QTc), in seconds. Format: Unit: sec.. Rule: Up to 2 decimal places.
ecg_qta_sec	number	No	12-lead ECG: QT interval (QTa), in seconds. Format: Unit: sec.. Rule: Up to 2 decimal places.
ecg_axis	string (100)	No	12-lead ECG: electrical axis.
colonoscopy · Object, nested in diagresult_item[]			
colonoscopy_findings	string (250)	No	Colonoscopy findings. Rule: Letters, numbers (up to 2 decimal places) and special characters.
colonoscopy_recos	string (250)	No	Recommendations after colonoscopy. Rule: Letters, numbers (up to 2 decimal places) and special characters.
spirometry · Object, nested in diagresult_item[]			
spirometry_findings	string (250)	No	Spirometry findings. Rule: Letters, numbers (up to 2 decimal places) and special characters.
spirometry_interp_recos	string (250)	No	Spirometry interpretation and recommendations. Rule: Letters, numbers (up to 2 decimal places) and special characters.
otherdiagexam · Object, nested in diagresult_item[]			
other_name_lab_image_exam	string (150)	Conditional	Name of the other laboratory or imaging test (code 99). Rule: Required if diagnostic_code = 99 (Others) and test_status = 01 (Done).
other_findings	string (250)	No	Findings of the other laboratory or imaging test. Rule: Letters, numbers (up to 2 decimal places) and special characters.
physiciansignoff · Object			
physician_name	string (150)	Yes	Printed name of the physician who signed the results.
physician_designation	string (150)	Yes	Designation of the physician.
physician_license_no	string (100)	Yes	Professional license number of the physician.
physician_accre_no	string (100)	Yes	PhilHealth accreditation number of the physician.

Response (after decryption)


```
{
  "status": "success",
  "code": 202,
  "message": "Submission accepted for processing",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
```

```
    "upload_transaction_no": "UH123456782026102500004",
    "form": "diagnostic_results",
    "processing_status": "queued",
    "case_no": "TH12345678202610230001",
    "soap_transaction_no": "SH123456782026102300001",
    "request_transaction_no": "DH123456782026102300001",
    "result_transaction_no": [
      "LH123456782026102400001",
      "LH123456782026102400002",
      "LH123456782026102400003"
    ]
  }
}
```

Field	Type	Returned	Description
data.upload_transaction_no	string (23)	Always	Number of this submission, generated by the service. Use it to check the outcome (Section 4.6.7). Format: U + accre_no + YYYY + MM + DD + 5-digit daily series number (23 characters).
data.form	string	Always	The form submitted: diagnostic_results.
data.processing_status	string	Always	queued – the submission passed the checks made on receipt and is waiting to be processed.
data.case_no	string	Always	Echoes case_no – the patient record.
data.soap_transaction_no	string	Always	Echoes soap_transaction_no – the consultation.
data.request_transaction_no	string	Always	Echoes request_transaction_no – the Diagnostic Request.
data.result_transaction_no	array (23 each)	Always	Echoes the result_transaction_no of every diagresult_item entry, as an array of strings in submission order.

Status values

processing_status = queued in the upload response; the final status (accepted or rejected) is read from Upload Status (4.6.7). Resending each result entry (result_transaction_no) with identical content returns HTTP 200 with the original upload_transaction_no.

Validation rules

Rule	Validation
Encryption and consent	The body is the encrypted envelope (Section 3.8). consent: true is sent at the top level of the body, beside the data groups.
Field names and nesting	Send each field inside its data group, using the names and JSON paths in the field table. A data group that does not apply is left out as a whole.
Values	Yes fields carry a valid value. Within each group sent, every string field is present: "" when it has no value. Number fields with no value are left out. null is never accepted (Section 3.3).

Rule	Validation
Types and sizes	Send each value with the JSON type shown. String sizes are maximums in bytes (UTF-8; ñ counts as two bytes). Numbers carry no unit; the unit is in the field description, except Diagnostic Results values that the form reports in two units, which have one field per unit (4.6.4). Codes and record numbers are strings, so leading zeros are kept.
Dates and times	MM/DD/YYYY, MM/YYYY, YYYY and HH:MM (24-hour), as stated per field (Section 3.7).
Coded values	Codes must be active codes (LIBRARY STATUS 1) of the named Library Reference worksheet. Yes or No fields use "Y" and "N". Where several codes are allowed, separate them with a comma and no spaces, within the field size.
Record numbers	case_no, soap_transaction_no and request_transaction_no are those of the Diagnostic Request (4.6.3). Each diagresult_item carries its own result_transaction_no (L, Section 3.9), generated by the EMR and unique per result.
Result entries	One diagresult_item per requested test. diagnostic_code must be a code sent in that request; request_transaction_no + diagnostic_code links the result to the requested test. test_status is required for every entry.
Result groups	When test_status = 01 (Done), nest the test's result group (table below) and send test_exam_date and test_lab_loc. Code 28 has no result group: send status and test_remarks only. Code 99 uses otherdiagexam.
Units	A result that the form reports in two units has one field per unit, named after the unit (for example fbs_results_mg_dl and fbs_results_mmol_l). Send the value in the field for the unit the laboratory reported and leave the other out; at most one field of each pair is sent. Other numeric results carry no unit; their unit is in the field description.
Precision and characters	Numeric results follow the decimal limits in the field table: up to 2 decimal places for CBC, UACR, FBS, HbA1c, OGTT, lipid profile, AFP, ALT, AST, creatinine, ALP, serum albumin, serum electrolytes and ECG values; 3 for specific gravity and 1 for pH; whole numbers for fecalysis counts and the Kato-Katz EPG; leukocyte differential values from 0 to 100. Urinalysis microscopic results are text (for example "0-2"). uacr_ratio is computed by the EMR in mg/g from uacr_albumin (mg/dL) and uacr_creatinine (mmol/L).
Kato-Katz	When fecalysis_kato_katz_results = 01 (normal or no parasites seen), leave out fecalysis_kato_katz_epg_value and send fecalysis_kato_katz_intensity as "".
Physician sign-off	physician_name, physician_designation, physician_license_no and physician_accre_no are required.

Errors

The errors common to the six upload endpoints apply (Section 4.6). Problems found after queueing are reported through Upload Status.

Sample error response

```
{
  "status": "error",
  "code": 400,
  "message": "Invalid request payload",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "errors": [
    {
      "field": "diagresult_item[0].result_transaction_no",
      "issue": "validation_error"
    }
  ]
```

```
}
```

4.6.5 Drugs and Medicines Upload

Purpose

Submits the medication prescription written during a consultation, one medicine entry per medicine, with dispensing details. Fields follow Data Dictionary Annex E (Rev. 6, 10/26/2026).

Item	Value
Endpoint	POST /api/v1/yakap-data-upload/medicine
Authentication	Bearer token (Section 3.2); the facility is the accre_no in the token
Encryption	Request body and response data encrypted (Section 3.8, Annex C); errors in plain JSON
Success	HTTP 202 Accepted (200 on an identical resend)

Business rules and preconditions

- Record numbers: meds_transaction_no (M) follows Section 3.9. One number covers the whole prescription: case_no, soap_transaction_no and meds_transaction_no carry the same values in every medicine entry.
- Medicine selection: drug_code, generic_code, strength_code and form_code take Konsulta Drug Library codes (external). For a medicine not in that library, send other_medicine and oth_med_drug_grouping; the library code fields are then sent as "".
- Instructions: route takes a Medicine Route code and instruction_frequency an Instruction Frequency code (for example "PO", "TID").
- Checked after queueing and reported through Upload Status: case_no and soap_transaction_no match an accepted consultation with medication_prescription_flag = Y; meds_transaction_no is not already used.

Request (before encryption)

```
{
  "consent": true,
  "medicine": [
    {
      "case_no": "TH123456782026102300001",
      "soap_transaction_no": "SH123456782026102300001",
      "meds_transaction_no": "MH123456782026102300001",
      "drug_code": "<drug code>",
      "medicine_category": "<category code>",
      "generic_code": "<generic code>",
      "salt_code": "<salt code>",
      "strength_code": "<strength code>",
      "form_code": "<form code>",
      "unit_code": "<unit code>",
      "package_code": "<package code>",
```

```
      "other_medicine": "",
      "oth_med_drug_grouping": "NCD",
      "route": "PO",
      "instruction_quantity": "1 tablet",
      "instruction_strength": "500 mg",
      "instruction_frequency": "TID",
      "quantity": 21,
      "prescription_date": "10/23/2026",
      "actual_unit_price": 2.5,
      "total_amount_price": 52.5,
      "is_dispensed": "Y",
      "date_dispensed": "10/23/2026",
      "dispensing_personnel": "ANA P. CRUZ, RPh",
      "is_applicable": "Y",
      "medicine_ext": {
        "instruction_duration": "7 days"
      },
      "advice": {
        "special_instructions": "Take after meals."
      }
    }
  ],
  "physiciansignoff": {
    "physician_name": "MARIA L. SANTOS, MD",
    "physician_designation": "Attending Physician",
    "physician_license_no": "0123456",
    "physician_accre_no": "1234-5678901-2"
  }
}
```


Konsulta Drug Library codes (external) are shown as placeholders such as <drug code>; replace them with codes from that library.

Payload structure

Data group	Structure	Content and applicability	Fields
medicine	Array	One entry per medicine prescribed: record numbers, medicine, instructions, quantities, prices and dispensing. At least one entry. Each entry may carry nested medicine_ext and advice objects.	25
medicine_ext	Object, nested in each medicine entry	Treatment duration for that medicine. Required in every medicine entry (instruction_duration is required).	1
advice	Object, nested in each medicine entry	Special instructions for that medicine. Optional.	1
physiciansignoff	Object	Prescribing physician's name, designation, license number and accreditation number, once per prescription. Always required.	4

Request fields

Parameter	Type	Required	Description
medicine · Array			

Parameter	Type	Required	Description
case_no	string (23)	Yes	Patient case number that links the prescription to the patient, FPE and consultation records. Format: T+ACCRE_NO+YYYY+MM+DD+99999.
soap_transaction_no	string (23)	Yes	Transaction number of the consultation that ordered the prescription. Format: S+ACCRE_NO+YYYY+MM+DD+99999.
meds_transaction_no	string (23)	Yes	Transaction number of the medicine prescription. Format: M+ACCRE_NO+YYYY+MM+DD+99999.
drug_code	string (20)	Yes	Medicine prescribed (Konsulta drug library code). Valid values: External library: lib_medicine (Konsulta Drug Library; not in the Library Reference Document).
medicine_category	string (20)	No	Medicine category. Valid values: External library: lib_medicine category (Konsulta Drug Library; not in the Library Reference Document).
generic_code	string (20)	Yes	Generic name code of the medicine. Valid values: External library: lib_medicine_generic (Konsulta Drug Library; not in the Library Reference Document).
salt_code	string (20)	No	Salt code of the medicine. Valid values: External library: lib_medicine_salt (Konsulta Drug Library; not in the Library Reference Document).
strength_code	string (20)	Yes	Strength or dosage code of the medicine. Valid values: External library: lib_medicine_strength (Konsulta Drug Library; not in the Library Reference Document).
form_code	string (20)	Yes	Dosage form code (for example tablet or capsule). Valid values: External library: lib_medicine_form (Konsulta Drug Library; not in the Library Reference Document).
unit_code	string (20)	No	Unit code of the medicine. Valid values: External library: lib_medicine_unit (Konsulta Drug Library; not in the Library Reference Document).
package_code	string (20)	No	Package or volume code of the medicine. Valid values: External library: lib_medicine_package (Konsulta Drug Library; not in the Library Reference Document).
other_medicine	string (250)	Conditional	Full description of a medicine not in the drug library. Rule: Required if the medicine is not in the drug library.
oth_med_drug_grouping	string (20)	No	Drug grouping of a medicine not in the drug library. Valid values: Library Reference – Medicine Drug Grouping.
route	string (20)	Yes	Route of administration. Valid values: Library Reference – Medicine Route. Rule: Previously free text (Oral, Sublingual, ...); send the library code.
instruction_quantity	string (50)	Yes	Quantity per intake (for example 1 tablet or 5 mL).
instruction_strength	string (100)	No	Strength per intake.

Parameter	Type	Required	Description
instruction_frequency	string (20)	Yes	Frequency of intake (for example once daily). Valid values: Library Reference – Instruction Frequency. Rule: Previously free text (OD, BID, TID, ...); send the library code.
medicine_ext · Object, nested in medicine[]			
instruction_duration	string (50)	Yes	Duration of treatment (for example 7 days).
medicine · Array			
quantity	number	Yes	Total quantity prescribed. Rule: Computed by the EMR as quantity per intake x frequency x duration and sent in the request; PCAPI does not compute it.
prescription_date	string (MM/DD/YYYY)	Yes	Date of the prescription. Format: MM/DD/YYYY.
advice · Object, nested in medicine[]			
special_instructions	string (500)	No	Special instructions or advice (for example take with meals).
medicine · Array			
actual_unit_price	number (10,2)	No	Actual unit price of the medicine. Format: PHP, 2 decimal places.
total_amount_price	number (10,2)	No	Total price of the medicine issued. Format: PHP, 2 decimal places. Rule: Computed by the EMR as quantity x actual_unit_price and sent when known.
is_dispensed	string (1)	No	Indicates whether the medicine was dispensed. Valid values: "Y" - Yes; "N" - No.
date_dispensed	string (MM/DD/YYYY)	Conditional	Date the medicine was dispensed. Format: MM/DD/YYYY. Rule: Required if is_dispensed = Y
dispensing_personnel	string (150)	Conditional	Name of the pharmacist or dispensing personnel. Rule: Required if is_dispensed = Y
is_applicable	string (1)	Yes	Indicates whether the medicine record applies. Valid values: "Y" - Yes; "N" - No (default Y if prescribed).
physiciansignoff · Object			
physician_name	string (150)	Yes	Printed name of the prescribing physician who signs the prescription. Rule: Sent once per prescription in physiciansignoff.
physician_designation	string (150)	Yes	Designation of the physician.
physician_license_no	string (100)	Yes	Professional license number of the physician.
physician_accre_no	string (100)	Yes	PhilHealth accreditation number of the prescribing physician.

Response (after decryption)

```
{
  "status": "success",
  "code": 202,
  "message": "Submission accepted for processing",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
    "upload_transaction_no": "UH123456782026102500005",
    "form": "medicine",
    "processing_status": "queued",
    "case_no": "TH123456782026102300001",
    "soap_transaction_no": "SH123456782026102300001",
    "meds_transaction_no": "MH123456782026102300001"
  }
}
```

Field	Type	Returned	Description
data.upload_transaction_no	string (23)	Always	Number of this submission, generated by the service. Use it to check the outcome (Section 4.6.7). Format: U + accre_no + YYYY + MM + DD + 5-digit daily series number (23 characters).
data.form	string	Always	The form submitted: medicine.
data.processing_status	string	Always	queued – the submission passed the checks made on receipt and is waiting to be processed.
data.case_no	string	Always	Echoes case_no – the patient record.
data.soap_transaction_no	string	Always	Echoes soap_transaction_no – the consultation.
data.meds_transaction_no	string	Always	Echoes meds_transaction_no – the prescription.

Status values

processing_status = queued in the upload response; the final status (accepted or rejected) is read from Upload Status (4.6.7). Resending the prescription (meds_transaction_no) with identical content returns HTTP 200 with the original upload_transaction_no.

Validation rules

Rule	Validation
Encryption and consent	The body is the encrypted envelope (Section 3.8). consent: true is sent at the top level of the body, beside the data groups.
Field names and nesting	Send each field inside its data group, using the names and JSON paths in the field table. A data group that does not apply is left out as a whole.
Values	Yes fields carry a valid value. Within each group sent, every string field is present: "" when it has no value. Number fields with no value are left out. null is never accepted (Section 3.3).
Types and sizes	Send each value with the JSON type shown. String sizes are maximums in bytes (UTF-8; ñ counts as two bytes). Numbers carry no unit; the unit is in the field description, except Diagnostic Results values that the form reports in two units, which have one field per unit (4.6.4). Codes and record numbers are strings, so leading zeros are kept.

Rule	Validation
Dates and times	MM/DD/YYYY, MM/YYYY, YYYY and HH:MM (24-hour), as stated per field (Section 3.7).
Coded values	Codes must be active codes (LIBRARY STATUS 1) of the named Library Reference worksheet. Yes or No fields use "Y" and "N". Where several codes are allowed, separate them with a comma and no spaces, within the field size.
Record numbers	meds_transaction_no (M) follows Section 3.9. One number covers the whole prescription: case_no, soap_transaction_no and meds_transaction_no carry the same values in every medicine entry.
Medicine selection	drug_code, generic_code, strength_code and form_code take Konsulta Drug Library codes (external). For a medicine not in that library, send other_medicine and oth_med_drug_grouping; the library code fields are then sent as "".
Instructions	route takes a Medicine Route code and instruction_frequency an Instruction Frequency code (for example "PO", "TID").
Computed values	quantity = units per intake × frequency × duration; total_amount_price = quantity × actual_unit_price (PHP, 2 decimals). Both are computed by the EMR.
Dispensing	date_dispensed and dispensing_personnel are required when is_dispensed = Y.
Physician sign-off	physiciansignoff is sent once per prescription with physician_name, physician_designation, physician_license_no and physician_accre_no, all required.

Errors

The errors common to the six upload endpoints apply (Section 4.6). Problems found after queueing are reported through Upload Status.

Sample error response

```
{
  "status": "error",
  "code": 400,
  "message": "Invalid request payload",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "errors": [
    {
      "field": "medicine[0].route",
      "issue": "validation_error"
    }
  ]
}
```

4.6.6 Referral Request Upload

Purpose

Submits a referral raised from a consultation: to a specialist, other primary care services, or a facility or service. Fields follow Data Dictionary Annex F (Rev. 7, 10/26/2026).

Item	Value
Endpoint	POST /api/v1/yakap-data-upload/referral

Item	Value
Authentication	Bearer token (Section 3.2); the facility is the accre_no in the token
Encryption	Request body and response data encrypted (Section 3.8, Annex C); errors in plain JSON
Success	HTTP 202 Accepted (200 on an identical resend)

Business rules and preconditions

- Record numbers: referral_transaction_no (R) follows Section 3.9 and is unique per referral; one consultation may raise several referrals, each carrying its soap_transaction_no.
- Link to the consultation: case_no and soap_transaction_no are those of a consultation submitted with referral_flag = Y. Patient, date, time, service-delivery and co-payment fields repeat that consultation's values.
- Patient verification: The Referral has no patient_verification_mode; pcu_transaction_code is required when the consultation was verified with PCU.
- Checked after queueing and reported through Upload Status: case_no and soap_transaction_no match an accepted consultation with referral_flag = Y; referral_transaction_no is not already used.

Request (before encryption)


```
{
  "consent": true,
  "soap": {
    "case_no": "TH123456782026102300001",
    "soap_transaction_no": "SH123456782026102300001",
    "patient_type": "MM",
    "patient_pin": "123456789012",
    "patient_age": "36 YR(S), 3 MO(S), 19 DAY(S)",
    "method_of_service_delivery": "F",
    "pcu_transaction_code": "PCU-LOG-TRANS-NO",
    "co_payment_flag": "Y",
    "co_payment_date_payment": "10/23/2026",
    "co_payment": 300,
    "co_payment_balance": 600,
    "consultation_date": "10/23/2026",
    "consultation_time": "10:15"
  },
  "referral": {
    "referral_transaction_no": "RH123456782026102300001",
    "referral_type": "01,02",
    "referral_specialist": "Pulmonology",
    "referral_specialist_other_spec": "",
    "referral_reason": "Persistent wheezing; for pulmonary evaluation.",
    "referral_primary_care_services": "01,02",
    "referral_facility_service": "01,02",
    "referral_others_spec": ""
  },
  "physiciansignoff": {
```

```
    "physician_name": "MARIA L. SANTOS, MD",
    "physician_designation": "Attending Physician",
    "physician_license_no": "0123456",
    "physician_accre_no": "1234-5678901-2"
  }
}
```

The sample is a member, so the guardian group is left out.

Payload structure

Data group	Structure	Content and applicability	Fields
soap	Object	Referral header: links the referral to the patient record and the consultation, with patient and co-payment details. Always required.	13
guardian	Object	Parent or guardian. Required when patient_type = DD (dependent); left out when patient_type = MM (member).	7
referral	Object	Referral number and referral details. Always required.	8
physiciansignoff	Object	Referring physician: name, designation, license number and accreditation number. Always required.	4

Request fields

Parameter	Type	Required	Description
soap · Object			
case_no	string (23)	Yes	Patient case number that links the referral to the patient, FPE and consultation records. Format: T+ACCRE_NO+YYYY+MM+DD+99999.
soap_transaction_no	string (23)	Yes	Transaction number of the consultation that made the referral. Format: S+ACCRE_NO+YYYY+MM+DD+99999.
patient_type	string (2)	Yes	Patient type: member or dependent. Valid values: Library Reference – Patient Type.
patient_pin	string (12)	Yes	PhilHealth Identification Number (PIN) of the patient.
patient_age	string (30)	Yes	Age of the patient on the consultation date. Format: Y YR(S), M MO(S), D DAY(S) (e.g., 1 YR(S), 0 MO(S), 25 DAY(S)). Rule: Required in the request. The backend computes the age from the patient's date of birth on the PhilHealth record and consultation_date and rejects a submitted value that does not match.
guardian · Object			
guardian_name	string (150)	Conditional	Full name of the parent or guardian (surname, first name, middle name, suffix). Rule: Required if patient_type = DD (dependent). Leave out when patient_type = MM (member).

Parameter	Type	Required	Description
guardian_age	number	Conditional	Age of the parent or guardian, in years. Rule: Required if patient_type = DD (dependent). Leave out when patient_type = MM (member).
guardian_sex	string (1)	Conditional	Sex of the parent or guardian. Valid values: Library Reference – Sex. Rule: Required if patient_type = DD (dependent). Leave out when patient_type = MM (member).
guardian_birthday	string (MM/DD/YYYY)	Conditional	Date of birth of the parent or guardian. Format: MM/DD/YYYY. Rule: Required if patient_type = DD (dependent). Leave out when patient_type = MM (member).
guardian_contact_no	string (15)	Conditional	Contact number of the parent or guardian. Rule: Required if patient_type = DD (dependent). Leave out when patient_type = MM (member).
guardian_relationship	string (100)	Conditional	Relationship of the parent or guardian to the patient. Valid values: Library Reference – Guardian Relationship. Rule: Required if patient_type = DD (dependent). Leave out when patient_type = MM (member).
guardian_pin	string (12)	No	PhilHealth Identification Number (PIN) of the parent or guardian.
soap · Object			
method_of_service_delivery	string (1)	Yes	Method of service delivery for the consultation. Valid values: Library Reference – Service Delivery Method.
pcu_transaction_code	string (20)	Conditional	PhilHealth Check Utility (PCU) transaction code. Rule: Required if the consultation identified by soap_transaction_no was verified with patient_verification_mode = PCU (Annex B). Annex F does not carry patient_verification_mode or one_time_pin; the consultation's values apply.
co_payment_flag	string (1)	Yes	Indicates whether the patient has a co-payment. Valid values: "Y" - With co-payment (max. PHP 900 per year for private facilities); "N" - No co-payment (government health institutions).
co_payment_date_payment	string (MM/DD/YYYY)	No	Date the co-payment was paid. Format: MM/DD/YYYY.
co_payment	number	No	Co-payment amount paid, in PHP.
co_payment_balance	number	No	Remaining co-payment balance, in PHP.
consultation_date	string (MM/DD/YYYY)	Yes	Date of the consultation. Format: MM/DD/YYYY.
consultation_time	string (5)	Yes	Time of the consultation (24-hour). Format: HH:MM.
referral · Object			

Parameter	Type	Required	Description
referral_transaction_no	string (23)	Yes	Transaction number of the referral request. Format: R+ACCRE_NO+YYYY+MM+DD+99999. Rule: Unique per referral. One consultation may have one or more referrals; each carries soap_transaction_no of the consultation that made it, and that consultation must have referral_flag = Y. A resubmission with the same referral_transaction_no is treated as the same referral, not a new one.
referral_type	string (1000)	Yes	Referral destination types. Valid values: Library Reference – Referral Type; multiple selection allowed (codes separated by a comma). Rule: Select at least one. Applicable if Annex B referral_flag = Y.
referral_specialist	string (250)	Conditional	Specialty referred to. Valid values: The specialty is sent as text. Rule: Required if referral_type includes 01 (Refer to specialist).
referral_specialist_other_spec	string (250)	Conditional	Specialty not in the list. Rule: Required if referral_specialist = Other Specialist.
referral_reason	string (500)	Conditional	Reason for referral. Rule: Required if referral_type includes 01 (Refer to specialist). Recommended for all referral types.
referral_primary_care_services	string (250)	Conditional	Other primary care services referred to. Valid values: Library Reference – Referral Primary Care Service; multiple selection allowed (codes separated by a comma). Rule: Required if referral_type includes 02 (Refer to other primary care services).
referral_facility_service	string (500)	Conditional	Facilities or services referred to. Valid values: Library Reference – Referral Facility Service; multiple selection allowed (codes separated by a comma). Rule: Required if referral_type includes 03 (Refer to facility or service).
referral_others_spec	string (250)	Conditional	Other referral destination. Rule: Required if referral_type includes 99 (Others).
physiciansignoff · Object			
physician_name	string (150)	Yes	Printed name of the referring physician.
physician_designation	string (150)	Yes	Designation of the physician.
physician_license_no	string (100)	Yes	Professional license number of the physician.
physician_accre_no	string (100)	Yes	PhilHealth accreditation number of the referring physician.

Response (after decryption)

```
{
  "status": "success",
  "code": 202,
  "message": "Submission accepted for processing",
  "timestamp": "2026-10-25T10:15:30",
```

```
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
    "upload_transaction_no": "UH123456782026102500006",
    "form": "referral",
    "processing_status": "queued",
    "case_no": "TH123456782026102300001",
    "soap_transaction_no": "SH123456782026102300001",
    "referral_transaction_no": "RH123456782026102300001"
  }
}
```


Field	Type	Returned	Description
data.upload_transaction_no	string (23)	Always	Number of this submission, generated by the service. Use it to check the outcome (Section 4.6.7). Format: U + accre_no + YYYY + MM + DD + 5-digit daily series number (23 characters).
data.form	string	Always	The form submitted: referral.
data.processing_status	string	Always	queued – the submission passed the checks made on receipt and is waiting to be processed.
data.case_no	string	Always	Echoes case_no – the patient record.
data.soap_transaction_no	string	Always	Echoes soap_transaction_no – the consultation.
data.referral_transaction_no	string	Always	Echoes referral_transaction_no – the referral.

Status values

processing_status = queued in the upload response; the final status (accepted or rejected) is read from Upload Status (4.6.7). Resending the referral (referral_transaction_no) with identical content returns HTTP 200 with the original upload_transaction_no.

Validation rules

Rule	Validation
Encryption and consent	The body is the encrypted envelope (Section 3.8). consent: true is sent at the top level of the body, beside the data groups.
Field names and nesting	Send each field inside its data group, using the names and JSON paths in the field table. A data group that does not apply is left out as a whole.
Values	Yes fields carry a valid value. Within each group sent, every string field is present: "" when it has no value. Number fields with no value are left out. null is never accepted (Section 3.3).
Types and sizes	Send each value with the JSON type shown. String sizes are maximums in bytes (UTF-8; ñ counts as two bytes). Numbers carry no unit; the unit is in the field description, except Diagnostic Results values that the form reports in two units, which have one field per unit (4.6.4). Codes and record numbers are strings, so leading zeros are kept.
Dates and times	MM/DD/YYYY, MM/YYYY, YYYY and HH:MM (24-hour), as stated per field (Section 3.7).
Coded values	Codes must be active codes (LIBRARY STATUS 1) of the named Library Reference worksheet. Yes or No fields use "Y" and "N". Where several codes are allowed, separate them with a comma and no spaces, within the field size.

Rule	Validation
Record numbers	referral_transaction_no (R) follows Section 3.9 and is unique per referral; one consultation may raise several referrals, each carrying its soap_transaction_no.
Link to the consultation	case_no and soap_transaction_no are those of a consultation submitted with referral_flag = Y. Patient, date, time, service-delivery and co-payment fields repeat that consultation's values.
Patient verification	The Referral has no patient_verification_mode; pcu_transaction_code is required when the consultation was verified with PCU.
Dependent patients	The guardian group is required when patient_type = DD and left out when patient_type = MM.
Referral destination	referral_type takes one or more Referral Type codes: 01 requires referral_specialist and referral_reason; 02 requires referral_primary_care_services; 03 requires referral_facility_service; 99 requires referral_others_spec.
Specialist	Until PhilHealth issues the specialty library, referral_specialist carries the specialty as text.
Physician sign-off	physician_name, physician_designation, physician_license_no and physician_accre_no are required.

Errors

The errors common to the six upload endpoints apply (Section 4.6). Problems found after queueing are reported through Upload Status.

Sample error response

```
{
  "status": "error",
  "code": 400,
  "message": "Invalid request payload",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "errors": [
    {
      "field": "referral.referral_type",
      "issue": "validation_error"
    }
  ]
}
```

4.6.7 Upload Status

Purpose

Returns the outcome of a submission made through 4.6.1 to 4.6.6. Poll it with the upload_transaction_no until processing_status is accepted or rejected.

Item	Value
Endpoint	GET /api/v1/yakap-data-upload/status/{upload_transaction_no}
Authentication	Bearer token (Section 3.2); the facility is the accre_no in the token
Encryption	Request body and response data encrypted (Section 3.8, Annex C); errors in plain JSON

Item	Value
Success	HTTP 200
Request body	None (GET); the response data is encrypted

Business rules

- Only submissions made for the facility in the bearer token can be read.
- Poll with a growing interval (for example 2, 4, 8 seconds, capped at 60 seconds); a submission stays queued while its parent record is processed.
- A rejected record is corrected and resubmitted with the same record number.

Request

Parameter	Type	Required	Description
upload_transaction_no (path)	string (23)	Yes	Number returned when the submission was accepted (U + accre_no + YYYY + MM + DD + 5-digit daily series). Path parameter; no request body. Only submissions made for the facility in the bearer token can be read.

Response (after decryption)

```
{
  "status": "success",
  "code": 200,
  "message": "Upload status retrieved",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
    "upload_transaction_no": "UH123456782026102500002",
    "form": "consultation",
    "processing_status": "accepted",
    "received_at": "2026-10-25T10:15:30",
    "processed_at": "2026-10-25T10:15:42",
    "case_no": "TH123456782026102300001",
    "soap_transaction_no": "SH123456782026102300001",
    "errors": []
  }
}
```

A rejected submission lists the problems in data.errors, using the request field paths:

```
{
  "status": "success",
  "code": 200,
  "message": "Upload status retrieved",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
    "upload_transaction_no": "UH123456782026102500005",
```

```
    "form": "medicine",
    "processing_status": "rejected",
    "received_at": "2026-10-25T10:16:05",
    "processed_at": "2026-10-25T10:16:09",
    "case_no": "TH123456782026102300001",
    "soap_transaction_no": "SH123456782026102300001",
    "meds_transaction_no": "MH123456782026102300001",
    "errors": [
      {
        "field": "medicine[0].soap_transaction_no",
        "issue": "validation_error"
      }
    ]
  }
}
```


Field	Type	Returned	Description
data.upload_transaction_no	string (23)	Always	The submission being reported on (U + accre_no + YYYY + MM + DD + 5-digit daily series number, 23 characters).
data.form	string	Always	fpe, consultation, diagnostic_request, diagnostic_results, medicine or referral.
data.processing_status	string	Always	See the status values below.
data.received_at	string (YYYY-MM-DDTHH:MM:SS)	Always	When the submission was accepted, YYYY-MM-DDTHH:MM:SS.
data.processed_at	string (YYYY-MM-DDTHH:MM:SS)	Conditional	When processing finished, YYYY-MM-DDTHH:MM:SS. Left out while queued or processing.
data.<record numbers>	string	Always	The record numbers of the submission, as returned on upload (for example case_no and soap_transaction_no). For Diagnostic Results, result_transaction_no is returned as an array of strings, one per result entry.
data.errors	array	Always	One { field, issue } entry per problem when processing_status = rejected; an empty array otherwise.
data.errors[].field	string	Always	JSON path of the field with the problem, for example medicine[0].soap_transaction_no.
data.errors[].issue	string	Always	Issue code (Section 3.4). Problems found after queueing are reported as validation_error.

Status values

processing_status	Meaning
queued	Accepted on receipt and waiting to be processed.
processing	Being processed.
accepted	Recorded. The record can be referenced by later submissions and appears in the Primary Care Validator.
rejected	Not recorded; see errors. Correct and resubmit with the same record number.

Problems found after queueing are reported with the issue code validation_error and the field path.

Validation rules

- upload_transaction_no (path): 23 characters, U + accre_no + YYYY + MM + DD + 5-digit series; its accre_no must equal the accre_no in the token. No request body.

Errors

HTTP	Issue	When
400	validation_error	upload_transaction_no is not 23 characters.
401	unauthorized	Bearer token missing, invalid, or expired (Section 3.2). Request a new token.
404	upload_not_found	No submission with this number for the facility in the token.
500	internal_error	Contact PhilHealth support with the request_id. Do not retry automatically.

Sample error response

```
{
  "status": "error",
  "code": 404,
  "message": "Upload not found",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "errors": [
    {
      "field": "upload_transaction_no",
      "issue": "upload_not_found"
    }
  ]
}
```

4.7 Service 07 – YAKAP Patient Verification Code

Purpose

Validates a YAKAP Patient Verification Code, the one-time PIN PhilHealth issues to a patient for use when no PCU transaction code is available. PCAPI does not generate the code.

Item	Value
Endpoint	POST /api/v1/yakap-patient-verification-code
Authentication	Bearer token (Section 3.2); the facility is the accre_no in the token
Encryption	Request body and response data encrypted (Section 3.8, Annex C); errors in plain JSON
Success	HTTP 200 with data.status = VALID

Business rules

- The code is checked against patient_pin, the facility in the token and transaction_date.
- Validation does not use up the code: the same code can be sent as one_time_pin, with patient_verification_mode = OTP, in every Empanelment, Selection, FPE and Consultation request for that patient, facility and date.
- The envelope status says whether the request was processed; data.status says whether the code is valid. Always read data.status.

Request (before encryption)

```
{
  "patient_pin": "123456789012",
  "one_time_pin": "<code issued to the patient>",
  "transaction_date": "10/25/2026",
  "consent": true
}
```

Parameter	Type	Required	Description
patient_pin	string (12)	Yes	PIN of the patient, 12 digits.
one_time_pin	string (20)	Yes	The YAKAP Patient Verification Code issued by PhilHealth to the patient.
transaction_date	string (MM/DD/YYYY)	Yes	Date of the transaction the code was issued for.
consent	boolean	Yes	Must be true: the provider's attestation that the patient's explicit consent was obtained before this request (Implementation Guide 3.5). A missing or false value returns 403 consent_required.

Response (after decryption)

```
{
  "status": "success",
  "code": 200,
  "message": "Verification code is valid.",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
    "patient_pin": "123456789012",
    "accre_no": "H12345678",
    "transaction_date": "10/25/2026",
    "status": "VALID"
  }
}
```

Field	Type	Returned	Description
status	string	Always	Overall API processing status: “success” when the request was processed. It is not the verification result; read data.status for that.
code	number	Always	API response code (Section 3.3); 200 on success.
message	string	Always	Human-readable description of the verification result. Informational; do not match on its text.
timestamp	string (YYYY-MM-DDTHH:MM:SS)	Always	Date and time when the API response was generated.
request_id	string (UUID)	Always	Unique identifier of the API request, for tracking and troubleshooting. Quote it when contacting PhilHealth support.
data.patient_pin	string (12)	Always	PhilHealth Identification Number (PIN) of the beneficiary. Echoes the request.
data.accre_no	string (9)	Always	Accreditation number of the requesting YAKAP Clinic, taken from the bearer token (Section 3.2).
data.transaction_date	string (MM/DD/YYYY)	Always	Echoes the transaction_date sent in the request: the date the YAKAP Patient Verification Code was requested for.
data.status	string	Always	Validation result of the submitted YAKAP Patient Verification Code; VALID in a success response. Valid values: Library Reference – Verification Code Status.

Status values (Library Reference – Verification Code Status)

data.status	Meaning	How it is returned
VALID	The code is valid.	HTTP 200, data.status = VALID.
INVALID	The code is incorrect or does not match.	HTTP 422, issue code_invalid.
EXPIRED	The code has passed its validity period.	Reserved; not returned in this release.
USED	The code has already been used.	Reserved; not returned in this release.

Validation rules

- patient_pin: 12 digits. one_time_pin: at most 20 characters. transaction_date: MM/DD/YYYY. consent: true.

Errors

HTTP	Issue	When
400	validation_error	A field missing or malformed.
400	decryption_failed / hash_mismatch	The encrypted request cannot be read (Section 3.8).
401	unauthorized	Bearer token missing, invalid, or expired (Section 3.2). Request a new token.
403	consent_required	consent is missing or not true (Section 3.5).

HTTP	Issue	When
404	code_not_found	No verification code exists for the PIN.
422	code_invalid	The code does not match, or was issued for another facility or date. Ask the patient for the current code; do not retry the same code.
500	internal_error	Contact PhilHealth support with the request_id. Do not retry automatically.

Sample error response

```
{
  "status": "error",
  "code": 422,
  "message": "Verification code is not valid",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "errors": [
    {
      "field": "one_time_pin",
      "issue": "code_invalid"
    }
  ]
}
```

4.8 Service 08 – YAKAP Availment Slip

Purpose

Returns the YAKAP Availment Slip of a beneficiary for an effective year, at the facility in the token, as a PDF file.

Item	Value
Endpoint	POST /api/v1/yakap-availment-slip
Authentication	Bearer token (Section 3.2); the facility is the accre_no in the token
Encryption	Request body and response data encrypted (Section 3.8, Annex C); errors in plain JSON
Success	HTTP 200; data decrypts to a PDF file (docMimeType = application/pdf)

Business rules

- The slip is always for the facility in the token; accre_no is not sent.
- eff_year is required (no default).
- Errors are always plain JSON, never a PDF.

Request (before encryption)

```
{
  "patient_pin": "123456789012",
```

```
  "eff_year": "2026",
  "consent": true
}
```

Parameter	Type	Required	Description
patient_pin	string (12)	Yes	PIN of the beneficiary, 12 digits.
eff_year	string (YYYY)	Yes	Effective year of the slip.
consent	boolean	Yes	Must be true: the provider's attestation that the patient's explicit consent was obtained before this request (Implementation Guide 3.5). A missing or false value returns 403 consent_required.

Response

data carries the encrypted envelope (Annex C) with docMimeType = application/pdf; it holds the PDF file instead of JSON.

```
{
  "status": "success",
  "code": 200,
  "message": "Availment slip generated",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "data": {
    "docMimeType": "application/pdf",
    "hash": "<lowercase hex SHA-256 of the PDF file>",
    "key1": "",
    "key2": "",
    "iv": "<base-64 IV>",
    "doc": "<base-64 encrypted PDF file>"
  }
}
```

Field	Type	Returned	Description
data.docMimeType	string	Always	application/pdf
data.hash	string	Always	Lowercase hex SHA-256 of the PDF file (64 characters)
data.key1	string	Always	Reserved; empty string
data.key2	string	Always	Reserved; empty string
data.iv	string	Always	Base-64 initialization vector (16 bytes)
data.doc	string	Always	Base-64 encrypted PDF file; decrypt with Annex C

Handling the PDF

Step	What the EMR does
1. Decrypt	Decrypt data with Annex C. Because docMimeType is application/pdf, keep the decrypted bytes as bytes; do not read them as text.
2. Check the hash	Compute the SHA-256 of those bytes and compare it with hash.
3. Use the file	Save, display or print it. Suggested name: availment_slip_<patient_pin>_<eff_year>.pdf.

Status values

None: HTTP 200 with docMimeType = application/pdf means the slip was generated; 404 availment_not_found means no slip is available.

Validation rules

- patient_pin: 12 digits. eff_year: four-digit year. consent: true.

Errors

HTTP	Issue	When
400	validation_error	patient_pin not 12 digits or eff_year not a four-digit year.
400	decryption_failed / hash_mismatch	The encrypted request cannot be read (Section 3.8).
401	unauthorized	Bearer token missing, invalid, or expired (Section 3.2). Request a new token.
403	consent_required	consent is missing or not true (Section 3.5).
404	availment_not_found	No YAKAP availment for the patient_pin at your facility for eff_year (no slip is available).
500	internal_error	Contact PhilHealth support with the request_id. Do not retry automatically.

Sample error response


```
{
  "status": "error",
  "code": 404,
  "message": "Availment not found",
  "timestamp": "2026-10-25T10:15:30",
  "request_id": "550e8400-e29b-41d4-a716-446655440000",
  "errors": [
    {
      "field": "patient_pin",
      "issue": "availment_not_found"
    }
  ]
}
```

Annexes

Annex A – Data Dictionary and Library Reference

The Data Dictionary rev20261026 is the authoritative source for every field; the Library Reference rev20261026 for every code.

Worksheet	Content	Parameters
Summary – All Forms	Parameter counts per annex	622
Annex A – FPE	Section 4.6.1	143
Annex B – Consultation	Section 4.6.2	272
Annex C – Diagnostic Request	Section 4.6.3	7
Annex D – Diagnostic Results	Section 4.6.4	137
Annex E – Medicine	Section 4.6.5	31
Annex F – Referral Request	Section 4.6.6	32
Annex G – Service Payloads	Token, Services 01 to 05, 07, 08, upload requests (consent) and responses, Upload Status, the two envelopes	246 rows
Transaction Identifiers	Role and format of each record number (Section 3.9)	–
Validation Rules	Checks a backend applies to each request field, with the null-handling rules	–
Diagnostic Result Applicability	Result group for each Diagnostic Examination code	–
Revision History	Changes per release	–

- Map EMR data to an upload form from the matching annex; build the body from the JSON PATH column.
- Use Annex G for every non-form endpoint, including the upload responses.
- Read CONSTRAINT and the Validation Rules worksheet before mapping a field.
- Coded fields name a Library Reference worksheet; its Library Index lists every library, its code format and the fields that use it. Send only codes with LIBRARY STATUS 1. Konsulta Drug Library, ICD-10 and PSGC codes are external.

Annex B – PCU Result and Status Code Reference

Result code	data.status	Meaning	Validator pcu.status
100	psaerror	General PSA processing error.	FAILED
101, 102	invalid	PSA could not validate the identity or liveness data.	FAILED
103	–	Not described in the PCU code list; treated as not verified.	FAILED
104	PSA API 104	LIVENESS or PSA credential or session-related error.	FAILED

Result code	data.status	Meaning	Validator pcu.status
105	success	PhilHealth number found; KONSULTA is searched.	VERIFIED
106	duplicate	The profile requires further verification.	FAILED
107	deceased	Deceased-related membership outcome; KONSULTA is searched.	FAILED
108	norecord	No PhilHealth number found.	FAILED
109	success	Tagged deceased in membership and updated to active because of the member's liveness check.	VERIFIED
Varies	error	Unmapped PCU business response; inspect message.	FAILED

HTTP and gateway errors of the PCU endpoints are listed in Section 4.1. HTTP-level failures without a result code are not counted as PCU attempts.

Annex C – Guidelines for Data Encryption Using the Cipher Key

Data is encrypted with AES-256-CBC. PhilHealth issues a cipher key for each accreditation number (facility) served by a certified Service Provider; use the key of the facility in the bearer token. Any programming language may be used. Scope: every endpoint in Section 4, for the whole request body and for the data member of a successful response; errors and the token endpoint are not encrypted.

Encrypted Data Envelope

```
{
  "docMimeType": "{MIME type of the data}",
  "hash": "{SHA-256 of the data before encryption}",
  "key1": "",
  "key2": "",
  "iv": "{initialization vector, base-64}",
  "doc": "{encrypted data, base-64}"
}
```

Field	Value
docMimeType	MIME type of the plain data: application/json, or application/pdf for the Availment Slip.
hash	SHA-256 of the plain data (UTF-8 bytes of the JSON, or the PDF bytes), lowercase hexadecimal, 64 characters.
key1, key2	Reserved; always empty strings.
iv	16 random bytes, base-64.
doc	AES-256-CBC encrypted data, base-64.

Encryption Procedure

1. Hash. Compute the SHA-256 of the UTF-8 bytes of the plain JSON and write it as lowercase hexadecimal.

2. Derive the key. Compute the SHA-256 of the facility cipher key; the 32-byte digest is the AES-256 key.

3. Prepare the IV. Generate 16 random bytes and encode them in base-64.

4. Encrypt. Pad the data with null bytes (0x00) to a multiple of 16 bytes (no padding when already a multiple), encrypt with AES-256-CBC with padding turned off in your library (not PKCS#7), and encode the result in base-64.

5. Build the envelope. docMimeType, hash (step 1), key1 and key2 as "", iv (step 3) and doc (step 4).

Decryption Procedure

1. Derive the key as in encryption step 2.

2. Decode iv and doc from base-64.

3. Decrypt with AES-256-CBC, padding off, and remove the trailing 0x00 bytes. For application/json, read the bytes as UTF-8. For application/pdf, keep the bytes: a valid PDF ends with the %%EOF marker, so removing trailing 0x00 bytes does not alter it.

4. Check the hash. Compute the SHA-256 of the result and compare it with hash; if they differ, discard the data and contact PhilHealth support with the request_id.

Test Vector

Use this vector to check an implementation before staging tests. The body is an illustrative JSON object (not a complete Selection request); the test cipher key is not a real credential.

Input or output	Value
Cipher key (ASCII)	PCAPI-TEST-CIPHER-KEY-0001
AES key = SHA-256 of the cipher key (hex)	8e6d47cdcd376941a5f5e71a76161e2f28f98c4941d31c7791e0255899eb05dd
iv (bytes 00 to 0F), base-64	AAECAwQFBgcICQoLDA0ODw==
Plain JSON (60 bytes, UTF-8, no spaces)	{"patient_pin":"123456789012","selection_date":"10/24/2026"}
hash (SHA-256, lowercase hex)	c74558f2df0c6d3e26b22853bc46388d712689001f03d6f003b8f73d9f4a17f0
doc (4 null bytes of padding, 64 bytes), base-64	8qipXLTaqv/erRM3acals23bNbNzdX5NeVpUWWYljJdsCUm3x1GfNvTheN/rR5AMpVVSYQmPVNLPcTp78aV84Q==

Decrypting doc with the same key and iv, then removing the trailing null bytes, must return the plain JSON, and its SHA-256 must equal hash.