

Bell 412 Pre Flight Inspection

RP-C RP-C4120

Date 08/24/2026

STATUS INITIAL

FUSELAGE - FRONT

1. Cabin Nose	- Condition; all glass clean; wipers stowed.	✓	JDC
2. Remote Hydraulic Filter Bypass Indicator	- Verify normal.	✓	JDC
3. Pitot Tubes	- Unobstructed.	✓	JDC
4. Static Ports (L & R)	- Unobstructed.	✓	JDC
5. Cabin Nose Ventilators	- Unobstructed.	✓	JDC
6. Nose Compartment Door	- Secure.	✓	JDC
7. Battery Vent and Drain Tubes	- Unobstructed.	✓	JDC
8. Searchlight and Landing Light	- Stowed.	✓	JDC
9. Antennas	- Condition and security.	✓	JDC

FUSELAGE - CABIN LEFT SIDE

1. Copilot Door	- Condition and operation; glass clean. Check security of emergency release handle.	✓	JDC
2. Position Lights	- Condition.	✓	JDC
3. Passenger Door	- Condition and operation; glass clean. Condition of pop-out windows.	✓	JDC
4. Landing Gear	- Condition; handling wheels removed.	✓	JDC
5. Passenger Step	- Condition and security.	✓	JDC

FUSELAGE - AFT LEFT SIDE

1. No. 1 Engine Compartment	- Check.	✓	JDC
2. No. 1 Engine Oil Level	- Verify actual presence of oil in sight gauge. Visually check oil level. Filler cap secured.	✓	JDC
3. N ₂ Governor Spring	- Check condition.	✓	JDC
4. Engine Fire Extinguisher	- Check bottle pressure gauge and temperature range.	✓	JDC
5. Combining Gearbox Filter	- Check bypass indicator retracted.	✓	JDC
6. Oil Cooler Blower	- Unobstructed.	✓	JDC
7. Avionics Compartment	- Security of components; check OVER TRQ warning flag (cat's eye) for indication of overtorque. AFCS computers secured; compartment door secured.	✓	JDC
8. Access Door and Engine Cowling	- Secured.	✓	JDC
9. Drain Lines	- Clean and unobstructed.	✓	JDC
10. Engine Exhaust Ejectors	- Covers removed; unobstructed.	✓	JDC

TAILBOOM

1. Tailboom	- Condition; access covers secured.	✓	JDC
2. Tail Rotor Driveshaft Covers	- Secured.	✓	JDC

Bell 412 Pre Flight Inspection

RP-C RP-C4120

Date 08/24/2026

STATUS INITIAL

TAILBOOM (CONTINUED)

CAUTION: Do not bend elevator trailing edge tab.

3. Elevator	- Condition and security; check for spring condition by moving elevator toward the leading-edge-down position.	✓	JDC
4. Tail Rotor (90°) Gearbox	- Verify actual presence of oil in sight gauge. Visually check oil level; check filler cap and chip detector plug for security.	✓	JDC
5. Tail Rotor Blades	- Visually check condition and cleanliness.	✓	JDC
6. Tail Rotor	- Condition and free movement on flapping axis.	✓	JDC
7. Tail Rotor Yoke	- Evidence of static-stop contact damage (deformed static-stop yield indicator).	✓	JDC
8. Tail Skid	- Condition and security.	✓	JDC
9. Intermediate (42°) Gearbox	- Verify actual presence of oil in sight gauge. Visually check oil level. Check filler cap and chip detector plug for security.	✓	JDC
10. Elevator	- Condition and security.	✓	JDC
11. Tailboom	- Condition.	✓	JDC
12. Baggage Compartment	- Cargo secured, smoke detector condition, door secured.	✓	JDC

FUSELAGE - AFT RIGHT SIDE

1. Aft Compartment	- Check unobstructed.	✓	JDC
2. Tail Rotor Actuator	- Check.	✓	JDC
3. Engine Fire Extinguisher	- Check bottle pressure gauge and temperature range.	✓	JDC
4. Combining Gearbox Oil Level	- Verify actual presence of oil in sight gauge. Visually check oil level.	✓	JDC
5. Oil Cooler Blower	- Unobstructed.	✓	JDC
6. No. 2 Engine Compartment	- Check.	✓	JDC
7. No. 2 Engine Oil Level	- Verify actual presence of oil in sight gauge. Visually check oil level. Filler cap closed.	✓	JDC
8. Access Doors and Engine Cowling	- Secured.	✓	JDC
9. Fuel Filler	- Visually check quantity; secure cap.	✓	JDC

FUSELAGE - CABIN RIGHT SIDE

1. Passenger Door	- Condition and operation; glass clean. Condition of pop-out windows.	✓	JDC
2. Transmission Oil	- Verify actual presence of oil in sight gauge. Visually check oil level.	✓	JDC
3. Position Lights	- Condition.	✓	JDC
4. Landing Gear	- Condition; handling wheels removed.	✓	JDC
5. Passenger Step	- Condition and security.	✓	JDC

Bell 412 Pre Flight Inspection

RP-C RP-C4120

Date 08/24/2026

STATUS INITIAL

FUSELAGE - CABIN RIGHT SIDE (CONTINUED)

- | | | | |
|---------------|--|---|-----|
| 6. Pilot Door | - Condition and operation; glass clean. Check security of emergency release handles. | ✓ | JDC |
|---------------|--|---|-----|

CABIN TOP

- | | | | |
|---|--|---|-----|
| 1. Hub and Sleeve Assembly | - Check condition. | ✓ | JDC |
| 2. Swashplate, Support Assembly, and Collective Lever | - Check condition. | ✓ | JDC |
| 3. Main Rotor Pitch Links | - Security and condition. | ✓ | JDC |
| 4. Mast Retaining Nut | - Secured. | ✓ | JDC |
| 5. Yoke Assembly | - Condition. | ✓ | JDC |
| 6. Pitch Horns | - Security and condition. | ✓ | JDC |
| 7. Elastomeric Bearings, Lead-Lag Dampers | - Check general condition. | ✓ | JDC |
| 8. Blade Retention Bolts | - Security and proper latching. | ✓ | JDC |
| 9. Droop Restrainers | - Security and condition. Verify droop-stop clevis in lower position of cam plate. | ✓ | JDC |
| 10. Simple Pendulum Absorbers | - Security and condition. | ✓ | JDC |
| 11. Main Driveshaft and Coupling | - Condition, security, and grease. Check temp-plates (four places on each coupling) for evidence of elevated temperature indicated by a dot changing color to black. | ✓ | JDC |

CAUTION: If any temp-plate is missing or has black dots, maintenance personnel shall assist in determining airworthiness.

- | | | | |
|--|---|---|-----|
| 12. Transmission Oil Filler Cap | - Secured. | ✓ | JDC |
| 13. No. 1 and No. 2 Hydraulic Reservoirs | - Visually check fluid levels; caps secured. | ✓ | JDC |
| 14. Antennas | - Condition and security. | ✓ | JDC |
| 15. Combining Gearbox Oil Filler Cap | - Secured. | ✓ | JDC |
| 16. Anticollision Light | - Condition and security. | ✓ | JDC |
| 17. No. 1 and No. 2 Engine Air Intakes | - Unobstructed; check particle separator door closed. | ✓ | JDC |
| 18. Engine and Transmission Cowling | - Secured. | ✓ | JDC |
| 19. Fresh Air Inlet Screen | - Unobstructed. | ✓ | JDC |
| 20. Rotor Brake Reservoir Cap | - Security. | ✓ | JDC |

Bell 412 Pre Flight Inspection

F.O.B. 70%

Released by:

Juan Dela Cruz

Juan Dela Cruz

Mechanic

SAMPLE-AP-0412

A&P License No.

Accepted by:

Maria Santos

Maria Santos

Pilot

SAMPLE-CHPL-0412

CHPL No.

Procedures by Flight Manual Preflight Inspection, FAA Approved, revised 16 October 2009, Rev. 29.

SAMPLE - NOT FOR
OPERATIONAL USE