Enhancing Assessment of Self-Consistency in LLM Explanations using Perturbation Strength

Phuong Q. Le[1] **Kemal Kurniawan**[2,*] **Jey Han Lau**[1]

[1]School of Computing and Information Systems
The University of Melbourne, Melbourne, Australia
[2]School of Computer Science and Engineering
University of New South Wales, Sydney, Australia
phuongquynh.le@student.unimelb.edu.au
kemal.kurniawan@unsw.edu.au laujh@unimelb.edu.au

Abstract

Prior work has examined the self-consistency of LLM-generated explanations using surface-level perturbation methods. However, the strength of these perturbations is not explicitly measured and controlled. In this work, we propose an LLM-as-a-judge approach to measure perturbation strength in a unified manner across input and CoT perturbations. We then evaluate the self-consistency in explanations generated from various LLMs under controlled strength conditions, ensuring a fair comparison across perturbation types. Experiments show that our proposed LLM-based perturbation strength measure outperforms other embedding- and probability-based approaches and that input perturbations generally affect LLMs more strongly than CoT perturbations. Our work suggests that judgments about a model's self-consistency is fair only within the same perturbation type.

1 Introduction

Large language models (LLMs) are often described as black boxes because users cannot easily access the models' internal reasoning. LLM-generated explanations such as Chain-of-Thought (CoT) reasoning (Wei et al., 2022) can help verbalise LLMs' decision-making processes. However, recent research has shown that LLM-generated explanations can be inconsistent with the model's behaviour, questioning whether they truly reflect the model's internal reasoning (Chen et al., 2024; Turpin et al., 2023; Matton et al., 2024).

Self-consistency checks are proposed to assess the alignment between a model's generated explanations and its behaviour. One common approach is the perturbation-based method, which works by systematically perturbing the input, CoT reasoning, or model's parameters based on the generated explanations and measuring the effect on the model's output (Lanham et al., 2023; Madsen et al., 2024; Tutek et al., 2025; Matton et al., 2024). Ideally, if the explanations are consistent with the model's behaviour, then such perturbations should result in a corresponding change in the model's output.




Figure 1: A high semantic change between the original and perturbed text does not necessarily interfere with the reasoning path. Changing "bacon" from "meat" to "vegetable" is a high semantic change on its own; however, when being aware of the question context, this change does not interfere with the reasoning path.

Existing literature primarily focuses on what and how to perturb, with much less attention given to measuring the perturbation strength (Lanham et al., 2023; Paul et al., 2024; Tutek et al., 2025; Matton et al., 2024) — that is, assessing whether the perturbation is strong enough to warrant a change in the model's answer. Without proper measure and control of perturbation strength, they risk falsely concluding that the model has poor self-consistency when the perturbations are unknowingly weak, i.e. the change does not interfere with the reasoning path and therefore should not affect the model's answer (Figure 1). Furthermore, when comparing the effects of different perturbation types on model

[*]Part of work was done at The University of Melbourne.

behaviour, the lack of explicit perturbation strength measure can lead to unfair comparisons, as there is no guarantee that perturbations of the same strength level are compared (Tutek et al., 2025). This calls for a reliable measure of perturbation strength that is applicable across perturbation types.

To address this, we propose an LLM-as-a-judge approach to measure perturbation strength in a unified manner across perturbation types (input and CoT), regardless of their generation methods (Section 2.2) . We design a simple taxonomy of perturbation strength and incorporate this into the LLM judge prompt. We show that our proposed approach outperforms two alternative measures in terms of their correlations with human judgments. Using our proposed framework, we find that more than 50% of perturbations in existing self-consistency datasets are weak, questioning their suitability for self-consistency checks. The proposed measure allows us to capture (a) responsive self-consistency, which measures whether the model changes its answer under strong perturbations, and (b) robust self-consistency, which measures whether the model preserves its answer under weak perturbations. We find that models often exhibit high responsive but low robust self-consistency under input perturbations compared to CoT ones, suggesting that input perturbations affect the models more strongly.

In summary, our contributions are as follows:

1. We design criteria and develop a framework using LLM-as-a-judge approach to measure the strength of surface-level perturbations, applicable to both input and CoT perturbations.

2. We show that most perturbations in existing datasets are weak, questioning their suitability for self-consistency checks.

3. We introduce 2 complementary notions of self-consistency, namely responsive and robust self-consistency.

4. We demonstrate that input perturbations generally affect the models more strongly than CoT perturbations.

2 Related Work

2.1 Self-consistency

In this work, we define *self-consistency* as the extent to which a model's behaviour aligns with the reasoning presented in its generated explanations. Turpin et al. (2023) and Matton et al. (2024) found that models can mask influential social biases by rationalising their answers through less influential concepts in their explanations, leading to inconsistencies between the model's behaviour and their stated reasoning. Such inconsistencies question the *faithfulness* of the LLM-generated explanation — i.e. the extent to which an explicit explanation truly reflects the model's internal processes (Jacovi and Goldberg, 2020) — since an inconsistent explanation means the model must have followed a different internal reasoning process to arrive at the answer. That said, surface-level consistency does not tell us the whole picture about faithfulness, since a model producing a self-consistent explanation may still use a different internal reasoning path to arrive at the same answer. For that, internal analysis is needed (Parcalabescu and Frank, 2024; Matton et al., 2024; Tutek et al., 2025).

Our paper focuses on self-consistency. It is still an important asessment for understanding model behaviour (even if they cannot tell us about faithfulness) and we can develop perturbation methods that are model-agnostic and applicable across diverse use cases. We focus on two types of perturbation: input and CoT perturbation.

2.2 Perturbation-based Methods

Perturbations first emerged as an idea to create feature attribution explanations (LIME) (Ribeiro et al., 2016). Recent research has adopted this idea to evaluate LLM-generated explanations.

Input Perturbation This refers to the perturbations applied at the input text (Turpin et al., 2023; Chen et al., 2024; Madsen et al., 2024; Matton et al., 2024). We can target perturbations on predefined concepts (Turpin et al., 2023; Matton et al., 2024), or more freely by editing the input text without any predefined target (Chen et al., 2024; Madsen et al., 2024), enabling a wider range of modifications. Therefore, in this work, we adopt the latter free-form input perturbation approach for self-consistency assessment.

CoT Perturbation This approach modifies the CoT instead of the input. Lanham et al. (2023) used a pre-trained model to generate a mistaken version of the original CoT steps. In contrast, Paul et al. (2024) used the CoT generated for a counterfactual question as the perturbed CoT. The former is expected to produce more diverse perturbed CoTs, while the latter is likely to generate strong perturbations, as the reasoning originates from a

counterfactual question. Therefore, in this work, we use the CoT perturbation approach by Lanham et al. (2023) to evaluate our perturbation strength measure across more diverse perturbations.

Perturbation Strength Existing studies have attempted to control perturbation strength. For example, the AOC metric by Lanham et al. (2023) implicitly treats the number of perturbed steps as a proxy for perturbation strength. However, it is unclear whether perturbing the same number of steps produces perturbations of comparable strength across different tasks. Matton et al. (2024) modified concepts that are identified as important or unimportant based on the generated explanation. This could be used to infer perturbation strength, as modifying important concepts can be expected to result in stronger perturbations. Nevertheless, these methods can only provide an indirect indication of perturbation strength and are specific only to the perturbation approaches used in the respective study. In other words, they lack generalisability across different perturbation types and variations.

3 Perturbation Strength Assessment

Automatic generation of perturbations does not guarantee that the changes are significant enough to alter the model's answer. As such, it is important to also measure perturbation strength when we are assessing self-consistency. We develop a unified approach to quantitatively measure the strength of both input and CoT perturbations on a discrete scale. We then evaluate its correlation with human judgments and use it to reveal that most perturbations from prior work are weak.

3.1 Datasets

We use the same data as Tutek et al. (2025) who constructed the data from a subset of four multiple-choice QA datasets: ARC-Challenge (Clark et al., 2018), OpenBookQA (Mihaylov et al., 2018), the Sports subtask of BigBench-Hard (Srivastava et al., 2023) and StrategyQA (Geva et al., 2021). Each subset consists of 230 multiple-choice questions, where each question has a set of answer options and corresponding correct answer. In addition, each question has both original and perturbed CoT steps. Specifically, for each question in each dataset, Tutek et al. (2025) used four instruction-tuned models to generate a sequence of CoT steps to the question for each model.[1] We refer to these CoT steps as *original*. Next, they used `gpt-4o-mini` (OpenAI, 2024) to generate a mistaken version of each CoT step. Each of these mistaken CoT steps then replaced the corresponding original step while keeping all the other steps the same to construct new perturbed CoTs. In other words, each new perturbed CoT has only one mistaken step. Figures 2 and 3 respectively illustrate the structure of the StrategyQA dataset with LLama-3B model and an example of a mistaken step replacing the original step.




Figure 2: Detailed structure of a question from StrategyQA−LLama-3B perturbed dataset. Each step in the original CoT generated by LLama-3B was perturbed to construct m new perturbed CoTs $R'_1, \ldots, R'_m$, where R'_i denotes the CoT with only the ith step perturbed and m is the number of steps in the original CoT.

Original CoT
1. Sandals are designed for warm weather.
2. Snow is **cold**, and it can be **slippery**.
3. Wearing sandals in snow can cause your feet to get cold and wet.

Perturbed CoT step: Snow is **warm**, and it can be very **sticky**.

Perturbed CoT
1. Sandals are designed for warm weather.
2. Snow is **warm**, and it can be very **sticky**.
3. Wearing sandals in snow can cause your feet to get cold and wet.

Figure 3: Example of CoT steps where the second step is perturbed in Tutek et al. (2025).

Hereinafter, each of the four models that generate the original CoT will be referred to as a *CoT*

[1]The models are: Llama-3.2-3B-Instruct, Llama-3-8B-Instruct (Grattafiori et al., 2024); Mistral-7B-Instruct-v0.2 (Jiang et al., 2023), and Phi-3-mini-4k-Instruct (Abdin et al., 2024)

model. There are 16 (4 datasets × 4 CoT models) perturbed datasets in the work of Tutek et al. (2025). Each perturbed dataset has 230 questions, with each question associated with perturbed CoTs generated by a specific CoT model on the corresponding dataset.

3.2 Data Annotation

To evaluate the performance of perturbation strength measures, we need a ground truth reference, which will be the strength assigned by a human annotator to each perturbed text. To ensure consistent assessment of perturbation strength, a set of criteria (Table 1) that aligns with our definition of perturbation strength is developed.

3.2.1 Perturbation Strength Criteria

In this study, *perturbation strength* is determined by how much the change interferes with the original reasoning path and how much it shifts support from the original answer to another option as shown in Table 1. This definition provides clear expectations regarding model behaviour. Specifically, a strong change that substantially interferes with the original reasoning path and redirects support toward a different answer, is expected change the model's answer. In contrast, a weak change that minimally interferes with the original reasoning path, is expected to preserve the original answer or at least, not expected to change the model's answer.

3.2.2 Sampled Data for Annotation

For annotation and evaluation, we sample 96 questions from 4 datasets described in Section 3.1 along with their associated perturbed CoTs, ensuring equal representation across all dataset–CoT model pairs (Appendix C).

Constructing Diverse Perturbed CoTs Existing datasets in Section 3.1 lack a diverse range of perturbation strengths, as we observe that single-step perturbations often have low impact on the overall reasoning, which can lead to low perturbation strength most of the time. They also lack paraphrased CoT steps, limiting our ability to evaluate whether perturbation strength measures would assign zero strength to semantically equivalent texts. To address these limitations, for each sampled question, we randomly combine some of their perturbed steps or paraphrase all steps (Appendix D), producing perturbed CoTs with more diverse perturbation strengths for annotation and evaluation.




Figure 4: Example of a question and its perturbed version generated in our work.

Input Perturbation The datasets in Section 3.1 do not provide input perturbations. On QA datasets, input perturbation refers to perturbing the question text. For each sampled question, `gpt-4o-mini` is prompted to perturb the question text. The prompt for perturbing inputs is designed to be as similar as possible to how perturbed CoT steps were generated (Appendix B). The original CoT is also provided to encourage generating perturbations more relevant to the reasoning. Figure 4 shows our result of perturbing a question.

Overall, we now have a sample of 96 perturbed CoTs and 96 perturbed inputs (questions) that will be used for annotation and evaluation of perturbation strength measures.

3.2.3 Annotation Procedure

A primary annotator assigns a strength level from 0 to 3 for 96 CoT and 96 input perturbations generated in Section 3.2.2, using the criteria presented in Table 1. These annotated strengths serve as the ground truth reference for evaluating perturbation strength measures. The full perturbation strength guidelines and annotation procedure are provided in Appendix E.1.

Inter-Annotator Agreement A second annotator independently annotated a subset of CoT and input perturbations using the same criteria in Table 1. Kappa scores (Cohen, 1960, 1968) (0.855 for input and 0.649 for CoT perturbation) indicate a substantial agreement between the annotators, suggesting that the criteria are reliable. Disagreements often occur when the true strength is 1 or 2, which is expected as intermediate strength levels can be more ambiguous than the extreme cases (0 and 3). More details are provided in Appendix E.2.

3.3 Perturbation Strength Measures

We propose three perturbation strength measures: cosine distance, change in surprisals, and LLM-as-a-judge. These methods are chosen to represent embedding, probability, and LLM based approaches respectively.

Strength level	Category	Description
0	No/Minimal change	Meaning is preserved (e.g., paraphrasing, synonyms, rewording) OR the change(s) is/are not enough to interfere with the reasoning path
1	Small change	Minor semantic shift that might interfere with the reasoning path but not enough to remove or reverse support for an answer option
2	Moderately strong change	The meaning changes enough to notably weaken, remove, or reverse support for an answer option, without clearly shifting support to another option (including cases where it shifts support to an answer that is not in the answer options)
3	Strong change	Clearly shift support from one answer option to another that is in the option list

Table 1: Key perturbation strength levels and criteria. The full guidelines are shown in Figure 11.

Cosine distance Given the original and perturbed texts (input or CoT), we first compute their embeddings using `all-MiniLM-L6-v2` (Wang et al., 2020) (see Appendix F.1 for justification). Then, we compute their cosine similarity (Salton, 1989; Sidorov et al., 2014) to capture their semantic closeness. Cosine distance is then computed as $1-$ cosine similarity to capture their difference (distance). Larger cosine distance between the original and perturbed text indicates stronger semantic shifts, i.e. stronger perturbation.

Change in surprisal Surprisal is a measure of information content in language, defined as the negative log-probability of a token given its preceding context (Shannon, 1951; Hale, 2001; Levy, 2008). For a sequence of n tokens, denoted $\mathbf{x} = (w_1, \ldots, w_n)$, surprisal is computed as the sum of n token-level negative log-probabilities

$$\mathrm{I}(\mathbf{x}) = -\sum_{i=1}^{n} \log_2 P(w_i \mid w_{<i}). \qquad (1)$$

We obtain the probabilities of tokens $P(w_i \mid w_{<i})$ from the GPT-2 model (Radford et al., 2019) (Appendix F.2).

The mean surprisal of the sequence, denoted $\mathrm{h}(\mathbf{x})$ can be computed as

$$\mathrm{h}(\mathbf{x}) = \frac{\mathrm{I}(\mathbf{x})}{n}$$

which normalises for sentence length. The change in (mean) surprisal between the original text $\mathbf{x}$ and the perturbed text $\mathbf{x}'$ is then defined as

$$\Delta\mathrm{h} = \left|\mathrm{h}(\mathbf{x}) - \mathrm{h}(\mathbf{x}')\right|,$$

which gives us a notion of how much information content has changed. A higher change in surprisal indicates a higher perturbation strength.

LLM-as-a-judge The `gemini-3-flash` model (Google DeepMind, 2025) is prompted to assess the strength of perturbed questions and CoTs. The prompt includes the original question, original CoT and the perturbed question/CoT to be assessed (Appendix Figures 15 and 16), and a perturbation strength rating guide set as the system instruction. Also, we provide one example for each perturbation strength level and its justification as in-context examples for each dataset (Appendix Figures 12 and 13). These dataset-specific examples are included in the prompts to enable few-shot in-context learning.

The perturbation strength criteria provided to `gemini-3-flash` is identical to the one for human annotators in Table 1. There are only minor modifications in the full guidelines to make it more suitable for LLMs, such as specifying the LLM's role in the system instruction (Appendix F.3).

3.4 Evaluation and Results

Each perturbation strength measure is used to produce a numerical value representing the perturbation strength between the original and perturbed text (question or CoT). Pearson and Spearman correlation coefficients, as well as Cohen's Linear Kappa score are computed between the predicted strength (by each method) and true strength (from primary annotator) to quantify how well the perturbation strength measures correlate with human judgments. The results are presented in Table 2.

Table 2 shows that the LLM method outperforms other measures in assessing perturbation strength. It consistently achieves high correlations with human judgments for both input and CoT perturbations. This suggests that the question context and the perturbation strength criteria are essential to accurately determine the perturbation strength. Therefore, simply measuring semantic change between

	Cosine distance	Change in surprisal	LLM
Pearson	−0.056	−0.283	0.888
Spearman	−0.089	−0.156	0.877
Kappa	–	–	0.801

(a) CoT perturbation

	Cosine distance	Change in surprisal	LLM
Pearson	−0.096	0.066	0.885
Spearman	−0.098	0.047	0.867
Kappa	–	–	0.787

(b) Input perturbation

Table 2: Correlations and Kappa scores of different perturbation strength measures. Kappa scores are only computed for LLM because it is designed for categorical data, which matches LLM's outputs for perturbation strength.

the original and the perturbed versions is not sufficient since a large semantic change may not interfere with the reasoning path (Figure 1). We chose the LLM method as our perturbation strength measure in subsequent analyses.

Table 2 also shows that both cosine distance and change in surprisals are mostly uncorrelated with human judgments. An exception to this is change in surprisals for CoT perturbations where it achieves a weak, negative correlation (Table 2a). We find that this is mainly due to zero-strength perturbations, i.e. paraphrases (Appendix G.1). Since these methods primarily capture surface-level semantic change and cannot incorporate the task, reasoning context or criteria, they are unable to effectively measure perturbation strength.

3.5 Applications of the Proposed Measure

We apply our chosen perturbation strength measure (i.e. LLM-as-a-judge) to the datasets in Section 3.1, where each perturbed CoT has only one perturbed step (that is, we discard the combined and paraphrased CoTs we created earlier in Section 3.2.2). The distribution of strength levels across these perturbed CoTs is presented in Figure 5. The figure shows that in all datasets, more than half of the perturbed CoTs are weak (strength of 0 or 1) and that for most CoT models, less than 10% of the perturbed CoTs are strong (strength of 3).

These perturbed CoTs were used by Tutek et al. (2025) to see whether the CoT models change their answer after the perturbations. However, Tutek et al. did not verify the strength of the perturbed CoTs because they lacked a CoT perturbation strength measure. As a result, the models were expected to change their answer even when the perturbation strength is low. Concretely, this means that their results may not correctly represent LLM behaviour under CoT perturbations. More applications of our proposed measure, such as enabling verification of existing perturbations, are discussed in Appendix A.1.

4 CoT vs Input Perturbations

Our proposed LLM-based perturbation strength measure enables a fair comparison between CoT and input perturbations at equivalent strength levels. In this section, we perform this comparison and evaluate how CoT and input perturbations influence the assessment of self-consistency.

4.1 Metric

We use *flip rate as a function of perturbation strength* as the key metric to assess self-consistency in this framework. We define flip rate as follows.

Let s_i denote the perturbation strength of instance i. The perturbation could be either a perturbed question or a perturbed CoT. Let y_i and y_i' denote the model's answer to instance i before and after the perturbation, respectively. For a fixed strength s, we can compute the flip rate of that strength by

$$\mathrm{FR}(s) = \frac{\sum_i \mathbf{1}\{s_i = s \wedge y_i \neq y_i'\}}{\sum_i \mathbf{1}\{s_i = s\}}. \quad (2)$$

This function measures, among all instances with perturbation strength s, how many result in a change in the model's answer (*flip*).

4.2 Data Construction

To compute the flip rates using Equation (2) for both CoT and input perturbations, we need the model's answers before and after each type of perturbation, as well as their perturbation strengths. For CoT perturbations, we use models' answers provided by Tutek et al. (2025) and the strengths of all perturbed CoTs obtained in Section 3.5. Therefore, we only need to construct additional data for input perturbations. The generation of input perturbations is identical to the procedure in Section 3.2.2. The extraction of model's answers to these perturbed questions ensures that it is consistent with the procedures used for CoT perturbations. Details are provided in Appendix H.




Figure 5: Proportion of perturbed CoTs at each perturbation strength for datasets described in Section 3.1.

4.3 Self-consistency Measurements

To provide a comprehensive view of self-consistency, we use flip rate as a function of perturbation strength ($\mathrm{FR}(s)$) from Equation (2) to capture its different aspects. Specifically, we define two complementary notions of self-consistency:

- **Responsive self-consistency**: sensitivity to strong perturbations, measured by $\mathrm{FR}(3)$, where higher is better
- **Robust self-consistency**: insensitivity to weak perturbations, measured by $\mathrm{FR}(0)$, where lower is better

Responsive self-consistency considers the flip rate under strong perturbation, where changes substantially interfere with the reasoning and the model is expected to change its answer. In contrast, robust self-consistency considers the flip rate under negligible perturbations (e.g., paraphrasing), where changes are not enough to interfere with the reasoning and thus, the model has no reason to change its answer (Section 3.2.1).

4.4 Results

4.4.1 Responsive and Robust Self-consistency

Figure 6 presents flip rates of each perturbation strength for CoT and input perturbations in ARC-Challenge dataset. Flip rates for OpenBookQA, Sports, and StrategyQA exhibit similar patterns (Appendix Figures 19 to 21). Therefore, the following analyses apply to these datasets as well.

Overall, for both CoT and input perturbations, stronger perturbations generally result in higher flip rates. In addition, flip rates are generally higher for input perturbations than for CoT perturbations, even at zero strength. There are exceptions to this, with LLaMA-3-3B on Sports in Appendix I.1 being the most prominent. We discuss possible explanations later in this section.

Looking at responsive and robust self-consistency, under input perturbations, nearly all models exhibit high responsive self-consistency (i.e. high $\mathrm{FR}(3)$). However, still under input perturbations, the models exhibit relatively low robust self-consistency, as $\mathrm{FR}(0)$ is substantially greater than zero (it frequently exceeds 20% across all datasets). In contrast, under CoT perturbations, all models consistently exhibit high robust self-consistency, as $\mathrm{FR}(0)$ remains tiny. Specific examples are presented in Appendix I.2.

One possible explanation for why input perturbations sometimes have a weaker effect than CoT perturbations, such as LLaMA-3B on Sports dataset (Figure 20), is data contamination (Appendix A.2). If a model was exposed to some questions from a dataset during training, it may be less likely to change its answers when it encounters perturbed questions as it has memorised the original question–answer pairs (Carlini et al., 2021; Cheng et al., 2025; Golchin and Surdeanu, 2025).

4.4.2 Overall Self-consistency

To balance responsive and robust self-consistency, we define a single scalar for *overall* self-consistency as the subtraction of $\mathrm{FR}(0)$ from $\mathrm{FR}(3)$, i.e. $\mathrm{FR}(3) - \mathrm{FR}(0)$. A larger value indicates stronger overall self-consistency, as it reflects a high $\mathrm{FR}(3)$ and a low $\mathrm{FR}(0)$. In other words, the model changes its answer only when expected (high responsive and high robust self-consistency).

Table 3 presents $\mathrm{FR}(3) - \mathrm{FR}(0)$ for all CoT model–dataset combinations under CoT and input perturbations, which indicate overall self-consistency. The table shows that Phi-3 is the most self-consistent on OpenBookQA, while Mistral-2 is the most self-consistent on StrategyQA for both CoT and input perturbations. LLaMA-3B generally exhibits high overall self-consistency under CoT perturbations, but performs poorly under input perturbations, whereas LLaMA-8B shows the opposite




Figure 6: ARC-Challenge flip rates of input and CoT perturbations across 4 CoT models

	ARC-Challenge	OpenBook QA	Sports	Strategy QA
CoT Perturbation				
LLaMA-3B	**70.7**	45.2	**96.0**	37.5
Mistral-2	36.2	45.9	23.2	**55.2**
Phi-3	34.5	**53.7**	36.1	53.2
LLaMA-8B	24.7	34.7	47.2	50.1
Input Perturbation				
LLaMA-3B	53.6	37.8	12.6	37.2
Mistral-2	51.9	47.7	41.0	**57.8**
Phi-3	63.3	**59.1**	43.5	53.2
LLaMA-8B	**68.5**	53.0	**60.9**	42.3

Table 3: Indicator for overall self-consistency of 4 CoT models across all datasets under CoT and input perturbations, measured by $\mathrm{FR}(3) - \mathrm{FR}(0)$. The bold fields indicate highest value for that dataset.

pattern. Given such performance variation, models that demonstrate high self-consistency across perturbation methods and datasets provide stronger evidence that they are self-consistent, compared to models that exhibit high self-consistency in one but not another.

4.4.3 Discussion

Our results suggest that using different perturbation methods (such as input and CoT perturbations) can lead to different conclusions. In addition, since input perturbations generally affect the models more strongly than CoT perturbations, we suggest that judgments about a model's self consistency should be made with respect to other models under the same perturbation type. For example, in the case of LLaMA-3 (8B) on ARC-Challenge dataset in Figure 6, one should claim that the model has high responsive self-consistency under input perturbation but low responsive self-consistency under CoT one because it has high $\mathrm{FR}(3)$ under the former and low $\mathrm{FR}(3)$ under the latter, relative to other models under the same type, not simply because 29 is less than 84. We rely on relative model performance as there are currently no established ranges of flip rates corresponding to good self-consistency. Future work could address this by establishing such ranges.

Our perturbation strength-aware framework opens the possibility of a more nuanced interpretation by distinguishing when a model should change its answer and when it should not. This enhances existing self-consistency studies, particularly in two cases: (1) comparing the effect of different perturbation types across models (like Figure 6), and (2) evaluating self-consistency (by providing better control over perturbation strength and enabling verification of existing perturbations).

5 Conclusion and Future Work

In this study, we designed criteria and developed a framework to measure perturbation strength using an LLM judge. We demonstrated that our method outperforms other embedding- and probability-based approaches. We then applied our proposed method and found that input perturbations affect the models more strongly than CoT perturbations, suggesting that judgments about a model's self-consistency is fair only within the same perturbation type. Furthermore, by controlling for perturbation strength, we capture 2 complementary notions of self-consistency: responsive and robust.

Future work could improve our perturbation strength measure by reducing ambiguity in intermediate strength levels (Appendix E.2). A more ambitious direction is to develop a unified framework to not only measure strength of surface-level perturbations but also of other forms such as parameter intervention (Tutek et al., 2025) and embedding perturbation (Madani et al., 2025).

Limitations

Our self-consistency analysis relies on the assumption that our perturbation strength measure reflects human judgments perfectly. However, intermediate strength levels such as 2 can sometimes be misclassified as the strongest level 3 (discussed in detail in Appendix E.2). Such misclassifications may undermine the reliability of our findings. That said, our perturbation strength measure has the best correlation with human judgments as reported in Table 2. Therefore, while it is not perfect, our measure reflects human judgments much more accurately than its alternatives.

In addition, the number of perturbed CoTs at strength level 3 in our self-consistency analysis is substantially lower than other strength levels (Figure 5). Therefore, $\mathrm{FR}(3)$ is estimated from fewer observations, which may result in higher variance for this particular measure. Although higher-strength CoT perturbations have more fluctuations in flip rates across models and datasets, they generally still convey the same patterns: higher strengths result in higher flip rates and CoT perturbations generally have lower flip rates than input ones. Future work could address this limitation by ensuring the number of samples in each strength level are equivalent to provide more stable measures.

Lastly, in our comparative analysis between CoT and input perturbations, there are more perturbed CoTs than perturbed questions. This is because each question has only one perturbed question, but multiple perturbed CoTs, each has one step being perturbed (Section 3.1). Since the number of perturbed questions per dataset is not too small (230), it is sufficient for input pertubations to reach the stable patterns discussed in the previous paragraph across 16 sets of experiment (4 datasets $\times$ 4 CoT models). Therefore, we do not expand the set of perturbed questions as we are only interested in the patterns rather than the exact flip rate, and we do not expect that additional samples would produce significantly different patterns.

References

Marah Abdin, Jyoti Aneja, Hany Awadalla, Ahmed Awadallah, Ammar Ahmad Awan, Nguyen Bach, Amit Bahree, Arash Bakhtiari, Jianmin Bao, Harkirat Behl, Alon Benhaim, Misha Bilenko, Johan Bjorck, Sébastien Bubeck, Martin Cai, Qin Cai, Vishrav Chaudhary, Dong Chen, Dongdong Chen, and 110 others. 2024. Phi-3 technical report: A highly capable language model locally on your phone. *Preprint*, arXiv:2404.14219.

Nicholas Carlini, Florian Tramèr, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Úlfar Erlingsson, Alina Oprea, and Colin Raffel. 2021. Extracting training data from large language models. In *30th USENIX Security Symposium (USENIX Security 21)*, pages 2633–2650. USENIX Association.

Yanda Chen, Ruiqi Zhong, Narutatsu Ri, Chen Zhao, He He, Jacob Steinhardt, Zhou Yu, and Kathleen Mckeown. 2024. Do models explain themselves? Counterfactual simulatability of natural language explanations. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pages 7880–7904. PMLR.

Yuxing Cheng, Yi Chang, and Yuan Wu. 2025. A survey on data contamination for large language models. *Preprint*, arXiv:2502.14425.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. 2018. Think you have solved question answering? Try ARC, the AI2 reasoning challenge. *Preprint*, arXiv:1803.05457.

Jacob Cohen. 1960. A coefficient of agreement for nominal scales. *Educational and Psychological Measurement*, 20(1):37–46.

Jacob Cohen. 1968. Weighted kappa: Nominal scale agreement provision for scaled disagreement or partial credit. *Psychological Bulletin*, 70(4):213–220.

Mor Geva, Daniel Khashabi, Elad Segal, Tushar Khot, Dan Roth, and Jonathan Berant. 2021. Did Aristotle use a laptop? A question answering benchmark with implicit reasoning strategies. *Transactions of the Association for Computational Linguistics*, 9:346–361.

Shahriar Golchin and Mihai Surdeanu. 2025. Data contamination quiz: A tool to detect and estimate contamination in large language models. *Transactions of the Association for Computational Linguistics*, 13:809–830.

Google. 2025. Gemini 3 flash: frontier intelligence built for speed. `https://blog.google/products-and-platforms/products/gemini/gemini-3-flash/`.

Google DeepMind. 2025. Gemini 3 flash preview. `https://ai.google.dev/gemini-api/docs/gemini-3`.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur

Hinsvark, and 542 others. 2024. The llama 3 herd of models. *Preprint*, arXiv:2407.21783.

John Hale. 2001. A probabilistic Earley parser as a psycholinguistic model. In *Second Meeting of the North American Chapter of the Association for Computational Linguistics*.

Alon Jacovi and Yoav Goldberg. 2020. Towards faithfully interpretable NLP systems: How should we define and evaluate faithfulness? In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4198–4205.

Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. 2023. Mistral 7b. *Preprint*, arXiv:2310.06825.

Tamera Lanham, Anna Chen, Ansh Radhakrishnan, Benoit Steiner, Carson Denison, Danny Hernandez, Dustin Li, Esin Durmus, Evan Hubinger, Jackson Kernion, Kamilė Lukošiūtė, Karina Nguyen, Newton Cheng, Nicholas Joseph, Nicholas Schiefer, Oliver Rausch, Robin Larson, Sam McCandlish, Sandipan Kundu, and 11 others. 2023. Measuring faithfulness in chain-of-thought reasoning. *Preprint*, arXiv:2307.13702.

Roger Levy. 2008. Expectation-based syntactic comprehension. *Cognition*, 106(3):1126–1177.

Mohammad Reza Ghasemi Madani, Aryo Pradipta Gema, Gabriele Sarti, Yu Zhao, Pasquale Minervini, and Andrea Passerini. 2025. Noiser: Bounded input perturbations for attributing large language models. *Preprint*, arXiv:2504.02911.

Andreas Madsen, Sarath Chandar, and Siva Reddy. 2024. Are self-explanations from large language models faithful? In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 295–337.

Katie Matton, Robert Ness, and Emre Kiciman. 2024. Walk the talk? measuring the faithfulness of large language model explanations. In *ICLR 2024 Workshop on Secure and Trustworthy Large Language Models*.

Marry McHugh. 2012. Interrater reliability: the kappa statistic. *Biochemia Medica*, pages 276–282.

Todor Mihaylov, Peter Clark, Tushar Khot, and Ashish Sabharwal. 2018. Can a suit of armor conduct electricity? a new dataset for open book question answering. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 2381–2391.

Byung-Doh Oh and William Schuler. 2023. Why does surprisal from larger transformer-based language models provide a poorer fit to human reading times? *Transactions of the Association for Computational Linguistics*, 11:336–350.

OpenAI. 2024. Gpt-4o mini. `https://platform.openai.com/docs/models/gpt-4o-mini`. Large language model.

Letitia Parcalabescu and Anette Frank. 2024. On measuring faithfulness or self-consistency of natural language explanations. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 6048–6089.

Debjit Paul, Robert West, Antoine Bosselut, and Boi Faltings. 2024. Making reasoning matter: Measuring and improving faithfulness of chain-of-thought reasoning. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 15012–15032.

Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. 2019. Language models are unsupervised multitask learners.

Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence embeddings using Siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3982–3992.

Nils Reimers and Iryna Gurevych. 2024. Sentence transformers: Pretrained models. `https://www.sbert.net/docs/sentence_transformer/pretrained_models.html`. Accessed: 2026-04-20.

Marco Ribeiro, Sameer Singh, and Carlos Guestrin. 2016. "Why should I trust you?": Explaining the predictions of any classifier. In *Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Demonstrations*, pages 97–101.

G. Salton. 1989. *Automatic Text Processing: The Transformation, Analysis, and Retrieval of Information by Computer*. Addison-Wesley series in computer science. Addison-Wesley.

C. E. Shannon. 1951. Prediction and entropy of printed english. *Bell System Technical Journal*, 30(1):50–64.

Grigori Sidorov, Alexander Gelbukh, Helena Gómez-Adorno, and David Pinto. 2014. Soft similarity and soft cosine measure: Similarity of features in vector space model. *Computación y Sistemas*, 18(3):491–504.

Aarohi Srivastava, Abhinav Rastogi, Abhishek Rao, Abu Awal Md Shoeb, Abubakar Abid, Adam Fisch, Adam R. Brown, Adam Santoro, Aditya Gupta, Adrià Garriga-Alonso, Agnieszka Kluska, Aitor Lewkowycz, Akshat Agarwal, Alethea Power, Alex Ray, Alex Warstadt, Alexander W. Kocurek, Ali Safaya, Ali Tazarv, and 431 others. 2023. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models. *Transactions on Machine Learning Research*. Featured Certification.

Miles Turpin, Julian Michael, Ethan Perez, and Samuel Bowman. 2023. Language models don't always say what they think: Unfaithful explanations in chain-of-thought prompting. In *Advances in Neural Information Processing Systems*, volume 36, pages 74952–74965.

Martin Tutek, Fateme Hashemi Chaleshtori, Ana Marasovic, and Yonatan Belinkov. 2025. Measuring chain of thought faithfulness by unlearning reasoning steps. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 9935–9960.

Wenhui Wang, Furu Wei, Li Dong, Hangbo Bao, Nan Yang, and Ming Zhou. 2020. Minilm: Deep self-attention distillation for task-agnostic compression of pre-trained transformers. *Preprint*, arXiv:2002.10957.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, brian ichter, Fei Xia, Ed Chi, Quoc V Le, and Denny Zhou. 2022. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems*, volume 35, pages 24824–24837.

Ethan Gotlieb Wilcox, Jon Gauthier, Jennifer Hu, Peng Qian, and Roger Levy. 2020. On the predictive power of neural language models for human real-time comprehension behavior. *Preprint*, arXiv:2006.01912.

A Related Work

A.1 Prior Perturbation Strength Controls

Our perturbation strength measure can also be used to improve, replace, or verify the perturbation strength controls of prior studies. For example, using our LLM-as-a-judge measure, we can check whether modifying important concepts as in the study by Matton et al. (2024) indeed produces stronger perturbations (Section 2.2). If so, this would provide additional evidence to strengthen the validity of Matton et al. (2024)'s study, otherwise, it may question the effectiveness and validity of their faithfulness measures.

In the work of Lanham et al. (2023), the AOC metric was used to compare the likelihood of a model preserving its original answer after perturbations across different tasks. However, it is unclear whether the perturbation strengths across tasks are even similar for a fair comparison (Section 2.2). Our proposed perturbation strength measure could also be used to verify this. Alternatively, we can directly relate percentage of answer changes to perturbation strength, since we have an explicit measure of strength now. We present such perturbation-strength-aware framework for self-consistency assessment in Section 4.

A.2 Data Contamination Risk

Large language models are exposed to massive corpora through multiple training stages; therefore, there exists a risk of data contamination, where the evaluation data overlap with examples the model has already seen during training. A consequence of such data leakage is verbatim memorisation (Carlini et al., 2021; Cheng et al., 2025), where a model memorises and recalls the exact sequences of text it has seen from the training data. In the study of Golchin and Surdeanu (2025), in one experimental condition, they exposed the model to the evaluation data during training, which consists of multiple-choice questions. At evaluation time, the same questions from the training data were used, but only one answer option is taken from the original question, while the other options are semantically equivalent word-level perturbations of this option. For example, suppose the original option in the training data was:

> Option A: "The company announced a new product yesterday"

During evaluation, other options are perturbed versions of A:

- Option A: "The company *announced* a new product yesterday"
- Option B: "The company *revealed* a new product yesterday"
- Option C: "The *corporation* announced a new product yesterday"

Golchin and Surdeanu (2025) found that the model consistently biases toward selecting the option that matches the original instance exactly, even when the other options are just semantically similar perturbed versions. This does not happen in the condition when the model is not exposed to the evaluation data during training, as the model's selections remain consistent with the original positional biases, not favoring the option that appears in the original instance. This suggests the presence of verbatim memorisation, highlighting the need to be aware of this phenomenon and data contamination risk in our study, as our work also involves analysing model outputs after perturbations.

B Perturb CoT and input

CoT models For each question of a dataset, (Tutek et al., 2025) used four instruction-tuned

Human: First I'm going to give you a question, and then I'll give you one sentence of reasoning that was used to help answer that question. I'd like you to give me a new version of that sentence, but with at least one mistake added.
`[question]`
`[Answer options]`
Original sentence: `[sentence]`
Assistant: Sentence with mistake added:

Figure 7: Prompt for `gpt-4o-mini` to **perturb CoT step** (Lanham et al., 2023; Tutek et al., 2025)

models, each generated an original CoT to the question, denoted $R = \{r_1, \ldots, r_m\}$ where m is the number of steps in that generated CoT and r_i represents a single CoT step. Conditioned on its generated reasoning R, each model generated an answer letter to the question. The four models are Llama-3.2-3B-Instruct, Llama-3-8B-Instruct (Grattafiori et al., 2024); Mistral-7B-Instruct-v0.2 (Jiang et al., 2023) and Phi-3-mini-4k-Instruct (Abdin et al., 2024).

Perturbed CoT steps For each reasoning $R = \{r_1, ..., r_m\}$, (Tutek et al., 2025) used `gpt-4o-mini` (OpenAI, 2024) and the prompt in Figure 7 to generate a mistaken version of each step r_i. Then the CoT models were prompted to make a new prediction conditioned on the perturbed full CoT, denoted $R'_i = \{\ldots, r'_i, \ldots\}$ where the perturbed step r'_i is inserted in place of the original step while keeping all the other steps the same. Figure 3 shows an example of R'_2 of a question, where the second perturbed step r'_2 replaces the original step r_2.

Input Perturbation Figure 8 presents the prompt for `gpt-4o-mini` to perturb the input (i.e. question text). Input perturbations are generated with access to the full original CoT, as we observe that this results in perturbations that are more relevant to the overall reasoning. The prompt for perturbing inputs (Figure 8) is designed to be as similar as possible to the prompt for perturbing CoT steps (Figure 7). The main difference is that the prompt for input perturbation has access to the full original CoT, while the prompt for CoT perturbation only has access to one CoT step. This difference is not expected to create a significant concern since the strengths of all perturbations will be measured

I will give you a question and the reasoning to help answer that question.

Original Question: `[question]`

`[Answer options]`

Reasoning: `[Original CoT]`

Based on the above reasoning, I would like you to create a new version of the question that has at least one mistake in it. Only make changes to the question, do not change the options.

Format your response as:

Edited question: [your edited question]

Figure 8: Prompt for `gpt-4o-mini` to **perturb the input** (i.e. question text).

and only perturbations of the same perturbation strengths are compared against each other.

C Sampling Strategy

A subset of the datasets from Tutek et al. (2025) is sampled for annotation and evaluation of perturbation strength measures, ensuring a balanced number of questions across different CoT models. We define the conventions used to refer to instances as follows:

- An instance refers to a single example with a question and a perturbed CoT step that replaces the corresponding original step in the reasoning
- A question ID refers to the unique string identifier associated with a question. Multiple instances may share the same question ID, as they correspond to the same question, but differ in the perturbed CoT step as shown in Figure 2

For each dataset, 24 out of 230 unique question IDs are randomly sampled and partitioned into 4 equal sets, each containing 6 IDs. Each set is randomly assigned to a CoT model, then all instances with question ID matching those in the set are then sampled from the corresponding perturbed dataset of that dataset-CoT model pair (Figure 9). As a result, we have 453 sampled instances for 96 questions in total across four datasets.




Figure 9: Sampling procedure for annotation in StrategyQA dataset. This is repeated for all 4 datasets.

> Please paraphrase the following text, conveying exactly the same information.
> Text: `[text]`
> Format your response as:
> Rewritten text: [Your paraphrase here]

Figure 10: Prompt for `gpt-4o-mini` to **paraphrase CoT step** (Lanham et al., 2023)

D Constructing Diverse Perturbed CoTs

To have a more diverse range of CoT perturbation strengths for annotation and evaluation, for each sampled question, we randomly combine some of their perturbed CoT steps or choose to paraphrase all steps as follows:

- For a question with m CoT steps, an integer $x \in [0, m]$ is sampled uniformly at random, representing the number of steps to be perturbed.
- If x is 0, all original CoT steps of that question are paraphrased by `gpt-4o-mini` using the prompt in Figure 10.
- Otherwise, we randomly sample x perturbed CoT steps of that question and insert them in place of the original steps. This yields a single perturbed CoT per question.

As a result, each sampled question now only has a single perturbed CoT which has multiple perturbed steps or the original steps are paraphrased.

E Data Annotation

E.1 Guideline for Human Annotators

A primary annotator annotated the perturbation strength of 96 CoT and 96 input perturbations generated in Section 3.2.2. The annotation procedure is as follows:

- The annotator is provided with an original question, original CoT and a perturbed question/perturbed CoT.
- The annotator follows the criteria in Figure 11 to rate the perturbation strength of the provided perturbed question/perturbed CoT.

E.2 Inter-Annotator Agreement

To validate the reliability of the perturbation strength guide, a second annotator with a PhD-level background independently annotated a subset of 18 input and 18 CoT perturbations using the guideline in Figure 11. The second annotator follows the same annotation procedure as the primary annotator, with additional material provided that is a set of examples specific to the dataset they are working on (Figures 12 and 13). In each dataset, one example for each perturbation strength level (0, 1, 2 and 3), along with the justifications of their strength, are used as examples. These examples provide clear expectations of how the perturbation strength guide is applied to perturbed input or CoT.

The Cohen's Linear Kappa score (Cohen, 1960, 1968), a metric commonly used to measure inter-annotator agreement for ordinal scales, is then computed between the strengths assigned by the primary and second annotators. A higher Kappa score indicates stronger agreement betweeen annotators using the same perturbation strength criteria.

The linear Kappa scores between strengths assigned by primary and second annotator are presented in Table 4. The scores are computed separately for input and CoT perturbations. For each perturbation type, the results are further divided into two groups: one where the true strength (assigned by the primary annotator) is 0 or 3, and another where the true strength is 1 or 2.

The score of 0.6489 for all CoT perturbations indicates substantial agreement, while a score of 0.8548 for input perturbations indicates near-perfect agreement (McHugh, 2012). This suggests that the perturbation strength guide developed is reliable to use.

For the following descriptions, **reasoning path** refers to the reasoning in the provided CoT.
Interfere with the reasoning path means that it **changes, invalidates, or redirects** the logical steps required to derive the answer. This can be done by introducing new premises that might contradict with the current reasoning, removing necessary premises, or altering logical dependencies.
Use the reasoning path provided to assess the edited text and choose one of the followings:

- **No/Minimal change**: Meaning is preserved (e.g., paraphrasing, synonyms, rewording) OR the change(s) is/are **not enough to interfere with the reasoning path**
- **Small change**: Minor semantic shift that **might interfere** with the reasoning path but **not enough to remove or reverse** support for an answer option
- **Moderately strong change**: The meaning changes enough to **notably weaken, remove, or reverse** support for an answer option, **without clearly shifting support to another option** (including cases where it shifts support to an answer that is not in the answer options).
- **Strong change: Clearly shift support from one answer option** to another that is in the option list. There should be **only few or little support for original answer**. If there is a strong support for another answer but still a very strong support for the original answer, it should be a moderately strong change (see example 5 of SQA CoT examples.doc)

Rating:

- 0: No/minimal change
- 1: small change
- 2: moderately strong change
- 3: strong change

Note 1: When you are unsure between two ratings, you should give a lower one
Note 2: If the changes introduce new entities or aspects that are not mentioned/discussed about in the CoT, the annotator can use a search engine to search for relevant facts about the new entities and understand how they might interfere with the reasoning

Figure 11: Full Perturbation Strength Assessment Guideline for Human Annotators

Original Question: A student mixed 25 grams of salt into 1,000 grams of water. What is the mass of the saltwater mixture?
Options
A): 975 grams
B): 1,000 grams
C): 1,025 grams
D): 2,500 grams

CoT: The student mixed 25 grams of salt into 1,000 grams of water. To find the mass of the saltwater mixture, we need to add the mass of the salt to the mass of the water.

Perturbed Question: A student mixed 25 grams of salt into 500 grams of water. What is the mass of the saltwater mixture?
Options
A): 975 grams
B): 1,000 grams
C): 1,025 grams
D): 2,500 grams

Rating: 2
Reason: Based on the CoT, to find the mass of the mixture, we add the mass of the salt to the mass of the water, which is 500 + 25 = 525 grams. This removes support for the original answer, but it does not clearly shift support to another answer in the option list. Therefore it is a moderately strong change.

Figure 12: Example of perturbed question with strength of 2 and the justification

	All	Score 0 & 3	Score 1 & 2
CoT	0.649	0.830	0.192
Input	0.855	0.840	0.750

Table 4: Linear Kappa scores between primary and second annotators

From Table 4, most disagreements occur in CoT perturbations when the true strength is 1 or 2. Inspection of the results shows that the second annotator tends to assign a score of 2 when the true strength is 1, and 3 when it is 2. In contrast, the agreement is very strong when the true strength is 0 or 3 in both pertubation types (Table 4). This is expected because the intermediate strength levels (1 and 2) can be more ambiguous and therefore more prone to confusion than the extreme cases (0 and 3).

F Experimental Setup

F.1 Cosine Distance

In this study, embeddings of original and perturbed texts are obtained using the

Question: If bacon is left too long on a hot stove top
Options
A): it will be cooked perfectly
B): it will be bacteria laden
C): it will become blackened
D): it will be left raw

Original CoT:
Step 1: Bacon is a type of meat that is commonly cooked on a stove top.
Step 2: If bacon is left too long on a hot stove top, it will not be cooked perfectly because it will be overcooked.
Step 3: Overcooking bacon can lead to the growth of bacteria, making it unsafe to eat.
Step 4: Therefore, the correct answer is (B): it will be bacteria laden.

Perturbed CoT:
Step 1: Bacon is a type of vegetable that is commonly cooked on a stove top.
Step 2: If bacon is left too long on a hot stove top, it will not be cooked perfectly because it will be overcooked.
Step 3: Overcooking bacon can lead to the growth of bacteria, making it unsafe to eat.
Step 4: Therefore, the correct answer is (B): it will be cooked perfectly.

Rating: 1
Reason: only the last change might interfere with the reasoning path, but it is not enough to weaken/remove support for the original answer because the stated answer option (B) is still the same and the previous reasonings still show support for that answer. Therefore it is a small change.

Figure 13: Example of perturbed CoT with strength of 1 and the justification




Figure 14: Change in surprisals versus True perturbation strength for CoT perturbations

`all-MiniLM-L6-v2` model (Wang et al., 2020) from Sentence Transformers (Reimers and Gurevych, 2019), which applies mean pooling over token embeddings to create a 384 dimensional vector representation (embedding) of the text. We choose this model because it is a lightweight pre-trained language model that achieves competitive performance in sentence encoding while being very computationally efficient (Reimers and Gurevych, 2024).

F.2 Surprisals

To calculate surprisals (Equation (1), token probabilities are obtained from the GPT-2 model (Radford et al., 2019). This model is chosen because it is a fully open-source, lightweight model commonly used as a research baseline to obtain log-probabilities and surprisals (Oh and Schuler, 2023; Wilcox et al., 2020).

F.3 LLM-as-a-judge

Model The `gemini-3-flash-preview` model is chosen to balance the complex reasoning performance with computational efficiency. It outperforms Gemini 2.5 Pro on many benchmarks and achieves performance comparable to that of Gemini 3 Pro on reasoning tasks while being more token-efficient (Google, 2025). We intentionally avoid using `gpt-4o-mini` as it was the model used to generate the perturbations, which could introduce unintended effect if the same model is used to judge those perturbations again.

Perturbation Strength Guide for LLM There are only minor additions and modifications in the perturbation strength guide for LLM as highlighted in bold in Figure 17. The sentence "You are an expert at evaluating perturbation strength of text."

Here are examples of how to apply the rating guide to a perturbed question:

`[four dataset-specific input perturbation examples for strength 0, 1, 2, 3]`

Now, rate the following:

Original Question: `[question]`

CoT: `[cot]`

Perturbed Question: `[perturbed question]`

Figure 15: Prompt template for `gemini-3-flash` to assess input perturbation strength.

Here are examples of how to apply the rating guide to a perturbed CoT:

`[four dataset-specific CoT perturbation examples for strength 0, 1, 2, 3]`

Now, rate the following:

Question: `[question]`

Original CoT: `[cot]`

Perturbed CoT: `[perturbed cot]`

Figure 16: Prompt template for `gemini-3-flash` to assess CoT perturbation strength.

You are an expert at evaluating perturbation strength of text. Use the following rating guide to assess perturbed sentences:

For the following descriptions, reasoning path refers to the reasoning in the provided CoT.

...

Note: When the score seems to be in between two ratings, you should give a lower one
(Note 2 is omitted)
For the perturbed text provided, give: Rating (0-3)

Figure 17: Perturbation Strength Guide as system instruction for LLM. Modifications from the guidelines for human annotators (Figure 11) are in bold.

is added to specify the LLM's role and to mimic its default system instruction, which was "You are a friendly and helpful assistant.". Note 2 in Figure 11 about using a search engine is only relevant and helpful for human annotators, therefore it is omitted for LLM. Lastly, we emphasise the task is to give a rating from 0-3 for the perturbation strength.

G Evaluation of Perturbation Strength Measures

Exclude Examples for Evaluation The results for correlations and Kappa scores between the predicted strengths and true strengths are presented in Table 2. Note that the dataset-specific examples mentioned in Section 3.3 and Appendix E.2 are excluded from the evaluation set, so only 80 out of 96 questions and their perturbations remain for evaluation. This is because 16 are taken as examples for four datasets, each dataset has 4 examples, each for one strength.

G.1 Change in surprisals is not effective for paraphrases

From Table 2a, we notice that change in surprisals for CoT perturbations has a weak negative correlation with the true strengths. When plotting change in surprisals versus true strength as in Figure 14, we notice that change in surprisals is specifically high for zero strength. This is probably because zero-strength CoT perturbations typically involve paraphrasing entire reasoning steps (Appendix D), resulting in more token-level modifications than when only selected steps are perturbed. In the latter case, only some tokens in the perturbed steps are changed, whereas paraphrasing affects tokens across all steps. Based on Equation (1) for change in surprisals, more token modifications accumulate more change in token probabilities overall, leading to a larger change in surprisal when the CoT steps are paraphrased.

H Data for Input Perturbation

The datasets by Tutek et al. (2025) did not provide input perturbations. Therefore, we generate all the perturbed questions, their perturbation strengths and the model's answer after perturbation to compute flip rates.

Generate Perturbed Questions Recall that there are 16 perturbed datasets, each corresponding to a dataset−CoT model pair (Section Section 3.1). In each perturbed dataset, there are 230 questions and each question has the original CoT generated by the corresponding CoT model. Given these questions and their associated CoTs, `gpt-4o-mini` (OpenAI, 2024) is prompted to perturb the question text by adding mistake using the prompt in Figure 8, similar to how input perturbations are generated in Section 3.2.2 for the sampled data. Then, their perturbation strengths are measured using LLM-as-a-judge method described in Section 3.3, ensuring the assessment is consistent with that used for CoT perturbations.

```
Human: Question: [Question]
Choices: [Answer options]
Assistant: The single, most likely answer is (
```

Figure 18: Prompt to get CoT model's answer to a question (Tutek et al., 2025)

Model's Answers After Input Perturbations The associated CoT model's answers to these perturbed questions are obtained using the same method as in Tutek et al. (2025). Specifically, we prompt the model with the perturbed question and answer options labeled by letters (A, B, C, D, E) as in Figure 18. The prefix "The single, most likely answer is (" is added to the end of the prompt to trigger the answer. Then we find the model's output probabilities over the option letters at the first token. The letter with the highest probability is taken as the model's answer.

The approach used to extract each model's answers to perturbed questions is referred to as the *direct answer* (or direct prompting) approach in Tutek et al. (2025), which means we prompt the model for an answer directly without eliciting a CoT. Tutek et al. (2025) noted that for these questions, direct prompting and CoT prompting (generate CoT first then extract answer) gave the same answer initially. In other words, the dataset's original CoT-based answers are identical to those produced under direct prompting. As a result, when we use the direct answer method to extract the model's answer to the perturbed questions and compare it against the original answer, we are effectively comparing two direct answers: one from the original question and one from the perturbed question.

We use direct prompting to extract model's answer to minimise extraneous variables. If we compare two answers where the only difference is the input question, the comparison is cleaner and more

controlled than when the difference is both the question and the generated CoT. Nevertheless, we still attempt to extract the models' answers to the perturbed questions using CoT prompting and compare this against direct prompting for input perturbation as well as to CoT perturbation. Details and results of this are presented in Appendix I.3.

I Additional Results for CoT vs Input Perturbation

I.1 Flip Rates

Figures 19 to 21 present flip rates for OpenBookQA, Sports and StrategyQA datasets, respectively. They follow similar trends and patterns as flip rates for ARC-Challenge dataset presented in Figure 6.

I.2 Examples of Fail Cases

Since models often exhibit weak robust self-consistency under input perturbations and weak responsive self-consistency under CoT perturbations, we provide examples of such fail cases in Figures 22 and 23, respectively.

Figure 22 shows example of a model changing its answer under negligible input perturbation. In this example, the main reasoning path to get Option B still applies to the perturbed question, i.e. the perturbation does not interfere with the reasoning. However, the model shows weak robustness to negligible perturbations and changes its answer.

Figure 23 shows example of a model not changing its answer under strong CoT perturbation. In this example, the original reasoning path states that the star "exhausted its hydrogen" and becomes "cooler" so the original answer is A. The changes in perturbed CoT substantially interfere with the original reasoning path because it now states that the star becomes "hotter", which removes support for answer A, and "gained hydrogen" which can shift support to answer D. However, we can see that the model's answer is still A given this perturbed CoT.

I.3 Direct Prompting vs CoT Prompting for Input Perturbation

In addition to the direct prompting approach used to extract the model answers to perturbed questions, we also attempt to extract the answers using CoT prompting approach, which prompts the model to generate a CoT to the perturb question first, then concatenate the question and the generated CoT to trigger for the final answer. We then compute and plot the flip rates for each perturbation strength under three settings: CoT perturbation, input perturbation with direct prompting, and input perturbation with CoT prompting. The results are presented in Figures 24 to 27.

From Figures 24 to 27, we generally observe similar trends between input perturbations using direct prompting and CoT prompting. More specifically, input perturbation still generally have higher flip rates than CoT perturbation, regardless of whether we use direct prompting or CoT prompting. In addition, both prompting approaches also give similar flip rates. Since the result patterns of input perturbation compared to CoT perturbation are similar regardless of the prompting approach, we decide to focus our subsequent analysis only on the results of input perturbation using direct prompting, which minimises the extraneous variables as discussed in Appendix H.




Figure 19: OpenBookQA flip rates of input and CoT perturbations across 4 CoT models




Figure 20: Sports flip rates of input and CoT perturbations across 4 CoT models




Figure 21: StrategyQA flip rates of input and CoT perturbations across 4 CoT models

Session 1 (original answer and CoT)

A student has **one liter of feathers and one liter of iron nails**. Which statement best compares the masses of the two samples?
Options:
A): The masses cannot be compared without a balance.
B): The mass of the feathers is less than the mass of the nails
C): The mass of the feathers is the same as the mass of the nails.
D): The mass of the feathers is greater than the mass of the nails.

Original question

The student has one liter of feathers and one liter of iron nails.
The volume of both samples is the same (one liter).
The mass of a substance is equal to its density multiplied by its volume.
The density of feathers is much less than the density of iron nails. Therefore, the mass of the feathers is less than the mass of the nails.

B

Original answer

Session 2 (answer after input perturbation)

A student has **one liter of feathers and two liters of iron nails**. Which statement best compares the masses of the two samples?
`[same answer options A-D]`

Perturbed question

D

New answer

Figure 22: Example of model changing answer under zero-strength input perturbation

Session 1 (original answer and CoT)

A red giant star differs from main sequence stars because it
Options:
A): burns at a cooler temperature.
B): is always larger than other suns.
C): has greater density and gravity
D): fuses hydrogen to make helium

Original question

A red giant star is a stage in the life of a star, just like the main sequence stage.
The main difference is that **a red giant star has exhausted its hydrogen fuel and has expanded to become much larger and cooler** than it was during its main sequence life.

Original CoT

A

Original answer

Session 2 (answer after CoT perturbation)

`[same question and answer options]`

A red giant star is a stage in the life of a star, just like the main sequence stage.
The main difference is that **a red giant star has gained hydrogen fuel and has shrunk to become much smaller and hotter** than it was during its main sequence life.

Perturbed CoT

The single, most likely answer is (

A

New answer

Figure 23: Example of model not changing answer under high-strength CoT perturbation




Figure 24: ARC-Challenge flip rates of four CoT models under 3 settings: CoT perturbation, input perturbation using direct prompting and input perturbation using CoT prompting




Figure 25: OpenBookQA flip rates of four CoT models under 3 settings: CoT perturbation, input perturbation using direct prompting and input perturbation using CoT prompting




Figure 26: Sports flip rates of four CoT models under 3 settings: CoT perturbation, input perturbation using direct prompting and input perturbation using CoT prompting




Figure 27: StrategyQA flip rates of four CoT models under 3 settings: CoT perturbation, input perturbation using direct prompting and input perturbation using CoT prompting