



# Learning Representations from Imperfect Time Series Data via Tensor Rank Regularization

Paul Pu Liang<sup>1</sup>, Zhun Liu<sup>1</sup>, Yao-Hung Hubert Tsai<sup>1</sup>, Qibin Zhao<sup>2</sup>, Ruslan Salakhutdinov<sup>1</sup>, Louis-Philippe Morency<sup>1</sup>  
Carnegie Mellon University<sup>1</sup>, RIKEN Center for Artificial Intelligence Project<sup>2</sup>

## Introduction



## Our Proposed Model: Temporal Tensor Fusion Networks (T2FN)



**Problem:** Exact calculation of **tensor rank** is **NP-hard**

**Solution:** Adopt **efficient upper bound** instead:

$$r_{\mathcal{M}} \leq \sqrt{\frac{\prod_{i=1}^M d_i}{\max\{d_1, \dots, d_M\}}} \|\mathcal{M}\|_F$$

Constant for all input      Frobenius norm


**Loss function** of T2FN:  $\mathcal{L} = \ell(\hat{y}, y) + \lambda \cdot \|\mathcal{M}\|_F$

Task loss      Tensor rank regularizer


## Experiments and Results

### Two imperfect data settings


\* original entry      \* zeroed entry



### Experiment 1: Decomposition errors



### Exp. 2: Compare \w Other Models



**Conclusion:** Tensor rank regularization consistently improves performance at various levels of imperfect data.